FROG-IS

Single 8" Two-Way Coaxial Full-Range Loudspeaker

FI-CB8

Product Overview

The FI-CB8 is a compact, high-performance single 8-inch two-way coaxial full-range loudspeaker engineered for near-field sound reinforcement. It integrates a 1-inch imported titanium diaphragm compression driver with a 44mm voice coil and a direct-radiating 8-inch low-frequency transducer with a 50mm voice coil, both featuring ferrite magnet structures.

The coaxial configuration eliminates the acoustic path difference between drivers found in conventional loudspeakers, delivering uniform tonal balance and consistent coverage in the near field. An aluminum horn coupled with the woofer cone forms a wide-dispersion exponential high-frequency horn with an 80° (H) × 80° (V) coverage pattern. Utilizing advanced wavelet analysis technology, the crossover and driver structure are optimized to ensure that high and low frequencies arrive at the listener simultaneously, producing a natural, coherent soundstage.

Key Features

- Coaxial two-way design with a single 8" woofer and 1" titanium diaphragm compression driver for uniform near-field dispersion.
- Imported titanium diaphragm high-frequency driver delivers metallic clarity, high power handling and low distortion with refined, elegant tonality.
- Coaxial driver arrangement eliminates inter-driver path difference, ensuring consistent timbre across the listening area.
- Aluminum exponential horn combined with the woofer cone provides a wide 80° (H) × 80° (V) coverage angle.
- Wavelet-optimized crossover and driver structure align high and low frequency arrival times for natural, phase-coherent reproduction.
- Ferrite magnet structures on both drivers for reliable, consistent performance.
- 10 × M8 rigging points and base mount support flexible flying and stand-mount installation.
- Dual NL4MP speakON connectors with 1+/1– full-range input for reliable professional connectivity.
- Compact enclosure footprint ideal for space-critical installations.

Applications

- Classrooms and educational facilities
- Conference rooms and meeting spaces
- Music venues, restaurants and lounges
- Small-scale home theater main loudspeakers
- Fill and auxiliary loudspeakers
- Front-fill and under-balcony applications
- Surround sound channels

Technical Specifications

Parameter	Specification
Model	FI-CB8
System Type	Single 8" Two-Way Coaxial Full-Range Loudspeaker
Frequency Response	91 Hz – 20 kHz (-10 dB)
Sensitivity (1 W / 1 m)	93 dB
Nominal Impedance	8 Ω
Rated Power (AES)	300 W
Low-Frequency Driver	1 × 8" ferrite woofer, 50 mm voice coil
High-Frequency Driver	1 × 1" throat ferrite compression driver, 44 mm voice coil, titanium diaphragm
Nominal Coverage (H × V)	80° × 80°
Maximum SPL	116 dB (continuous) / 122 dB (peak)
Rigging Hardware	10 × M8 rigging points, base mount
Input Connectors	2 × NL4MP 4-pin speakON, 1+/1– full-range input
Dimensions (W × D × H)	28 × 20 × 28 cm
Net Weight	8 kg