FROG-IS

10" Ultra-Compact Subwoofer With One Passive Radiator

FI-SUB10U

Product Overview

The FI-SUB10U is an ultra-compact 10-inch subwoofer designed to deliver powerful, articulate low-frequency reinforcement in space-constrained environments. Featuring a long-excursion 10-inch ferrite woofer with a 50mm voice coil paired with a 10-inch passive radiator, it significantly reduces low-frequency harmonic distortion for clean, transparent bass reproduction.

Housed in a precision CNC-machined enclosure with tight-tolerance dado joinery, the cabinet exhibits exceptional rigidity and effectively suppresses panel resonance, resulting in solid, pure low-frequency performance. Its compact form factor and versatile mounting options allow flexible placement without occupying valuable floor space, making it ideal for home theater, entertainment rooms and conference facilities.

Key Features

- Ultra-compact enclosure design with multiple mounting options for flexible, space-saving placement.
- Built-in 10" long-excursion ferrite woofer with 50 mm voice coil for deep, dynamic bass output.
- Equipped with a 10" passive radiator to greatly reduce low-frequency harmonic distortion for clean, transparent bass.
- Precision CNC-machined cabinet with tight-tolerance dado joinery for maximum structural rigidity.
- Highly rigid enclosure effectively suppresses panel resonance, delivering solid and pure low-frequency performance.
- Extended frequency response down to 25 Hz for immersive low-end coverage.
- Professional Phoenix connector for reliable, secure signal connection.
- 4 Ω nominal impedance for efficient amplifier matching.

Applications

- Home theater low-frequency reproduction
- Entertainment rooms and karaoke lounges

- Conference rooms and meeting spaces
- Compact commercial audio installations
- Multi-room residential audio systems

Technical Specifications

Parameter	Specification
Model	FI-SUB10U
System Type	10" Ultra-Compact Subwoofer With Passive Radiator
Frequency Response	25 Hz – 250 Hz
Sensitivity (1 W / 1 m)	90 dB
Nominal Impedance	4 Ω
Rated Power (AES)	400 W
Low-Frequency Driver	1 × 10" ferrite woofer, 50 mm voice coil
Passive Radiator	1 × 10" passive radiator
Maximum SPL	114 dB (continuous) / 120 dB (peak)
Input Connector	1 × professional Phoenix connector
Dimensions (W × D × H)	62.4 × 19.5 × 34 cm
Net Weight	12 kg