

# Package ‘tidyoperators’

May 26, 2023

**Title** Infix operators for tidier R code

**Version** 0.0.9

**Description** The 'tidyoperators' R-package adds some much needed infix operators, and a few functions, to make your R code much more tidy. It includes infix operators for additional logic operators, safer float (in)equality operators, and infix operators for custom row- and column-wise ordering of matrices. It also adds some stringi-based string related functions and operators. It also adds operators and a few functions to help reduce unnecessary repetitive code. And finally, it also adds some functions and an operator for easier package/library management. The 'tidyoperators' R-package has only one dependency, namely 'stringi', though it does allow multi-threading of some of the string-related functions (when appropriate) via the suggested 'stringfish' R-package.

**License** MIT + file LICENSE

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.2.3

**Suggests** this.path (>= 1.3.0),  
rlang,  
knitr,  
rmarkdown,  
stringfish (>= 0.15.7),  
testthat (>= 3.0.0)

**VignetteBuilder** knitr

**Depends** R (>= 4.1.0)

**Imports** stringi (>= 1.7.12)

**Config/testthat/edition** 3

**URL** <https://github.com/tony-aw/tidyoperators>

**BugReports** <https://github.com/tony-aw/tidyoperators/issues>

## R topics documented:

float_logic . . . . .	2
inplace_math . . . . .	4

inplace_str_arithmetic . . . . .	6
inplace_str_subset . . . . .	7
logic_ops . . . . .	9
matrix_ops . . . . .	11
pkgs . . . . .	13
stri_join_mat . . . . .	14
stri_locate_ith . . . . .	16
str_arithmetic . . . . .	18
str_subset_ops . . . . .	20
substr_repl . . . . .	21
s_pattern . . . . .	25
tidyoperators_help . . . . .	26
transform_if . . . . .	27

<b>Index</b>	<b>30</b>
--------------	-----------

---

float_logic	<i>Safer float (in)equality operators</i>
-------------	---

---

## Description

The %f==%, %f!=%, %f<%, %f>%, %f<=%, %f>= operators perform "float logic". They are virtually equivalent to the regular (in)equality operators,

==, !=, <, >, <=, >=,

except for one aspect. The float logic operators assume that if the absolute difference between x and y is smaller than the Machine tolerance, `sqrt(.Machine$double.eps)`, then x and y ought to be consider to be equal.

Thus these provide safer float logic.

For example: `0.1*7 == 0.7` returns FALSE, even though they are equal, due to the way floating numbers are stored in programming languages like R. But `0.1*7 %f==% 0.7` returns TRUE.

There are also the `x %f{ }% bnd` and `x %f!{ }% bnd` operators, where `bnd` is a vector of length 2, or a 2-column matrix (`nrow(bnd)==length(x)` or `nrow(bnd)==1`).

The `x %f{ }% bnd` operator checks if x is within the closed interval with bounds defined by `bnd`.

The `x %f!{ }% bnd` operator checks if x is outside the closed interval with bounds defined by `bnd`.

## Usage

`x %f==% y`

`x %f!=% y`

`x %f<% y`

`x %f>% y`

`x %f<=% y`

`x %f>=% y`

`x %f{ }% bnd`

```
x %f!{}% bnd
```

## Arguments

<code>x, y</code>	numeric vectors, matrices, or arrays, though these operators were specifically designed for floats (class "double").
<code>bnd</code>	either a vector of length 2, or a matrix with 2 columns and 1 row, or else a matrix with 2 columns where <code>nrow(bnd)==length(x)</code> . The first element/column of <code>bnd</code> gives the lower bound of the closed interval; The second element/column of <code>bnd</code> gives the upper bound of the closed interval;

## Examples

```
x <- c(0.3, 0.6, 0.7)
y <- c(0.1*3, 0.1*6, 0.1*7)
print(x); print(y)
x == y # gives FALSE, but should be TRUE
x != y # gives TRUE, should be FALSE
x > y # not wrong
x < y # gives TRUE, should be FALSE
x %f==% y # here it's done correctly
x %f!=% y # correct
x %f<% y # correct
x %f>% y # correct
x %f<=% y # correct
x %f>=% y # correct

x <- c(0.3, 0.6, 0.7)
bnd <- matrix(c(0.29, 0.59, 0.69, 0.31, 0.61, 0.71), ncol=2)
x %f{}% bnd
x %f!{}% bnd

# These operators still work for non-float numerics also:
x <- 1:5
y <- 1:5
x %f==% y
x %f!=% y
x %f<% y
x %f>% y
x %f<=% y
x %f>=% y

x <- 1:5
y <- x+1
x %f==% y
x %f!=% y
x %f<% y
x %f>% y
x %f<=% y
x %f>=% y

x <- 1:5
y <- x-1
x %f==% y
```

```

x %f!=% y
x %f<% y
x %f>% y
x %f<=% y
x %f>=% y

```

---

inplace\_math

*In-place modifying mathematical arithmetic*


---

## Description

In-place modifiers for addition, subtraction, multiplication, division, power, root, logarithm, and anti-logarithm.

`x %+ <-% y` is the same as `x <- x + y`

`x %- <-% y` is the same as `x <- x - y`

`x %* <-% y` is the same as `x <- x * y`

`x %/ <-% y` is the same as `x <- x / y`

`x %^ <-% p` is the same as `x <- x^p`

`x %rt <-% p` is the same as `x <- x^(1/p)`

`x %logb <-% b` is the same as `x <- log(x, base=b)`

`x %alogb <-% b` is the same as `x <- b^x`; if `b=exp(1)`, this is the same as `x <- exp(x)`

## Usage

```
x %+ <-% y
```

```
x %- <-% y
```

```
x %* <-% y
```

```
x %/ <-% y
```

```
x %^ <-% p
```

```
x %rt <-% p
```

```
x %logb <-% b
```

```
x %alogb <-% b
```

**Arguments**

x	a number or numeric (or 'number-like') vector, matrix, or array.
y	a number, or numeric (or 'number-like') vector, matrix, or array of the same length/dimension as x. It gives the number to add, subtract, multiply by, or divide by.
p	a number, or a numeric vector of the same length as x. It gives the power to be used.
b	a number, or a numeric vector of the same length as x. It gives the logarithmic base to be used.

**Value**

These operators do not return any value: they are in-place modifiers, and thus modify x directly.

**Examples**

```
x <- matrix(rpois(10, 10), ncol=2)
print(x)
x %+ <-% 3 # same as x <- x + 3
print(x)

x <- matrix(rpois(10, 10), ncol=2)
print(x)
x %- <-% 3 # same as x <- x - 3
print(x)

x <- matrix(rpois(10, 10), ncol=2)
print(x)
x %* <-% 3 # same as x <- x * 3
print(x)

x <- matrix(rpois(10, 10), ncol=2)
print(x)
x %/ <-% 3 # same as x <- x / 3
print(x)

x <- matrix(rpois(10, 10), ncol=2)
print(x)
x %^ <-% 3 # same as x <- x^3
print(x)

x <- matrix(rpois(10, 10), ncol=2)
print(x)
x %rt <-% 3 # same as x <- x^(1/3)
print(x)

x <- matrix(rpois(10, 10), ncol=2)
print(x)
x %logb <-% 3 # same as x <- log(x, base=3)
print(x)

x <- matrix(rpois(10, 10), ncol=2)
print(x)
x %alogb <-% 3 # same as x <- 3^x
print(x)
```

```
x <- 3
print(x)
x %alogb <- % exp(1) # same as x <- exp(x)
print(x)
exp(3) # notice this is the same.
```

---

inplace\_str\_arithmetic

*In place modifying string arithmetic*

---

## Description

In-place modifier versions of string arithmetic:

`x %s+ <-% y` is the same as `x <- x %s+% y`

`x %s- <-% p` is the same as `x <- x %s-% p`

`x %s* <-% n` is the same as `x <- x %s*% n`

`x %s/ <-% p` is the same as `x <- x %s/% p`

See also the documentation on string arithmetic: [string arithmetic](#).

Note that there is no in-place modifier versions of `%ss%`, `s_extract()`, and `s_repl()`.

## Usage

`x %s+ <-% y`

`x %s- <-% p`

`x %s* <-% n`

`x %s/ <-% p`

## Arguments

`x`, `y`, `p`, `n`      see [string arithmetic](#) and [s\\_pattern](#).

## Value

These operators do not return any value: they are in-place modifiers, and thus modify `x` directly.

**Examples**

```

y <- "a"
p <- "a|e|i|o|u"
n <- c(2, 3)

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
x %s+ <- y # same as x <- x %s+ y
print(x)

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
x %s- <- p # same as x <- x %s- p
print(x)

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
x %s* <- n # same as x <- x %s\* n
print(x)

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
x %s/ <- p # same as x <- x %s/ p
print(x)

#####

y <- "a"
# pattern with ignore.case=TRUE:
p <- s_pattern(regex = "A|E|I|O|U", ignore.case=TRUE)
n <- c(3, 2)

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
x %s+ <- y # same as x <- x %s+ y
print(x)

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
x %s- <- p # same as x <- x %s- p
print(x)

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
x %s* <- n # same as x <- x %s\* n
print(x)

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
x %s/ <- p # same as x <- x %s/ p
print(x)

```

---

inplace\_str\_subset      *In place modifying string subsetting*


---

**Description**

In-place modifier versions of string subsetting:

`x %sget <-% ss` is the same as `x <- x %sget% ss`

`x %strim <-% ss` is the same as `x <- x %strim% ss`

See also the documentation on string subsetting ([string subset](#)).  
 Note that there is no in-place modifier versions of `%ss%`.

**Usage**

```
x %sget <-% ss
```

```
x %strim <-% ss
```

**Arguments**

`x`, `ss`                      see [string subset](#).

**Value**

These operators do not return any value: they are in-place modifiers, and thus modify `x` directly.

**Examples**

```
ss <- c(2,2)

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
x %sget <-% ss # same as x <- x %sget% ss
print(x)

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
x %strim <-% ss # same as x <- x %strim% ss
print(x)

#####

ss <- c(2,2)

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
```



```

x %sget <-% ss # same as x <- x %sget% ss
print(x)

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
x %strim <-% ss # same as x <- x %strim% ss
print(x)

```

---

logic\_ops

---

*Logic operators*


---

## Description

Additional logic operators:

The `x %xor% y` operator is the "exclusive-or" operator, the same as `xor(x, y)`.

The `x %n%&% y` operator is the "not-and" operator, the same as `(!x) & (!y)`.

The `x %out% y` operator is the same as `!x %in% y`.

The `x %?=% y` operator checks if `x` and `y` are **both** unreal or unknown (i.e. NA, NaN, Inf, -Inf).

The `n %=numtype% numtype` operator is a vectorized operator that checks for every value of numeric vector `n` if it can be considered a number belonging to type `numtype`. See arguments for details.

The `s %=strtype% strtype` operator is a vectorized operator that checks for every value of character vector `s` if it can be seen as a certain `strtype`. See arguments for details.

The `s %sgrep% p` operator is a vectorized operator that checks for every value of character vector `s` if it has pattern `p`.

## Usage

```
x %xor% y
```

```
x %n%&% y
```

```
x %out% y
```

```
x %?=% y
```

```
s %sgrep% p
```

```
n %=numtype% numtype
```

```
s %=strtype% strtype
```

**Arguments**

<code>x, y</code>	see <a href="#">Logic</a> .
<code>s</code>	a character vector.
<code>p</code>	the result from <a href="#">s_pattern</a> , or else a character vector of the same length as <code>s</code> with regular expressions.
<code>n</code>	a numeric vector.
<code>numtype</code>	a single string giving the type if numeric to be checked. The following options are supported: <ul style="list-style-type: none"> <li>• <code>"~0"</code>: zero, or else a number whose absolute value is smaller than the Machine tolerance (<code>sqrt(.Machine\$double.eps)</code>).</li> <li>• <code>"B"</code>: binary numbers (exactly 0 or exactly 1);</li> <li>• <code>"prop"</code>: proportions - numbers between 0 and 1 (exactly 0 or 1 is also allowed);</li> <li>• <code>"N"</code>: Natural numbers (non-negative integers including zero);</li> <li>• <code>"I"</code>: Integers;</li> <li>• <code>"odd"</code>: odd integers;</li> <li>• <code>"even"</code>: even integers;</li> <li>• <code>"R"</code>: Real numbers;</li> <li>• <code>"unreal"</code>: infinity, NA, or NaN;</li> </ul>
<code>strtype</code>	a single string giving the type of string to be checked. The following options are supported: <ul style="list-style-type: none"> <li>• <code>"empty"</code>: checks if the string only consists of empty spaces.</li> <li>• <code>"unreal"</code>: checks if the string is NA, or if it has literal string "NA", "NaN" or "Inf", regardless if it has leading or trailing spaces.</li> <li>• <code>"numeric"</code>: checks if the string can be converted to a number, disregarding leading and trailing spaces. I.e. the string "5.0" can be converted to the actual number 5.0.</li> <li>• <code>"special"</code>: checks if the string consists of only special characters.</li> </ul>

**Examples**

```
x <- c(TRUE, FALSE, TRUE, FALSE, NA, NaN, Inf, -Inf, TRUE, FALSE)
y <- c(FALSE, TRUE, TRUE, FALSE, rep(NA, 6))
outcome <- data.frame(
```

```

x=x, y=y,
"x %xor% y"=x %xor% y, "x %n&% y" = x %n&% y, "x %?=% y" = x %?=% y,
check.names = FALSE
)
print(outcome)

1:3 %out% 1:10
1:10 %out% 1:3

n <- c(0:5, 0:-5, 0.1, -0.1, 0, 1, Inf, -Inf, NA, NaN)
1e-20 %=numtype% "~0"
n[n %=numtype% "B"]
n[n %=numtype% "prop"]
n[n %=numtype% "N"]
n[n %=numtype% "I"]
n[n %=numtype% "odd"]
n[n %=numtype% "even"]
n[n %=numtype% "R"]
n[n %=numtype% "unreal"]

s <- c(" AbcZ123 ", " abc ", " 1.3 ", " !#$%^&*() ", " ", " NA ", " NaN ", " Inf ")
s[s %=strtype% "empty"]
s[s %=strtype% "unreal"]
s[s %=strtype% "numeric"]
s[s %=strtype% "special"]

s <- c("Hello world", "Goodbye world")
p <- s_pattern(regex = c("Hello", "Hello"))
s %sgrep% p

```

matrix\_ops

*Infix operators for row- and column-wise re-ordering of matrices***Description**

Infix operators for custom row- and column-wise re-ordering of matrices

The `x %row% mat` operator re-orders the elements of every row of matrix `x` according to the ordering ranks given in matrix `mat`.

The `x %col% mat` operator re-orders the elements of every column of matrix `x` according to the ordering ranks given in matrix `mat`.

**Usage**

```
x %row% mat
```

```
x %col% mat
```

## Arguments

<code>x</code>	a matrix
<code>mat</code>	a matrix with the same dimensions as <code>x</code> , giving the ordering ranks of every element of matrix <code>x</code> .

## Details

If matrix `x` is a numeric matrix, and one wants to sort the elements of every row or column numerically, `x %row~% x` or `x %col~% x` would suffice, respectively.

If matrix `x` is not numeric, sorting the elements using `x %row~% x` and `x %col~% x` are still possible, but probably not the best option. In the non-numeric case, providing a matrix of ordering ranks for `mat` would be faster and give more accurate ordering. See the examples section.

If `mat` is a matrix of non-repeating random integers (i.e. `sample(1:length(x), replace=FALSE)` `sample(1:length(x)) |> matrix(ncol=ncol(x))`), `x %row~% mat` will randomly shuffle the elements of every row, where the shuffling order of every row is independent of the other rows. Similarly, `x %col~% mat` will randomly shuffle the elements of every column, where the shuffling order of every column is independent of the other columns.

These operators internally only use vectorized operations (no loops or apply-like functions), and are faster than re-ordering matrices using loops or apply-like functions.

## Value

A modified matrix.

## Examples

```
# numeric matrix ====

x <- matrix(sample(1:25), nrow=5)
print(x)
x %row~% x # sort elements of every row
x %row~% -x # reverse-sort elements of every row
x %col~% x # sort elements of every column
x %col~% -x # reverse-sort elements of every column

x <- matrix(sample(1:25), nrow=5)
print(x)
mat <- sample(1:length(x)) |> matrix(ncol=ncol(x)) # matrix of non-repeating random integers
x %row~% mat # randomly shuffle every row independently
x %col~% mat # randomize shuffle every column independently

# character matrix ====

x <- matrix(sample(letters, 25), nrow=5)
print(x)
mat <- stringi::stri_rank(as.vector(x)) |> matrix(ncol=ncol(x))
x %row~% mat # sort elements of every row
x %row~% -mat # reverse-sort elements of every row
x %col~% mat # sort elements of every column
```

```

x %col~% -mat # reverse-sort elements of every column

x <- matrix(sample(letters, 25), nrow=5)
print(x)
mat <- sample(1:length(x)) |> matrix(ncol=ncol(x)) # matrix of non-repeating random integers
x %row~% mat # randomly shuffle every row independently
x %col~% mat # randomize shuffle every column independently

```

---

**pkgs**


---

*Package import management operator and functions*


---

**Description**

The alias `%m import <-% pkgs` operator imports the namespaces of an R package (or a small set of R packages that "belong" to each other) under the same alias.

The `import_data(dataname, package)` function gets a specified data set from a package.

Unlike `utils::data()`, `import_data()` returns the dataset directly, and allows assigning the dataset like so:

```
mydata <- import_data(...).
```

The `force_libPaths()` function allows the user to force R to specific libraries. This was needed since base R's `.libPaths()` function only allows adding new library paths, not overwrite existing ones. The library paths are of course re-set again every time R restarts.

**Usage**

```
alias %m import <-% pkgs
```

```
import_data(dataname, package)
```

```
force_libPaths(lib_vec)
```

**Arguments**

<code>alias</code>	a variable name (unquoted), giving the (not yet existing) object where the package(s) are to be assigned to.
<code>pkgs</code>	a character vector with the package name(s). NOTE: The order matters! If 2 packages share objects with the same name, the package named last will overwrite the earlier named package.
<code>dataname</code>	a single string, giving the name of the dataset.
<code>package</code>	a single string, giving the name of the package.
<code>lib_vec</code>	a character vector giving the new library path(s). Just like in <code>.libPaths()</code> , the order matters: R will first look for packages in the first path in <code>.libPaths()</code> , and if it cannot find the package(s), it will look for the packages in the second path in <code>.libPaths()</code> , etc.

## Details

The `alias %m import <-% pkgs` command is essentially the same as `alias <- loadNamespace("packagename")` except the `alias %m import <-% pkgs` operator allows assigning multiple packages to the same alias, and this operator does not import internal functions (i.e. internal functions are kept internal, as they should).

The `alias %m import <-% pkgs` operator will tell the user about conflicting objects. It will also inform the user when importing a package that consists mostly of infix operators.

Note: the user should not use the `alias %m import <-% pkgs` operator unless the user knows what he/she is doing.

The operator will give a warning when more than 3 packages being imported into the same alias.

## Value

For `%m import <-%`:

The variable named in the `alias` argument will be created (if it did not already exist), and it will contain the (merged) package environment.

For `import_data()`:

Returns the data directly. Thus, one can assign the data like so: `mydata <- import_data(...)`.

For `force_libPaths()`:

Adjusts the R library paths as defined in `.libPaths()` directly.

## References

McBain (2019, June 20). Before I Sleep: Hacking R's library paths. Retrieved from <https://milesmcBain.com/posts/hacking-r-library-paths/>

## Examples

```
## Not run:
force_libPaths("/mylibrary")
fv %m import <-% c("data.table", "collapse", "tidytable")
d <- import_data("chicago", "gamair")

## End(Not run)
```

---

stri\_join\_mat

Concatenate Character Matrix Row-wise or Column-wise

---

## Description

The `stri_join_mat()` function (and their aliases `stri_c_mat` and `stri_paste_mat`) perform row-wise (`margin=1`; the default) or column-wise (`margin=2`) joining of a matrix of strings, thereby transforming a matrix of strings into a vector of strings.

**Usage**

```
stri_join_mat(mat, margin = 1, sep = "", collapse = NULL)

stri_c_mat(mat, margin = 1, sep = "", collapse = NULL)

stri_paste_mat(mat, margin = 1, sep = "", collapse = NULL)
```

**Arguments**

mat	a matrix of strings
margin	the margin over which the strings must be joined. If margin=1, the elements in each row of matrix mat are joined into a single string. Thus if the matrix has 10 rows, it returns a vector of 10 strings. If margin=2, the elements in each column of matrix mat are joined into a single string. Thus if the matrix has 10 columns, it returns a vector of 10 strings.
sep, collapse	as in <a href="#">stri_join</a> .

**Details**

The examples section show the uses of the `stri_join_mat()` function.

**Value**

The `stri_join_mat()` function, and its aliases, return a vector of strings.

**Examples**

```
# re-ordering characters in strings ====

x <- c("Hello world", "Goodbye world")
print(x)
mat <- stringi::stri_split_boundaries(x, simplify = TRUE, type="character")
rank <- stringi::stri_rank(as.vector(mat)) |> matrix(ncol=ncol(mat))
sorted <- mat %row~% rank
print(sorted)
stri_join_mat(sorted, margin=1)
stri_join_mat(sorted, margin=2)

#####

# re-ordering words ====

x <- c("Hello everyone", "Goodbye everyone")
print(x)
mat <- stringi::stri_split_boundaries(x, simplify = TRUE, type="word")
rank <- stringi::stri_rank(as.vector(mat)) |> matrix(ncol=ncol(mat))
sorted <- mat %row~% rank
print(sorted)
stri_c_mat(sorted, margin=1) # <- alias for stri_join_mat
stri_c_mat(sorted, margin=2)

#####
```

```
# re-ordering sentences ====

x <- c("Hello, who are you? Oh, really?! Cool!", "I don't care. But I really don't.")
print(x)
mat <- stringi::stri_split_boundaries(x, simplify = TRUE, type="sentence")
rank <- stringi::stri_rank(as.vector(mat)) |> matrix(ncol=ncol(mat))
sorted <- mat %row~% rank
print(sorted)
stri_paste_mat(sorted, margin=1) # <- another alias for stri_join_mat
stri_paste_mat(sorted, margin=2)
```

---

stri_locate_ith	<i>Locate <math>i^{th}</math> Pattern Occurrence</i>
-----------------	--

---

## Description

The `stri_locate_ith` function locates the  $i^{th}$  occurrence of a pattern in each string of some character vector.

## Usage

```
stri_locate_ith(str, i, ..., regex, fixed, coll, charclass, simplify = FALSE)
```

## Arguments

<code>str</code>	a string or character vector.
<code>i</code>	<p>a number, or a numeric vector of the same length as <code>str</code>. This gives the <math>i^{th}</math> instance to be replaced.</p> <p>Positive numbers are counting from the left. Negative numbers are counting from the right. I.e.:</p> <p><code>stri_locate_ith(str, i=1, ...)</code> gives the position (range) of the first occurrence of a pattern.</p> <p><code>stri_locate_ith(str, i=-1, ...)</code> gives the position (range) of the last occurrence of a pattern.</p> <p><code>stri_locate_ith(str, i=2, ...)</code> gives the position (range) of the second occurrence of a pattern.</p> <p><code>stri_locate_ith(str, i=-2, ...)</code> gives the position (range) of the second-last occurrence of a pattern.</p> <p>If <code>abs(i)</code> is larger than the number of instances, the first (if <code>i &lt; 0</code>) or last (if <code>i &gt; 0</code>) instance will be given.</p> <p>For example: suppose a string has 3 instances of some pattern;</p> <p>then if <code>i &gt;= 4</code> the third instance will be located,</p> <p>and if <code>i &lt;= -3</code> the first instance will be located.</p>
<code>...</code>	more arguments to be supplied to <a href="#">stri_locate</a> and <a href="#">stri_count</a> .
<code>regex, fixed, coll, charclass</code>	a character vector of search patterns, as in <a href="#">stri_locate</a> .
<code>simplify</code>	either TRUE or FALSE (default = FALSE):



- If FALSE, stri\_locate\_ith returns a list, usable in the [stri\\_sub\\_all](#) functions (for example: to transform all matches).
- If TRUE, stri\_locate\_ith returns an integer matrix of positions and lengths.

## Value

If simplify = FALSE, stri\_locate\_ith returns a list, one element for each string. Each list element consists of a matrix with 2 columns and one row:

The first column gives the start position of the  $i^{th}$  occurrence of the pattern.

The second column gives the end position of the  $i^{th}$  occurrence of the pattern.

When simplify=FALSE, the results can be used in the from argument in the [stri\\_sub\\_all](#) functions, for example to transform the  $i^{th}$  matches (see examples section below).

If simplify = TRUE (default), stri\_locate\_ith this returns an integer matrix with 3 columns:

The first column gives the start position of the  $i^{th}$  occurrence of the pattern.

The second column gives the end position of the  $i^{th}$  occurrence of the pattern.

The third column gives the length of the position range of the  $i^{th}$  occurrence of the pattern.

If no matches are found in a string, NA is filled in for the start and end positions (and length).

## Examples

```
# simple pattern ====
```

```
x <- rep(paste0(1:10, collapse=""), 10)
print(x)
out <- stri_locate_ith(x, 1:10, regex = as.character(1:10), simplify=TRUE)
cbind(1:10, out)
```

```
x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
p <- rep("a|e|i|o|u", 2)
out <- stri_locate_ith(x, c(-1, 1), regex=p, simplify=TRUE)
print(out)
substr(x, out[,1], out[,2])
```

```
#####
```

```
# ignore case pattern ====
```

```
x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
p <- rep("A|E|I|O|U", 2)
out <- stri_locate_ith(x, c(1, -1), regex=p, case_insensitive=TRUE, simplify=TRUE)
substr(x, out[,1], out[,2])
```

```
#####
```

```
# multi-character pattern ====

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
# multi-character pattern:
p <- rep("AB", 2)
out <- stri_locate_ith(x, c(1, -1), regex=p, simplify=TRUE, case_insensitive=TRUE)
print(out)
substr(x, out[,1], out[,2])

#####

# Replacement transformation using stringi ====

x <- c("hello world", "goodbye world")
loc <- stri_locate_ith(x, c(1, -1), regex="a|e|i|o|u", simplify = FALSE)
extr <- stringi::stri_sub_all(x, from=loc)
repl <- lapply(extr, \(x)chartr(x, old = "a-zA-Z", new = "A-Za-z"))
stringi::stri_sub_all_replace(x, loc, replacement=repl)
```

---

str\_arithmetic

*String arithmetic*


---

## Description

String arithmetic operators.

The `x %s+% y` operator is equivalent to `stringi::stri_c(x,y)`.

The `x %s-% p` operator removes character/pattern defined in `p` from `x`.

The `x %s*% n` operator repeats every element of `x` for `n` times, and glues them together.

The `x %s/% p` operator counts how often regular expression or character pattern `p` occurs in each element of `x`.

## Usage

`x %s+% y`

`x %s-% p`

`x %s*% n`

`x %s/% p`

**Arguments**

x	a string or character vector.
y	a string, or a character vector of the same length as x.
p	the result from <a href="#">s_pattern</a> , or else a character vector of the same length as x with regular expressions.
n	a number, or a numeric vector of the same length as x.

**Details**

These operators and functions serve as a way to provide straight-forward string arithmetic, missing from base R.

**Value**

The %s+%, %s-%, and %s\*% operators return a character vector of the same length as x.  
The %s/% returns a integer vector of the same length as x.

**Examples**

```
x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
y <- c("a", "b")
p <- rep("a|e|i|o|u", 2) # same as p <- s_pattern(regex=rep("a|e|i|o|u", 2))
n <- c(3, 2)

x %s+% y # =paste0(x,y)
x %s-% p # remove all vowels from x
x %s*% n
x %s/% p # count how often vowels appear in each string of vector x.
```

#####

```
x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
y <- "a"
# pattern that ignores case:
p <- s_pattern(regex=rep("A|E|I|O|U", 2), ignore.case=TRUE)
n <- c(2, 3)

x %s+% y # =paste0(x,y)
x %s-% p # remove all vowels from x
x %s*% n
x %s/% p # count how often vowels appears in each string of vector x.
```

**Description**

String subsetting operators.

The `x %ss% s` operator allows indexing a single string as-if it is an iterable object.

The `x %sget% ss` operator gives a certain number of the first and last characters of `x`.

The `x %strim% ss` operator removes a certain number of the first and last characters of `x`.

**Usage**

```
x %ss% s
```

```
x %sget% ss
```

```
x %strim% ss
```

**Arguments**

<code>x</code>	a string or character vector.
<code>s</code>	a numeric vector giving the subset indices.
<code>ss</code>	a vector of length 2, or a matrix with 2 columns with <code>nrow(ss)==length(x)</code> . The object <code>ss</code> should consist entirely of non-negative integers (thus 0, 1, 2, etc. are valid, but -1, -2, -3 etc are not valid). The first element/column of <code>ss</code> gives the number of characters counting from the left side to be extracted/removed from <code>x</code> . The second element/column of <code>ss</code> gives the number of characters counting from the right side to be extracted/removed from <code>x</code> .

**Details**

These operators serve as a way to provide straight-forward string sub-setting.

**Value**

The `%ss%` operator always returns a vector or matrix, where each element is a single character.

**Examples**

```
x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
ss <- c(2,3)
```

```

x %sget% ss

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
ss <- c(1,0)
x %sget% ss

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
ss <- c(2,3)
x %strim% ss

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
ss <- c(1,0)
x %strim% ss

```

---

substr\_repl

*Sub-string functions*


---

## Description

Fully vectorized sub-string functions.

These functions extract, replace, add-in, transform, or re-arrange, the  $i^{th}$  pattern occurrence or position range.

The `substr_repl(x, rp, ...)` function replaces a position (range) with string `rp`.

The `substr_chartr(x, old, new, ...)` function transforms the sub-string at a position (range) using `chartr(old, new)`.

The `substr_addin(x, addition, side, ...)` function adds the additional string addition at the side (specified by argument `side`) of a position.

The `substr_extract(x, type, ...)` function extracts the string at, before, or after some position.

The `substr_arrange(x, arr, ...)` function sorts (alphabetically or reverse-alphabetically) or reverses the sub-string at a position (range).

**Usage**

```
substr_repl(x, rp, ..., loc = NULL, start = NULL, end = NULL, fish = FALSE)
```

```
substr_chartr(
  x,
  old = "a-zA-Z",
  new = "A-Za-z",
  ...,
  loc = NULL,
  start = NULL,
  end = NULL,
  fish = FALSE
)
```

```
substr_addin(
  x,
  addition,
  side = "after",
  ...,
  loc = NULL,
  at = NULL,
  fish = FALSE
)
```

```
substr_extract(
  x,
  type = "at",
  ...,
  loc = NULL,
  start = NULL,
  end = NULL,
  fish = FALSE
)
```

```
substr_arrange(
  x,
  arr = "incr",
  ...,
  loc = NULL,
  start = NULL,
  end = NULL,
  opts_collator = NULL,
  fish = FALSE
)
```

**Arguments**

<code>x</code>	a string or character vector.
<code>rp</code>	a string, or a character vector of the same length as <code>x</code> , giving the replacing strings.
<code>...</code>	only applicable if <code>fish=TRUE</code> ; other arguments to be passed to the <code>stringfish</code> functions.

loc	The result from the <a href="#">stri_locate_ith</a> function. It does not matter if the result is in the list form ( <code>simplify = FALSE</code> ), or in the matrix form ( <code>simplify = TRUE</code> ). See <a href="#">stri_locate_ith</a> . NOTE: you cannot fill in both <code>loc</code> and <code>start</code> , <code>end</code> , or both <code>loc</code> and <code>at</code> . Choose one or the other.
start, end	integers, or integer vectors of the same length as <code>x</code> , giving the start and end position of the range to be modified.
fish	although <code>tidyoperators</code> has no dependencies other than <code>stringi</code> , it does allow the internal functions to use the multi-threadable <code>stringfish</code> functions. To do so, set <code>fish=TRUE</code> ; this requires <code>stringfish</code> to be installed.
old, new	see <a href="#">chartr</a> . Defaults to <code>old="a-zA-Z"</code> , <code>new="A-Za-z"</code> , which means upper case characters will be transformed to lower case characters, and vice-versa.
addition	a string, or a character vector of the same length as <code>x</code> , giving the string(s) to add-in.
side	which side of the position to add in the string. Either "before" or "after".
at	an integer, or integer vector of the same length as <code>x</code> .
type	a single string, giving the part of the string to extract. 3 options available: <ul style="list-style-type: none"> <li>• <code>type = "at"</code>: extracts the string part at the position range;</li> <li>• <code>type = "before"</code>: extracts the string part before the position range;</li> <li>• <code>type = "after"</code>: extracts the string part after the position range.</li> </ul>
arr	a single string, giving how the sub-string should be arranged. 3 options available: <ul style="list-style-type: none"> <li>• <code>arr = "incr"</code>: sort the sub-string alphabetically.</li> <li>• <code>arr = "decr"</code>: sort the sub-string reverse alphabetically.</li> <li>• <code>arr = "rev"</code>: reverse the sub-string.</li> <li>• <code>arr = "rand"</code>: randomly shuffles the sub-string.</li> </ul>
opts_collator	as in <a href="#">stri_rank</a> . Only used when <code>arr = "incr"</code> or <code>arr = "decr"</code> .

## Details

These functions serve as a way to provide straight-forward sub-string modification and/or extraction.

All `substr_` functions internally only use fully vectorized R functions (no loops or apply-like functions).

## Value

A modified character vector. If no match is found in a certain string of character vector `x`, the unmodified string is returned. The exception is for the `substr_extract()` function: in this function, non-matches return NA.

## Examples

```
# numerical substr ====

x <- rep("12345678910", 2)
start=c(1, 2); end=c(3,4)
substr_extract(x, start=start, end=end)
substr_extract(x, type="before", start=start, end=end)
substr_extract(x, type="after", start=start, end=end)
substr_repl(x, c("??", "!!"), start=start, end=end)
substr_chartr(x, start=start, end=end)
substr_addin(x, c(" ", "~"), "after", at=end)
substr_addin(x, c(" ", "~"), "before", at=start)
substr_arrange(x, start=start, end=end)
substr_arrange(x, "decr", start=start, end=end)
substr_arrange(x, "rev", start=start, end=end)
substr_arrange(x, "rand", start=start, end=end)

start=10; end=11
substr_extract(x, start=start, end=end)
substr_extract(x, type="before", start=start, end=end)
substr_extract(x, type="after", start=start, end=end)
substr_repl(x, "??", start=start, end=end)
substr_chartr(x, start=start, end=end)
substr_addin(x, " ", "after", at=end)
substr_addin(x, " ", "before", at=start)

start=5; end=6
substr_extract(x, start=start, end=end)
substr_extract(x, type="before", start=start, end=end)
substr_extract(x, type="after", start=start, end=end)
substr_repl(x, "??", start=start, end=end)
substr_chartr(x, start=start, end=end)
substr_addin(x, " ", "after", at=end)
substr_addin(x, " ", "before", at=start)

#####

# simple pattern ====

x <- c("goodGOODGoodgO0d", "goodGOODGoodgO0d", paste0(letters[1:13], collapse=""))
print(x)
loc <- stri_locate_ith(
  # locate second-last occurrence of "good" of each string in x:
  x, -2, regex="good", case_insensitive=TRUE
)
substr_extract(x, loc=loc) # extract second-last "good"
substr_repl(x, c("??", "!!", " "), loc=loc) # replace second-last "good"
substr_chartr(x, loc=loc) # switch upper/lower case of second-last "good"
substr_addin(x, c(" ", "~", " "), "after", loc=loc) # add white space after second-last "good"
substr_addin(x, c(" ", "~", " "), "before", loc=loc) # add white space before second-last "good"
substr_arrange(x, loc=loc) # sort second-last "good"
substr_arrange(x, "decr", loc=loc) # reverse-sort second-last "good"
substr_arrange(x, "rev", loc=loc) # reverse second-last "good"
substr_arrange(x, "rand", loc=loc) # randomly shuffles "good"
```



s\_pattern

*Pattern attribute assignment***Description**

The %s-% and %s/% operators, their in-place equivalents, as well as the %sgrep% operator, all perform pattern matching for some purpose. By default the pattern matching is interpreted as case-sensitive regex patterns from `stringi`.

The `s_pattern` function allows the user to specify exactly how the pattern should be interpreted. To use more refined pattern definition, simply replace the right-hand-side expression `p` in the relevant operators with a call from the `s_pattern()` function.

The `s_pattern()` function uses the exact same argument convention as `stringi`. For example:

- `s_pattern(regex=p, case_insensitive=FALSE, ...)`
- `s_pattern(fixed=p, ...)`
- `s_pattern(coll=p, ...)`
- `s_pattern(charclass=p, ...)`

All arguments in `s_pattern()` are simply passed to the appropriate functions in `stringi`.

For example:

`x %s/% p` counts how often regular expression `p` occurs in `x`,

whereas `x %s/% s_pattern(fixed=p, case_insensitive=TRUE)` will do the same, except it uses fixed (i.e. literal) expression, and it does not distinguish between upper case and lower case characters.

For consistency with base R and with packages such as `stringr`, one can also fill in `ignore.case=TRUE` or `ignore_case=TRUE` instead of `case_insensitive=TRUE`, and `s_pattern` will still understand that.

**Usage**

```
s_pattern(...)
```

**Arguments**

... pass `stringi` arguments here. I.e. `regex=p, coll=p, charclass=p, case_insensitive=FALSE`, etc. See the documentation in the `stringi` R package.

**Details**

The `s_pattern()` function only works in combination with the functions and operators in this package. It does not affect functions from base R or functions from other packages.

**Value**

The `s_pattern(...)` call returns a list with arguments that will be passed to the appropriate functions in `stringi`.

## Examples

```
x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
p <- rep("a|e|i|o|u", 2) # same as p <- s_pattern(regex=rep("a|e|i|o|u", 2))
x %s/% p # count how often vowels appear in each string of vector x.

x <- c(paste0(letters[1:13], collapse=""), paste0(letters[14:26], collapse=""))
print(x)
p <- s_pattern(regex=rep("A|E|I|O|U", 2), case_insensitive=TRUE)
x %s/% p # count how often vowels appear in each string of vector x.
```

---

tidyoperators\_help

*The tidyoperators help page*

---

## Description

Welcome to the tidyoperators help page!

The 'tidyoperators' R-package adds some much needed infix operators, and a few functions, to make your R code much more tidy. It includes infix operators for additional logic operators, safer float (in)equality operators, and infix operators for custom row- and column-wise ordering of matrices. It also adds some stringi-based string related functions and operators. It also adds operators and a few functions to help reduce unnecessary repetitive code. And finally, it also adds some functions and an operator for easier package/library management. The 'tidyoperators' R-package has only one dependency, namely 'stringi', though it does allow multi-threading of some of the string-related functions (when appropriate) via the suggested 'stringfish' R-package.

The tidyoperators R package adds the following functionality:

- [Infix logical operators](#) for exclusive-or, not-and, not-in, number-type, and string-type.
- [Safer \(in\)equality operators for floating numbers](#).
- Infix operators for [In-place modifiers for mathematical arithmetic](#).
- Infix operators for [string arithmetic](#).
- Infix operators for [string sub-setting](#).
- Infix operators for [In-place modifying string arithmetic](#).
- Infix operators for [In-place modifying string sub-setting](#).
- [Infix operators for row- and column-wise rank-based re-ordering of matrices](#).

- The tidyoperators package adds additional stringi functions, namely `stri_locate_ith` and `stri_join_mat` (and aliases). These functions use the same naming and argument convention as the rest of the stringi functions, thus keeping your code consistent.
- The fully vectorized `sub-string functions`, that extract, replace, add-in, transform, or re-arrange, the ith pattern occurrence or location.
- The `s_pattern` helper function for string operators.
- The `transform_if` function, and some related infix operators.
- [A new package import management operator and function.](#)
- Most stringi pattern expressions options are available for the string-pattern-related functions, when appropriate.
- This R package has only one dependency: stringi. No other dependencies, as to avoid "dependency hell".
- Although this package has no other dependencies, it allows multi-threading of functions (when appropriate) through third-party packages (like stringfish).

Please also have a look at the Read-Me file on the Github main page before using this package:  
<https://github.com/tony-aw/tidyoperators>

## Usage

```
tidyoperators_help()
```

---

transform_if	<i>The transform_if function and the subset_if operators</i>
--------------	--

---

## Description

Consider the following code:

```
x[cond(x)] <- trans(x[cond(x)])
```

Here a conditional subset of the object `x` is transformed with function `trans`, where the condition is using a function referring to `x` itself (namely `cond(x)`). Consequently, reference to `x` is written four times!

The tidyoperators package therefore adds the `transform_if()` function which will tidy this up.

```
x <- transform_if(x, cond, trans)
```

is exactly equivalent to

```
x[cond(x)] <- trans(x[cond(x)])
```

The tidyoperators package also adds 2 "subset\_if" operators:

The `x %[if]% cond` operator selects elements from vector/matrix/array `x`, for which the result of

cond(x) returns TRUE.

The x %[!if]% cond operator selects elements from vector/matrix/array x, for which the result of cond(x) returns FALSE.

The tidyoperators package also adds the x %unreal <-% repl operator:

x %unreal <-% repl is the same as x[is.na(x)|is.nan(x)|is.infinite(x)] <- repl

## Usage

```
transform_if(x, cond, trans = NULL)
```

```
x %[if]% cond
```

```
x %[!if]% cond
```

```
x %unreal <-% repl
```

## Arguments

x	a vector, matrix, or array.
cond	a function that returns a binary logic (TRUE, FALSE) vector of the same length/dimensions as x (for example: is.na).

- Elements of x for which cond(x)==TRUE are transformed / selected;
- Elements of x for which cond(x)==FALSE are not transformed /selected.

trans	the transformation function to use. For example: log.
repl	the replacement value.

## Details

The transform\_if(x, cond, trans) function does not rely on any explicit or implicit loops, nor any third-party functions.

## Value

The transform\_if() function returns the same object x, with the same dimensions, except with the subset transformed.

Note that this function **returns** object x, to modify x directly, one still has to assign it. To keep your code tidy, consider combining this function with magrittr's in-place modifying piper-operator (%<>%). I.e.:

```
very_long_name_1 %<>% transform_if(cond, trans)
```

The subset\_if - operators all return a vector with the selected elements.

The x %unreal <-% repl operator does not return any value:

it is an in-place modifiers, and thus modifies x directly. The object x is modified such that all NA, NaN and Inf elements are replaced with repl.

**Examples**

```
object_with_very_long_name <- matrix(-10:9, ncol=2)
print(object_with_very_long_name)
object_with_very_long_name |> transform_if(\(x)x>0, log)
object_with_very_long_name %[if]% \(\(x)x %in% 1:10
object_with_very_long_name %[!if]% \(\(x)x %in% 1:10

x <- c(1:9, NA, NaN, Inf)
print(x)
x %unreal <- 0 # same as x[is.na(x)|is.nan(x)|is.infinite(x)] <- 0
print(x)
```

# Index

## \* **join\_mat**

stri\_join\_mat, 14  
%\* <-% (inplace\_math), 4  
%+ <-% (inplace\_math), 4  
%- <-% (inplace\_math), 4  
%/ <-% (inplace\_math), 4  
%=numtype% (logic\_ops), 9  
%=strtype% (logic\_ops), 9  
%?=% (logic\_ops), 9  
%[!if]% (transform\_if), 27  
 %[if]% (transform\_if), 27  
%^ <-% (inplace\_math), 4  
%alogb <-% (inplace\_math), 4  
%col~% (matrix\_ops), 11  
%f!=% (float\_logic), 2  
%f<=% (float\_logic), 2  
%f<% (float\_logic), 2  
%f==% (float\_logic), 2  
%f>=% (float\_logic), 2  
%f>% (float\_logic), 2  
%logb <-% (inplace\_math), 4  
%m import <-% (pkgs), 13  
%n&% (logic\_ops), 9  
%out% (logic\_ops), 9  
%row~% (matrix\_ops), 11  
%rt <-% (inplace\_math), 4  
%s\* <-% (inplace\_str\_arithmetic), 6  
%s\*% (str\_arithmetic), 18  
%s+ <-% (inplace\_str\_arithmetic), 6  
%s+% (str\_arithmetic), 18  
%s- <-% (inplace\_str\_arithmetic), 6  
%s-% (str\_arithmetic), 18  
%s/ <-% (inplace\_str\_arithmetic), 6  
%s/% (str\_arithmetic), 18  
%sget <-% (inplace\_str\_subset), 7  
%sget% (str\_subset\_ops), 20  
%sgrep% (logic\_ops), 9  
%ss% (str\_subset\_ops), 20  
%strim <-% (inplace\_str\_subset), 7  
%strim% (str\_subset\_ops), 20  
%unreal <-% (transform\_if), 27  
%xor% (logic\_ops), 9

A new package import management

operator and function, 27

chartr, 23

float\_logic, 2

force\_libPaths (pkgs), 13

import\_data (pkgs), 13

In-place modifiers for mathematical  
arithmetic, 26

In-place modifying string arithmetic,  
26

In-place modifying string sub-setting,  
26

Infix logical operators, 26

Infix operators for row- and  
column-wise rank-based  
re-ordering of matrices, 26

inplace\_math, 4

inplace\_str\_arithmetic, 6

inplace\_str\_subset, 7

Logic, 9

logic\_ops, 9

matrix\_ops, 11

pkgs, 13

s\_pattern, 6, 9, 19, 25, 27

Safer (in)equality operators for  
floating numbers, 26

str\_arithmetic, 18

str\_subset\_ops, 20

stri\_c\_mat (stri\_join\_mat), 14

stri\_count, 16

stri\_join, 15

stri\_join\_mat, 14, 27

stri\_locate, 16

stri\_locate\_ith, 16, 23, 27

stri\_paste\_mat (stri\_join\_mat), 14

stri\_rank, 23

stri\_sub\_all, 17

string arithmetic, 6, 26

string sub-setting, 26

string subset, [8](#)  
sub-string functions, [27](#)  
substr\_addin(substr\_repl), [21](#)  
substr\_arrange(substr\_repl), [21](#)  
substr\_chartr(substr\_repl), [21](#)  
substr\_extract(substr\_repl), [21](#)  
substr\_repl, [21](#)  
  
tidyoperators\_help, [26](#)  
transform\_if, [27](#), [27](#)