



servocylinder

ultramotion.com/servo-cylinder-datasheet

servocylinder

Standard - Series A1

STEP



3D CAD Model with Mounting Options

Part Number:


A1CZ9A-B0M1E0

The A1 Series.

Weights:

A1CZ9A: 2.91 lbs

M1: 0.35 lbs




Standard Servo Cylinder

The A1 Series actuator is our standard Servo Cylinder model. It is best suited to cleaner indoor environment, and is available at a lower cost than our other sealed models.


- IP50 Environmental protection
- Molex Micro-fit Connector

PERFORMANCE

Z9 Performance - 24 Volts



Life vs. Load, Servo Cylinder Ballscrews




Z (Standard Ball Screw) model features:

- High efficiency 1/8" lead ball screw with single length nut
- This screw/nut combination will backdrive against a load of ~10 lbf, without power
- Speeds to 14 in/s
- Forces to 170 lbf (continuous), 340 lbf (peak)
- Standard axial backlash <0.005"
- [Contact Ultra Motion](#) for applications requiring >10,000,000 inches of travel


DIMENSIONS

1.75" Stroke, 100W Motor
A1Z9A



[illegible][illegible]

3/4



No.	Pin for "C" Controller	Flying Lead Color (CBL-S-AV/AC-D) For "N" Controller only	Flying Lead Color (CBL-A1DEV)
1	CAN_L	GREEN	WHITE
2	GND	BLACK	BROWN
3	TRX-	GREEN (DB9)	GREEN
4	IN1+	PURPLE	VIOLET
5	IN2+	GREY	GRAY
6	IN3+	BLUE	BLUE
7	V+	RED (Spade Terminal)	RED (Spade Terminal)
8	V+	RED (Spade Terminal)	RED (Spade Terminal)
9	CAN_H	GREEN	RED
10	GND	RED (DB9)	BLACK
11	TRX+	YELLOW (DB9)	YELLOW
12	IN1-	ORANGE	ORANGE
13	IN2-	GREYW/ WHITE	PINK
14	IN3-	BLUEW/ WHITE	TAN
15	GND	BLACK (Spade Terminal)	BLACK (Spade Terminal)
16	GND	BLACK (Spade Terminal)	BLACK (Spade Terminal)

Chat directly with one of our engineers.

Email will be replied to within one business day.

888-321-9178
631-298-9179
Fax: 631-298-6593

Ultra Motion
22355 County Road 48
Unit 21
Cutchogue, NY 11935

Our business hours:
Monday - Friday
9AM - 5PM EST

© Ultra Motion 1994 - 2025