



section a-a

- 1 custom orb, corrugated iron, colour bond
- 2 100 x 50 mm hdwd battens at 900 crs. (on edge)
- 3 50 mm roll fibreglass insulation with sisilation.
- 4 19 mm timber ceiling
- 5 275 x 75 millsawn oregon rafters
- 6 beam - ex sec pole. 300 diam.
- 7 oregon millsawn fascias—250 x 50 under gutters  
—350 x 50 without gutters
- 8 zincalume guttering
- 9 capping
- 10 sec. pole as posts.
- 11 ballustrade 200 x 50 mm
- 12 275 x 75 rafter.
- 13 packer above rafter 175 x 75
- 14 100 mm stud wall.
- 15 19 mm t&g timber floor.
- 16 150 x 50 mm oregon floor joists
- 17 brick floor
- 18 25 mm mortar bed
- 19 waterproof membrane
- 20 50 mm packing sand
- 21 100 mm concrete slab in bathroom
- 22 waterproof membrane
- 23 50 mm packing sand
- 24 525 x 350 mm footing with two layers F11 trench mesh, top & bottom.
- 25 400 x 400 x 400 deep isolated concrete pad under post.
- 26 layout brickwork containing dpc's etc.

- .f - fixed
  - d - glass door
  - fl - fanlight
    - cross indicates flywire screen
  - dp - down pipe
  - p - posts
- ⇒ spray under floor for termites etc.,  
as per council regs.
- ⇒ check dimensions prior to start

KNOX- studio    SHOREHAM

design Alistair Knox & associates  
mt Pleasant rd Eltham 439 7404

drawn Danny  
date february 1985  
scales 1:100 1:50

Job № 1232