
1) <u>1:1</u>



X(K1, K2, A1) (K2 needs to be unique)


Y(<u>K2</u>, A2)

or

X(<u>K1</u>, A1)

Y(<u>K2</u>, **K1**, A2) (K1 needs to be unique)


2) <u>1:M</u>



X(<u>K1</u>, A1)

Y(<u>K2</u>, **K1**, A2)

3) M:N (Binary Relationship)




X(<u>K1</u>, A1)

Y(<u>K2</u>, A2)

R(**K1**, **K2**, A3)

4) M:N (Ternary Relationship)




X(<u>K1</u>, A1)

Y(<u>K2</u>, A2)

Z(<u>K3</u>, A3)


R(**K1**, **K2**, **K3**, A4)

5) <u>1:M Entity with Total Participation</u>




X(<u>K1</u>, A1) Y(**K1**, <u>K2</u>, A2) (K1 cannot be null)

6) 1:M Weak Entity with Total Participation (assume that A2 is the partial key)




X(<u>K1</u>, A1) Y(<u>**K1**</u>, <u>A2</u>, A3)

7) 1:1 and 1:M Unary Relationship



 $X(\underline{K1}, A1, K2)$ (if it is 1:1, then we require K2 to be unique) OR $X(\underline{R1-K1}, A1, \mathbf{R2-K1})$ (if it is 1:1, then we require R2-K1 to be unique)

8) M:N Unary Relationship



X(<u>K1</u>, A1)


R(<u>**K1**</u>, <u>**K2**</u>)

OR

X(<u>R1-K1</u>, A1)

R(<u>**R1-K1**, **R2-K1**</u>)

9) <u>ISA 1</u>




X(<u>K1</u>, A1)

Y(**K1**, A2, A3)

Z(**K1**, A4, A5)

10) ISA 2 (the "d" means disjoint)



Y(<u>K1</u>, A1, A2, A3)

Z(<u>K1</u>, A1, A4, A5)

K1 is not bolded because it is not a foreign key in our case. Although Y and Z are "subclasses" of X, we do **not** create table X. Hence, K1 is not bolded.