Normal Touch and Go Circuits

In-Flight Reference Card — Phase 2 — Stage C2A | E8, E11, E12

AIM: Land from a powered approach and conduct touch-and-go circuits to solo standard.

- [ ] DP **Circuit 1**: Instructor demos to landing and T&G; student follows through; patter aiming point, gate, hold-off, T&G sequence
- [ ] P **Circuit pattern**: Established in C1, continue practice; BUMPFISH and radio without prompting
- [ ] P **Approach**: ***Power*** is primary path control; airspeed with attitude; 70 kt, flap 2, 3000 RPM
- [ ] P **Gate at 300 ft**: Verbalise "stable" every circuit; go-around if unstable
- [ ] P **Hold-off**: Level attitude ***over*** aiming point, still descending; shift focus to far end; progressive backpressure until touchdown attitude; hold to touchdown; lower nosewheel gently
- [ ] P **TGL**: ***Flap before power***; trim; full power; takeoff
- [ ] P **Go-around**: Min one per session student-initiated; any time gate not met

AIMING POINT REFERENCE

- **Rises** -> too low; add power
- **Drops** -> too high; reduce power
- **Wind gradient** -> prepared for sudden sink on short final
- **Ground effect** -> may cause float; do not force touchdown

COMMON ERRORS

- **High and fast** -> PAT — power and attitude together
- **Hold-off too early** -> Balloon; consistent visual trigger
- **Bounce/balloon** -> Go-around **always**; no salvage
- **T&G rushed** -> Flap before power — every time

STANDARDS FOR PROGRESSION

P S C NC

Progressing (P): Gate with occasional prompting; ASI +10/-5 kt; touchdown –50/+250 m; prompting still needed for go-arounds; control intervention no longer required

Solo (S) — two separate flights: Gate without prompting; ASI +5/-0 kt; touchdown –0/+100 m; TGL with correct technique independently; go-around decisions made independently with no prompting

⚠️ **SAFETY** Ceiling **>1500 ft AGL** · Wind <15 kt · Crosswind <5 kt · Take control if approach unstable below 200 ft · monitor fatigue