Scenario Based Stalling

In-Flight Reference Card — Phase 3 — Lesson 10 | E10

AIM: Identify and recover from stalls in all configurations with emphasis on realistic circuit and departure scenarios.

- [ ] P **Departure/transit/aerodrome arrival**: Student as PIC
- [ ] DP **HASSELL**: Demo; student completes — ***repeat every 15 minutes***
- [ ] P **S&L stalls**: Clean, approach, landing configs — ***(known from L06; practice only)***
- [ ] DP **Climb stall (50% power)**: Demo symptoms; student identifies and recovers
- [ ] DP **Descent stall**: Demo — note lower nose attitude makes recognition harder; student practices
- [ ] DP **Turning stall 30°**: Outer wing stalls; wing drop; ***rudder stops roll, ailerons neutral***; student practices
- [ ] D **Slipping turn stall 30°**: Increased outer wing AoA; wing drop; recovery demo only
- [ ] DP **Go-around scenario**: Full flap; demo to pre-stall only; student prevents stall on “recover” prompt
- [ ] DP **EFATO scenario**: Power to idle on upwind; demo fixation on landing area; student practices
- [ ] DP **Elevator trim stall**: Trim nose-up, full power — rapid pitch-up; push against trim, reduce power if needed, retrim; student practices
- [ ] D **Spin entry awareness**: Above Va only; patter entry conditions; recover immediately

COMMON ERRORS

- **Aileron on wing drop** -> Rudder first; ailerons neutral until unstalled
- **Aggressive pitch in go-around** -> Set attitude and wait; don’t chase airspeed
- **Backpressure in EFATO** -> Accept the descent; natural stability
- **Aerobatics** -> Do not stall with aggressive nose up pitch and high power settings. +25° pitch limit >5000 RPM

STANDARDS FOR PROGRESSION

P S C NC

Progressing (P): Symptoms before full stall in >=2 scenarios; recovery with minor prompting
C standard: All configs at onset; <=300 ft; turning stall — rudder on drop; scenarios without instructor input; HASSELL every 15 min **Note: L06 + L10 = two-flight stalling requirement satisfied**

⚠️ **SAFETY Smooth air required** · **Above 2500 ft AGL** · All recoveries above 2500 ft AGL · Pro-spin inputs below V_A **prohibited** · Take control at first sign of incipient spin · **+25° pitch limit when >5000 RPM**