



AIM: Climb at various rates and angles to a predetermined altitude while maintaining balance.

P QNH: Set and verify

☐

DP E8 Takeoff: Instructor ground roll/lift-off; student takes control after lift-off – maintain climbout attitude and heading

☐

DP Vy climb: PAT to establish; Vy ± 5 kt, hdg $\pm 5^\circ$; student practices; **Nose down + lookout every 500 feet**

☐

DP Level-off from Vy: APT – anticipate 50 ft (10% ROC); student aims for ± 100 ft

☐

P Short Straight and Level practice: S&L ± 150 ft, hdg $\pm 10^\circ$ -> LARI. Correct deviations with PAT -> LARI

☐

D Descent: Instructor can discuss next demonstration with student while descending.

☐

DP Vy to Vx climb: Start Vy climb, transition to Vx. Show steeper attitude and reduced VS; student practices and compares

☐

DP Descent: Student or instructor descends.

☐

D Flap effect: Demo degraded performance with flap extended

☐

P Practice: Practice all climbing elements

☐

COMMON ERRORS

- **Airspeed chasing** -> Hold the attitude; airspeed follows
- **Forgetting nose-down** -> Every 500 feet or about every 4th LARI cycle; build the habit now
- **No right rudder** -> Left-turning tendency – anticipate
- **Late level-off** -> Anticipate; 10% ROC rule
- **Nose high after level-off** -> Lots of forward pressure required at TOC – anticipate.

STANDARDS FOR PROGRESSION

P S **Progressing (P):** ASI +10/-5 kt, hdg $\pm 8^\circ$; level-off ± 200 ft; nose-down with reminders
Solo (S): ASI +5/-0 kt, hdg $\pm 5^\circ$; level-off ± 150 ft; nose-down without prompting

C NC

SAFETY Exercises **above 1000 ft AGL** · EFATO brief completed · Monitor engine temps in sustained climb · Monitor ear discomfort · Clear horizon and surface wind <25 knots