



AIM: Recognise and recover from nose-high and nose-low unusual attitudes; manage in-flight emergencies using the ADM framework.

P **Departure/transit:** Student as PIC; HASSELL before UA exercises

☐

DP **Jammed controls on climbout:** ADM – **“How much time?”**; test landing config at altitude before committing; student participates. Some suggested instructor prompts: what next?, how do you think that will go?, any problems with that plan?, what resources do you need?, who can you talk to for help? etc.

☐

D **Nose-high UA:** Instructor creates; recovery – push, power if needed, roll wings level if bank present

☐

D **Nose-low UA:** Instructor creates; recovery – **throttle, roll wings level, ease back once level – not before**

☐

P **UA practice:** Instructor creates – nose-high wings level -> with bank -> nose-low wings level -> with bank; student recovers on “recover” prompt

☐

DP **In-flight fire:** “Engine fire” – procedure as per POH; student performs from memory

☐

DP **Smoke/fumes:** Procedure as per POH; student performs from memory

☐

P **Trim failure:** Instructor applies deflection without comment; student identifies, compensates

☐

P **Scenario:** “Smoke from behind the panel at 3500 ft – actions?”

☐

P **Return:** Student as PIC

☐

COMMON ERRORS

- **Backpressure before wings level (nose-low)** -> Level wings first – every time
- **Rushing decisions** -> **“How much time?”** first – stop panic; start problem-solving

STANDARDS FOR PROGRESSION

P **S** **Progressing (P):** Nose-high – pushes and levels; nose-low – throttle then wings before backpressure; fire with minor sequencing error; ADM with some prompting

C **NC** **C standard:** Both UAs correct sequence; fire memory items promptly; ADM – assesses time available; no instructor input

⚠ SAFETY Above 2500 ft AGL - All recoveries above 2000 ft AGL - Brief max nose-up angle and max nose-low airspeed before flight - **Fire simulation: fuel selector NOT closed in flight**