



AIM: Identify the symptoms of an impending stall in a range of configurations and execute a safe, timely recovery to normal flight. Recover from a fully developed stall to normal flight. Manage the aircraft confidently in slow flight.

P E8: Independent; no prompting at any stage

☐

P HASSELL: Student completes before sequence – **and every 15 minutes**

☐

P S&L stall review: Clean and approach config; one of each; confirm L6 standard retained

☐

DP Turning stall 30° AoB: Outer wing stalls; wing drop; **rudder stops roll, ailerons neutral;** student practices

☐

DP Climb (50% power) & Descent stall: Demo symptoms; power causes instability; student practices

☐

D Slipping turn stall 30° AoB: Increased outer wing AoA; wing drop; recovery demo only

☐

DP Go-around scenario: Full flap; demo to pre-stall only; student prevents stall on “recover” prompt

☐

DP EFATO scenario: Power to idle on upwind; demo fixation on landing area; student practices

☐

DP Elevator trim stall: Trim nose-up, full power – rapid pitch-up; push against trim, reduce power if needed, retrim; student practices

☐

D Spin entry awareness: Above V_a only; patter entry conditions; recover immediately

☐

COMMON ERRORS

- **Aileron on wing drop** -> Relax backpressure first; rudder; ailerons neutral until unstalled
- **Aggressive pitch in go-around** -> Set attitude and wait; don't chase airspeed
- **Backpressure in EFATO** -> Accept the descent; natural stability
- **Aerobatics** -> 60° AoB bank limit. +/- 30° pitch limit. There is no need to exceed these to achieve lesson goals

STANDARDS FOR PROGRESSION

P S

Progressing (P): Turning stall recovery with one prompt; ailerons neutral; ≤ 400 ft

C NC

Solo (S): Turning stall ≤ 300 ft; rudder on wing drop without prompting; go-around and EFATO prevention correct; trim stall recovery correct; HASSELL without prompting

Note: Two-flight stalling requirement (E7 + E10) now satisfied. Full C requires Phase 3.

⚠ SAFETY Smooth air required · Above 2500 ft AGL · All recoveries above 2500 ft AGL · Pro-spin inputs below V_a prohibited · Take control at first sign of incipient spin · +25° pitch limit when >5000 RPM