



AIM: Build solo circuit experience, consolidate all circuit competencies toward C standard, and develop full independence in pre-flight administration.

PRE-SOLO SELF-BRIEF (EVERY SESSION)

- **NAIPS:** TAF/GAF/GPWT obtained and interpreted; wind, vis, cloud, validity – conditions suitable?
- **BOM radar:** precipitation checked as supplemental
- **NOTAMs:** checked; any items relevant to circuit operations today?
- **Maintenance release:** reviewed; all items acceptable; brief instructor on anything noted
- **EFATO plan:** where will I land at 200 ft? At 400 ft? On crosswind?
- **Radio failure plan:** what will I do if radio fails while downwind?
- **Gate commitment:** I will go-around if any gate/abort point criterion is not met at 300 ft – no exceptions
- **IMSAFE:** am I genuinely fit to fly?

DUAL CHECK – C STANDARD TARGETS

- Circuit: height ± 75 ft; BUMPFISH and radio automatic
- Gate: applied unconditionally; go-around proactive and timely
- Landing: touchdown point +150 m; smooth consistent hold-off; directional control
- T&G: fully independent; flap before power every time
- Pre-flight admin: NAIPS TAF/GAF/GPWT correct; NOTAMs thorough; MR reviewed completely and briefed clearly

STANDARDS FOR PROGRESSION

P S

Minimum for Phase 3: ≥ 2 hours solo circuit time + all E8/E11/E12 at or approaching C standard on dual check

C NC

Solo (S): Height ± 100 ft; BUMPFISH complete; all calls correct; gate applied every approach; landing +250 m; EFATO managed

C standard: Height ± 75 ft; gate unconditional; landing +150 m; all admin fully independent

SOLO CIRCUITS – STUDENT RESPONSIBILITIES

- Student conducts circuits independently; instructor observes from ground
- **Gate/abort point applied every approach solo** – go-around without prompting if not met
- **BUMPFISH every downwind leg** without prompting
- Self-debrief after each session: describe each circuit; note gate compliance on every approach
- Report any deviations to instructor honestly after landing

COMMON ERRORS

- **Rushing T&G reconfiguration solo** → Flap and trim before power – every time, no shortcuts
- **Gate/abort point not applied solo** → If session debrief reveals gate was not applied, priority correction before next solo
- **Fatigue not self-recognised** → Know when to call it; stop the session; do not continue flying when tired

⚠ SAFETY Solo minima apply every session: ceiling >1500 ft AGL · vis >8 km · no turbulence · xwind within solo authorisation · **Student must review MR and brief instructor before every solo** · Instructor observes all solo circuits with radio on CTAF · Monitor solo fatigue during self-debrief – end session if detected