



AIM: Depart the circuit, operate in the training area, and return using the correct overhead joining procedure.

P **Departure:** All startup, taxi, radio; takeoff; instructor guides on departure type; turns in circuit direction until **3 NM clear or 1500 ft AGL**

☐

P **Area departure call:** When clear of circuit; track to training area on visual landmarks

☐

P **Training area:** Identify boundaries; alerted see-and-avoid; verbalise traffic picture

☐

DP **Overhead join:** Instructor assists inbound radio; hands back at circuit entry; student — inbound call 5-10 NM; overfly **2000 ft AGL**; **identify likely runway in use before reaching aerodrome**; non-active side; cross upwind threshold; "Joining" call; BUMPFISH; TGL

☐

P **Other joins:** Inbound call; 1000 ft AGL early; join chosen leg; sequence with traffic

☐

P **Repetition:** Depart and rejoin as time permits

☐

COMMON ERRORS

- **Turning against circuit direction** -> With circuit until 3 NM clear or 1500 ft
- **Descending before runway identified** -> Identify from windsock and traffic; circle if uncertain
- **Over-using radio** -> Lookout is primary; radio informs the picture

STANDARDS FOR PROGRESSION

P **S**

Progressing (P): Departure with minor guidance; join with minor guidance; runway identified overhead

C **NC**

Solo standard (S): Departure with mostly correct procedure and radio calls; join correctly and consistently on crosswind; sequences with traffic correctly and maintains SA

C standard: Correct departure and join on any nominated leg of the circuit; runway identified before descent; traffic integrated; radio usage correct; lookout primary; boundaries monitored; weather and operational requirements integrated into SA and accounted for confidently

⚠ SAFETY Ceiling **>2000 ft AGL** overhead airfield (2000 AGL overfly is recommended by CASA, however 1500 AGL is available as minimum) · Fuel calculated before departure · Overhead join preferred: monitor for traffic conflicts