



AIM: Conduct a simulated forced landing into a suitable field and conduct all emergency procedures (ABC checks).

P **Departure/transit:** Student as PIC; *awareness of landing fields*

☐

D **ABC demo:** Instructor calls “engine failure”; works through full sequence aloud – A, B, C, D, E, F; FLWOP circuit to high-key then low-key; sideslip if high; go-around at 500 ft

☐

P **ABC – first 1-2 attempts:** Instructor assists recall if needed; student works through sequence

☐

P **ABC – subsequent attempts:** From memory; go-around at 500 ft – *never below*

☐

P **Return:** Student as PIC; join; land independently

☐

ABC QUICK REFERENCE

- **A – Attitude:** Best glide; trim – **first and most time-critical**
- **B – Best Field:** 6-S; aim point at **one-third**; high-key; low-key
- **C – Checks (FAST):** Fuel; Air; Switches; Throttle – after A and B only
- **D – Declare:** MAYDAY – callsign, position, problem, plan, POB; Centre preferred
- **E – Explain:** Pax brief; seatbelt tight; brace; reassure
- **F – Final:** All switches off; **flap before master if electric flaps**

COMMON ERRORS

- **Delayed attitude** -> A is first; every second costs height
- **Checks before A and B** -> FAST only after field chosen and glide established
- **MAYDAY on CTAF** -> Centre first; 121.5 or CTAF if Centre not available
- **Too high on glide** -> Correct early

STANDARDS FOR PROGRESSION

P **S**

E14b Solo (S) – first of two flights:

Solo (S): A within 5 s; ABC from memory; MAYDAY correct; low-key 1000 ft; field made with margin; PSL heights correct

C **NC**

⚠ SAFETY Training go-around height **minimum 500 ft AGL** – specified before flight; **never breach** · **Do not operate** such that a real engine failure would endanger the aircraft · PSL 300 ft pass: aerodrome only