



AIM: Conduct short and soft field takeoffs and landings to C standard using correct technique and performance calculations.

DP Short field TO: Brakes held; full power checked; rotate at Vr precisely; Vx to obstacle; Vy clear; student x3 ☐

DP Short field landing: Gate at 300 ft; positive touchdown just past threshold; **maximum braking**; rearward elevator during rollout; student x3; go-around if not on target ☐

DP Soft field TO: Continuous rolling – **no stopping**; lift at minimum speed; **lower nose immediately** for ground effect; student x2 ☐

P Soft field landing x2: Smooth hold-off; **hold nose up throughout rollout**; no hard braking; taxi clear immediately ☐

PERFORMANCE CALCULATION

- Inputs: temperature, density alt, wind, weight
- **Safety margin: minimum 1.5x calculated distance**
- Confirm TODA and LDA before every operation
- Account for surface condition
- **If margin not met -> do not attempt**

COMMON ERRORS

- **Late rotation (SF TO)** -> Rotate at Vr – delay adds distance
- **Extra airspeed (SF landing)** -> Fly the attitude; positive touchdown
- **Stopping on surface (soft TO)** -> continuous roll
- **No safety margin** -> Always apply 1.5x

STANDARDS FOR PROGRESSION

P S C standard dual before flight test – solo SF not required.

C NC C: SF TO – Vr precisely, Vx ± 3 kt; SF landing – target +50 m, max braking; Soft TO – continuous roll, ground effect; Soft landing – nose up throughout

⚠ SAFETY Confirm surface before ops. **If margin not met – do not attempt**. Heightened monitoring throughout