

varp python API documentation

Instance functions

```
varpy.new(options)
```

Create a new varp instance from a dict of options

- {'size': size}
Initial variable table size
- {'qtype': 'lifo'|'fifo'|'recursive'}
use lifo/fifo strategy in bcp
- {'xref': x}
use cross references if x is True
- {'hash': x}
use hash table for clauses if x is True
- {'edge': x}
use edge tables for 2-clauses if x is True

```
varpy.clone(vp, options)
```

Clone the varp instance using setting options from varpy.new with the follow additions:

- {'level': l}
clone bindings up until level l
- {'set': **clauseset** | [**clauseset**]}
- {'queue', x}
clone bcp queue only if x is True.

where **clauseset** = 'delta'|'gamma'|'beta'|'alpha'

```
varpy.info(vp, item)
```

Get varp information

- version
- 'bcp_counter'
- 'conflict_counter'
- 'max_conflicting'
- 'num_conflicting'
- 'number_of_variables'
- 'number_of_clauses'
- 'number_of_edges'
- 'number_of_dead_clauses'
- 'number_of_dead_edges'
- 'number_of_learnt_clauses'
- 'number_of_bound_variables'
- 'number_of_subst_variables'
- 'number_of_unbound_variables'

- 'clause_n_counter'
- 'clause_2_counter'
- 'clause_3_counter'
- 'clause_d_counter'
- 'edge_2_counter'
- 'edge_d_counter'
- 'size'
- 'qtype'
- 'max_level'
- 'min_level'
- 'max_bound'
- 'literal_size'
- 'literal_integer'
- 'value_packing'
- 'edge'
- 'xref'
- 'hash'
- 'init_phase'
- 'use_phase'

```
varpy.config(vp, item, value)
```

Set configurable items in varp

- 'max_conflicting'
set max number of conflicts during bcp (<= MAX_CONFLICTING=1024)
- 'xref'
turn on (True) or off (False) cross reference handling
- 'hash'
turn on (True) or off (False) hash table handling
- 'qtype'
set style of literal queueing in bcp
where value is one of
'lifo' | 'fifo' | 'recursive'

```
varpy.add_variable(vp [,is_atom])
```

Create a new variable. The variable is return as an index to the next available variable in the variable table. Mark the new variable as atom if is_atom is **True**. The atom status may later be queried with variable info. is_atom defaults to **True**.

```
varpy.add_variables(vp, num, [,is_atom])
```

Create **num** new variables. The variables are return as a tuple (**firstindex**, **lastindex**). If is_atom is **True** then the variables are marked as atom.

```
varpy.value(vp, x)
```

Return **True** | **False** | **None**,
Value, None is return if variables undefined.

```
varpy.bind(vp, x, [,l])
```

Bind variable **x** to True. If level **l** is given then that level is used to the variable is bound on that level else the variable is bound on the current level as set with `varpy.set_level`.

```
varpy.decide(vp, x [,l])
```

Bind variable **x** to True and mark **x** as a decision variable. If level **l** is given then that level is used to the variable is bound on that level else the variable is bound on the current level as set with `varpy.set_level`.

```
varpy.subst(vp, x, y)
```

Substitute one literal for an other. Apply the substitution [**x/y**] that is, all instances of **y** are replaced by **x** in all clauses. The literal **y** is then linked to **x** so it will keep the same status and value as that of **x**.

NOTE that cross references must be enabled before `varpy.subst` can be used, that is a call to `varpy.config(vp, 'xref', True)` must have been made prior a call to `varpy.subst`.

```
varpy.implication_clause(vp, x)
```

Return the clause index for the clause where literal **x** became a unit.

```
varpy.implication_level(vp, x)
```

Return the bind level for variable **x**, where it was assigned during bcp.

```
varpy.implication_pos(vp, x)
```

Return the position where literal **x** is found in the implication clause.

```
varpy.conflicting_clause(vp, i)
```

Return the *i*'th conflicting clause found during the last bcp. The number of conflicting clauses that can be returned is 'num_conflicting'.

```
varpy.is_variable(vp, x)
```

Return **True** if literal **x** is unbound. Return **False** otherwise

```
varpy.is_bound(vp, x)
```

Return **True** if literal **x** is bound, through substitution, to an other variable. Return **False** otherwise.

```
varpy.is_equal(vp, x, y)
```

Check if literal **x** and literal **y** are the equal, that is bound to the same variable or are bound to the same constant.

```
varpy.is_used(vp, x [,value])
```

Check if literal **x** is used in any clause or is forced to be in use by a previous setting of value. This makes "free" variables be included in fist and next_unbound calls.

```
varpy.is_atom(vp, x [,value])
```

Check if literal **x** is an **atom**, that is marked as atomic formula when adding new variables or set using is_atom(vp, x, True)

```
varpy.set_level(vp, l)
```

Set current level to **l**. Note that level 0 is treated as constant level. So be careful when setting level to 0.

```
varpy.keep_level(vp, l)
```

Keep all bindings on level **l** by removing the undo information.

```
varpy.move_level(vp, src, dst)
```

Move bindings from level **src** to level **dst**.

```
varpy.undo_level(vp, l)
```

Undo all bindings on level **l**.

```
varpy.undo(vp)
```

Undo bindings typically after an nbind. Undo will undo all bindings until a decision and flip the variable if not already flipped.

```
varpy.bcp(vp [, [x1,...,xn] [,all]])
```

Run value propagation. Return **True** if no contradiction is found, **False** otherwise.

[EXPERIMENTAL]

If literals **x1..xn** are given they are checked for "turbo" rule, that is, if all clauses that xi is a part of are true regardless of the value of xi. If 'all' is true then all xi's must be true for the rule to hold. If turbo rule is successful then varpy.**turbo** is returned.

[EXPERIMENTAL]

```
varpy.nbcvp(vp)
```

decide and bind next unbound variables until either no more variables to bind, return True, or a contradiction is reached, then return False. nbcvp can be use with undo to implement a tight loop for simple backtracking.

```
def bt(vp):
    while not varpy.nbcp(vp):
        if varpy.undo(vp) == False:
            return False # contradiction
        return True # model
```

```
varpy.add_clause(vp, [x1,...,xn] [,clause_set])
```

Create a new clause, given as a literal list and return the new clause index. All variables indices must already have been created by calling add_variable. The clause create is installed in one of four clause sets: 'delta', 'gamma', 'alpha', 'beta'. The 'delta' clauseset is use to store the "problem" formula clauses while 'gamma' is used for storing learnt clauses. However the conflict clause(s) created by varpy.conflict are created in 'alpha' and may then, by user, moved into 'gamma'.

```
varpy.get_clause(vp, cix [, skip | varpy.undefined [, raw]] )
```

Retrieve a clause as list given the clause index **cix**.
If literal **x** is given then literal **x** is removed from the clause list returned. if **raw** is **True** then literals bound on level=0 are also return as normal, otherwise they are removed.
If all literals in the clause are **False**, that is the clause is contrdictory empty list [] is returned. If any literal is **True** then **True** is returned.

```
varpy.find_clause(vp, [x1,...,xn])
```

Check if the clause [**x1**,...,**xn**] exist among the clausesets. return clause index if found, return **False** otherwise.

```
varpy.compress_clause(vp, cix | [x1,...,xn])
```

Return a compressed version of the clause [**x1**,...,**xn**], or the clause given by the clause index cix.
It writes a utf8 like code with 0x80 bit for continuation bit and 7-bits per byte for integer value. The LSB is coded as the literal sign.

-1000 is translated to unsigned by

```
2*1000 + 1 = 0xb11111010001
```

which is divided in groups of 7 bits starting from LSB

```
(1)1010001, (0)0001111
```

while 1000 is translated to

```
2*1000 = 0xb11111010000
```

which is divided in groups of 7 bits starting from LSB

```
(1)1010000, (0)0001111
```

Then sequence of coded literals are then terminated with a zero.

```
varpy.clause_info(vp, cix, item)
```

Get information about clause given by clause index cix

- 'length'
- 'jump'
- 'status'
- 'watch0'
- 'watch1'
- 'watch'

```
varpy.variable_info(vp, x, item)
```

Get information about variable x

- 'implication'
- 'implication_clause'
- 'implication_pos'
- 'level'
- 'phase'
- 'is_atom'
- 'is_used'
- 'degree'
- 'symbol'

```
varpy.literal_info(vp, x, item)
```

Get information about literal x

- 'degree'
- 'user'
- 'edge'
- 'symbol'

```
varpy.del_clause(vp, cix | [x1,...,xn])
```

Delete clause **cix** or **[x1,...,xn]** from clausesets.

NOTE: When deleting clauses by giving it as a list, then hashing may be enable (varpy.config(vp, 'hash', True)) to gain reasonable speed.

```
varpy.clean_clause(vp, cix)
```

Cleanup clause by removing all false literals on level 0.
if clause is contradictory then exception is raised

```
varpy.clean_edges(vp, x)
```

Remove **x** edges, that is clauses on form [-x,y] where y is constant.

```
varpy.get_clauses(vp, cix, skip, raw)
```

Return a list of literals given by clause index **cix**.
Remove the literal **skip** from the returned list.
Also remove literals on level 0 if **raw** is **False**.

```
varpy.get_decision(vp, l)
```

Get literal on decision level **l**.

```
varpy.get_undo_state(vp, l)
```

DEBUG

Return the undo state on level **l**

- **varpy.set**
- **varpy.toggle**
- **varpy.done**
- **varpy.undef**

```
varpy.get_bindings(vp, l, clauseinfo, as_trail, as_tuple)
```

Return all bindings on level **l**. Return them in order of when binding where made if **as_trail** is **True** otherwise the bindings are returned as latest binding first. if **as_tuple** is **True** then bindings are returned as a tuple otherwise a list is returned.

if **clauseinfo** is **True** then a list of tuples (literal, pos, implication_clause) are returned otherwise a list of literals are returned. A negative literal means that the variable is bound to **False** a positive literal means that the variable is bound to **True**.

```
varpy.get_nbindings(vp, count, clauseinfo)
```

Return a maximum of **count** bindings with the latest binding first.

if **clauseinfo** is **True** then a list of tuples (literal, pos, implication_clause) are returned otherwise a list of literals are returned. A negative literal means that the variable is bound to **False** a positive literal means that the variable is bound to **True**.

```
varpy.get_number_of_bindings(vp, l)
```

Return number of bindings on level **l**.

```
varpy.order_sort(vp, key1, key2, arg)
```

Order variables according to **key1** and then **key2**, an optional **arg** may be supplied when needed by sorting.

The sort keys available are:

- 'identity'
Sort according to when the variable number, this mostly corresponds to when the variable was created.

- 'random'
Sort variables using a uniform distribution, an integer seed may be given as **arg**.
- 'degree'
Sort literals according to the number of time they occur in the clauses.
- 'rank'
Sort literals according to the sum of ranks for all occurrences in all clauses. The rank for literal x is defined as the sum of $1/|c_i|$ for all clauses c_i where x is a member.
- 'user'
Sort literals according to a user value, that can be set by using the varpy.**set_user_cunt**(vp, x, unsigned)

If the sort key is prefixed with a '+' then sorting is ascending. If prefix is '-' then the sort is descending, which is also the default.

```
varpy.order_first(vp, [x1,...,xn])
```

Update current sort order so that literals **x1..xn** are placed first.

```
varpy.order_last(vp, [x1,...,xn])
```

Update current sort order so that literals **x1..xn** are placed last.

```
varpy.next_unbound(varp [, previous])
```

Return the next unbound literal in the current variable order. If **previous** is given then start looking for unbound literals from that point.

```
varpy.queue_first(varp)
```

DEBUG Return the first literal on the bcp queue.

```
varpy.queue_next(vp, x)
```

DEBUG Return the next literal on the bcp queue, following literal **x**, that must previously have been returned from varpy.queue_first or varpy.queue_next.

```
varpy.queue_clear(varp)
```

Remove all literals enqueued on the bcp queue by calls to varpy.bind or varpy.decide.

```
varpy.add_symbol(vp, x|xs, string|term)
```

Associate a term or string to a variable **x** or variables **xs**, for example the name of the variable.

The term or string must not be associated with other variables or an exception will occur.

If the variable part is a list **xs** then the symbol refer to a list of variables, integer encoding or bit vector.
Integer encoding should store least significant bit first (at index 0)

```
varpy.del_symbol(vp, string|term)
```

Remove the symbol from the symbol table.

```
varpy.find_symbol(vp, symbol)
```

Given a symbol return the variable assoicated with it.
If no assoication is found **False** is returned.

```
varpy.first_symbol(vp)
```

Find first symbol in the symbol table. Return **False** if not found. Try not use **False** as a symbol.

```
varpy.next_symbol(vp, symbol)
```

Given a symbol in the symbol table (must be present), find next symbol in the symbol table. Return **False** if not found. Try not use **False** as a symbol.
If symbol table is updated while calling next_symbol then the behaviour is undefined.

```
varpy.use_clause(vp, cix)
```

Update the clause **cix** timestamp to the current bcp_counter, the number of bcp's that has been run since **vp** instance was created.

```
varpy.bump(vp, x, n)
```

"bump" a variable **x** to move it in the dynamic variable order.
Either bump value **n** is one of

- 'next', move variable to the top position, next variable to be assigned
- 'log2', bump value is calculated to $\log_2(\text{'number-of-variables'})$
- 'log10', bump value is calculated to $\log_{10}(\text{'number-of-variables'})$
- 'rank', bump value is set to the length of the implication clause.

Or the **n** is a floating point ration between zero and one that will give the the number of steps to move, 0.1 means move 10% in number of variables.

Or the value is an integer that gives an absolute number of steps to move.

```
varpy.subscribe(vp, flag|[flag])
```

Flags

- 'variable'
- 'atom'
- 'number_of_variables'
- 'number_of_bound_variables'
- 'number_of_subst_variables'

- 'number_of_clauses'
- 'number_of_dead_clauses'
- 'max_level'
- 'max_bound'
- 'min_level'

```
varpy.clauseset_size(vp, s)
```

Where **s** is one of 'delta', 'gamma', 'alpha', 'beta'

```
varpy.clauseset_offset(vp, s)
```

Get offset where **s** is one of 'delta', 'gamma', 'alpha', 'beta'

```
varpy.clauseset_offset(vp, s, offset)
```

Set offset where **s** is one of 'delta', 'gamma', 'alpha', 'beta'

```
varpy.clauseset_sort(vp, s)
```

Sort clauses in the clause set **s**, where **s** is one of 'delta', 'gamma', 'alpha', 'beta'. The clauses are sorted according to the internal use counter set by varpy.use_clause.

```
varpy.clauseset_first(vp, s)
```

get clause index of first clause in clauseset **s**

```
varpy.clauseset_next(vp, s)
```

get clause index to the next clause in clauseset **s**

```
varpy.set_user_count(vp, x, count)
```

Set user value for literal **x** to **count**.

```
varpy.conflict(vp, level, bump, i)
```

Do conflict analysis, called with level where the conflict **i** was found and the **bump** factor that is applied to variables involved in the conflict. Return value is a clause index in clauseset 'alpha'. This clause may then be minimized and later moved to 'gamma'.

```
varpy.minimize(vp, cix)
```

Minimize clause, may be called after varpy.conflict and requires that literals and levels are set like after the conflict.

```
varpy.move_clause(vp, cix, set)
```

Move clause **cix** to clauseset **set**.

NOTE that this function is currently limited to clause in 'alpha' and set must be 'gamma'

```
varpy.unmark(vp)
```

Clear all marks

```
varpy.mark(vp, l | [x1,...,xn] | (x1,...,xn), [clear])
```

Mark variables **x1..xn** or all bindind on level **l**.

Optionally if **clear** is **False** then marks are concatinated to the previous marks, otherwise the marks are cleared before adding new ones.

```
varpy.intersect_marks(vp, l | [x1,...,xn] | (x1,...,xn))
```

Keep all marks that are present in bindings on level **l** or the literals **x1...xn**. Clear the other marks.

```
varpy.intersect_var(vp, x, l | [x1,...,xn] |(x1,...,xn), as_tuple)
```

Return all marks that are present in bindings on level **l** or the literals **x1..xn**. Return the marks in a list if **_as_tuple** if **False** or as a tuple if **as_tuple** is **True**.

```
varpy.get_marked(vp, as_tuple)
```

Return the marks in a list if **_as_tuple** if **False** or as a tuple if **as_tuple** is **True**.