

# Index

*Note:* Page numbers with “F” denote figures; “t” tables.

## A

A3967SLB bipolar stepper motor, 609  
Ab function, 47  
Access methods, Ethernet, 510–513  
    e-mail, 512  
    using custom application, 512  
    using HyperTerminal, 511  
    using web browser on PC, 511, 511f  
Acos function, 48  
Action commands, 339  
Active RFID tags, 370  
ADC\_Get\_Sample function, 504, 535  
ADC\_Init function, 503–504  
Adc\_Read(0) function, 131–136, 144–146  
Alarm clock, real-time, 436–439, 436f–438f, 440f  
Altimeter display on GLCDs, 490–501, 491f, 493f, 495f–496f, 501f  
Arbitrary waveform generation, 229–234, 232f–233f, 235f  
Arrays, 12–13  
    character, 12–13  
Asin function, 48  
Assembly language instructions, 45  
Assembly program, 2  
Atan function, 48  
Atan2 function, 48  
Automotive project *see* CAN bus;  
    Local interconnect network (LIN) bus

## B

Barometer display on GLCDs, 490–501, 491f, 493f, 495f–496f, 501f  
Baud rate, 290, 303–304  
BEGIN–END, 52, 52f  
Biased split termination of CAN bus, 552–553  
Bipolar A/D converter, 216  
Bipolar stepper motors, 600  
    drive, 608–611, 609f–612f, 614f  
    driving sequence, 601f  
    windings, 600f  
Bit stuffing in CAN bus, 556  
Bluetooth, 5f  
    master mode, serial communication in, 361–369, 362f, 364f, 368f  
    program testing, 368–369  
    slave mode, serial communication in, 333–361, 335f–336f, 338f–339f, 343f–348f, 353f–354f, 356f  
    making connection, 342  
    manual connection, 342–346  
    modifications, 355  
    program testing, 352–355  
    RN41 module, 334–335, 334f  
BusyXLCD function, 149  
BusyxUSART function, 299  
Buzzer, 156

## C

C, <address> command, 341  
Calculator  
    with keypad and liquid crystal display, 190–201, 190f–194f, 202f

    program using built-in keypad function, 195f, 198–201, 199f  
    PC-based, 304–306, 305f, 307f, 310f  
CAN bus, 535–536, 550–577, 551f  
    bit stuffing, 556  
    configuration mode, 561  
    data frame, 553–555  
    disable mode, 561  
    error frame, 555  
    error recognition mode, 562  
    listen-only mode, 561  
    logic states, 552f  
    loop-back mode, 561  
    message reception, 562–563  
    message transmission, 562  
    nominal bit timing, 556–558  
    normal operation mode, 561  
    overload frame, 555–556  
PIC microcontroller interface, 558–559, 558f–559f  
PIC18F258 microcontroller, 559–561  
remote frame, 555  
temperature sensor and display project, 568, 569f–570f, 577f  
COLLECTOR processor, 569  
COLLECTOR program, 574–577, 575f  
DISPLAY processor, 569–570  
DISPLAY program, 570–574, 571f  
termination methods, 553f

- CAN bus (*Continued*)
    - timing parameters calculation, 563–564
  - CAN\_Initialize function, 565, 574
  - CANGetOperationMode function, 565
  - CANRead function, 567
  - CANSetBaudRate function, 566
  - CANSetFilter function, 566
  - CANSetMask function, 566
  - CANSetOperationMode function, 565
  - CANWrite function, 567
  - Card Identification Register (CID), 450
  - Card Specific Data Register (CSD), 450
  - Carrier Sense Multiple Access with Collision Detection (CSMA/CD) protocol, 509
    - with Arbitration on Message Priority (CSMA/CD + AMP), 550
  - Case sensitivity, 11
  - CCS C compiler, 10, 581
  - Change commands, 339
  - Character arrays, 12–13
  - Click boards, 310–311
    - RFID, 372f
  - Clock
    - real-time, 414–435, 421f–422f, 426f, 428f, 430f
    - alarm clock, 436–439, 436f–438f, 440f
  - Clock edge mode, 401
  - Clock polarity (CP), 404, 404f
  - Closed-loop DC motor speed
    - control, 616, 616f, 624–630, 627f–628f
  - ClosexUSART function, 299
  - CMX-Tiny+, 581
  - Command frame identifiers, 538
  - Comments, 11
  - Common-anode7-segment display, 109, 116f
  - Common-cathode7-segment display, 109, 115f
  - Complex instruction set computer *see* CISC
  - Configuration
    - bits, specifying, 45
    - mode of CAN module, 561
  - Constants, 12, 44–45
  - Contact debouncing, 194–198
  - Contact noise, 194–198
  - Control flow, 15–19
    - iteration statements, 17
    - selection statements, 15
  - Control register, 405
  - Controller area network *see* CAN bus
  - Controller chips, Ethernet, 510
  - CONV function, 55
  - Convert\_Date\_Time function, 429, 434
  - Cooperative scheduling, 579, 579f
    - multitasking, 581–589, 582f–584f, 586f
  - Cos function, 47
  - Cosh function, 47
  - CR95HF, 385f
    - operational modes, 374
    - startup sequence, 374
  - CustomChar function, 164–168
- D**
- D command, 340
    - basic settings with, 341f
  - Data clock rate, 400
  - Data frame in CAN bus, 553–555
    - ACK field, 555
    - arbitration field, 554
    - control field, 554, 555t
    - CRC field, 555
    - data field, 554
    - start of frame, 554
  - Data memory, 6
  - DataRdyxUSART function, 299
  - DC motors control, 613–619, 617f–619f
    - closed-loop transfer function, 616f
    - electrical circuit, 615f
    - open-loop transfer function, 616f
  - \_delay function, 46–47
  - \_delay3 function, 46–47
  - Delay\_ms function, 76–77, 92–93
    - \_delay\_ms function, 46–47, 74
    - \_delay\_ms(5) function, 149
    - \_delay\_ms(15) function, 149
  - Delay\_Seconds function, 74, 80, 94, 160
    - \_delay\_us function, 46–47
  - Diagnostic frames, 538
  - Dice, LED, 85–94, 90f–92f, 92t, 93f, 95f
    - two-dice project, 94–98, 100f–102f, 104f
    - using random number generator, 94, 97f, 99f
  - Digital signal processing (DSP), 522–535, 528f–532f
    - filter structure, 525–527, 530f
  - Digital thermometer, 168–171, 168f–170f
  - Digital-to-analog converter (DAC), 214–216, 215f
  - Direct current (DC) motor control system, 3–4, 6f
  - Disable mode of CAN module, 561
  - Display function, 123, 127
  - Display\_Date\_Time function, 429, 435
  - Display\_PTA function, 501
  - Display\_Temperature function, 412
  - DISPLY function, 55–57
  - Do statement, 19
  - DO-ENDO, 54, 54f
  - DO-FOREVER, 54, 54f
- E**
- EasyPIC V7 development board, 39–42
    - \_EEPROM\_DATA function, 47
  - Electronic stadiometer, 248
  - EM4100 RFID tag, 375–376, 375f
    - data format, 376f
  - E-mail, 512, 512f
  - Embedded controller *see* Microcontrollers
  - ENC28J6 Ethernet controller chip, 510
  - ENC28J60 Ethernet controller chip, 510–511, 510f, 513, 515
  - Error frame in CAN bus, 555
  - Error function, 501

Error recognition mode of CAN module, 562  
 Ethernet, 550  
   UDP-based control, 521–522, 522f–523f, 526f  
   web browser-based control, 508–521, 513f–517f, 519f  
   connectivity, 509  
   embedded access methods, 510–513  
   embedded controller chips, 510, 510f  
   packet format, 509f  
 External interrupt, four-digit multiplexed 7-segment event LED counter using, 175–186, 178f–180f, 183f, 186f–187f

## F

FloatToStr function, 294–296  
 Flowcharts, 51–57  
   representing for loops in, 36  
 Fluid level control system, 3, 3f, 5f  
   with Bluetooth, 5f  
   with keypad and LCD, 4f  
 Fonts, LCD, 160–168, 164f–167f  
 For statement, 17–18, 84–85, 116–118, 123, 127–128, 131–136, 144–146, 289, 504, 574  
   loop, 92–93, 107–109, 125–126, 194, 219–220, 475, 602  
   representing in flow charts, 63  
 Format\_Temperature function, 412–413  
 4 × 4 keypad *see* Keypad  
 Four-digit multiplexed 7-segment LED counter, 125–128, 127f–130f, 132f  
   using external interrupt, 175–186, 178f–180f, 183f, 186f–187f  
 FreeRTOS, 581  
 Frequency counter with LCD, 262–268, 262f–265f  
 FSfclose function, 465–466  
 FSfopen function, 465–466  
 FSfopenpgm function, 465–466

FSInit function, 465–466  
 FSread function, 465  
 FSremove function, 466  
 FSremovepgm function, 466  
 FSwrite function, 465  
 Functions, 20  
   library, 20, 21t

## G

Get commands, 339  
 Getkeypad function, 192–198  
 Get\_Response function, 546–550  
 GetsxUSART function, 300  
 Get\_Temperature function, 469, 475  
 Glcd\_Box function, 484  
 Glcd\_Circle function, 485  
 Glcd\_Circle\_Fill function, 485  
 Glcd\_Dot function, 482–483  
 Glcd\_Fill function, 482  
 Glcd\_H\_Line function, 483  
 Glcd\_Image function, 487  
 Glcd\_Init function, 481–482, 503  
 Glcd\_Line function, 483, 504–507  
 Glcd\_Rectangle function, 483–484  
 Glcd\_Rectangle\_Round\_Edges function, 484  
 Glcd\_Rectangle\_Round\_Edges\_Fill function, 484  
 Glcd\_Set\_Font function, 485  
 Glcd\_Set\_Font\_Adv function, 486  
 Glcd\_Set\_Page function, 482  
 Glcd\_Set\_Slide function, 482  
 Glcd\_Set\_X function, 482  
 Glcd\_V\_Line function, 483  
 Glcd\_Write\_Char function, 485–486  
 Glcd\_Write\_Char\_Adv function, 486  
 Glcd\_Write\_Const\_Text\_Adv function, 487  
 Glcd\_Write\_Data function, 482  
 Glcd\_Write\_Text function, 485–486  
 Glcd\_Write\_Text\_Adv function, 486–487  
 Global positioning system (GPS) with LCD output, 306–317, 310f–314f, 317f  
 Goto statement, 19

GPIO commands, 339  
 Graphical User Interface (GUI), 521  
 Graphics LCD displays (GLCDs), 477–490, 488f–489f  
   barometer, thermometer, and altimeter display on, 490–501, 491f, 493f, 495f–496f, 501f  
   display coordinates, 481f  
   128 × 64 pixel, 478–479  
   operation, 480  
   plotting temperature variation on, 501–508, 502f–505f, 508f  
   shapes drawn on, 490f  
   structure, 480f

## H

#pragma config statement, 74  
 HD44780 LCD controller module, 141–142  
   pin configuration of, 142t  
 High-level languages, 2  
 High/Low game, 206–214, 208f–210f, 213f–214f  
   generating random number, 207  
 HTTP, 511  
 Human height measurement, 248–258, 249f–251f, 253f, 255f  
 HyperTerminal, 297, 298f, 511

## I

I, <value 1>, <value 2> command, 341  
 I/O pins  
   accessing individual, 45  
   two-dice project using fewer pins, 98–109, 105t, 106f, 106t, 107f, 107t, 108f, 110f, 111t, 112f–113f  
 I<sup>2</sup>C bus, 396, 420, 421f, 422, 435, 491, 493  
 If statement, 15–17  
 IF–THEN–ELSE–ENDIF, 52, 53f  
 IF–THEN–ENDIF, 52, 53f  
 Init\_LCD function, 407  
 Init\_Pressure function, 494  
 Init\_SPI function, 407  
 Initialize\_CR95HF function, 379  
 InitTask function, 590

Internal registers of TC72, 404t  
 Internet, 508  
 Interrupt isr function, 160  
 Interrupt service routines (ISRs),  
   46, 56–57, 175–177, 179,  
   182–186, 235–236, 242,  
   244, 352, 363–367,  
   590–591, 627  
 Iteration statements, 17  
 Itoa function, 48, 152

**K**

K command, 341  
 Keypad  
   calculator, 190–201, 190f–195f,  
     199f, 202f  
   High/Low game, 206–214,  
     208f–210f, 213f–214f  
   structure, 191f  
 Keypad\_Init function, 198  
 Keypad\_Key\_Click function,  
   198  
 Keypad\_Key\_Press function,  
   198

**L**

Labs function, 47  
 Lcd\_Chr function, 435  
 Lcd\_Out function, 164–168  
 Led\_Out function, 146  
 Library functions, 20, 21t  
   peripheral libraries, 49  
   software, 46–49  
 Light emitting diodes (LEDs)  
   chasing, 70–76, 72f–75f  
   current sinking mode, 70–71,  
     71f  
   current sourcing mode, 71–72,  
     72f  
   complex flashing, 76–77,  
     77f–79f  
   dice, 85–98, 90f–92f, 92t, 93f,  
     95f, 97f, 99f  
   random flashing, 78–80,  
     80f–82f  
   7-segment LED counter,  
     109–118, 114f–117f, 117t,  
     118f–119f  
   voltmeter, 129–140, 133f–135f,  
     137f

Liquid crystal display (LCD)  
   calculator, 190–201, 190f–195f,  
     199f, 202f  
   custom fonts, 160–168,  
     164f–167f  
   frequency counter with,  
     262–268, 262f–265f  
   GLCDs, 477–490, 478t,  
     479f–481f, 488f–490f  
   High/Low game, 206–214,  
     208f–210f, 213f–214f  
   output, GPS with, 306–317,  
     310f–314f, 317f  
   voltmeter, 140–152, 143f–145f,  
     147t, 148f, 151t, 152f–153f  
   connecting LCD to  
     microcontroller, 142–143  
     HD44780 LCD module,  
       141–142, 142t  
 Listen-only mode of CAN module,  
   561  
 LM35DZ temperature sensor, 469,  
   501–502, 538  
 LMD18200T motor controller chip,  
   619, 619f  
 Local interconnect network (LIN)  
   bus, 535–550, 539f, 540f,  
     542f, 543f, 547f–549f  
   Get\_Response function,  
     546–550  
   MASTER node, 541  
   with one master and three slaves,  
     536f  
   protocol, 536–538, 537f  
   Send\_Header function,  
     541–546  
   SLAVE node, 546–550  
 Lock, RFID, 387–389, 388f,  
   390f–391f  
 Log function, 48  
 Log10 function, 48  
 Logic probe, 81–85, 83f–84f,  
   86f–87f, 87t, 88f–89f  
 LongToStr function, 146, 193, 306,  
   469  
 Loop-back mode of CAN module,  
   561  
 Looping, 63f–65f, 63  
 Low pass FIR digital filter,  
   522–535, 528f–532f

coefficients, 530f  
 structure, 525–527  
 LPS331AP sensor, 490–501  
   registers, 492t  
 LSB register, 405  
 LTrim function, 146, 306

**M**

Main Program function, 412  
 Manufacturer ID, 405  
 Master mode, 361–369  
   Bluetooth serial communication,  
     361–369, 362f, 364f, 368f  
 Master Synchronous Serial Port  
   (MSSP) module, 389–396  
   configuration for SPI master  
     mode, 400  
   in SPI mode, 396–397, 397f  
 MAX232, 291–292  
   pin configuration, 292f  
 MCP 201 LIN bus, 538–539  
 Measure function, 289–290  
 Mechanical stadiometer, 248f  
 Memcmp function, 48  
 Memory organization *see* Data  
   memory, organization;  
   Program memory,  
   organization  
 Message reception in CAN bus,  
   562–563, 562f  
 Message transmission in CAN bus,  
   562  
 MF1ICS50 RFID tag, 376–377  
   memory organization, 377f  
 MicroC/OS-II, 581  
 Microcomputer, defined, 1  
 Microcontrollers  
   defined, 1  
   fluid level control system, 3f  
   program development, 51  
   PDL and flowcharts, 52–57  
 Microprocessor, 2  
 mikroBUS, 311  
 mikroC Pro, 9  
   arrays, 12–13  
   functions, 20  
   library, 20, 21t  
   modifying flow of control, 15–19  
   operators, 15  
   pointers, 13–14

program structure, 10–12, 10f  
 structures, 14  
 variable types, 11t  
 Minielectronic organ, 258–261,  
 259f–261f  
 Mmc\_Fat\_Activate function,  
 455–456  
 Mmc\_Fat\_Append function, 455,  
 475  
 Mmc\_Fat\_Assign function, 455  
 Mmc\_Fat\_Close function,  
 456–457  
 Mmc\_Fat\_Delete function, 455  
 Mmc\_Fat\_EOF function, 456  
 Mmc\_Fat\_Exists function, 455  
 Mmc\_Fat\_Get\_File\_Dat function,  
 455  
 Mmc\_Fat\_Get\_File\_Size function,  
 455  
 Mmc\_Fat\_Init function, 455  
 Mmc\_Fat\_MakeDir function, 455  
 Mmc\_Fat\_Open function,  
 456–457, 456t  
 Mmc\_Fat\_QuickFormat function,  
 455–456  
 Mmc\_Fat\_Read function, 455–457,  
 475  
 Mmc\_Fat\_ReadN function, 456  
 Mmc\_Fat\_Rename function, 455  
 Mmc\_Fat\_Reset function,  
 455, 475  
 Mmc\_Fat\_Rewrite function,  
 455–457  
 Mmc\_Fat\_Seek function, 455  
 Mmc\_Fat\_Tell function, 455  
 Mmc\_Fat\_Write function,  
 455–457, 475  
 Mmc\_Set\_File\_Date function, 455  
 Motor speed  
   control, closed-loop, 624–630,  
   627f–628f  
   measurement, 619–624,  
   620f–622f  
 MPLAB C18 C compiler, 10  
 MPLAB X IDE, 29  
 MPLAB XC8 C compiler, 10  
 MPLAB XC8 C compiler, 10,  
 29–49  
 MDD library functions, 463,  
 463t–464t

programming other boards,  
 39–42  
 XC8 language features, 42–49  
   accessing individual bits of  
   variable, 45  
   accessing individual I/O pins,  
   45  
   assembly language  
   instructions, 45  
   constants, 44–45  
   interrupt service routines, 46  
   peripheral libraries, 49  
   persistent qualifier, 45  
   program startup, 46  
   program template, 43–44,  
   43f  
   software library functions,  
   46–49  
   specifying configuration bits,  
   45  
   variable types, 44, 44t  
 MSB register, 405  
 Mult function, 20  
 Multitasking, 578–581  
   cooperative scheduling, 579,  
   579f, 581–589, 582f–584f,  
   586f  
   preemptive scheduling,  
   580–581, 580f  
   round-robin scheduling,  
   579–580, 579f, 590–594,  
   590f, 592f, 595f

## N

Negative temperatures, displaying,  
 413–414  
 Newline function, 294–296, 469  
 NMEA sentences, 310, 312,  
 316–317  
 Nominal bit timing in CAN bus,  
 556–558  
 Normal operation mode of CAN  
 module, 561  
 Number function, 94  
 Numbers function, 98, 105–106

## O

100Base-T, 509–510  
 128 × 64 pixel, 478–479, 479f  
 pin configuration, 478t

One-phase full-step sequencing,  
 598, 599t  
 ON–OFF temperature control,  
 317–325, 317f  
 OpenADC function, 136  
 Open-loop transfer function of DC  
 motor, 616, 616f  
 OpenSPIx function, 226  
 OpenXLCD function, 149–150  
 OpenxUSART function, 300  
 Operation Control Register (OCR),  
 450  
 Operators in C, 15  
 Optical encoders, 619–624,  
 620f–622f  
 Organ, minielectronic, 258–261,  
 259f–261f  
 OSA-RTOS, 581  
 Overload frame in CAN bus,  
 555–556

## P

Parallel LCDs, 141  
 Passive RFID tags, 370, 370f,  
 375–377  
 PCF8583 RTC chip, 414–435  
   pin layout, 425f  
   registers, 424f  
   hours, 424f  
   weekday–month, 424f  
   year–date, 424f  
 PCSGU250, 525, 528f  
 Peripheral libraries, 49  
 Persistent qualifier, 45  
 Personal computer (PC)  
   -based calculator, 304–306,  
   305f, 307f, 310f  
   Ethernet access using web  
   browser on, 511, 511f  
 PIC18F258 microcontroller,  
 559–561  
   *see also* CAN bus  
 PICC18 C compiler, 9–10  
 PICDEM PIC18 Explorer  
   development board, 26–29,  
   26f  
   block diagram, 28f  
   module connections, 28–29  
   programming and debugging, 29  
 Piconet, 333

PICos18, 581  
 PICtail Daughter Board,  
     457f–458f, 462  
 PlotAxis function, 503–504  
 Pointers, 13–14  
 Preemptive scheduling, 580–581,  
     580f  
 Pressure\_Read function, 494  
 Pressure\_Write function, 494  
 Program  
     startup, 46  
     template, 43–44, 43f  
 Program description languages  
     (PDLs), 51–57  
 Program memory, 6  
 Pseudorandom number generator  
     function, 94  
 Pulse width modulated (PWM)  
     modules, 156, 244, 247,  
     624–627  
 PutcXLCD function, 150  
 PutrsXLCD function, 150  
 PutrsxUSART function, 303  
 PutsXLCD function, 150

**R**

R,1 command, 341  
 Radiofrequency identification  
     (RFID), 369–387,  
     370f–371f, 373f, 375f,  
     375t, 376f–380f, 385f, 387f  
 click board, 372f  
 CR95HF  
     operational modes, 374  
     startup sequence, 374  
 lock, 387–389, 388f, 390f–391f  
 passive tags, 375–377  
 UART communication, 374–375  
 Rand function, 48, 207, 212  
 Random access memory *see* RAM  
 Random flashing light emitting  
     diodes, 78–80  
 Random number generator, 94  
 Reaction timer, 268–276,  
     269f–271f, 273f  
 Read only memory *see* ROM  
 Read\_Alarm\_Flag function, 439  
 Read\_Altimeter\_Value function,  
     501  
 Read\_Date\_Time function, 429

Reading data in SD cards, 451  
 Read\_Pressure\_Value function, 494  
 Read\_Temperature function, 407  
 Read\_Temperature\_Value function,  
     494  
 ReadxUSART function, 303  
 Real-time clock (RTC), 414–435,  
     421f–422f, 426f, 428f, 430f  
     alarm clock, 436–439,  
     436f–438f, 440f  
 Real-time operating system  
     (RTOS), 578, 580  
 Reduced instruction set computer  
     *see* RISC  
 Registers  
     alarm control, 437f  
     LPS331AP sensor, 492t  
     PCF8583 RTC chip, 424f  
     SPI mode, 397–398  
 Relative humidity measurement,  
     277–290, 277f, 279t, 281t,  
     282f–285f, 290f  
     acknowledgment, 279  
     conversion command, 279  
     conversion of signal output,  
     280–281  
     RESET, 277–278  
     Status register, 279–280  
     transmission start sequence, 278  
 Remote frame in CAN bus, 555  
 Remote Transmit Request (RTR),  
     551, 553–554  
 REPEAT–UNTIL, 55, 55f  
 Request\_Short\_Info function, 379  
 Reset\_Sequence function,  
     289–290  
 Return statement, 147  
 RN41 Bluetooth module, 334–335,  
     334f  
 Round function, 49  
 Round-robin scheduling, 579–580,  
     579f  
     multitasking with variable CPU  
     time allocation, 590–594,  
     590f, 592f, 595f  
 RS232, 304  
     serial output, thermometer with,  
     290–304, 291f, 291t,  
     292f–295f, 298f–301f  
 RTOS.C, 590

**S**

SA, <value> command, 339  
 Salvo, 580–581  
 Sawtooth waveform generation,  
     217–219, 218f–223f, 225f,  
     227f  
 Sbit statements, 164–171  
 ScopeFIR program, 525, 529f  
 SD cards, 446f, 452f–454f,  
     457f–461f, 466f–467f  
     -based temperature data logger,  
     466–476, 468f, 470f,  
     476f–477f  
     deleting existing file, 466  
     holder, 451f  
 MPLAB XC8  
     library options, 464, 464t  
     MDD library functions, 463,  
     463t–464t  
     microcontroller memory  
     usage, 464–465, 465t  
     operation in SPI mode,  
     449–450  
     reading data, 451  
     reading from existing file, 465  
     sequence of function calls,  
     465  
     setting configuration files, 462  
     specifications, 447t  
     standard card  
         pin definitions, 449t  
         pin layout, 448f  
         writing data, 451  
         writing to existing file, 465  
 SD Configuration Register (SCR),  
     450  
 Select\_Protocol\_14443 function,  
     385–386  
 Selection statements, 15  
 Semipassive RFID tags, 370  
 Send\_Command function, 363  
 Send\_Header function, 541–546  
 Send\_To\_TC72 function, 407  
 Sequencing, 52, 53f  
 SerDDRamAddr function, 151  
 Serial clock polarity, 404f  
 Serial communication  
     Bluetooth  
         master mode, 361–369, 362f,  
         364f, 368f

- slave mode, 333–361,
    - 334f–336f, 338f–339f,
    - 343f–348f, 353f–354f, 356f
  - pins required for, 291t
  - RS232 serial output, thermometer
    - with, 290–304, 291f–295f,
    - 298f–299f, 301f
  - using USB-RS232 converter
    - cable, 297
  - using USB-UART port,
    - 299–304, 300f
  - Serial Ethernet board, 515f
  - Serial LCDs, 141
  - Set commands, 339
  - Set\_Date\_Time function, 429, 439
  - Set\_RTC\_Alarm function, 439
  - SetSpeed function, 630
  - 7-segment LED counter, 109–118,
    - 114f–117f, 117t,
    - 118f–119f
  - four-digit multiplexed, 125–128,
    - 127f–130f, 132f
  - two-digit multiplexed, 120–125,
    - 120f–121f, 121t,
    - 122f–124f, 126f
  - SHT11 temperature and relative
    - humidity sensor, 277f
  - Sin function, 47, 234–235
  - Sine waveform, 234–239, 237f,
    - 239f–240f
  - Sinh function, 47
  - Slave mode Bluetooth serial
    - communication, 333–361,
    - 334f–336f, 338f–339f,
    - 343f–348f, 353f–354f, 356f
  - Sleep function, 49
  - SM, <value> command, 340
  - SN, <value> command, 340
  - SO, <value> command, 340
  - Software library functions, 46–49
  - Sound generation, 156–160,
    - 156f–159f, 161f
  - Sound\_Play function, 157
  - SP, <string> command, 340
  - SP11\_Write function, 535
  - SPI bus, 216–217, 217f, 447–448
    - complex bus project, 389–414,
    - 406f, 408f, 415f
    - clock edge mode, 401
    - control register, 405
    - data clock rate, 400
    - displaying fractional part, 414
    - displaying negative
      - temperatures, 413–414
    - enabling SPI mode, 401–402
    - LSB and MSB registers, 405
    - manufacturer ID, 405
    - MSSP configuration for SPI
      - master mode, 400
    - MSSP in SPI mode, 396–397,
      - 397f
    - MSSP module, 389–396
    - operation in SPI mode, 398,
      - 399f
    - receiving data from slave, 400
    - sending data to slave, 400
    - SPI mode registers, 397–398,
      - 398f–399f
    - TC72 internal registers, 404t,
      - 405
    - TC72 read/write operations,
      - 404–405
    - TC72 temperature sensor,
      - 402–403
  - SPI\_Ethernet\_doPacket function,
    - 519
  - SPI\_Ethernet\_Init function, 516
  - SPI\_Ethernet\_UserTCP function,
    - 522
  - SPI\_Ethernet\_UserUDP function,
    - 522
  - SPI\_Init function, 219–220, 516
  - SPI\_Set\_Active function, 222
  - SPIx\_Init function, 220
  - SPIx\_Init\_Advanced function, 220
  - SPIx\_Read function, 220
  - SPIx\_Write function, 220
  - Split termination of CAN bus,
    - 552–553
  - Sqrt function, 49
  - Square waveform, 239–247,
    - 243f–247f
  - SR,, 341–346
  - Srand function, 207, 212
  - SSPxCON1 register, 398, 399f
  - SSPxSTAT register, 398, 398f
  - Stadiometer, 248
    - mechanical, 248f
  - Standard termination of CAN bus,
    - 552–553
  - StartTasks function, 590, 594
  - Statements
    - iteration, 17
    - selection, 15
  - Stepper motor control
    - bipolar motor drive, 608–611,
      - 609f–612f, 614f
    - complex control of unipolar
      - motor, 604–608,
      - 605f–606f
    - unipolar motor drive, 598–602,
      - 601f–603f
  - Stepper\_Motor function, 608
  - Strchr function, 296
  - String functions, 49
  - Structures, 14
  - SU, <value> command, 340
  - Subprograms, 55, 56f
    - structure, 56–57, 56f
  - SwapTask function, 594
  - Switch statement, 16, 193, 582
- ## T
- Tan function, 47
  - Tanh function, 47
  - TC72 temperature sensor,
    - 402–403
    - internal registers, 404t, 405
    - pin configuration, 402f
    - read/write operations,
      - 404–405
  - TCP protocol, 509, 512, 512t, 519
  - Telnet interface, 511
  - Temperature
    - data logger, SD card-based,
      - 466–476, 468f, 470f,
      - 476f–477f
    - measurement, 277–290, 277f,
      - 279t, 281t, 282f, 282t,
      - 283f–285f, 290f
    - acknowledgment, 279
    - conversion command, 279
    - conversion of signal output,
      - 280–281
    - RESET, 277–278
    - Status register, 279–280
    - transmission start sequence,
      - 278
  - ON–OFF control, 317–325,
    - 317f–320f, 324f, 825

Temperature (*Continued*)

- sensor and display using CAN, 568, 569f–570f, 577f
- COLLECTOR processor, 569
- COLLECTOR program, 574–577, 575f
- DISPLAY processor, 569–570
- DISPLAY program, 570–574, 571f
- TC72 temperature sensor, 402–403
- variation plotting on GLCDs, 501–508, 502f–505f, 508f

Terminal emulator software, 297

Thermometer

- digital, 168–171, 168f–170f
- display on GLCDs, 490–501, 491f, 493f, 495f–496f, 501f
- with RS232 serial output, 290–304, 291f, 291t, 292f–295f, 298f–301f

39HS02 bipolar stepper motor, 611f

Timing parameters calculation in CAN bus, 563–564

Toascii function, 49

Tolower function, 49

Toupper function, 49

Transducers, ultrasonic, 249f

Transmission\_Start\_Sequence function, 289–290

Triangle waveform generation, 229, 230f–231f

Trunc function, 49

Two-dice project, 94–98, 100f–102f, 104f

- using fewer I/O pins, 98–109, 105t, 106f, 106t, 107f, 107t, 108f, 110f, 111t, 112f–113f

Two-digit multiplexed 7-segment LED, 120–125, 120f–121f, 121t, 122f–124f, 126f

Two-dimensional arrays, 13

Two-phase full-step sequencing, 598, 599t

Two-phase half-step sequencing, 599, 600t

**U**

UAG2 stepper motor, 601–602

UART communication, 374–375

UART\_Set\_Active function, 297

Uart1\_Data\_Ready function, 306

Uart1\_Read function, 306

Uart1\_Read\_Text function, 316

UARTx\_Data\_Ready function, 296

UARTx\_Init function, 296

UARTx\_Read function, 296

UARTx\_Read\_Text function, 296

UARTx\_Tx\_Idle function, 296

UARTx\_Write function, 297

UARTx\_Write\_Text function, 297

UCN5804B stepper motor, 604

UDP protocol, 512, 512t, 519

- based Ethernet control, 521–522, 522f–523f, 526f

Ultrasonic human height measurement, 248–258, 249f–251f, 253f, 255f

Unconditional frame identifiers, 538

Unipolar A/D converter, 216

Unipolar stepper motors, 598–599

- complex control of, 604–608, 605f–606f
- drive, 598–602, 601f–603f
- windings, 599f

Universal serial bus (USB)

- USB-RS232 converter cable, 297
- USB-UART port, 299–304, 300f

Universal Synchronous—

- Asynchronous Receiver—Transmitter (UDART), 292

Universal Synchronous—

- Asynchronous Receiver—Transmitter (USART), 306

Unsigned long, 144–146

**V**

Variable

- accessing individual bits of, 45
- names, 11
- types, 11t, 44, 44t

Void functions, 20

Voltmeter

- LCD, 140–152, 143f–145f, 147t, 148f, 151t, 152f–153f
- LED, 129–140, 133f–135f, 137f

**W**

Waveform generation, 214–247, 215f

- arbitrary waveform, 229–234, 232f–233f, 235f
- DAC, 215–216, 215f
- sawtooth waveform, 217–219, 218f–223f, 225f, 227f
- sine waveform, 234–239, 237f, 239f–240f
- SPI bus, 216–217, 217f
- square waveform, 239–247
- triangle waveform, 229, 230f–231f

Web browser-based control of Ethernet, 508–521, 509f–517f, 519f

While statement, 18, 389, 541, 546

- loop, 193–194

WriteCmdXLCD function, 151

WriteSPI function, 226

WritexUSART function, 303

Writing data in SD cards, 451

**X**

XC8. *see* MPLAB XC8 compiler, XC8 language features