

Note: Page numbers followed by “f” refer to figures, respectively.

8 bit register, 1
24 hour clock, 93–95

A

Accurate timing, 91
Acos, 162
Acquisition time, 62
ADCON0, 59–60
ADCON1, 60–61, 61f, 73, 73f, 74
ADCON2, 61–62, 61f
Adding files to a project, 32f
Alpha numeric display, 75
Analogue measurements, 59, 115–118
Analogue to digital conversion, 59
Asin, 162
Atan, 162

B

Binary number, 8
Bits, 1–2
Break points, 103, 105f

C

C file, 36
C function, 18
C language, 161
C program, 5
C programming language, 2–3
Capacitance measurement, 154–157
Character display address, 82
Chess clock, 143–151
Compiling C code, 19, 21f
Conditional operators, 169
Configuring A to D, 59
Configuring the LCD, 75–81
Conversion clock speed, 61
Conversion time, 62
Cos, 163
Cosh, 163
Countdown timer, 139–143

D

Data pulse train, 130f
Data types, 169
Decimal number, 8
Define statement, 58
Delays, 6–7
Development kit, 118, 118f, 126
Disco lights, 39–41
Displaying measurements, 82–83
Displaying room temperature, 83

E

EEADR register, 135
EECON1 register, 135, 135–136, 136f
EECON2 register, 135, 138
EEDATA register, 135, 138
EEPROM data memory, 135
Equations, 154–155
Error handling, 19
Error types, 19–21
Event timing, 90–91
Exp, 163

F

Float, floating point number, 72
For loop, 40

G

Global interrupt enable, 97
GO_DONE bit, 67–68
Greenhouse, 69, 70f

H

Header code, 87–88
Header program, 41, 41–42, 41f
Hex file, 5, 21, 33
Hexadecimal number, 8
High priority interrupt, 97
Hitachi HD44780 LCD control IC, 75

I

ICD 3, 119
 If statement, 43, 49–50
 If-else statement, 44–46
 In-circuit debugger, 103
 In-circuit debugger3 (ICD3), 5, 21, 21, 23*f*
 Include statement, 16–18
 Inputs, 43
 Int, integer, 67
 Integrated development environment, IDE, 5
 Interrupt enable, 97
 Interrupt every 10 minutes, 102
 Interrupt flag, 98
 Interrupt service routine, 98
 Interrupts, 97

K

Keypad header code, 58
 Keypad program, 52–54
 Keypad scanning, 49

L

LCD, 155–156
 LCD Character Set, 80*f*
 LCD header, 81
 LCD program, 76–79
 Least significant bit, 1
 Line numbers, 8, 11*f*, 30
 Log, 165
 Log10, 165
 Loops, 7–8
 Loops in a program, 39
 Low priority interrupt, 97

M

Machine code file, 8–9
 Main function, 40, 46
 Maths header, 162, 167
 Memory location, 1, 1*f*
 Microchip C18 Toolsuite, 9, 13*f*
 Microcontroller, 1
 Most significant bit, 1
 MPLAB, 5–6, 8–19, 22–25, 103–128
 MPLAB C18, 9, 13*f*, 18
 MPLABX, 5–6, 24–25, 120–123
 MPLABX XC8, 5, 25, 25, 27, 28*f*
 Multiple A to D, 70

O

One minute delay, 92–93
 One second time, 92
 OSCCON, 69, 72
 Oscillator configuration, 7, 18
 Outputs, 35

P

PIC18(L)F43K22, 73, 74*f*
 PIC18F1220, 1
 PIC18F2420, 73
 PIC18F4420, 73, 74*f*
 PICkit3, 5, 21, 21, 23*f*, 33, 126
 PORTA, 70, 72
 PORTB, 1, 1–2, 2*f*, 70, 72
 Porting code, 87
 Potential divider, 151, 160
 Pow, 166
 Pragma statement, 16, 18
 Prescaler, 89
 Processor frequency, 106
 Programming the
 microcontroller, 21–23, 33*f*
 Project files, 14, 14*f*
 Project window, 27, 29*f*, 32*f*
 Project wizard, 9, 12*f*, 25
 Projects, 139
 Pull-ups, 51

R

Radio receiver, 129
 Radio transmitter, 129
 RB4-7 change interrupt, 98
 Resistance measurement, 151–154
 Result register, 62–63
 Return values, 162, 167

S

Second delay, 38
 Set address function, 79
 Simulator, 103
 Sin, 166
 Single step, 110, 111*f*
 Sinh, 167
 Solar panel, 71–73, 71*f*
 Source files, 27, 29, 29, 32*f*
 Special function registers, 103
 Sqrt, 167

Stimulus file, 123
Stopwatch, 103–111, 106*f*, 110*f*, 124–128

T

Tan, 167
Tanh, 167
Temperature measurement, 59, 63, 71
Temperature sensing IC, LM335, 65
Thermistor, 63–64
Thirty minute delay, 95–96
Timer/Counter modules, 89
TMR0 overflow interrupt, 97, 101–102
TMR0, 89
TMR0 prescaler, 142
TRISA, 70, 72
TRISB, 2
TRISB, 72

U

User registers, 106

V

Voltmeter, 157–160

W

Watch dog timer, 18
Watch window, 103, 106, 107*f*, 108*f*, 110, 111*f*,
112, 113*f*, 117*f*, 118
While loop, 7–8
WR, write bit, 135
WREN, write enable bit, 135
WriteChar function, 82–83, 85
WriteCmd, write command, 77–79, 84–85
Year delay, 96