

---

## O-RAN Work Group 10 (OAM for O-RAN) **O-RAN O1 Interface Specification**

Copyright © 2026 by the O-RAN ALLIANCE e.V.

The copying or incorporation into any other work of part or all of the material available in this specification in any form without the prior written permission of O-RAN ALLIANCE e.V. is prohibited, save that you may print or download extracts of the material of this specification for your personal use, or copy the material of this specification for the purpose of sending to individual third parties for their information provided that you acknowledge O-RAN ALLIANCE as the source of the material and that you inform the third party that these conditions apply to them and that they must comply with them.

O-RAN ALLIANCE e.V., Buschkauler Weg 27, 53347 Alfter, Germany

Register of Associations, Bonn VR 11238, VAT ID DE321720189

---

# Contents

|                                                             |    |
|-------------------------------------------------------------|----|
| Foreword.....                                               | 4  |
| Modal verbs terminology .....                               | 4  |
| Introduction .....                                          | 4  |
| 1 Scope .....                                               | 5  |
| 2 References .....                                          | 5  |
| 2.1 Normative references .....                              | 5  |
| 2.2 Informative references .....                            | 6  |
| 3 Definition of terms, symbols and abbreviations.....       | 7  |
| 3.1 Terms .....                                             | 7  |
| 3.2 Symbols .....                                           | 7  |
| 3.3 Abbreviations.....                                      | 7  |
| 4 General Requirements .....                                | 9  |
| 4.1 Void .....                                              | 9  |
| 4.2 Void .....                                              | 9  |
| 4.3 HyperText Transfer Protocol (HTTP).....                 | 9  |
| 4.4 Void .....                                              | 9  |
| 4.5 Void .....                                              | 9  |
| 4.6 Void .....                                              | 9  |
| 4.7 File Transfer Protocol (SFTP, FTPeS or HTTPS) .....     | 9  |
| 4.8 Security .....                                          | 10 |
| 5 O1 Notifications .....                                    | 10 |
| 5.1 General.....                                            | 10 |
| 5.2 O-RAN Defined O1 Notification.....                      | 11 |
| 5.2.1 Requirements.....                                     | 11 |
| 5.2.2 stdDefinedNamespace name space for O-RAN .....        | 11 |
| 6 Management Services .....                                 | 12 |
| 6.1 Provisioning Management Services.....                   | 12 |
| 6.1.0 Overview .....                                        | 12 |
| 6.1.1 General NETCONF Requirements.....                     | 12 |
| 6.1.2 Create Managed Object Instance.....                   | 13 |
| 6.1.3 Modify Managed Object Instance Attributes .....       | 14 |
| 6.1.4 Delete Managed Object Instance.....                   | 15 |
| 6.1.5 Read Managed Object Instance Attributes .....         | 16 |
| 6.1.6 Notify Managed Object Instance Changes .....          | 17 |
| 6.1.7 Void.....                                             | 19 |
| 6.1.8 NETCONF Session Establishment.....                    | 19 |
| 6.1.9 NETCONF Session Termination.....                      | 19 |
| 6.1.10 Lock Data Store.....                                 | 20 |
| 6.1.11 Unlock Data Store .....                              | 21 |
| 6.1.12 Commit.....                                          | 21 |
| 6.1.13 Notify Event .....                                   | 22 |
| 6.1.14 Data Node Tree Reliability Notifications.....        | 23 |
| 6.2 Fault Supervision Management Services .....             | 26 |
| 6.2.0 Overview .....                                        | 26 |
| 6.2.1 Fault Notification .....                              | 26 |
| 6.2.2 Fault Supervision Control .....                       | 27 |
| 6.2.3 Fault History Supervision Control and Reporting ..... | 28 |
| 6.3 Performance Assurance Management Services .....         | 29 |
| 6.3.0 Overview .....                                        | 29 |

|                                                                                              |                                                                                                           |    |
|----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|----|
| 6.3.1                                                                                        | Performance Data File Reporting.....                                                                      | 29 |
| 6.3.2                                                                                        | Performance Data Streaming.....                                                                           | 35 |
| 6.3.3                                                                                        | Measurement Job Control .....                                                                             | 37 |
| 6.3.4                                                                                        | O-RAN Defined Performance Measurements.....                                                               | 38 |
| 6.4                                                                                          | Trace Management Services.....                                                                            | 38 |
| 6.4.0                                                                                        | Overview .....                                                                                            | 38 |
| 6.4.1                                                                                        | Call Trace .....                                                                                          | 39 |
| 6.4.2                                                                                        | Minimization of Drive Testing (MDT) .....                                                                 | 41 |
| 6.4.3                                                                                        | Radio Link Failure (RLF) .....                                                                            | 41 |
| 6.4.4                                                                                        | RRC Connection Establishment Failure (RCEF) .....                                                         | 42 |
| 6.4.5                                                                                        | Trace Control .....                                                                                       | 42 |
| 6.4.6                                                                                        | Streaming Trace .....                                                                                     | 43 |
| 6.4.7                                                                                        | UE Identifiers for Trace Records .....                                                                    | 44 |
| 6.4.8                                                                                        | RRC reporting .....                                                                                       | 44 |
| 6.5                                                                                          | File Management Services.....                                                                             | 45 |
| 6.5.0                                                                                        | Overview .....                                                                                            | 45 |
| 6.5.1                                                                                        | File Ready Notification .....                                                                             | 45 |
| 6.5.2                                                                                        | List Available Files .....                                                                                | 46 |
| 6.5.3                                                                                        | File Transfer to and from File Management MnS Producer.....                                               | 47 |
| 6.5.4                                                                                        | Download File from remote file server .....                                                               | 48 |
| 6.5.5                                                                                        | Void.....                                                                                                 | 50 |
| 6.6                                                                                          | Heartbeat Management Capability .....                                                                     | 50 |
| 6.6.0                                                                                        | Overview .....                                                                                            | 50 |
| 6.6.1                                                                                        | Heartbeat Notification .....                                                                              | 50 |
| 6.6.2                                                                                        | Heartbeat Control .....                                                                                   | 51 |
| 6.7                                                                                          | Registration Management capability .....                                                                  | 51 |
| 6.7.0                                                                                        | Overview .....                                                                                            | 51 |
| 6.7.1                                                                                        | PNF Plug-n-Connect .....                                                                                  | 51 |
| 6.7.2                                                                                        | O1 Registration .....                                                                                     | 52 |
| 6.8                                                                                          | PNF Software Management Services .....                                                                    | 57 |
| 6.8.0                                                                                        | Overview .....                                                                                            | 57 |
| 6.8.1                                                                                        | Software Package Naming and Content.....                                                                  | 57 |
| 6.8.2                                                                                        | Software Inventory .....                                                                                  | 58 |
| 6.8.3                                                                                        | Software Download.....                                                                                    | 59 |
| 6.8.4                                                                                        | Software Activation Pre-Check.....                                                                        | 61 |
| 6.8.5                                                                                        | Software Activate.....                                                                                    | 62 |
| 6.9                                                                                          | PNF Reset Management Services.....                                                                        | 64 |
| 6.9.0                                                                                        | Overview .....                                                                                            | 64 |
| 6.9.1                                                                                        | PNF Reset Command.....                                                                                    | 64 |
| 6.9.2                                                                                        | Notifications .....                                                                                       | 67 |
| 6.10                                                                                         | Void .....                                                                                                | 67 |
| 6.11                                                                                         | Generic Management Capabilities .....                                                                     | 67 |
| 6.11.1                                                                                       | Overview .....                                                                                            | 67 |
| 6.11.2                                                                                       | Subscription Control .....                                                                                | 67 |
| 6.11.3                                                                                       | Reliable Notifications.....                                                                               | 68 |
| Annex A: Void .....                                                                          |                                                                                                           | 71 |
| Annex B: (informative) Guidelines and Example for stdDefined VES Events.....                 |                                                                                                           | 72 |
| B.1:                                                                                         | Guidelines for use of stdDefined VES for sending 3GPP-specified or O-RAN-specified O1 notifications ..... | 72 |
| B.2:                                                                                         | Example stdDefined VES event for a new alarm notification .....                                           | 73 |
| Annex C: (informative) Streaming Trace Management Activation Example .....                   |                                                                                                           | 75 |
| Annex D: (normative) Recommendation for UE Identifier Format in Trace Header .....           |                                                                                                           | 79 |
| Annex E: (informative) Reliable Notifications – Detection & Retrieval Procedure example..... |                                                                                                           | 81 |
| Annex (informative): Change History .....                                                    |                                                                                                           | 82 |

---

## Foreword

This Technical Specification (TS) has been produced by WG10 of the O-RAN ALLIANCE.

The content of the present document is subject to continuing work within O-RAN and may change following formal O-RAN approval. Should the O-RAN ALLIANCE modify the contents of the present document, it will be re-released by O-RAN with an identifying change of version date and an increase in version number as follows:

version xx.yy.zz

where:

- xx: the first digit-group is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc. (the initial approved document will have xx=01). Always 2 digits with leading zero if needed.
- yy: the second digit-group is incremented when editorial only changes have been incorporated in the document. Always 2 digits with leading zero if needed.
- zz: the third digit-group included only in working versions of the document indicating incremental changes during the editing process. External versions never include the third digit-group. Always 2 digits with leading zero if needed.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the O-RAN Drafting Rules (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are NOT allowed in O-RAN deliverables except when used in direct citation.

---

## Introduction

The O-RAN O1 management services follow existing 3GPP standards wherever possible. The focus of the present document is to identify the use cases which conform to existing 3GPP standards, identify gaps in management services for O-RAN and define needed extensions. For identified gaps, the goal is to modify the 3GPP standards to include the needed O-RAN extensions and update the references in the present document as the 3GPP standards evolve to cover the gaps. In cases where the 3GPP standards are not modified, O-RAN extensions are specified in this, and other, O-RAN documents. O-RAN extensions are compatible with 3GPP standards as much as possible to avoid divergence. If extensions and gaps are not specified, it is expected that the management services producers and consumers are conforming to referenced 3GPP specifications.

This O1 Interface Specification specifies the management services (MnS) supported in the O-RAN architecture between O1 compliant Managed Elements (MnS producers) and the SMO (MnS consumer). It defines common MnS descriptions, requirements, procedures, operations, and notifications. O-RAN end-to-end OAM use cases and OAM architectural principles are specified in O-RAN TS O-RAN Operations and Maintenance Architecture [i.13].

---

# 1 Scope

The present document defines O-RAN OAM interface services and protocols for the O-RAN O1 interface. The present document studies the services conveyed over the interface, including management services, procedures, operations, and corresponding solutions, and identifies existing standards and industry work that can serve as a basis for O-RAN work.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies. In the case of a reference to a 3GPP document, a non-specific reference implicitly refers to the latest version of that document in 3GPP Release 18, or the latest 3GPP release prior to Release 18 that includes that document.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, O-RAN cannot guarantee their long-term validity.

The following referenced documents are necessary for the application of the present document.

- [1] 3GPP TS 28.314 V19.1.0: "Management and orchestration; Plug and Connect; Concepts and requirements".
- [2] 3GPP TS 28.315 V19.0.0: "Management and orchestration; Plug and Connect; Procedure flows".
- [3] 3GPP TS 28.532 V19.3.0: "Management and orchestration; Generic management services".
- [4] 3GPP TS 28.537 V19.4.0: "Management and orchestration; Management capabilities".
- [5] Void
- [6] 3GPP TS 28.550 V19.2.0: "Management and orchestration; Performance assurance".
- [7] 3GPP TS 28.622 V19.6.0: "Telecommunication management; Generic Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS)".
- [8] 3GPP TS 32.341 V19.0.0: "Telecommunication management; File Transfer (FT) Integration Reference Point (IRP); Requirements".
- [9] 3GPP TS 32.342 V19.0.0: "Telecommunication management; File Transfer (FT) Integration Reference Point (IRP); Information Service (IS)".
- [10] Void
- [11] 3GPP TS 32.421 V19.4.0: "Telecommunication management; Subscriber and equipment trace; Trace concepts and requirements".
- [12] 3GPP TS 32.422 V19.5.0: "Telecommunication management; Subscriber and equipment trace; Trace control and configuration management".
- [13] 3GPP TS 32.423 V19.5.0: "Telecommunication management; Subscriber and equipment trace; Trace data definition and management".
- [14] 3GPP TS 32.432 V19.0.0: "Telecommunication management; Performance measurement: File format definition".
- [15] O-RAN.WG1.TS.OAD: "O-RAN Architecture Description".
- [16] Void

- [17] O-RAN.WG11.TS.SRCS.0: "O-RAN Security Requirements and Controls Specifications".
- [18] ONAP VES Event Listener Specification v7.2.1, January 16, 2021.
- [19] RFC 6022, "YANG Module for NETCONF Monitoring", IETF, October 2010.
- [20] RFC 6241, "Network Configuration Protocol (NETCONF)", IETF, June 2011.
- [21] RFC 7950, "The YANG 1.1 Data Modeling Language", IETF, August 2016.
- [22] RFC 7951, "JSON Encoding of Data Modeled with YANG", IETF, August 2016.
- [23] 3GPP TS 28.623 V19.6.0: "Telecommunication management; Generic Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions".
- [24] RFC 6243, "With-defaults Capability for NETCONF", IETF, June 2011.
- [25] 3GPP TS 28.632 V19.0.0: "Telecommunication management; Inventory Management (IM) Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS)".
- [26] 3GPP TS 28.111 V19.4.0: "Management and orchestration; Fault Management (FM)".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies. In the case of a reference to a 3GPP document, a non-specific reference implicitly refers to the latest version of that document in 3GPP Release 18, or the latest 3GPP release prior to Release 18 that includes that document.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, O-RAN cannot guarantee their long-term validity.

The following referenced documents are not necessary for the application of the present document, but they assist the user with regard to a particular subject area.

- [i.1] 3GPP TR 21.905 V19.1.0: "Vocabulary for 3GPP Specifications".
- [i.2] 3GPP TS 28.316 V19.0.0: "Management and orchestration; Plug and Connect; Data formats".
- [i.3] 3GPP TS 28.531 V19.2.0: "Management and orchestration; Provisioning".
- [i.4] 3GPP TS 28.533 V19.4.0: "Management and orchestration: Architecture framework".
- [i.5] 3GPP TS 28.552 V19.6.0: "Management and orchestration; 5G performance measurements".
- [i.6] Void
- [i.7] Void
- [i.8] 3GPP TS 32.346 V19.0.0: "Telecommunication management; File Transfer (FT) Integration Reference Point (IRP): Solution Set (SS) definitions".
- [i.9] 3GPP TS 37.320 V19.1.0: "Universal Terrestrial Radio Access (UTRA), Evolved Universal Terrestrial Radio Access (E-UTRA) and Next Generation Radio Access; Radio measurement collection for Minimization of Drive Tests (MDT); Overall description; Stage 2".
- [i.10] Void
- [i.11] Void
- [i.12] Void
- [i.13] O-RAN.WG10.TS.OAM-Architecture: "O-RAN Operations and Maintenance Architecture".

- [i.14] O-RAN.WG10.TS.Information Model and Data Models.0: "O-RAN Information Model and Data Models Specification".
- [i.15] 3GPP TS 32.158 V19.1.0: "Management and orchestration; Design rules for REpresentational State Transfer (REST) Solution Sets (SS)".
- [i.16] O-RAN.WG10.TS.O1NRM.0: "O1 Network Resource Model ".
- [i.17] O-RAN.WG10.TS.O1PMeas: "O-RAN O1 Performance Measurements Specification".
- [i.18] Void
- [i.19] O-RAN.WG5.O-DU-O1: "O1 Interface specification for O-DU".
- [i.20] O-RAN.WG5.O-CU-O1: "O1 Interface specification for O-CU-UP and O-CU-CP".
- [i.21] 3GPP TS 32.156 V19.3.0: "Telecommunication management; Fixed Mobile Convergence (FMC) model repertoire".
- [i.22] O-RAN.WG6.ORCH-USE-CASES: "Cloudification and Orchestration Use Cases and Requirements for O-RAN Virtualized RAN".

---

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the terms given in 3GPP TR 21.905 [i.1] and the following apply.

NOTE: A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [i.1].

**NF Deployment:** Refer to O-RAN WG6.ORCH-USE-CASES, Cloudification and Orchestration Use Cases and Requirements for O-RAN Virtualized RAN [i.22], clause 1.2.1

### 3.2 Symbols

For the purposes of the present document, the symbols given in 3GPP TR 21.905 [i.1] apply.

NOTE: A symbol defined in the present document takes precedence over the definition of the same symbol, if any, in 3GPP TR 21.905 [i.1].

### 3.3 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [i.1] and the following apply.

NOTE 1: An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [i.1].

|       |                                                |
|-------|------------------------------------------------|
| 3GPP  | 3 <sup>rd</sup> Generation Partnership Project |
| ASN.1 | Abstract Syntax Notation One                   |
| CM    | Configuration Management                       |
| CRUD  | Create, Read, Update, Delete                   |
| FS    | Fault Supervision                              |

|             |                                                              |
|-------------|--------------------------------------------------------------|
| FTPES       | File Transfer Protocol with Explicit SSL/TLS encryption      |
| GPB         | Google Protocol Buffers                                      |
| HTTP        | HyperText Transfer Protocol                                  |
| HTTPS       | HTTP Secure                                                  |
| ID          | IDentifier                                                   |
| IETF        | Internet Engineering Task Force                              |
| IOC         | Information Object Class                                     |
| IP          | Internet Protocol                                            |
| JSON        | JavaScript Object Notation                                   |
| MDT         | Minimization of Drive Testing                                |
| ME          | Managed Element                                              |
| MF          | Managed Function                                             |
| MHI         | Mobility History Information                                 |
| MnS         | Management Service                                           |
| MOC         | Managed Object Class                                         |
| MOI         | Managed Object Instance                                      |
| Near-RT RIC | O-RAN Near Real Time RAN Intelligent Controller              |
| NETCONF     | NETwork CONFiguration protocol                               |
| NF          | Network Function                                             |
| NGRAN       | Next Generation Radio Access Network                         |
| NMS         | Network Management System                                    |
| NR          | New Radio                                                    |
| NRM         | Network Resource Model                                       |
| O-CU-CP     | O-RAN Central Unit – Control Plane.                          |
| O-CU-UP     | O-RAN Central Unit – User Plane                              |
| O-DU        | O-RAN Distributed Unit                                       |
| O-RAN       | Open Radio Access Network                                    |
| O-RU        | O-RAN Radio Unit                                             |
| ONAP        | Open Network Automation Platform                             |
| PM          | Performance Management or Performance Measurements           |
| PNF         | Physical Network Function                                    |
| RA          | Random Access                                                |
| RAN         | Radio Access Network                                         |
| RCEF        | RRC Connection Establishment Failure                         |
| REST        | REpresentational State Transfer                              |
| RFC         | Request For Comments                                         |
| RLF         | Radio Link Failure                                           |
| RRC         | Radio Resource Control                                       |
| SA5         | Services & System Aspects Working Group 5 Telecom Management |
| SBMA        | Services Based Management Architecture                       |



NOTE 2: See 3GPP TS 28.533 [i.4], clause 4.

|      |                                          |
|------|------------------------------------------|
| SDO  | Standards Defining Organization          |
| SMO  | Service Management and Orchestration     |
| SFTP | SSH File Transfer Protocol               |
| SHR  | Successful Handover Report               |
| SPR  | Successful PSCell Addition/Change Report |
| SSH  | Secure Shell                             |
| TLS  | Transport Layer Security                 |
| TR   | Technical Report                         |
| TRS  | Trace Recording Session                  |
| TS   | Technical Specification                  |
| UE   | User Equipment                           |
| URI  | Uniform Resource Identifier              |
| VES  | VNF Event Stream                         |
| VNF  | Virtualized Network Function             |
| XML  | eXtensible Markup Language               |

---

## 4 General Requirements

### 4.1 Void

### 4.2 Void

### 4.3 HyperText Transfer Protocol (HTTP)

REQ-HTP-FUN-1: Management Service producers and consumers that use HTTP shall support HTTP v1.1 or higher.

REQ-HTP-FUN-2: Management Service producers and consumers that use HTTP should support HTTP v2.0.

### 4.4 Void

### 4.5 Void

### 4.6 Void

### 4.7 File Transfer Protocol (SFTP, FTPeS or HTTPS)

File Transfer shall be performed using a secure file transfer protocol from or to the File Management MnS Producer (SFTP, FTPeS or HTTPS) as defined in clause 7.1.3 of 3GPP TS 28.537 [4].

## 4.8 Security

Security requirements specified in O-RAN Security Requirements and Controls Specifications [17] clause 5.2.2 shall apply.

---

# 5 O1 Notifications

## 5.1 General

An O1 notification is a JSON encoded asynchronous notification sent from a MnS producer to a MnS consumer over the O1 interface using REST/HTTPS.

An O1 notification shall be in one of the following formats:

- SDO O1 format;
- VES O1 format.

An SDO O1 format notification is an O1 notification formatted as specified by a Standards Defining Organization (SDO). Currently, O1 supports SDO O1 format notifications that are either 3GPP-specified or O-RAN-specified. SDO O1 format notifications are formatted as specified by the SDO and sent without a VES header.

3GPP-specified O1 notifications are specified in 3GPP TS 28.532 [3] clauses 11 and 12, and in 3GPP TS 28.111 [26] clause 8.

O-RAN-specified O1 notifications are specified in the O-RAN O1 Network Resource Model Specification [i.16].

O-RAN-specified O1 notifications should follow 3GPP naming and format where possible to reduce the number of variants that need to be supported. Specifically, O-RAN-specified O1 notifications should:

- be named "o1NotifyXxx";
- include the common 3GPP notification fields objectClass, objectInstance, notificationId, notificationType, eventTime and systemDN;
- include an additionalText and/or additionalInformation field when appropriate.

A VES O1 format notification is an O1 notification formatted as specified by VES Event Listener Specification [18], consisting of a common event header and domain-specific event fields. VES O1 format notifications are categorized into 2 types, based on domain:

- Harmonized VES;
- Legacy VES.

Harmonized VES refers to the stdDefined VES event specified in VES Event Listener Specification [18] that allows a VES event to carry, as its payload, a notification specified by an SDO. In the case of O-RAN O1 Interface Specification, a harmonized stdDefined VES event carries either a 3GPP-specified O1 notification or an O-RAN specified O1 notification as its payload.

Legacy VES refers to any VES event specified in the VES Event Listener Specification [18], except for stdDefined. Legacy VES events are fully defined in [18] and do not rely on an SDO to specify the content of the payload. The Legacy VES events supported by O1 Interface Specification is PNF Registration.

Legacy VES events are supported for backward compatibility. However, harmonized VES events are preferred. Use of harmonized VES events results in less notification variants for the producers and the consumers because a harmonized VES O1 format notification is effectively an SDO O1 format notification wrapped in a VES common event header.

Two attributes are used to communicate the notification format between MnS producer and MnS consumer:

- o1NotifyFormatCapabilities indicates whether the MnS producer supports the capability to send notifications in SDO O1 format, VES O1 format or both. This attribute is set by the MnS producer at the Managed Element

level, meaning the capability is for all O1 notifications sent by that MnS producer. It is not per notification type. This attribute is read-only for the MnS consumer.

- o1NotifyFormatConfig indicates whether the MnS consumer wants to receive notifications in SDO O1 format or VES O1 format. This attribute is optional to be supported by MnS producer. This attribute is configured by the MnS consumer at the Managed Element level, meaning the configuration is for all O1 notifications sent by that MnS producer. It is not per notification type. If the MnS producer supports both formats, the MnS producer sets the value for this attribute to the default value of VES O1 format when the MOI is created and the MnS consumer is permitted to change the value to SDO O1 format if desired. Otherwise, if the MnS producer only supports one notification format, this attribute is absent.

Configuration attributes are specified in the O-RAN O1 Network Resource Model Specification [i.16].

It is not necessary to have an attribute to indicate whether harmonized VES or legacy VES is sent for VES format because the domain of the event is provided in the VES common event header and the schema of the event is provided by the Network Function at onboarding time.

## 5.2 O-RAN Defined O1 Notification

### 5.2.1 Requirements

REQ-ON-FUN-1: O-RAN defined O1 registration notification shall be JSON encoded for sending via REST/HTTPS.

REQ-ON-FUN-2: Schema for O-RAN defined O1 notification shall be specified using OpenAPI.

REQ-ON-FUN-3: If VES O1 format is configured to be used, O-RAN defined O1 notification shall be presented in harmonized VES format and schemaReference shall refer to O-RAN defined schema in O-RAN public repository when it is available.

NOTE 1: O-RAN public repository is not created yet.

NOTE 2: Before the schema for the O-RAN defined notification is available in the O-RAN public repository, the schemaReference in the VES O1 format for O-RAN defined O1 notification does not need to be a path to the public repository.

### 5.2.2 stndDefinedNamespace name space for O-RAN

O-RAN defines following name space for VES O1 format-harmonized VES format: OR-Registration

For O-RAN defined performance measurements, the short form of measurement name has prefix "OR.". The source of the definition is clear, so there is no need to have a separate O-RAN name space for performance measurement.

O-RAN defined performance measurements should use 3GPP-PerformanceMeasurement name space and refer to 3GPP schema.

## 6 Management Services

### 6.1 Provisioning Management Services

#### 6.1.0 Overview

Provisioning management services allow a Provisioning MnS Consumer to configure attributes of managed objects on the Provisioning MnS Producer that modify the Provisioning MnS Producer's capabilities in its role in end-to-end network services and allows a Provisioning MnS Producer to report configuration changes to the Provisioning MnS Consumer. NETCONF is used for the Provisioning Management Services to Create Managed Object Instance, Delete Managed Object Instance, Modify Managed Object Instance Attributes and Read Managed Object Instance Attributes. A RESTful/HTTP notification with data modelled using YANG is used to notify the Provisioning MnS subscribed Consumers when a configuration change occurs.

Stage 1 Provisioning management services are specified in 3GPP TS 28.531 [i.3] clause 6.3.

Stage 2 Provisioning operations and notifications are specified in 3GPP TS 28.532 [3] clause 11.1.1.

Stage 3 Provisioning operations for YANG/NETCONF solution set are specified in 3GPP TS 28.532 [3] clause 12.1.3.

Stage 3 Provisioning notifications for "YANG/NETCONF-based- solution set" with data modelled using YANG in a RESTful notification is specified in 3GPP TS 28.532 [3] clause 12.1.3.

For the VES header support, refer to 3GPP TS 28.532 [3] clause 12.1.2. The media type of the notification, as specified by the "Content-Type" header in the HTTP POST request, shall be "application/json".

NOTE: In the payload, the data is encoded according to 3GPP TS 28.532 [3] clause 12.1.3.2.5 (except for the content type in the header). Consumption of the payload is implementation dependent.

IETF reference documents for NETCONF and YANG include RFC 6241 [20] and RFC 7950 [21].

#### 6.1.1 General NETCONF Requirements

REQ-GNC-FUN-1: The provisioning management service producer and consumer shall support the following NETCONF operations as specified in RFC 6241 [20]:

- get
- get-config
- edit-config
- lock
- unlock
- close-session
- kill-session

Other operations are optional.

REQ-GNC-FUN-2: The provisioning management service producer and consumer shall support the following NETCONF capabilities as specified in RFC 6241 [20]:

- writable-running
- rollback-on-error
- validate

- xpath

Other capabilities defined in RFC 6241 [20] are optional.

REQ-GNC-FUN-3: The provisioning management service producer and consumer shall support a running datastore for NETCONF. Support for a candidate datastore is optional.

REQ-GNC-FUN-4: The provisioning management service producer and consumer shall support YANG1.1, defined in RFC 7950 [21], including coexistence with YANG Version 1 as specified therein.

REQ-GNC-FUN-5: The provisioning management service producer shall have the capability to establish a NETCONF session with its authorized consumer upon request from the consumer.

REQ-GNC-FUN-6: The provisioning management service producer shall support an established NETCONF session until the authorized consumer terminates the session.

NOTE: The consumer may want to perform multiple provisioning management services operations during a single NETCONF Session.

REQ-GNC-FUN-7: The provisioning management service producer shall have the capability to terminate a NETCONF session with its authorized consumer when requested to do so by the authorized consumer.

REQ-GNC-FUN-8: The provisioning management service producer shall have the capability to make provisioning operation results persistent over a reset.

REQ-GNC-FUN-9: The provisioning management service producer and consumer shall support NETCONF over SSH or NETCONF over TLS.

REQ-GNC-FUN-10: The provisioning management service producer shall support /netconf-state/schemas subtree and <get-schema> RPC defined in RFC 6022 [19] for all supported YANG modules.

REQ-GNC-FUN-11: The provisioning management service producer shall support RFC 6243 [24] "With-defaults capability for NETCONF" as defined by 3GPP TS 28.532 [3], clause 12.1.3.3.2.

## 6.1.2 Create Managed Object Instance

### 6.1.2.1 Description


Provisioning MnS Consumer sends a synchronous provisioning update request to the Provisioning MnS Producer to create a Managed Object Instance (MOI) on the Provisioning MnS Producer and set its attribute values.

### 6.1.2.2 Requirements

The mapping of operations specified in 3GPP TS 28.532 [3] clauses 12.1.3.1.1 and 12.1.3.1.2 shall apply.

### 6.1.2.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.1.2.3-1 Create MOI**

**Pre-Conditions:**

- NETCONF session has been established with Provisioning MnS Producer. NETCONF session has authorized privileges into the identified section of the data store.
- Optionally, target data store has been locked.

**Procedure:**

1. Provisioning MnS Consumer sends NETCONF edit-config create operation to Provisioning MnS Producer:
  - a. Provisioning MnS Producer creates the MOI(s) in the target data store as described in the edit-config operation.
2. Provisioning MnS Producer returns NETCONF response.

## 6.1.3 Modify Managed Object Instance Attributes

### 6.1.3.1 Description


Provisioning MnS Consumer sends synchronous provisioning updates to the Provisioning MnS Producer to modify the attributes of a MOI on the Provisioning MnS Producer.

### 6.1.3.2 Requirements

The mapping of operations specified in 3GPP TS 28.532 [3] clauses 12.1.3.1.1 and 12.1.3.1.4 shall apply.

### 6.1.3.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.1.3.3-1 Modify MOI Attributes**

**Pre-Conditions:**

- NETCONF session has been established with Provisioning MnS Producer. NETCONF session has authorized privileges into the identified section of the data store.
- Optionally, target data store has been locked.

**Procedure:**

1. Provisioning MnS Consumer sends NETCONF edit-config create, replace, or delete operation to Provisioning MnS Producer:
  - a. Provisioning MnS Producer modifies the MOI(s) in the target data store as described in the edit-config operation.
2. Provisioning MnS Producer returns NETCONF response.

## 6.1.4 Delete Managed Object Instance

### 6.1.4.1 Description


Provisioning MnS Consumer sends synchronous provisioning updates to the Provisioning MnS Producer to delete a MOI and its children on the Provisioning MnS Producer.

### 6.1.4.2 Requirements

The mapping of operations specified in 3GPP TS 28.532 [3] clauses 12.1.3.1.1 and 12.1.3.1.5 shall apply.

### 6.1.4.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.1.4.3-1 Delete MOI**

**Pre-Conditions:**

- NETCONF session has been established with Provisioning MnS Producer. NETCONF session has authorized privileges into the identified section of the data store.
- Optionally, target data store has been locked.

**Procedure:**

1. Provisioning MnS Consumer sends NETCONF edit-config delete or remove operation to Provisioning MnS Producer:
  - a. Provisioning MnS Producer deletes the MOI(s) in the target data store as described in the edit-config operation.
2. Provisioning MnS Producer returns NETCONF response.

## 6.1.5 Read Managed Object Instance Attributes

### 6.1.5.1 Description

Provisioning MnS Consumer sends synchronous provisioning request to the Provisioning MnS Producer to return the values of attributes of its MOI(s) on the Provisioning MnS Producer.


### 6.1.5.2 Requirements

The mapping of operations specified in 3GPP TS 28.532 [3] clauses 12.1.3.1.1 and 12.1.3.1.3 shall apply.

### 6.1.5.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.





**Figure 6.1.5.3-1 Read MOI Attributes**

**Pre-Conditions:**

- NETCONF session has been established with Provisioning MnS Producer. NETCONF session has authorized privileges into the identified section of the data store.

**Procedure:**

1. Provisioning MnS Consumer sends NETCONF get or get-config operation to Provisioning MnS Producer:
  - a. Provisioning MnS Producer retrieves the MOI(s) and its attributes from the target data store as described in the get or get-config operation.
2. Provisioning MnS Producer returns the data in the NETCONF response.

## 6.1.6 Notify Managed Object Instance Changes

### 6.1.6.1 Description


Provisioning MnS Producer sends an asynchronous notifyMOIChanges Notification to the Provisioning MnS Consumer to report configuration changes to one or more MOIs on the Provisioning MnS Producer. Refer to 3GPP TS 28.532 [3] clause 12.1.3.2.5 for details.

### 6.1.6.2 Requirements

The mapping of notifications specified in 3GPP TS 28.532 [3] clause 11.1.1.11 shall apply.

### 6.1.6.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.1.6.3-1 Notify Managed Object Instance Changes**

Pre-conditions:

- One or more MOIs are created, deleted or modified in the running data store of the Provisioning MnS Producer.
- Provisioning MnS Consumer has subscribed for notifyMOIChanges notifications.

Procedure:

1. Provisioning MnS Producer sends notifyMOIChanges notification to the Provisioning MnS Consumer over HTTP/TLS. Mutual certificate authentication is performed.

Post-condition:

- Provisioning MnS Consumer reconciles its copy of the Provisioning MnS Producer configuration database with the change.

#### 6.1.6.4 Operations and Notifications

Refer to clause 5.1 for details on O1 notification formats, including SDO O1 format and VES O1 format notifications, categorized as Harmonized VES.

The O1-supported 3GPP-specified CM notification is:

- notifyMOIChanges

A single notifyMOIChanges notification can report one or more MOI creations, MOI deletions and/or MOI attribute value changes in one notification.

The attribute name value pairs in the CM notifications are provided using YANG 1.1 encoded in JSON format as specified in RFC 7951 [22].

## 6.1.7 Void

## 6.1.8 NETCONF Session Establishment

### 6.1.8.1 Description


Provisioning MnS Consumer uses the NETCONF Session Establishment procedure to establish a NETCONF session on the Provisioning MnS Producer.

### 6.1.8.2 Requirements

Requirements for NETCONF session establishment specified in RFC 6241[20] shall apply.

### 6.1.8.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.1.8.3-1 NETCONF Session Establishment**

## 6.1.9 NETCONF Session Termination

### 6.1.9.1 Description


Provisioning MnS Consumer uses the NETCONF Session Termination procedure to gracefully terminate a NETCONF session on a Provisioning MnS Producer.

### 6.1.9.2 Requirements

NETCONF session termination shall be as specified in RFC 6241[20] Section 7.8.

### 6.1.9.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.1.9.3-1 NETCONF Session Termination**

## 6.1.10 Lock Data Store

### 6.1.10.1 Description


Provisioning MnS Consumer uses the Lock Data Store procedure to lock a target data store on a Provisioning MnS Producer. This procedure is optional, but recommended, to prevent unpredictable behavior during configuration changes.

### 6.1.10.2 Requirements

NETCONF lock data store should be as specified in RFC 6241 [20] Section 7.5.

### 6.1.10.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.1.10.3-1 Lock Data Store**

## 6.1.11 Unlock Data Store

### 6.1.11.1 Description


Provisioning MnS Consumer uses the Unlock Data Store procedure to unlock a target data store on a Provisioning MnS Producer.

### 6.1.11.2 Requirements

NETCONF unlock data store should be as specified in RFC 6241 [20] Section 7.6.

### 6.1.11.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.1.11.3-1 Unlock Data Store**

## 6.1.12 Commit

### 6.1.12.1 Description


Provisioning MnS Consumer uses the Commit procedure to commit a configuration change to the running data store of the Provisioning MnS Producer. This is necessary to make the configuration change effective if it was made in the candidate data store. If the configuration change was made in the running data store, the commit procedure is not used.

### 6.1.12.2 Requirements

Requirements for NETCONF commit specified in RFC 6241 [20] Section 8.4 shall apply.

### 6.1.12.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.1.12.3-1 Commit**

## 6.1.13 Notify Event

### 6.1.13.1 Description


Provisioning MnS Producer sends an asynchronous notifyEvent Notification to the Provisioning MnS Consumer to report a network event has occurred with potential service impacts. Please, refer to 3GPP TS 28.532 [3] clause 11.1.1.10 for details.

### 6.1.13.2 Requirements

The mapping of notifications specified in 3GPP TS 28.532 [3] clause 11.1.1.10 and the NETCONF/YANG solution set specified in 3GPP TS 28.532 [3] clause 12.1.3.2.6 shall apply.

### 6.1.13.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.1.13.3-1 Notify Event**

Pre-conditions:

- A notification subscription including NotifyEvent has been explicitly or implicitly created specifying the Provisioning Mns Consumer as the notification recipient.
- One or more network events have occurred with potential service impact

Procedure:

1. Provisioning MnS Producer sends notifyEvent notification to the Provisioning MnS Consumer over HTTP/TLS. Mutual certificate authentication is performed.

Post-condition:

- Provisioning MnS Consumer has received a notifyEvent notification

#### 6.1.13.4 Operations and Notifications

Refer to clause 5.1 for details on O1 notification formats, including SDO O1 format and VES O1 format notifications, categorized as Harmonized VES.

The O1-supported 3GPP-specified CM notification is:

- notifyEvent

### 6.1.14 Data Node Tree Reliability Notifications

#### 6.1.14.1 Overview

The notification types notifyPotentialFaultyDataNodeTree and notifyDataNodeTreeSyncRecommended indicate changes in the reliability of the MnS Producer's data node tree. They help in indicating when the MnS Producer becomes unreliable and when it has regained reliability.

#### 6.1.14.2 Notify Potential Faulty Data Node Tree Notification

##### 6.1.14.2.1 Description

Provisioning MnS Producer sends an asynchronous notifyPotentialFaultyDataNodeTree to the Provisioning MnS Consumer when the data within the node tree is considered potentially unreliable, indicating that subsequent data node

tree change notifications may also be inaccurate or inconsistent. Refer to 3GPP TS 28.532 [3], clause 11.1.1.12.1 for details.


#### 6.1.14.2.2 Requirements

The mapping of notifications specified in 3GPP TS 28.532 [3] clause 11.1.1.12.1 shall apply.

For reliable notification requirements, refer to clause 6.11.3.2.

#### 6.1.14.2.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.1.14.2-1 Notify Potential Faulty Data Node Tree**

Pre-Conditions:

- Provisioning MnS Consumer has subscribed to notifyPotentialFaultyDataNodeTree notifications

Procedure:

1. The Provisioning MnS Producer detects that the information within the data node tree is potentially faulty and unreliable
2. The Provisioning MnS Producer identifies and specifies the affected portion of the data node tree that may be unreliable.
3. The Provisioning MnS Producer sends the notifyPotentialFaultyDataNodeTree notification to Provisioning MnS Consumer.

Post-Condition:

- The Provisioning MnS Consumer receives the notifyPotentialFaultyDataNodeTree notification

#### 6.1.14.3 Notify Data Node Tree Sync Recommended

##### 6.1.14.3.1 Description

Provisioning MnS Producer sends an asynchronous notifyDataNodeTreeSyncRecommended to the Provisioning MnS Consumer and recommends resynchronizing the Provisioning MnS Consumer's copy of the data node tree with the Provisioning MnS Producer's current version after it becomes reliable again. Refer to 3GPP TS 28.532 [3], clause 11.1.1.13.1 for details




### 6.1.14.3.2 Requirements

The mapping of notifications specified in 3GPP TS 28.532 [3] clause 11.1.1.13.1 shall apply.

### 6.1.14.3.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service.. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.1.14.3-1 Notify Data Node Tree Sync Recommended**

Pre-Conditions:

- Provisioning MnS Consumer has subscribed to notifyDataNodeTreeSyncRecommended notifications

Procedure:

1. The Provisioning MnS Producer detects that the information within the data node tree has become reliable again
2. The Provisioning MnS Producer recommends the Provisioning MnS Consumer to resynchronize its copy of the data node tree with the current data node tree on the MnS Producer.

Post-Condition:

- The Provisioning MnS Producer sends the notifyDataNodeTreeSyncRecommended notification
- Upon receipt, the Provisioning MnS Consumer re-synchronizes with the current data node tree on the Provisioning MnS Producer.

### 6.1.14.3.4 Operations and Notifications

Refer to clause 5.1 for details on O1 notification formats, including SDO O1 format and VES O1 format notifications, categorized as Harmonized VES.

The O1-supported 3GPP-specified CM notifications are:

- notifyPotentialFaultyDataNodeTree
- notifyDataNodeTreeSyncRecommended

## 6.2 Fault Supervision Management Services

### 6.2.0 Overview

Fault supervision management services allow a Fault Supervision MnS Producer to report errors and events to a Fault Supervision MnS Consumer and allows a Fault Supervision MnS Consumer to perform fault supervision operations on the Fault Supervision MnS Producer, such as get alarm list. The Fault supervision management services include the optional capability of Fault History Supervision Control and Reporting.

Stage 1 Fault Supervision MnS is specified in 3GPP TS 28.111 [26].

Stage 2 Fault Supervision notifications are specified in 3GPP TS 28.111 [26] clause 8.

Stage 2 AlarmList IOC and AlarmRecord data type are specified in 3GPP TS 28.111 [26] clauses 7.3.2 and 7.3.1.

Stage 3 Solution Set for NETCONF/YANG is specified in 3GPP TS 28.111 [26] annex A.3.

### 6.2.1 Fault Notification

#### 6.2.1.1 Description

Fault Supervision MnS Producer sends asynchronous Fault notification event to Fault Supervision MnS Consumer when an alarm occurs, is cleared, or changes severity.

#### 6.2.1.2 Requirements

The following fault supervision data report service requirements specified in 3GPP TS 28.111 [26] clause 5 shall apply:

- REQ-FM-MC-1 for sending alarm notifications
- REQ-FM-MC-2 for alarm notification subscription
- REQ-FM-MC-3 for alarm notification unsubscription
- REQ-FM-MC-5 for reading the alarm list
- REQ-FM-MC-6 for reading the alarm list with a filter
- REQ-FM-MC-7 for sending changed alarm notifications
- REQ-FM-MC-8 for sending cleared alarm notifications
- REQ-FM-MC-9 for sending new alarm notifications
- REQ-FM-MC-10 to support indicating a potentially faulty alarm list
- REQ-FM-MC-11 for sending alarm list rebuilt notification

The following requirements from 3GPP TS 28.111 [26] clause 5 may apply:

- REQ-FM-MC-4 for filtering the alarm notifications that are reported
- NOTE: Filtering is best done at the SMO level.
- REQ-FM-MC-14 for sending acknowledgement state change notifications

#### 6.2.1.3 Procedures

Procedures for subscription and notifications are described in 3GPP TS 28.622 [7] clause 4.3.22 and 3GPP TS 28.111 [26] clause 6.12.

## 6.2.1.4 Operations and Notifications

Refer to clause 5.1 for details on O1 notification formats, including SDO O1 format and VES O1 format notifications, categorized as Harmonized VES.

The Fault Supervision MnS Producer shall support the following 3GPP-specified Fault Supervision notifications are:

- notifyNewAlarm
- notifyChangedAlarmGeneral
- notifyClearedAlarm
- notifyAlarmListRebuilt

NotifyChangedAlarmGeneral permits the producer to report the severity change and any other attribute changes associated with this alarm in a single notification. The other 3GPP Fault Supervision notifications specified in 3GPP TS 28.111 [26] are optional.

The Fault Supervision MnS Producer should support the following 3GPP-specified Fault Supervision notifications:

- notifyAckStateChanged

If the NF supports alarm acknowledgement, it should have the capability to provide NotifyAckStateChanged.

- notifyPotentialFaultyAlarmList

The Fault supervision MnS producer shall not send 3GPP-specified fault supervision notifications when the state of an AlarmList MOI is locked or disabled, as specified in TS 28.111 [26], clause 6.13.

## 6.2.2 Fault Supervision Control

### 6.2.2.1 Description

Starting with 3GPP Release 16, dedicated operations for Management Services Use Cases are supported by IOCs with attributes that can be read and/or set using generic provisioning mechanisms. For Fault Supervision, an AlarmList IOC is specified in 3GPP TS 28.111 [26] clause 7.3.2 that represents the capability to store and manage alarm records. There is one AlarmList per Fault Supervision MnS Producer, created by the Producer. The AlarmList contains one AlarmRecord for each active alarm. The AlarmRecords in the AlarmList can be read by the Fault Supervision MnS Consumer, with an optional filter to retrieve selected AlarmRecords based on the value of attributes in the AlarmRecord. For example, Fault Supervision MnS Consumer is able to retrieve only those AlarmRecords with perceivedSeverity = CRITICAL.

As described in 3GPP TS 28.111 [26] clause 6.11, the reliability of an AlarmList indicates whether its AlarmRecords are up to date or not.

The conditions for adding, deleting, or updating AlarmRecords in an AlarmList MOI, as determined by the AlarmList state, are specified in clause 6.13 of 3GPP TS 28.111 [26]. When the state of an AlarmList MOI is locked or disabled, the AlarmRecords in the AlarmList MOI are not reliable, as described in 3GPP TS 28.111 [26], clause 6.13.

### 6.2.2.2 Requirements

The following fault supervision data control service requirements from 3GPP TS 28.111 [26] clause 5 may apply to the Fault Supervision MnS Producer:

- REQ-FM-MC-12 to support alarm acknowledgement.

NOTE 1: There is no Use Case that requires a NF to acknowledge an alarm. This operation is best done at the SMO level.

- NF that does not support the alarm acknowledgement from the MnS Consumer shall consider cleared alarms as automatically acknowledged so that they may be removed from the AlarmList.
- REQ-FM-MC-13 to support manual alarm clearing.

NOTE 2: Manual clearing of alarms is only for ADMC (Automatically Detected, Manually Cleared) alarms.

- NF that supports ADMC alarms should support the manual alarm clearing operation.

AlarmList IOC definition shall be as specified in 3GPP TS 28.111 [26] clause 7.3.2 with attribute definitions in specified in 3GPP TS 28.111 [26] clause 7.4.1.

YANG solution set for AlarmList IOC shall be as specified in 3GPP TS 28.111 [26] clause A.3.

### 6.2.2.3 Procedures

NETCONF protocol and YANG data models are used to get and set the attributes of the AlarmRecords in the AlarmList.

Refer to clause 6.1 for procedures to read MOI attributes and modify MOI attributes using NETCONF.

Refer to clause 6.2.2.1 for the reliability conditions of getting and setting attributes of the AlarmRecords in the AlarmList depending on the AlarmList states.

### 6.2.2.4 Void

## 6.2.3 Fault History Supervision Control and Reporting

### 6.2.3.1 Description

The Fault History Supervision Control and Reporting allows a Fault Supervision MnS Producer to report to a Fault Supervision MnS Consumer relevant information about raised, changed, or cleared alarms in the past. Generalizing, it allows to report information about alarms updates.

When an alarm is raised, the Fault Supervision MnS Producer stores the relevant initial data of a new alarm, according to the information exposed by the notifyNewAlarm notification.

When an alarm is modified or cleared, the Fault Supervision MnS Producer stores the relevant data of the alarm change, according to the information exposed by the notifyChangedAlarmGeneral, or notifyClearedAlarm.

When an alarm list is locked or disabled, alarm records are not reliable, as consequences also the capability of the Fault Supervision MnS Producer to store alarm changes is not reliable.

Reliable notifications enable MnS Consumer to detect, retrieve and restore missing notifications, refer clause 6.11.3. This provides partial support for use case involving storage of reliability related notifications, such as notifyPotentialFaultyAlarmList and notifyAlarmListRebuilt.

### 6.2.3.2 Requirements

The following requirements shall apply:

- REQ-FSHQ\_MC-1 The Fault Supervision MnS Producer shall have the capability to store the relevant data of alarms updates if the Fault History Supervision Control and Reporting capability is provided.
- REQ-FSHQ\_MC-2 The Fault Supervision MnS Producer shall have the capability to store the alarm updates even when the ability to send alarm notifications to subscribed consumer(s) is not available (e.g. during a disturbance), if Fault History Supervision Control and Reporting capability is provided.
- REQ-FSHQ\_MC-3 The Fault Supervision MnS Producer shall allow authorized consumers to retrieve the stored alarm updates if Fault History Supervision Control and Reporting capability is provided.

NOTE: The Fault Supervision MnS Producer allows authorized consumers to retrieve alarm updates for a specific time window. The time window may include present time.

- REQ-FSHQ\_MC-4 The Fault Supervision MnS Producer shall have the capability to store the notifyAlarmListRebuilt notification if Fault History Supervision Control and Reporting capability is provided. In case, it may also have the capability to store the notifyPotentialFaultyAlarmList notification.

- REQ-FSHQ\_MC-5 The Fault Supervision MnS Producer should have the capability to report the perceivedSeverity at the time of the alarm creation, if Fault History Supervision Control and Reporting capability is provided.

## 6.3 Performance Assurance Management Services

### 6.3.0 Overview

Performance Assurance Management Services allow a Performance Assurance MnS Producer to report file-based (bulk) and/or streaming (real time) performance data to a Performance Assurance MnS Consumer and allows a Performance Assurance MnS Consumer to perform performance assurance operations on the Performance Assurance MnS Producer, such as selecting the measurements to be reported and setting the frequency of reporting.

Use cases for PM services are specified in 3GPP TS 28.550 [6] clause 5.1.

Stage 2 notifyFileReady and notifyFilePreparationError notifications are specified in 3GPP TS 28.532 [3].

Stage 2 PerfMetricJob IOC is specified in 3GPP TS 28.622 [7] clause 4.3.31.

Stage 3 Solution Sets for OpenAPI and YANG are specified in 3GPP TS 28.623 [23].

Stage 2 and 3 for streaming data reporting service are specified in 3GPP TS 28.532 [3].

3GPP defined 5G performance measurements are specified in 3GPP TS 28.552 [i.5]. In addition to the 3GPP-defined measurements, it is possible to have O-RAN defined measurements and vendor supplied measurements. Clause 6.3.4 provides requirements for O-RAN defined measurements. O-RAN defined measurements are named with an "OR." prefix. Vendor supplied measurements are named with a "VS." prefix.

### 6.3.1 Performance Data File Reporting

#### 6.3.1.1 Description

A Performance Assurance MnS Producer that provides file-based (bulk) performance data reporting shall support at least one of the following: the PM data pull-based file reporting method or the PM data push-based file reporting method.

In the pull-based file reporting method for PM data file reporting, the Performance Assurance MnS Producer sends asynchronous notifyFileReady notification event to Performance Assurance MnS Consumer when PM File(s) is ready for retrieval or the Performance Assurance MnS producer sends asynchronous notifyFilePreparationError notification event to Performance Assurance MnS Consumer when there is any error while preparing the file(s). The notifyFileReady notification contains information needed to retrieve the file such as filename and the location where the file can be retrieved. Performance Assurance MnS Consumer retrieves the PM File(s) from the location specified in the notifyFileReady notification. The notifyFilePreparationError notification contains error reasons as specified in 3GPP TS 28.532 [3], clause 11.6.1.2.2.

In the push-based file reporting method the Performance Assurance MnS Producer makes PM Files(s) available for retrieval by transferring the PM File(s) to an entity such as a designated file server or to the Performance Assurance MnS Consumer as described in 3GPP TS 28.537 [4] clause 7.3.1. The file location where the PM File(s) are to be pushed, the designated file server, is identified by the Performance Assurance MnS Consumer when creating the PerfMetricJob IOC using the "FileLocation" attribute. If the Performance Assurance MnS Producer is capable of providing notifications related to the file transfer operation using the notifyFileReady or notifyFilePreparationError notification event, the Performance Assurance MnS Producer can send the notifyFileReady or notifyFilePreparationError notification event to the subscribed Performance Assurance MnS Consumers. When transferring files, a secure connection is established between the Performance Assurance MnS Producer and the Performance Assurance MnS Consumer or the designated file server and the method for reporting the collected PM data to the MnS Consumer is defined in the PerfMetricJob IOC (see clause 6.3.3).

## 6.3.1.2 Requirements

### 6.3.1.2.1 Pull-based Performance Data File Reporting Requirements

When the pull-based Performance Data File Reporting method is used, the requirements specified in 3GPP TS 28.550 [6] clause 5.2.2 shall apply.

### 6.3.1.2.2 Push-based Performance Data File Reporting Requirements

When the push-based Performance Data File Reporting method is used, the following requirements apply.

REQ-OPM-PUSH-FUN1: The Performance Assurance MnS Producer responsible for the push-based Performance Data File Reporting method shall have the capability to send the NF performance data file to its authorized Performance Assurance MnS Consumer or a designated file server as described in 3GPP 28.537 [4] clause 7.3.1.

REQ-OPM-PUSH-FUN2: The Performance Assurance MnS Producer responsible for the push-based Performance Data File Reporting method shall provide support for the file transfer protocols specified in 3GPP TS 28.537 [4] clause 7.1.3 in the client role of the protocol.

REQ-OPM-PUSH-FUN3: The Performance Assurance MnS Consumer responsible for the push-based Performance Data File Reporting method shall provide support for the file transfer protocols specified in 3GPP TS 28.537 [4] clause 7.1.3 in the server role of the protocol.

REQ-OPM-PUSH-FUN4: The Performance Assurance MnS Producer responsible for the push-based Performance Data File Reporting method shall provide the ability to announce the capability to support notifications related to the completion of the file transfer.

REQ-OPM-PUSH-FUN5: When supported, the Performance Assurance MnS Producer responsible for the push-based Performance Data File Reporting method shall provide the Performance Assurance MnS Consumers the ability to subscribe to receive notifications related to completion of the file transfer.

## 6.3.1.3 Procedures

### 6.3.1.3.1 Pull-based Performance Data File Reporting Procedure


#### 6.3.1.3.1.0 Introduction

When the pull-based Performance Data File Reporting method is used, the procedure based on the use case described in 3GPP TS 28.550 [6] clause 5.1.1.2 is used.

#### 6.3.1.3.1.1 Pull-based Performance Data File Reporting Procedure for file ready events

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.

In the pull-based file reporting method for PM data file reporting, the Performance Assurance MnS Producer sends asynchronous notifyFileReady notification event to Performance Assurance MnS Consumer when PM File(s) is ready for retrieval as specified in 3GPP TS 28.532 [3], clause 11.6.1.1.1.



**Figure 6.3.1.3.1.1-1 Pull-based PM Data File Reporting and Retrieval**

Pre-condition:

- Performance Assurance MnS Consumer has subscribed to notifyFileReady notifications.


Procedure:

1. A new PM data file is available on the Performance Assurance MnS Producer.
2. Performance Assurance MnS Producer sends notifyFileReady notification to Performance Assurance MnS Consumer over HTTP/TLS. Mutual certificate authentication is performed.
3. Performance Assurance MnS Consumer sets up a secure file transfer protocol connection to the location provided in the notifyFileReady notification and gets the PM data file(s). Secure file transfer protocols are described in 3GPP TS 28.537 [4], clause 7.1.3.

#### 6.3.1.3.1.2 Pull-based Performance Data File Reporting Procedure for file preparation error events

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.

In the pull-based file reporting method for PM data file reporting, the Performance Assurance MnS producer sends asynchronous notifyFilePreparationError notification event to Performance Assurance MnS Consumer when there is any error while preparing the file(s), as specified in 3GPP TS 28.532 [3], clause 11.6.1.2.1.



**Figure 6.3.1.3.1.2-1 Pull-based PM Data File Reporting while FilePreparation error**

Pre-condition:

- Performance Assurance MnS Consumer has subscribed to notifyFilePreparationError notifications.

Procedure:

1. A new PM data file(s) could not be prepared due to an error which occurred while preparing the file.
2. Performance Assurance MnS producer sends notifyFilePreparationError notification to Performance Assurance MnS consumer over HTTP/TLS with the reason of the error. Reasons for the error are as described in 3GPP TS 28.532 [3], clause 11.6.1.2.2.

### 6.3.1.3.2 Push-based Performance Data File Reporting Procedure

#### 6.3.1.3.2.0 Introduction


When the push-based Performance Data File Reporting method is used, the following procedures are used when the PM file(s) is ready for retrieval or when there is an error while preparing the file.

#### 6.3.1.3.2.1 Push-based Performance Data File Reporting Procedure with optional file ready event

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.

When the push-based Performance Data File Reporting method is used, and if Performance Assurance MnS producer is capable of providing notification to the Performance Assurance MnS Consumer when PM file(s) is ready for retrieval, the following procedure is used.





**Figure 6.3.1.3.2.1-1 Push-based PM Data File Establishment and Data Transmission**

Pre-condition:

- Performance Assurance MnS Producer is configured to produce push-based file reporting to the location of a file server or to the Performance Assurance MnS Consumer, as designated by the Performance Assurance MnS Consumer at the PerfMetricJob IOC creation. (Figure 6.3.1.3.2.1-1 depicts the scenario of pushing the file to a designated file server)
- A PM data file is available at the Performance Assurance MnS Producer to transmit to the File Server.
- (Optionally) Performance Assurance MnS Consumer has subscribed to file transfer operation notifications.


Procedure:

1. PM File(s) are available to the Performance Assurance MnS Producer
2. Performance Assurance MnS Producer transmits the PM file(s) to the Performance Assurance MnS Consumer or to a file server designated by the Performance Assurance MnS Consumer by the file location provided in the PerfMetricJob.
3. If the Performance Assurance MnS Producer is capable of reporting file notifications and Performance Assurance MnS Consumer has subscribed to receive the notifications, the Performance Assurance MnS Producer sends notifyFileReady notification to the Performance Assurance MnS Consumer after the file transfer.
4. In case of push-based file reporting method to a designated filer server, Performance Assurance MnS Consumer retrieves the PM file(s) from the File Server

#### 6.3.1.3.2.2 Push-based Performance Data File Reporting Procedure with optional file preparation error event

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.

When the push-based Performance Data File Reporting method is used, and if Performance Assurance MnS producer is capable of providing notification to the Performance Assurance MnS Consumer when there is error in preparing the PM file(s), the following procedure is used.



**Figure 6.3.1.3.2.2-2 Push-based PM Data File Establishment and Data Transmission**

Pre-condition:

- Performance Assurance MnS Producer is configured to produce push-based file reporting to the location of a file server or to the Performance Assurance MnS Consumer, as designated by the Performance Assurance MnS Consumer at the PerfMetricJob IOC creation.
- (Optionally) Performance Assurance MnS Consumer has subscribed to file transfer operation notifications.

Procedure:

1. A new PM data file(s) could not be prepared due to an error which occurred while preparing the file.
2. If the Performance Assurance MnS Producer is capable of reporting file notifications and Performance Assurance MnS Consumer has subscribed to receive the notifications, the Performance Assurance MnS Producer sends notifyFilePreparationError notification to the Performance Assurance MnS Consumer with the reason of the error. Reasons for the error are as described in 3GPP TS 28.532 [3], clause 11.6.1.2.2.

#### 6.3.1.4 Operations and Notifications

Refer to clause 5.1 for details on O1 notification formats, including SDO O1 format and VES O1 format notifications, categorized as Harmonized VES.

The O1-supported 3GPP-specified file transfer operation notifications are:

- notifyFileReady;
- notifyFilePreparationError.

#### 6.3.1.5 PM File Generation and Reporting

When the pull-based Performance Data File Reporting method is used, the following PM File Generation and Reporting requirements apply:

- PM file generation and reporting shall be as specified in 3GPP TS 28.532 [3] clause 11.6.

When the push-based Performance Data File Reporting method is used, the following PM File Generation and Reporting requirements apply:

- The Performance Assurance MnS Producer shall support the file transfer protocols 3GPP TS 28.537 [4] clause 7.1.3.

- The Performance Assurance MnS Producer shall always act as the client while the MnS consumer shall always act as the server of file transfer actions.

#### 6.3.1.6 PM File Content

PM file content shall be as specified in 3GPP TS 28.532 [3] clause 11.3.2.1.2.

#### 6.3.1.7 PM File Naming

PM file naming shall be as specified in 3GPP TS 28.532 [3] clause 11.3.2.1.4.

#### 6.3.1.8 PM File XML Format

PM file XML format shall be as specified in 3GPP TS 28.532 [3] clause 12.3.2 and/or in 3GPP TS 32.432 [14] clause 4.1.

#### 6.3.1.9 Void

### 6.3.2 Performance Data Streaming

#### 6.3.2.1 Description

Performance Assurance MnS Producer streams high volume asynchronous streaming performance measurement data to Performance Assurance MnS Consumer at a configurable frequency. A secure WebSocket connection is established between the Performance Assurance MnS Producer and the Performance Assurance MnS Consumer. The connection supports the transmission of one or more streams of PM data. Each stream of PM data is configured as a PerfMetricJob (see clause 6.3.3). The Performance Assurance MnS Producer supplies information about the supported streams to the consumer during the connection establishment. The connection may be established to support one or more streams. Streams can be added or removed from the connection as the PerfMetricJobs are added or deleted. The connectionID that carries the streaming PM data is provided to the Performance Assurance MnS Producer during the establishment of the WebSocket connection by the Performance Assurance MnS Consumer.


#### 6.3.2.2 Requirements

Requirements for Streaming PM specified in 3GPP TS 28.550 [6] clause 5.2.3 shall apply.

#### 6.3.2.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.

Use Cases for Streaming PM are described in 3GPP TS 28.550 [6] clause 5.1.1.3. Operations and notifications described in 3GPP TS 28.532 [3] clause 11.5 are applicable to both Streaming PM and Streaming Trace.



**Figure 6.3.2.3-1 Perf Data Streaming Connection Establishment and Data Transmission**

Pre-condition:

- Performance Assurance MnS Producer is configured to produce PerfMetricJob to be delivered via streaming PM to the Performance Assurance MnS Consumer.

Procedure:

1. Performance Assurance MnS Producer requests to establish a WebSocket connection to begin streaming PM data and provides MetaData about the streams that are to be sent on the connection
2. Performance Assurance MnS Consumer accepts the request to upgrade the connection to a WebSocket.
3. Performance Assurance MnS Producer transmits binary encoded data to consumer while performance job is active.

#### 6.3.2.4 Operations and Notifications

3GPP TS 28.532 [3] clause 11.5.1 defines the following operations that an O-RAN compliant NF that supports streaming PM shall support. These are the same operations as listed in clause 6.4.6. They are repeated here, as it is possible that a NF may support different levels of streaming for trace and performance assurance.

- establishStreamingConnection operation is specified in 3GPP TS 28.532 [3] clause 11.5.1.1. Establishing the streaming connection is initiated via an HTTPS POST followed by an HTTP GET (upgrade) to establish the WebSocket connection.
- terminateStreamingConnection operation is specified in 3GPP TS 28.532 [3] clause 11.5.1.2. This operation is accomplished via a WebSocket Close Frame to tear down the streaming connection when all stream jobs on this connection have been terminated. The delivery of WebSocket Close Frame is provided by the underlying TCP.
- reportStreamData operation is specified in 3GPP TS 28.532 [3] clause 11.5.1.3. The streamData field contains the streaming PM data which is encoded according to the format defined in 3GPP TS 28.550 [6] Annex G which provides the ASN.1 definition of the Performance Data Stream Units. The delivery of WebSocket Close Frame is provided by the underlying TCP.

If O-RAN NF supports the capability of sending multiple PM streams across the WebSocket connection, the following operations shall be supported.

- addStream operation is specified in 3GPP TS 28.532 [3] clause 11.5.1.4. This operation is used when a new Performance Assurance Stream (PM job started) is added on the Performance Assurance MnS Producer to be

delivered to this consumer, and the NF supports multiple streams per connection. The addStream operation is accomplished via an HTTP POST.

- deleteStream operation is specified in 3GPP TS 28.532 [3] clause 11.5.1.5. This operation is used when a Performance Assurance Stream (PM job stopped) is deleted from the connection between the Performance Assurance MnS Producer and the Performance Assurance MnS Consumer. The deleteStream operation is accomplished via an HTTP DELETE.

The following operations specified in 3GPP TS 28.532 [3] clause 11.5.1 may be supported by O-RAN NFs:

- getConnectionInfo operation is specified in 3GPP TS 28.532 [3] clause 11.5.1.6. This operation allows the performance data streaming service producer to get information from the performance data streaming service consumer on the streams active on the connection.
- getStreamInfo operation is specified in 3GPP TS 28.532 [3] clause 11.5.1.7. This operation allows the performance data streaming service producer to get the information for one or more streams from the streaming consumer (i.e., stream target).

No notifications have been defined for Performance Data Streaming.

### 6.3.2.5 PM Streaming Data Generation and Reporting

3GPP TS 28.550 [6] Annex C lists all the Performance Data Stream Unit Content Items. Annex C of the present document provides a description of the establishment of the WebSocket connection and the subsequent operations provided as part of the data streaming service. The example utilizes the trace service, but the operations around the establishment and tear down of the connection are the same for streaming PM and streaming Trace. The WebSocket connection remains until all streams configured to be provided between the Performance Assurance MnS Producer and the Performance Assurance MnS Consumer have been terminated.

### 6.3.2.6 PM Streaming Data Format

PM Streaming data shall be delivered according to the format specified in the input parameters of the establishStreamConnection operation specified in 3GPP TS 28.532 [3] clause 11.5.1.1.2.

## 6.3.3 Measurement Job Control

### 6.3.3.1 Description

Starting with 3GPP Release 16, Performance Assurance Control supported by IOCs with attributes that can be read and/or set using generic provisioning mechanisms in the Measurement Job Control Service. Measurement jobs can be created and terminated by creating and deleting a PerfMetricJob MOI. Measurement jobs can be queried by getting the attributes of a PerfMetricJob MOI. Measurement jobs can be temporarily suspended or resumed by modifying the administrativeState attribute of a PerfMetricJob MOI to LOCKED or UNLOCKED.

### 6.3.3.2 Requirements

Requirements for measurement job control specified in 3GPP TS 28.550 [6] clause 5.2.1 shall apply.

PerfMetricJob IOC definition shall be as specified in 3GPP TS 28.622 [7] clause 4.3.31 with attribute definitions in specified in 3GPP TS 28.622 [7] clause 4.4.1. SupportedPerfMetricGroup datatype shall be as specified in 3GPP TS 28.622 [7] clause 4.3.32. ReportingCtrl shall be as specified in 3GPP TS 28.622 [7] clause 4.3.33.

YANG solution set for PerfMetricJob IOC shall be as specified in 3GPP TS 28.623 [23] clauses 4.4 and E.2.

### 6.3.3.3 Procedures

Measurement job creation, termination, query, suspend and resume are described in 3GPP TS 28.622 [7] clause 4.3.31.

NETCONF protocol and YANG data models are used to create MOI, delete MOI, modify attributes and get attributes of a PerfMetricJob. Refer to Provisioning management services clause for detailed procedures on how to perform these operations using NETCONF.

#### 6.3.3.4 Void

### 6.3.4 O-RAN Defined Performance Measurements

O1 performance measurements are defined in the O-RAN O1 Performance Measurements Specification [i.17] and 3GPP TS 28.552 [i.5].

PMCountGroup and CuCountGroup, described in O1 Interface specification for O-DU [i.19] and O1 Interface specification for O-CU-UP and O-CU-CP [i.20] respectively, can be used as filtering mechanisms for O-RAN defined O1 performance measurements. Filtering mechanisms defined in clause 4.2 of 3GPP TS 28.552 [i.5] can be used as well.

#### 6.3.4.1 Void

## 6.4 Trace Management Services

### 6.4.0 Overview

Trace management services allow a Trace MnS Producer to report file-based or streaming trace records to the Trace MnS Consumer. Trace Control provides the ability for the Trace MnS Consumer to start a trace session by configuring a Trace Job via the Trace Control IOC or by establishing a trace session that propagates trace parameters to other Trace MnS Producers via signaling. There are multiple levels of trace that can be supported on the Trace MnS Producer as described in 3GPP TS 32.421 [11] clause 4.1. The Trace MnS Producer may be configured to support file-based trace reporting or streaming trace reporting.

Trace Management Services specified in 3GPP TS 32.421 [11], 3GPP TS 32.422 [12] and 3GPP TS 32.423 [13] and supported on an applicable O-RAN ME include Call Trace, Minimization of Drive Testing (MDT), RRC Connection Establishment Failure (RCEF), Radio Link Failure TCE (RLF) and RRC reporting. All of these services follow a similar management paradigm. Trace Sessions are configured on the Trace MnS Producer with information on where and how to send the trace information to the consumer. The Trace MnS Producer creates trace records within a trace session as the trigger mechanism occurs. Trace records are produced and provided to the consumer until the trace session is terminated.

File-based trace collects trace records in files that are available to the consumer with a time delay. In the case of streaming trace, the data is sent in bursts across a WebSocket connection to the consumer, maintaining the relevance of the data while minimizing transport overhead.

Stage 1 Trace Management Service is specified in 3GPP TS 32.421 [11]. Use cases for trace are specified in clause 5.8 and elaborated in 3GPP TS 32.421 [11] Annex A. General Trace Requirements are found in 3GPP TS 32.421 [11] clause 5.1.

Stage 2 Trace Operations are found in 3GPP TS 32.422 [12] for 5G support of Call Trace and for streaming trace.

Stage 2 TraceJob IOC for management-based control is specified in 3GPP TS 28.622 [7] clause 4.3.30. Stage 2 for signaling based activation is found in 3GPP TS 32.422 [12].

Stage 3 definitions of trace record content for all trace types, XML trace file format, and streaming trace GPB record definition are found in 3GPP TS 32.423 [13].

Stage 3 TraceJob IOC mapping for management-based control is specified in 3GPP TS 28.623 [23] clauses 4.3, 4.4, E.1 and E.2.

Stage 2 and 3 definitions for streaming data reporting are specified in 3GPP TS 28.532 [3].

## 6.4.1 Call Trace

### 6.4.1.1 Trace Data Reporting

#### 6.4.1.1.1 Description

Trace Data can be reported from the Trace MnS Producer to the Trace MnS Consumer via trace files or via a streaming interface. For management-based activation, Trace Data is collected after the TraceJob is configured on the Trace MnS Producer, the Trace Session is activated, and the triggering event occurs. For signaling-based activation, the Trace Recording Session starts when the NF receives trace control and configuration parameters via one of the signaling messages specified in 3GPP TS 32.422 [12] clause 4.2.3.12.

When the Trace MnS Producer collects trace data to a file, the file is periodically provided to the Trace MnS Consumer. When the producer supports streaming trace, the trace is sent to the consumer via data bursts which are sent frequently enough to retain the relevance of the data while conserving transport resources. The WebSocket connection carrying the streaming trace is preserved for the duration of the streaming trace.

#### 6.4.1.1.2 Requirements

Requirements for Trace data specified in 3GPP TS 32.421 [11] clause 5.2 shall apply to both file-based and streaming trace.

#### 6.4.1.1.3 Procedures

Trace Data is binary encoded and reported in Trace Records. The procedures for reporting data are described in 3GPP TS 32.422 [12] clause 7. File-based trace reporting procedures are described in 3GPP TS 32.422 [12] clauses 7.1.1 and 7.2.1. Streaming trace reporting procedures are described in 3GPP TS 32.422 [12] clauses 7.1.2 and 7.2.2. Trace Record Contents are described in 3GPP TS 32.423 [13] clause 4. The Trace Record content is the same for trace jobs controlled by management-based activation and signaling-based activation. The raw trace record content is the same for file-based trace and streaming trace. Trace data is binary encoded in ASN.1. File-based trace is delivered in XML format with trace records encoded in ASN.1. Streaming trace is delivered in GPB encoded data bursts with the trace record payload containing ASN.1 encoded data.

Procedures for naming the trace data file are described in 3GPP TS 32.423 [13] Annex B. File Naming Convention is described in 3GPP TS 32.423 [13] clause B.1.

Trace files are produced in XML format. The XML format is described in 3GPP TS 32.423 [13] clause A2.2. Example XML files are provided in 3GPP TS 32.423 [13] Annex D.

If a trace file cannot be created, a trace failure notification file XML schema can be sent. The XML schema is provided in 3GPP TS 32.422 [12] clause A.5 and the naming convention for the file containing the failure is described in clause A.4.

For streaming trace, raw trace data is collected on the node and sent to the trace collector. The trace data is binary encoded. The format of the streaming trace data is provided in 3GPP TS 32.423 [13]. The reportStreamData operation is described in 3GPP TS 28.532 [3] clause 12.5.1.1.4.

### 6.4.1.2 Trace Session Activation

#### 6.4.1.2.1 Description

A trace session starts on a producer configured to support a TraceJob via management or signaling-based activation. Management-based trace session activation is initiated from the Provisioning Management Service Consumer to activate a TraceJob which has been configured on the producer. See clause 6.4.5. With signaling-based trace session activation, the producer receives a signaling message that contains trace consumer ID address (IP address for file-based or URI for streaming) along with trace control parameters. Each Trace session has a unique trace session identifier that is associated with all of the trace data collected for this session.



If the trace session is configured to be file-based, the producer collects the data and stores the data in a file. The producer optionally sends the file directly to the consumer or sends the location of the file to the consumer. File transport approach is not standardized.

3GPP TS 28.532 [3] supports the streaming of trace data from the producer to the consumer. Trace data for a trace session is collected and transmitted to the producer across a secure WebSocket connection in data bursts which are emitted frequently enough to ensure the relevance of the data while conserving transport resources. See clause 6.4.6 and Annex C of the present document for details on the streaming service.

#### 6.4.1.2.2 Requirements

Requirements for Trace Session activation for file-based and streaming trace specified in 3GPP TS 32.421 [11] clause 5.3.1 shall apply.

#### 6.4.1.2.3 Procedures

Procedures for activating a Trace Session via management-based control are described in 3GPP TS 32.422 [12] clause 4.1.1.1 for general procedures and 3GPP TS 32.422 [12] clause 4.1.1.9 for NGRAN specific procedures. Procedures for activating a Trace Session via signaling are described in 3GPP TS 32.422 [12] clause 4.1.2.1 and clause 4.1.2.16.

### 6.4.1.3 Trace Session Deactivation

#### 6.4.1.3.1 Description

A Trace Session is terminated/deactivated when any of the defined stop triggering events occur as specified in 3GPP TS 32.421 [11], such as a timer expiring, or the TraceJob Session is deactivated via management control.

#### 6.4.1.3.2 Requirements

Requirements for Trace Session deactivation specified in 3GPP TS 32.421 [11] clause 5.4.1 shall apply.

#### 6.4.1.3.3 Procedures

Procedures for Trace Session Deactivation are described in 3GPP TS 32.422 [12] clause 4.1.3.10 for management-based trace deactivation and 4.1.4.1.2 for signaling-based trace deactivation.

### 6.4.1.4 Trace Recording Session Activation

#### 6.4.1.4.1 Description

A trace recording session is a specific instance of the data specified to be collected for a particular trace session, for example, a specific call. For management-based activation, the trace recording session starts on a producer configured with an active trace session when a triggering event occurs, such as a new call starting. Each Trace recording session within a trace session has a unique trace recording session reference. This recording session reference and the session reference are included with each trace record, uniquely identifying the trace record as belonging to a particular trace recording session. For signaling-based activation, the Trace Recording Session starts when the NF receives trace control and configuration parameters via a control signaling message. 3GPP TS 32.422 [12] clause 4.2.3.12 outlines the procedures the node is to follow when determining when to begin a new trace recording session and when to continue with an existing session.

#### 6.4.1.4.2 Requirements

Requirements for starting Trace Recording Session specified in 3GPP TS 32.421 [11] clause 5.3.2 shall apply.

#### 6.4.1.4.3 Procedures

Procedures for starting a Trace Recording Session are described in 3GPP TS 32.422 [12] clause 4.2.1 for general cases. 3GPP TS 32.422 [12] clause 4.2.2.10 has details for management-based trace session activation and 4.2.3.12 has details when the trace session was activated via signaling.



## 6.4.1.5 Trace Recording Session Termination

### 6.4.1.5.1 Description

A Trace Recording Session is terminated when any of the defined stop triggering events occur or the Trace Session is deactivated.

### 6.4.1.5.2 Requirements

Requirements for stopping Trace Recording Session specified in 3GPP TS 32.421 [11] clause 5.4.2 shall apply.

### 6.4.1.5.3 Procedures

Procedures for Trace Recording Session Termination are described in 3GPP TS 32.422 [12] clause 4.2.4.10 and 4.2.5.13.

## 6.4.2 Minimization of Drive Testing (MDT)

### 6.4.2.1 Description

3GPP TS 37.320 [i.9] provides an overall description for MDT. An O-RAN network function can support Immediate and Logged MDT as described in 3GPP TS 37.320 [i.9]. Logged MDT and Immediate MDT can be configured to be file-based or streaming as per 3GPP TS 32.422 [12], clause 6. MDT measurements are described in 3GPP TS 37.320 [i.9]. 3GPP TS 32.421 [8], 32.422 [12] and 32.423 [13] describe the management of MDT and have been updated to support 5G.

### 6.4.2.2 Requirements

Requirements for managing MDT specified in 3GPP TS 32.421 [11] clause 6 shall apply.

### 6.4.2.3 Procedures

Procedures for Trace Session Activation are the same for MDT as for Call Trace and are described in 3GPP TS 32.422 [12] clause 4.1. Procedures for specifying MDT Trace selection conditions are described in 3GPP TS 32.422 [12] clause 4.1.5.

Procedures for Trace Recording Sessions start and stop for MDT are described in 3GPP TS 32.422 [12] clause 4.2.

Procedures for handling MDT sessions at handover for Immediate MDT are described in 3GPP TS 32.422 [12] clause 4.4 and Logged MDT in 3GPP TS 32.422 [12] clause 4.5.

Procedures for user consent handling in MDT are described in 3GPP TS 32.422 [12] clause 4.6.

Procedures for MDT reporting are described in 3GPP TS 32.422 [12] clause 6.

MDT Trace Record Contents are described in 3GPP TS 32.423[13] clause 4.

Trace file format for MDT Trace is described in 3GPP TS 32.423 [13] clause A.2.1. Example XML files are provided in 3GPP TS 32.423 [13] clause D.1.4.

## 6.4.3 Radio Link Failure (RLF)

### 6.4.3.1 Description

Radio Link Failure (RLF) reporting is a special Trace Session which provides the detailed information when a UE experiences an RLF event, and the reestablishment is successful to the source gNB. 3GPP TS 32.421 [11], 32.422 [12] and 32.423 [13] describe the management of RLF.

### 6.4.3.2 Requirements

Requirements for RLF specified in 3GPP TS 32.421 [11] clause 7 shall apply.

### 6.4.3.3 Procedures

Procedures for Trace session activation and deactivation for RLF reporting are described in 3GPP TS 32.422 [12] clause 4.3.1 and 4.3.2.

Procedures for specifying the RLF reporting job type when configuring the RLF reporting session are described in 3GPP TS 32.422 [12] clause 5.9a.

Procedures for RLF reporting follow standard trace reporting procedures documented in 3GPP TS 32.422 [12] clause 7.

## 6.4.4 RRC Connection Establishment Failure (RCEF)

### 6.4.4.1 Description

Radio Resource Control (RRC) Connection Establishment Failure (RCEF) is activated on the gNB as a special Trace Session where the job type indicates RCEF reporting only. The records are produced when a UE experiences an RCEF event and the RRC establishment is successful to the same gNB.

### 6.4.4.2 Requirements

Requirements for RCEF specified in 3GPP TS 32.421 [11] clause 7 shall apply.

### 6.4.4.3 Procedures

Procedures for trace session activation of RCEF are described in 3GPP TS 32.422 [12] clause 4.8.1.

Procedures for trace session deactivation for RCEF reporting are described in 3GPP TS 32.422 [12] clause 4.8.2.

Procedures for specifying the job type for RCEF are described in 3GPP TS 32.422 [12] clause 5.9a.

Procedures for RCEF Reporting are described in 3GPP TS 32.422 [12] clause 7.

## 6.4.5 Trace Control

### 6.4.5.1 Description

Starting with 3GPP Release 16, Management-based Trace Control is supported with IOCs with attributes that can be read and/or set using generic provisioning mechanisms in the Trace Control Service. For Trace Control, this includes operations such as Create TraceJob, Activate TraceJob, Deactivate TraceJob, and Query TraceJobs. TraceJobs can be created, activated, deactivated, and queried by setting and/or getting attributes in the TraceJob IOC. The TraceJob IOC supports Management-based activation for Call Trace, MDT, RLF, RCEF and RRC reporting.

Trace sessions can also be activated and deactivated via signaling-based configuration initiated from another NF to propagate a configured trace, such as a UE trace when the UE moves from one NF to another.

### 6.4.5.2 Requirements

Management-based activation and deactivation shall be done via the TraceJob IOC defined in 3GPP TS 28.622 [7] clause 4.3.30. Requirements for TraceJob activation specified in 3GPP TS 32.421 [11] clause 5.3.1 and requirements for TraceJob deactivation specified in 3GPP TS 32.421 [11] clause 5.4.1 shall apply for both Management and signaling activation.

### 6.4.5.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.

Management-based activation and deactivation accomplished using CRUD operations documented in clause 6.1. The attributes of the TraceJob are described in 3GPP TS 28.622 [7] clause 4.3.30.2. Constraints on these attributes are described in 3GPP TS 28.622 [7] clause 4.3.30.3. TraceJob IOC mapping for management-based control is documented in 3GPP TS 28.623 [23]. The YANG model for the TraceJob IOC is described in 3GPP TS 28.623 [23] clauses 4.4 and E.2.

Procedures for signaling-based Trace Session activation are described in 3GPP TS 32.422 [12] clause 4.1.2.

Procedures for signaling-based Trace Session deactivation are described in 3GPP TS 32.422 [12] clause 4.1.4.

## 6.4.6 Streaming Trace

### 6.4.6.0 Overview

A NF can be configured to deliver trace data via a file or via a streaming interface. The streaming capability was introduced in 3GPP Release 16. The additional requirements and procedures supported for streaming trace are provided in this clause. An example of the configuration, activation, recording and termination of a streaming trace connection are shown in Informative Annex C.

### 6.4.6.1 Requirements

As noted above, trace session and recording activation and deactivation, as well as the content of the trace record, are the same for file-based and streaming trace. The requirements for streaming trace delivery specified in 3GPP TS 32.421 [11] clause 5.5 shall apply. Operations for establishing the streaming connection, adding, and deleting streams from the connection and reporting streaming trace data shall be as specified in 3GPP TS 28.532 [3] clause 11.5. O-RAN NFs supporting streaming trace shall support the `establishStreamingConnection`, `reportStreamData` and `terminateStreamingConnection` operations. O-RAN NFs that support the multiplexing of trace streams across a single connection shall support the `addStream` and `deleteStream` operations. Optionally, the NF may also support the `getConnectionInfo` and `getStreamInfo` operations which allow the producer to query for information on the connection and streams on the connection. No notifications have been defined for streaming trace.

Stage 3 information on the streaming operations is provided in 3GPP TS 28.532 [3] clause 12.5 with Open API YAML definition provided in clause A.6.1.2.

### 6.4.6.2 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.

The procedure for `establishStreamingConnection` is an HTTP POST operation to provide the information on the stream to the consumer and to receive the Connection ID as a response. The HTTP POST is followed by an HTTP GET to upgrade the connection to a WebSocket connection. This operation is used when no connection is established between the producer and the consumer. The WebSocket connection can contain one or more streams of data from streaming trace or streaming PM. See 3GPP TS 28.532 [3] clause 12.5.1.1.2.

The `terminateStreamingConnection` is a WebSocket close frame operation. This operation is used when all streams on a connection have terminated. See 3GPP TS 28.532 [3] clause 12.5.1.1.3.

The `addStream` Operation is an HTTP POST to indicate that additional streams are being added to the connection. A stream corresponds to a trace job or a streaming PM job. See 3GPP TS 28.532 [3] clause 12.5.1.1.5.

The `deleteStream` Operation is an HTTP DELETE to indicate that a stream has been terminated from the connection. See 3GPP TS 28.532 [3] clause 12.5.1.1.6.

The `reportStreamData` is a WebSocket data frame sent across the connection containing the streaming trace or streaming PM data or an optional alive message indicating that the stream is active, but no data is available. See 3GPP TS 28.532 [3] clause 12.5.1.1.4.

The `getConnectionInfo` Operation is an HTTP GET from the producer to the consumer to obtain information about the connection, such as which streams are supported. See 3GPP TS 28.532 [3] clause 12.5.1.1.7.

The `getStreamInfo` Operation is an HTTP GET from the producer to the consumer to obtain information on the stream. See 3GPP TS 28.532 [3] clause 12.5.1.1.8.

Annex C provides a streaming trace activation example for management-based activation control.

## 6.4.7 UE Identifiers for Trace Records

### 6.4.7.1 Description

The contents of the Trace Records are specified in 3GPP TS 32.423 [13] clause 4 and Trace Record Header in 3GPP TS 32.423 [13] clause 5.2.2. The Trace Record containing protocol related messages may contain 3GPP defined UE identifiers corresponding to the protocol. These UE identifiers are a part of protocol messages sent as Trace Records. The Trace Header also contains RAN UE ID as an optional information element. However, for correlation of Trace Records from different O-RAN entities, the UE identifiers embedded in the protocol messages and the RAN UE ID in Trace Header may not be sufficient and may need to be complemented by other information. Hence a set of UE Identifiers and Node Identifiers are defined in O-RAN-Architecture-Description document [15] clause 5.5 for O-RAN ecosystem.

To enable correlation of Trace Records between O-RAN entities, Trace MnS Producer includes the optional RAN UE ID in the Trace Header when available and other applicable 3GPP UE identifiers defined in O-RAN-Architecture-Description document [15] clause 5.5 in the optional *vendorExtension* IE defined in 3GPP TS 32.423 [13] clause 5.2.2. in the Trace Header.

Refer to Annex D for the recommendation for UE Identifier format for *vendorExtension* IE in the Trace Header

## 6.4.8 RRC reporting

### 6.4.8.1 Description

Radio Resource Control (RRC) reporting is a set of reports generated by the UE and retrieved by gNB. This set of reports covers RLF, RCEF, RA, SHR, SPR and MHI reports of NR, as elaborated in 3GPP TS 32.421 [11] Annex A.18.

### 6.4.8.2 Requirements

Requirements for RRC reporting in 3GPP TS 32.421 [11] clause 7 shall apply.

### 6.4.8.3 Procedures

Procedures for trace session activation of RRC reporting are described in 3GPP TS 32.422 [12] clause 4.11.1.

Procedures for trace session deactivation for RRC reporting are described in 3GPP TS 32.422 [12] clause 4.11.2.

Procedures for specifying the job type for RRC reporting are described in 3GPP TS 32.422 [12] clause 5.9a.

Procedures for RRC reporting are described in 3GPP TS 32.422 [12] clause 7.

## 6.5 File Management Services

### 6.5.0 Overview

File management services allow a File Management MnS Consumer to get notification of new available files; query available files and request the transfer of files between the File Management MnS Producer and the File Management MnS Consumer.

Relevant 3GPP specifications for file transfer are 3GPP TS 28.537 [4], 3GPP TS 32.341 [8], 3GPP TS 32.342 [9] and 3GPP TS 32.346 [i.8].

### 6.5.1 File Ready Notification

#### 6.5.1.1 Description

The File Ready Notification notifies a File Management MnS Consumer that a file is available for retrieval from the File Management MnS Producer. In general, File Management MnS Producer sends a notifyFileReady notification for files that the File Management MnS Consumer has configured the File Management MnS Producer to collect on a periodic basis, such as file-based Trace Data or PM Measurement Reports.

#### 6.5.1.2 Requirements


The notifyFileReady notification shall be as specified in 3GPP TS 28.532 [3], clause 11.6.1.1.

#### 6.5.1.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.

File Management MnS Consumer configures a File Management MnS Producer to collect data files with specific characteristics that the File Management MnS Consumer desires, such as file-based Trace Data or PM Measurement Reports described in clause 6.3. After configuration, the File Management MnS Consumer terminates the configuration session and waits for the File Management MnS Producer to report that the file is ready for collection.

When a file is available, the File Management MnS Producer sends a notifyFileReady notification to the File Management MnS Consumer using REST/HTTPS.



**Figure 6.5.1.3-1 File Available for Transfer to Consumer**

Pre-condition:

- A new file is available on the File Management MnS Producer.

Procedure:

1. File Management MnS Producer sends notifyFileReady notification to File Management MnS Consumer over HTTP/TLS. Mutual certificate authentication is performed.

#### 6.5.1.4 Operations and Notifications

Refer to clause 5.1 for details on O1 notification formats, including SDO O1 format and VES O1 format notifications, categorized as Harmonized VES.

The O1-supported 3GPP-specified File Ready notification is:

- notifyFileReady

#### 6.5.1.5 File Types Supported

File Type requirements are documented in 3GPP TS 32.341 [8] clause 5.2.

#### 6.5.1.6 File Naming Requirements

Unless explicitly stated in the present document for particular File Types, the File Naming Convention specified in 3GPP TS 32.342 [9] Annex A shall apply.

### 6.5.2 List Available Files

#### 6.5.2.1 Description

File Management MnS Consumer queries the File Management MnS Producer to identify files that are available on the File Management MnS Producer. Upon receipt of the available files and their locations, the File Management MnS Consumer can determine the next appropriate action.

#### 6.5.2.2 Requirements


Requirements on the types of files specified in clause 5.2 of 3GPP TS 32.341 [8] shall apply.

#### 6.5.2.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.

List Available Files Use Case allows the File Management MnS Consumer to obtain a list of available files and their locations by reading the AvailableFileList IOC documented in 3GPP TS 32.342 [9]. A File Management MnS Consumer uses this management service in scenarios where the File Management MnS Producer is collecting information, such as logs, on a standard basis in support of debugging activities. Under normal operations, the File Management MnS Producer does not send this data to the File Management MnS Consumer as the File Management MnS Consumer does not need it. The File Management MnS Producer retains the data with the oldest data being overwritten when space is exhausted. In some scenarios, the File Management MnS Consumer wants to retrieve some, or all, of the available log files to resolve an issue. In this case, File Management MnS Consumer sends a NETCONF <get> command to the File Management MnS Producer to obtain the list of available files. File Management MnS Producer responds with AvailableFileList which contains a list of available files and their locations and file types. File Management MnS Consumer uses this information to transfer the desired files (see clause 6.5.3).

The File Management MnS Consumer does not have to initiate a file retrieval as a result of the obtaining the list of available files. There are use cases where the File Management MnS Consumer wants to verify that files are being collected or verify that all files of a particular type (PM for example) have been retrieved.



**Figure 6.5.2.3-1 List Available Files**

1. File Management MnS Consumer establishes NETCONF session with File Management MnS Producer.
2. File Management MnS Consumer sends NETCONF <get> <filter> to the File Management MnS Producer to retrieve the contents of the AvailableFileList.
3. File Management MnS Producer sends NETCONF <rpc-reply> <data> to the File Management MnS Consumer with list of available files on the File Management MnS Producer.
4. File Management MnS Consumer terminates NETCONF session with File Management MnS Producer.

## 6.5.3 File Transfer to and from File Management MnS Producer

### 6.5.3.1 Description

The File Transfer by File Management MnS Consumer Use Case provides the capability for a File Management MnS Consumer to transfer files from or to the File Management MnS Producer. In this use case, File Management MnS Consumer is the client and File Management MnS Producer is the file server.

The File Management MnS Consumer can perform this action as a result of:

1. notifyFileReady notification from the File Management MnS Producer informing the File Management MnS Consumer that a file(s) is available
2. Querying the File Management MnS Producer for the list of available files (see clause 6.5.2).
3. A need to transfer a file from a known location on the File Management MnS Producer.
4. A need to transfer a file to a known location on the File Management MnS Producer. Some examples of files that could be transferred to the File Management MnS Producer are:
  - Beamforming configuration file (Opaque Vendor specific data)
  - Machine Learning



## - Certificates

File Transfer is performed using a secure file transfer protocol (SFTP, FTPeS or HTTPS) from or to the File Management MnS Producer.

### 6.5.3.2 Requirements

File Transfer Requirements specified in clause 7.1.3 of 3GPP TS 28.537 [4] shall apply.

### 6.5.3.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.


**Case 1:** File Management MnS Consumer determines that a file needs to be transferred from the location provided by the File Management MnS Producer as a result of receiving a notifyFileReady notification from the File Management MnS Producer (described in clause 6.5.1).

**Case 2:** File Management MnS Consumer determines that a file needs to be transferred from the File Management MnS Producer as a result of receiving a list of available files from the File Management MnS Producer (described in clause 6.5.2)

**Case 3:** File Management MnS Consumer determines that a file needs to be transferred from the File Management MnS Producer from a known location on the File Management MnS Producer.

**Case 4:** File Management MnS Consumer determines that a file needs to be transferred to the File Management MnS Producer to a known location on the File Management MnS Producer.

File Management MnS Consumer initiates a secure file transfer using FTPeS, SFTP or HTTPS to transfer a file from or to the File Management MnS Producer.



**Figure 6.5.3.3-1 File Transfer by File Management MnS Consumer**

## 6.5.4 Download File from remote file server

### 6.5.4.1 Description

The File Management MnS Consumer has a file that needs to be downloaded to the File Management MnS Producer such as:

- Software file to upgrade software version executed on the File Management MnS Producer
- Beamforming configuration file (Opaque Vendor specific data)
- Machine Learning



- Certificates


The File Management MnS Consumer triggers the file download. The File Management MnS Producer uses a secure file transfer protocol to download the file from the location specified by the File Management MnS Consumer and then notifies the File Management MnS Consumer of the result of the download. In this use case, the File Management MnS Producer is the client. The file could be located on any File Server reachable by the File Management MnS Producer.

## 6.5.4.2 Requirements

General File Download requirements specified in clause 7.4.3 of 3GPP TS 28.537 [4] shall apply.

## 6.5.4.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.5.4.3-1 File Download**

Procedure:

1. File Management MnS Consumer establishes NETCONF session with File Management MnS Producer.
2. File Management MnS Consumer sends NETCONF RPC file-download request, including the location of the file to download, to the File Management MnS Producer to trigger a file download.
3. File Management MnS Producer replies with its ability to begin the download.
4. File Management MnS Consumer terminates NETCONF session with File Management MnS Producer.
5. File Management MnS Producer sets up a secure connection and downloads the file via a secure file transfer protocol (FTPeS, SFTP or HTTPS) and according to the O-RAN Security Requirements and Controls Specifications [17] clause 5.2.2.
6. (Optional) If the download takes a long time, File Management MnS Producer sends periodic downloadFile notifications to the File Management MnS Consumer with the current status of the download (download in progress).

7. When download completes, File Management MnS Producer sends a downloadFile notification to the File Management MnS Consumer with the final status of the download (success, file missing, failure).

#### 6.5.4.4 Operations and Notifications

Refer to clause 5.1 for details on O1 notification formats, including SDO O1 format and VES O1 format notifications, categorized as Harmonized VES.

NOTE: There are no File Download notifications defined in the present document.

#### 6.5.5 Void

## 6.6 Heartbeat Management Capability

### 6.6.0 Overview

Heartbeat management capability allows an MnS Producer to send heartbeats to an MnS Consumer (i.e. a notification recipient, according to 3GPP TS 28.622 [7], clause 4.3.21.1) and allows an MnS Consumer to configure the heartbeat services on an MnS Producer.

Stage 1 Heartbeat management capability is specified in 3GPP TS 28.537 [4]. This 3GPP specification is aligned with the Services Based Management Architecture (SBMA) approach defined in 3GPP TS 28.533 [i.4] clause 4 and contains Use Cases, Requirements and Procedures for configuring the heartbeat period, reading the heartbeat period, triggering an immediate heartbeat notification and emitting a periodic heartbeat notification.

Stage 2 notifyHeartbeat notification is specified in 3GPP TS 28.532 [3].

Stage 2 HeartbeatControl IOC is specified in 3GPP TS 28.622 [7] clause 4.3.21.

Stage 3 Solution Sets for OpenAPI and YANG are specified in 3GPP TS 28.623 [23].

### 6.6.1 Heartbeat Notification

#### 6.6.1.1 Description

MnS Producer sends asynchronous heartbeat notifications to MnS Consumer at a configurable frequency to allow MnS Consumer to supervise the connectivity from the MnS Producer.

#### 6.6.1.2 Requirements

Requirements for heartbeat notifications specified in 3GPP TS 28.537 [4] clause 4.2.2.2 shall apply.

#### 6.6.1.3 Procedures

Procedures for heartbeat notifications are described in 3GPP TS 28.537 [4] clause 4.3.2 and 4.3.3.

#### 6.6.1.4 Operations and Notifications

Refer to clause 5.1 for details on O1 notification formats, including SDO O1 format and VES O1 format notifications, categorized as Harmonized VES.

The O1-supported 3GPP-specified Heartbeat notification is:

- notifyHeartbeat.

## 6.6.2 Heartbeat Control

### 6.6.2.1 Description

Starting with 3GPP Release 16, dedicated operations for Management Services Use Cases are supported by IOCs with attributes that can be read and/or set using generic provisioning mechanisms. For Heartbeat management capability, a Heartbeat Control IOC is specified in 3GPP TS 28.622 [7] that includes attributes to Get/Set Heartbeat Period, (heartbeatNtfPeriod) and Trigger Immediate Heartbeat (triggerHeartbeatNtf).

### 6.6.2.2 Requirements

Requirements for heartbeat control specified in 3GPP TS 28.537 [4] clause 4.2.2.1 shall apply.

HeartbeatControl IOC definition shall be as specified in 3GPP TS 28.622 [7] clause 4.3.21.

YANG solution set for HeartbeatControl IOC shall be as in 3GPP TS 28.623 [23] clauses 4.4 and E.2.

### 6.6.2.3 Procedures

Procedures for heartbeat control are described in 3GPP TS 28.537 [4] clause 4.3.1 and 4.3.2.

NETCONF protocol and YANG data models are used to read and configure the heartbeatNtfPeriod and triggerHeartbeatNtf in the HeartbeatControl IOC. Refer to clause 6.1 for procedures to read MOI attributes and modify MOI attributes using NETCONF.

### 6.6.2.4 Void

## 6.7 Registration Management capability

### 6.7.0 Overview

The O1 Registration management capability enables a MnS Consumer to establish an O1 management connection with a MnS Producer, when it has completed its initialization phase and has sent the O1 Registration notification. This capability is deployment agnostic, and it is applicable both to physical and virtual deployment.

In case of a physical deployment, the MnS Producer supports sending the O1 Registration Notification (see clause 6.7.2) upon first PNF power-up/first start-up and any following start-up.

In case of a virtualized deployment, the MnS Producer supports sending the O1 Registration Notification, upon the virtualized deployment(s) (e.g. NF deployment(s)) have completed the start-up, and an O1 management connection establishment is required.

The PNF Plug-n-Connect scenario, described in clause 6.7.1 is relevant in a start-up without persistent memory, to dynamically obtain the necessary start-up configuration.

Relevant 3GPP specifications for PNF Plug-n-Connect (PnC) are 3GPP TS 28.314 [1], 28.315 [2] and 28.316 [i.2].

### 6.7.1 PNF Plug-n-Connect

#### 6.7.1.1 Description

PNF Plug-n-Connect (PnC) scenario enables a PNF to obtain the necessary start-up configuration to allow it to register with a MnS Consumer for subsequent management.

#### 6.7.1.2 Requirements

Specification requirement for Plug and Connect specified in 3GPP TS 28.314 [1] clause 6.2.1 shall apply.

### 6.7.1.3 Procedures

Functional elements involved in Plug and Connect, for example, IP Autoconfiguration services, DNS server, Certification Authority server, Security gateway and Software and Configuration Server (SCS) are described in 3GPP TS 28.315 [2] clause 4.2.

Plug-and-Connect and related procedures are described in 3GPP TS 28.315 [2] clause 5.

## 6.7.2 O1 Registration

### 6.7.2.1 Description

The MnS Producer sends the O1 Registration Notification when it has completed its initialization phase and is ready to be managed by the O1 interface. It is applicable to any start-up either with or without persistent data.

During start-up without persistent data, the MnS Producer can acquire its network layer parameters either via static procedures (e.g. pre-configured in the element) or via dynamic procedures (e.g. PNF Plug-n-Connect). The MnS Producer acquires the IP address of the MnS Consumer where the O1 Registration notification has to be sent. In addition, the MnS Producer also acquires the DN prefix [i.21] and optionally the RDN [i.21] values of the ManagedElement MOI to be created.

During start-up with persistent data, the MnS Producer sends the O1 registration notification only to MnS Consumer(s) previously subscribed to the O1 registration notification (see clause 6.1.7 in this document for the subscription control capability).

If no active subscription for the O1 Registration notification exists, then the same procedure defined for a start-up without persistent data, in accordance with clause 6.7.2.3.1 will be applicable.

The O1 Registration MnS Producer will periodically send the O1 Registration Notification (at vendor specified intervals) until a O1 management connection is established.

### 6.7.2.2 Requirements

REQ-PNFR-FUN-1: A MnS Producer shall support the capability to send the O1 Registration Notification when is ready to be managed via O1 interface

REQ-PNFR-FUN-2: A MnS Producer shall support the capability to send the O1 Registration Notification to the subscribed MnS consumer(s) in case of start-ups where subscription information have been persisted.

### 6.7.2.3 Procedures


#### 6.7.2.3.0 Overview

The procedures in the present clause are examples adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.

#### 6.7.2.3.1 First start-up and any following start-up without persistent data

PNF Registration procedure is illustrated by Figure 6.7.2.3.1-1. The MnS Producer sends an HTTP/TLS o1Registration notification to the MnS Consumer after initialization and OAM services are ready for the O1 management connection establishment and then to be put into service (e.g. applying further logical configuration).

The following procedure can be applied either to physical or virtual deployment.



**Figure 6.7.2.3.1-1 Registration Notification in case of a start-up without persistent data**

#### Pre-condition:

- Initialization procedure completed
  - In case of a physical deployment, Plug-n-Connect has been completed.
  - In case of a virtualized deployment, the deployment and the initialization of the virtualized components has been completed (e.g. NF Deployments have been instantiated via O2 interface).
  - MnS Producer has acquired its network layer parameters as the IP address of the MnS Consumer where the O1 Registration notification needs to be sent as well as the DN prefix [i.21] and optionally the RDN [i.21] values of the ManagedElement MOI to be created.
- OAM Services are available

#### Procedure:

1. MnS Producer sends o1Registration notification to MnS Consumer over HTTP/TLS. Mutual certificate authentication is performed. The MnS Producer will periodically send the o1Registration notification (at vendor specified intervals) until a O1 management connection is established.


#### Post-condition:

- MnS Consumer registers the MnS Producer so that it can be managed.
- MnS Consumer establishes the NETCONF session and check the MnS Producer configuration data.

### 6.7.2.3.2 Following start-up with persistent data

O1 Registration procedure in case of a start-up with persistent data is illustrated by Figure 6.7.2.3.2-1.

The following procedure can be applied either to physical or virtual deployment.



**Figure 6.7.2.3.2-1 Registration Notification for a MnS Producer start-up with persistent data**

Pre-condition:

- MnS Producer has persistent data including the subscribed MnS Consumer(s) per O1Registration notification
- MnS Producer has an active notification subscription (i.e. MnS Consumer(s) subscribed to receive O1Registration notification)
- OAM services in the MnS Producer are available again

Procedure:

1. MnS Producer sends o1Registration notification to MnS Consumer over HTTP/TLS in case of a start-up that require the re-establishment of the O1 interface, when the OAM services are available again. Mutual certificate authentication is performed. The MnS Producer will periodically send the o1Registration notification until a NETCONF session is established.

Post-condition:

- MnS Consumer takes advantage of the information that the MnS Producer is available again to register the MnS Producer status, re-establish the NETCONF session and check the MnS Producer configuration data.

## 6.7.2.4 Operations and Notifications

Refer to clause 5.1 for details on O1 notification formats, including SDO O1 format and VES O1 format notifications, categorized as Legacy VES and Harmonized VES.

The O-RAN-specified O1 Registration notification is:

- o1Registration, defined in table 6.7.2.4-1.

**Table 6.7.2.4-1: O1 registration notification parameters**

| Parameter Name   | S | Documentation and Allowed Value                                                                                                                                                                                                                    | Properties                                                            |
|------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| objectClass      | M | ManagedElement.objectClass<br>Class of the managed object, registering for service as defined in clause 11.1.1.7.2 of 3GPP TS 28.532 [3].                                                                                                          | Type: String<br>multiplicity: 1<br>isOrdered: N/A<br>isUnique: N/A    |
| objectInstance   | M | ManagedElement.objectInstance<br>Instance of the managed object, registering for service as defined in clause 11.1.1.7.2 of 3GPP TS 28.532 [3].                                                                                                    | Type: DN<br>multiplicity: 1<br>isOrdered: N/A<br>isUnique: N/A        |
| notificationId   | M | NotificationId<br>Identifier for the subject notification as defined in clause 11.1.1.7.2 of 3GPP TS 28.532 [3].                                                                                                                                   | Type: Integer<br>multiplicity: 1<br>isOrdered: N/A<br>isUnique: N/A   |
| notificationType | M | " o1Registration "                                                                                                                                                                                                                                 | Type: String<br>multiplicity: 1<br>isOrdered: N/A<br>isUnique: N/A    |
| eventTime        | M | Time when the NF is sending the registration as defined in clause 11.1.1.7.2 of 3GPP TS 28.532 [3].<br>DateTime type as defined in 3GPP TS 28.622 [7].                                                                                             | Type: DateTime<br>multiplicity: 1<br>isOrdered: N/A<br>isUnique: N/A  |
| systemDN         | M | DN of the MnS Producer of the notification as defined in clause 11.1.1.7.2 of 3GPP TS 28.532 [3].<br>NOTE: If an MnSAgent MOI is present, systemDN shall be the DN of an MnSAgent. If no MnSAgent is present the DN of the root MOI shall be used. | Type: DN<br>multiplicity: 1<br>isOrdered: N/A<br>isUnique: N/A        |
| serialNumber     | M | serialNumber = serial number of the unit as defined in clause 4.4.1 of 3GPP TS 28.632 [25].<br>Applicable only in case of a PNF.                                                                                                                   | Type: String<br>multiplicity: 0..1<br>isOrdered: N/A<br>isUnique: N/A |
| vendorName       | M | vendorName = name of the NF vendor as defined in clause 4.4.1 of 3GPP TS 28.622 [7].                                                                                                                                                               | Type: String<br>multiplicity: 0..1<br>isOrdered: N/A<br>isUnique: N/A |
| oamV4IpAddress   | M | IPv4 OAM IP address to be used by the manager to contact the NF.<br>Either oamV4IpAddress or oamV6IpAddress shall be provided depending upon what the network function supports.                                                                   | Type: String<br>multiplicity: 0..1<br>isOrdered: N/A<br>isUnique: N/A |
| oamV6IpAddress   | M | IPv6 OAM IP address to be used by the manager to contact the NF.<br>Either oamV4IpAddress or oamV6IpAddress shall be provided depending upon what the network function supports.                                                                   | Type: String<br>multiplicity: 0..1<br>isOrdered: N/A<br>isUnique: N/A |
| macAddress       | O | MAC address of the OAM of the unit                                                                                                                                                                                                                 | Type: String<br>multiplicity: 0..1<br>isOrdered: N/A<br>isUnique: N/A |
| unitFamily       | O | vendorUnitFamilyType = general type of HW unit as defined in clause 4.4.1 of 3GPP TS 28.632 [25].                                                                                                                                                  | Type: String<br>multiplicity: 0..1<br>isOrdered: N/A<br>isUnique: N/A |
| unitType         | O | vendorUnitTypeNumber = vendor name for the unit as defined in clause 4.4.1 of 3GPP TS 28.632 [25].                                                                                                                                                 | Type: String<br>multiplicity: 0..1<br>isOrdered: N/A<br>isUnique: N/A |
| modelName        | O | versionNumber = version of the unit from the vendor as defined in clause 4.4.1 of 3GPP TS 28.632 [25].                                                                                                                                             | Type: String<br>multiplicity: 0..1<br>isOrdered: N/A<br>isUnique: N/A |



| Parameter Name        | S | Documentation and Allowed Value                                                                                                                                                                                                                          | Properties                                                                      |
|-----------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
| softwareVersion       | O | swVersion = Version identifier of the software unit. This is the software provided by the vendor at onboarding to be run on this version of the NF and can contain multiple underlying software images as defined in clause 4.4.1 of 3GPP TS 28.632 [25] | Type: String<br>multiplicity: 0..1<br>isOrdered: N/A<br>isUnique: N/A           |
| softwareName          | O | swName = software release name as defined in clause 4.4.1 of 3GPP TS 28.632 [25].                                                                                                                                                                        | Type: String<br>multiplicity: 0..1<br>isOrdered: N/A<br>isUnique: N/A           |
| restartReason         | O | Reason the NF restarted, if known                                                                                                                                                                                                                        | Type: String<br>multiplicity: 0..1<br>isOrdered: N/A<br>isUnique: N/A           |
| manufactureDate       | O | dateOfManufacture = manufacture date of the unit as defined in clause 4.4.1 of 3GPP TS 28.632 [25].<br>DateTime type as defined in 3GPP TS 28.622 [7].                                                                                                   | Type: DateTime<br>multiplicity: 0..1<br>isOrdered: N/A<br>isUnique: N/A         |
| lastServiceDate       | O | dateOfLastService = date of last service or repair of the unit as defined in clause 4.4.1 of 3GPP TS 28.632 [25].<br>DateTime type as defined in 3GPP TS 28.622 [7].                                                                                     | Type: DateTime<br>multiplicity: 0..1<br>isOrdered: N/A<br>isUnique: N/A         |
| additionalInformation | O | Additional registration fields if needed. The content of the attribute is a list of attributeNames and string attributeValues.<br>NameValuePair type as defined in 3GPP TS 28.111 [26].                                                                  | Type: NameValuePair<br>multiplicity: 0..*<br>isOrdered: False<br>isUnique: True |

## 6.8 PNF Software Management Services

### 6.8.0 Overview

Software management services allow a PNF Software MnS Consumer to request a physical PNF Software MnS Producer to download, install, validate and activate a new software package and allow a physical PNF Software MnS Producer to report its software versions.

### 6.8.1 Software Package Naming and Content

PNF Software Package naming, content and format are vendor specific and do not require standardization in O-RAN. A PNF Software Package contains one or more files. Some of the files in the Software Package are optional for the PNF (example: a file that has not changed version). The PNF is aware of the content and format of its available Software Packages and can determine which files it needs to download.

The softwarePackage Managed Object Class (MOC) contains attributes about a software package such as:

- software package name;
- version;
- fileList;
- integrityStatus (valid, invalid, empty);
- runningState (active, passive);
- vendor;
- productName;
- softwareType (operational, factory);

- etc.

This MOC is applicable to VNFs and PNFs and is a generic term that O-RAN will use to refer to the software available on the PNF rather than the legacy term of software slot.

The PNF creates one instance of softwarePackage for each software package supported concurrently on the PNF. Typically, a PNF will have two softwarePackage MOIs for operational software; one with runningState = active and one with runningState = passive. Some PNFs also have a softwarePackage MOI for the factory software which would be read only. O-RAN can have PNFs that support more than one passive slot. In this case the inventory query result would show multiple MOIs with runningState=passive.

## 6.8.2 Software Inventory

### 6.8.2.1 Description


The PNF Startup and Registration MnS Consumer sends a Software Inventory Request and retrieves information about the software packages on the PNF Software MnS Producer.

### 6.8.2.2 Requirements

REQ-SWI-FUN-1: The PNF software management service producer shall have the capability to provide its authorized consumer information about the software packages on the PNF software management service producer.

### 6.8.2.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.8.2.3-1 Software Inventory**

Procedure:

1. PNF Software MnS Consumer establishes NETCONF session with PNF Software MnS Producer. The NETCONF session has authorized read privileges into the identified section of the data store.

2. PNF Software MnS Consumer sends NETCONF <rpc> <get><filter> to retrieve an optionally filtered subset configuration from the running configuration datastore. <filter> can be used to identify the software package MOIs. GET retrieves configuration and operational state of softwarePackage MOIs:
  - a. PNF Software MnS Producer retrieves software inventory information.
3. PNF Software MnS Producer returns requested data in NETCONF <rpc-reply> response.
4. PNF Software MnS Consumer terminates NETCONF session with PNF Software MnS Producer.

## 6.8.3 Software Download

### 6.8.3.1 Description

Software Download triggers the download of a specific software package to the PNF Software MnS Producer. This download service includes integrity checks on the downloaded software and the installation of the software into the software slot corresponding to the softwarePackage MOI.

### 6.8.3.2 Requirements

REQ-SWD-FUN-1: The PNF software management service producer shall have the capability to allow its authorized consumer to specify the location of software that is to be downloaded and to specify into which softwarePackage the software is to be stored.

REQ-SWD-FUN-2: The PNF software management service producer shall have the capability to verify if a software download is in progress and the ability to reject subsequent download commands until the one in progress completes.

REQ-SWD-FUN-3: The PNF software management service producer shall have the capability to deny download of software if the download request is not valid for the PNF software management service producer.


REQ-SWD-FUN-4: The PNF software management service producer shall have the capability to download needed files from a software server at a specified location.

REQ-SWD-FUN-5: The PNF software management service producer shall have the capability to perform integrity checks on downloaded software.

REQ-SWD-FUN-6: The PNF software management service producer shall have the capability to notify the PNF software management consumer with the software download result.

### 6.8.3.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.8.3.3-1 Software Download**

Procedure:

1. PNF Software MnS Consumer establishes NETCONF session with PNF Software MnS Producer. The NETCONF session has authorized execution privileges for retrieve file list and file-download rpcs.
2. PNF Software MnS Consumer sends NETCONF <rpc><software-download><remote-file-path><softwarePackage> to trigger a download of the software located at remoteFilePath and save its information in softwarePackage:
  - a. PNF Software MnS Producer validates the request. Validation includes determining if the operation can be performed. This is PNF Software MnS Producer specific but could include things like: checking that there is not a software download already in progress, softwarePackage is runningState = passive and softwareType = operational, etc.
3. PNF Software MnS Producer returns NETCONF <rpc-reply><software-download-status>.
4. PNF Software MnS Consumer terminates NETCONF session with PNF Software MnS Producer.
5. PNF Software MnS Producer initiates a secure connection and downloads via a secure file transfer protocol (FTPeS, SFTP or HTTPS) and according to the O-RAN Security Requirements and Controls Specifications [17] clause 5.2.2, the software package from remoteFilePath. PNF Software MnS Producer understands the software package format and downloads all the files it needs from the package. PNF Software MnS Producer decides where to store the software internally. This is PNF Software MnS Producer specific but could be a temporary location like /tmp:
  - a. PNF Software MnS Producer integrity checks the downloaded software. This is PNF Software MnS Producer specific but could include checking-checksum, correct software for the hardware, etc.
  - b. PNF Software MnS Producer stores the software in a persistent location.
  - c. PNF Software MnS Producer updates softwarePackage attributes for the downloaded software.
6. (Optional) If the download takes a long time, PNF Software MnS Producer may send periodic downloadFile notifications to the PNF Software MnS Consumer with the current status of the download (download in progress, integrity checks passed, install complete).

7. When download operation completes, PNF Software MnS Producer sends downloadFile event notification to PNF Software MnS Consumer with the final status of the download (success or the reason for failure).

#### 6.8.3.4 Operations and Notifications

Refer to clause 5.1 for details on O1 notification formats, including SDO O1 format and VES O1 format notifications, categorized as Harmonized VES.

NOTE: There are no File Download notifications defined in the present document.

### 6.8.4 Software Activation Pre-Check

#### 6.8.4.1 Description

Activation Pre-check is an optional Use Case that the Service Provider can choose to utilize prior to software activation to confirm that the PNF Software MnS Producer is in a good state to activate the new software and provide information needed for planning the timing of the software replacement--such as whether a reset or a data migration is required.


#### 6.8.4.2 Requirements

REQ-SPC-FUN-1: The PNF software management service producer shall have the capability to confirm that the software in the passive slot targeted for activation is good.

REQ-SPC-FUN-2: The PNF software management service producer shall have the capability to determine whether the activation of the targeted software requires a reset and/or data migration.

#### 6.8.4.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.



**Figure 6.8.4.3-1 Software Activation Pre-Check**

Procedure:

1. PNF Software MnS Consumer establishes NETCONF session with PNF Software MnS Producer.

2. PNF Software MnS Consumer sends NETCONF <rpc><activation-pre-check><softwarePackage> to trigger a pre-check of the software stored in softwarePackage and to return the results of the pre-check:
  - a. PNF Software MnS Producer performs the activation pre-check which includes validating that the software in softwarePackage is good, whether the activation of the software in softwarePackage will result in a reset and whether data migration is needed, etc.
3. PNF Software MnS Producer returns NETCONF <rpc-reply> to the PNF Software MnS Consumer with the results of the pre-check.
4. PNF Software MnS Consumer terminates NETCONF session with PNF Software MnS Producer.

## 6.8.5 Software Activate

### 6.8.5.1 Description

PNF Software MnS Consumer triggers the activation of a software package on the PNF Software MnS Producer including data migration and reset if needed.

### 6.8.5.2 Requirements

REQ-SWA-FUN-1: The PNF software management service producer shall have the capability to allow its authorized consumer to activate valid software in a specific softwarePackage.

REQ-SWA-FUN-2: The PNF software management service producer shall have the capability to verify whether a software activation is in progress and deny a concurrent activation of software.

REQ-SWA-FUN-3: The PNF software management service producer shall have the capability to deny activation of software if the activation request is not valid for the PNF software management service producer.

REQ-SWA-FUN-4: The PNF software management service producer shall have the capability to activate the softwarePackage.

REQ-SWA-FUN-5: The PNF software management service producer shall have the capability to reset the PNF software management service producer if the software activation requires it.

REQ-SWA-FUN-6: The PNF software management service producer shall provide the capability for the PNF software management service producer to send a re-set reason notification to its authorized consumer if the activation results in a reset.

REQ-SWA-FUN-7: The PNF software management service producer shall have the capability to perform data migration on the PNF software management service producer if the software activation requires it.

REQ-SWA-FUN-8: The PNF software management service producer shall have the capability to fall back to the previously active software if the new software cannot be activated.

REQ-SWA-FUN-9: The PNF software management service producer shall have the capability to fall back to the factory software if the new and the previously active software cannot be activated.

### 6.8.5.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.




Figure 6.8.5.3-1 Activate Software

#### Procedure:

1. PNF Software MnS Consumer establishes NETCONF session with PNF Software MnS Producer.
2. PNF Software MnS Consumer sends NETCONF <rpc><software-activate><softwarePackage> to trigger an activation of the software in softwarePackage:
  - a. PNF Software MnS Producer validates the request. This is PNF Software MnS Producer specific but could include things like checking that there is not a software activation already in progress, softwarePackage is runningState = passive and integrityStatus = valid, etc.
3. PNF Software MnS Producer returns status to the PNF Software MnS Consumer in the NETCONF <rpc-reply> response:
  - a. PNF Software MnS Producer performs the steps needed to make the softwarePackage the active one. This is PNF Software MnS Producer specific but includes things like updating the runningState of the about-to-be-active and previously-active software packages.
4. PNF Software MnS Consumer terminates NETCONF session with PNF Software MnS Producer.  
 (Optional) PNF Software MnS Producer performs data migration if necessary. PNF Software MnS Producer knows whether this is necessary.
5. (Optional) PNF Software MnS Producer performs reset if necessary. PNF Software MnS Producer knows whether reset is necessary. If a reset occurs, PNF Software MnS Producer sends a resetReason notification to the PNF Software MnS Consumer with the reason for the reset; in this case software activation.  
 (Optional) If the PNF Software MnS Producer cannot activate the software, PNF Software MnS Producer has recovery logic to fall back to the previously active software and potentially fallback to the factory software in a worst-case scenario.
6. (Optional) If the activation takes a long time, PNF Software MnS Producer sends periodic softwareActivate notifications to PNF Software MnS Consumer with the current status of the activation (e.g. activation in progress, data migration successful).
7. After activation operation completes, PNF Software MnS Producer sends a softwareActivate notification to PNF Software MnS Consumer with the final status of the activation.
8. PNF Software MnS Producer sends notifyMOIAttributeValueChanged to the PNF MnS Consumer updating the active software running on the PNF.

### 6.8.5.4 Operations and Notifications

Refer to clause 5.1 for details on O1 notification formats, including SDO O1 format and VES O1 format notifications, categorized as Harmonized VES.

NOTE: There are no Software Activate notifications defined in the present document.

## 6.9 PNF Reset Management Services

### 6.9.0 Overview

PNF Reset Management Services allow a PNF Reset MnS Consumer to trigger a reset of a HW unit of a PNF Reset MnS Producer on command.

### 6.9.1 PNF Reset Command

#### 6.9.1.1 Description

The PNF Reset Command procedure allows a PNF Reset MnS Consumer to trigger a reset of a HW unit of a PNF Reset MnS Producer on command. Any HW unit that is resettable via a reset command is represented by a managed object



instance (MOI) and is able to be identified by a distinguished name (DN). The NETCONF RPC <reset> command identifies the unit to reset by the DN. The unit to reset can be the entire PNF or a resettable HW subcomponent of the PNF. A resettable HW subcomponent of a PNF is a subcomponent of a PNF that is able to be independently reset and whose PNF Reset MnS Producer supports a reset command for the subcomponent. It is vendor and PNF-specific whether a PNF has resettable HW subcomponents. The reset command also has an attribute to identify the type of reset requested. The types of reset commands that a PNF supports are vendor and PNF specific. O-RAN O1 Interface Specification specifies two mandatory reset command types that every PNF supports: conditional and forced. A conditional reset command can be rejected by the PNF Reset MnS Producer depending on the conditions on the PNF, for example if the unit to reset is not in a proper state to reset, such as, if there is an emergency call in progress on the unit. A valid forced reset command cannot be rejected. Valid means that the unit to reset supports a reset command. Invalid forced resets will be rejected, for example, if the unit to reset is not a resettable HW unit, such as a cell. Vendors are allowed to extend the O1 specified reset command types to add vendor and PNF specific reset command types.

### 6.9.1.2 Requirements

REQ-RM-FUN-1: The PNF Reset MnS Producer shall support the capability for a PNF Reset MnS Consumer to trigger a reset of a HW unit of the PNF Reset MnS Producer on command.

REQ-RM-FUN-2: The PNF Reset MnS Producer shall support reset command types conditional and forced.

REQ-RM-FUN-3: The PNF Reset MnS Producer shall be allowed to reject a conditional reset command type.

NOTE 1: The validations performed and the reasons for a conditional reset rejection, if any, are vendor and PNF specific.


REQ-RM-FUN-4: The PNF Reset MnS Producer shall not be allowed to reject a valid forced command reset type.

NOTE 2: Valid means that the unit to reset supports a reset command. Invalid forced resets will be rejected, for example, if the unit to reset is not a resettable HW unit, such as a cell.

### 6.9.1.3 Procedures

The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service, aiming to help with the implementation of the O1 Interface specification. It outlines a possible flow and does not introduce new conformance requirements.

This procedure shows how a PNF Reset MnS Consumer triggers a reset of a HW unit of a PNF Reset MnS Producer on command. The HW unit to reset is identified by the <unitToReset> input attribute. The type of reset command is identified by the <resetCommandType> input attribute. The <status> output attribute returned in the NETCONF response indicates whether the reset command has been accepted. The unit is reset after the NETCONF response is returned. The reason for the reset (e.g., conditional reset command or forced reset command) is persistently stored by PNF Reset MnS Producer before executing the reset



**Figure 6.9.1.3-1 PNF Reset Command**

**Pre-conditions:**

- PNF Reset MnS Consumer has established a NETCONF session to the PNF Reset MnS Producer as described in Provisioning Management Services, clause 6.1.8. The NETCONF session has authorized execution privileges for <reset> RPC.
- (Optionally) PNF Reset MnS Consumer has locked the appropriate DS of the PNF Reset MnS Producer as described in Provisioning Management Services, clause 6.1.10.

**Procedure:**

1. PNF Reset MnS Consumer sends NETCONF <rpc> <reset> <unitToReset><resetCommandType> to PNF Reset MnS Producer, indicating the unit to reset and the type of reset command.
2. PNF Reset MnS Producer validates the command. Validation is vendor and PNF specific but typically includes verifying that the <unitToReset> is resettable and can be reset at this time. A conditional reset command type allows the PNF Reset MnS Producer to reject the reset command, depending on the conditions on the PNF, for example if an emergency call is in progress. The conditions are vendor and PNF specific. A valid forced reset command type cannot be rejected. Valid means that the unit to reset supports a reset command. Invalid forced resets will be rejected, for example if the unit to reset is not a resettable HW unit, such as a cell. If the reset command is accepted, the reset reason (e.g., conditional reset command or forced reset command) is stored persistently on the PNF Reset MnS Producer.
3. PNF Reset MnS Producer responds, indicating in the <status> attribute whether the command is accepted. If the command is rejected, the <rpc-reply> contains an <rpc-error> element with the reason for the rejection.
4. Unit is reset.

**Post-conditions**

- (Optionally) PNF Reset MnS Consumer unlocks the DS of the PNF Reset MnS Producer after sending the reset command, as described in Provisioning Management Services, clause 6.1.11.
- (Optionally) PNF Reset MnS Consumer terminates the NETCONF session to the PNF Reset MnS Producer after sending the reset command, as described in Provisioning Management Services, clause 6.1.9.

#### 6.9.1.4 Operations

Information Model and YANG solution set for the NETCONF RPC <reset> command and its attributes will be specified in the O-RAN O1 Network Resource Model Specification [i.16].

### 6.9.2 Notifications

REQ-RN-FUN-1: A PNF MnS Producer shall support the capability to inform a PNF MnS Consumer that a reset has occurred and the reason that a HW unit has reset.

REQ-RN-FUN-2: A PNF MnS Producer shall save the reason for a reset persistently before resetting.

NOTE 1: This requirement applies to resets that occur under the control of the PNF.

REQ-RN-FUN-3: If a reset reason has not been saved persistently, the PNF MnS Producer shall set the reset reason to unknown in the notification.

NOTE 2: This requirement applies to resets that occur unexpectedly before the reset reason could be stored.

## 6.10 Void

## 6.11 Generic Management Capabilities

### 6.11.1 Overview

The Generic Management Capability defines capabilities that are not specific to any single management service but are applicable across multiple domains, such as Fault Management (FM), Performance Management (PM), and Configuration Management (CM). These capabilities provide common mechanisms that enable the realization of management functionalities across different domains.

Examples include mechanisms for subscription handling, Reliable Notifications.

### 6.11.2 Subscription Control

#### 6.11.2.1 Description

Subscription Control allows a MnS Consumer to subscribe to notifications emitted by a MnS Producer.

Starting with 3GPP Release 16, dedicated operations for Management Services Use Cases are supported by IOCs with attributes that can be read and/or set using generic provisioning mechanisms. For Subscription Control, the Subscribe and Unsubscribe operations are replaced with a NtfSubscriptionControl IOC as specified in 3GPP TS 28.622 [7] clause 4.3.22. NtfSubscriptionControl IOC contains attributes that allow a MnS Consumer to set the recipient address for the notifications and identify the scope of notifications desired. Optionally, the types of notifications desired, and notification filtering can also be provided. If filtering of the notifications is supported, only those notifications that match the specified value would be sent. For example, notifyNewAlarm notifications can be filtered to send only those with severity set to major or critical.

#### 6.11.2.2 Requirements

NtfSubscriptionControl IOC definition shall be as specified in 3GPP TS 28.622 [7] clause 4.3.22 with attribute definitions specified in 3GPP TS 28.622 [7] clause 4.4.1.

YANG models for NtfSubscriptionControl shall be as specified in 3GPP TS 28.623 [23] clauses 4.4 and E.2.

### 6.11.2.3 Procedures

NtfSubscriptionControl MOIs can be created and deleted by the system or pre-installed. Optionally, the NtfSubscriptionControl MOIs can be created and deleted, and attributes modified using NETCONF/YANG by the management service consumer following the procedures described in this Provisioning MnS clause.

### 6.11.2.4 Operations and Notifications

NtfSubscriptionControl IOC can be used to subscribe to notifications. In addition, HeartbeatControl IOC specified in 3GPP TS 28.622 [7] clause 4.3.21 can be used to subscribe to heartbeat notifications as specified in 3GPP TS 28.622 [7] Figure 4.2.1-5; i.e., by creating the HeartbeatControl MOI as a child of the NtfSubscriptionControl MOI.

## 6.11.3 Reliable Notifications

### 6.11.3.1 Description

Reliable notifications provide a mechanism to ensure that MnS Consumers do not lose critical management notifications. For example, due to transport issues or producer unreliability. They extend the basic functionality by introducing mechanisms that simplify the detection of gaps in notifications, the retrieval of missed notifications, and the recovery process when MnS Producer data becomes unreliable.

Reliable notifications address 3 scenarios primarily:

- Detection: Enable MnS Consumer to identify missed or lost notifications through sequenceNo and subscriptionId in the Common notification header as specified in 3GPP TS 28.532 [3], clause 11.0.2 and supported by lastSequenceNo in NtfSubscriptionControl, which reflects the latest sequence number sent for a subscription instance as specified in 3GPP TS 28.622 [7], clause 4.3.22. Refer Annex E for example.
- Retrieval: Enable MnS Consumer to access notifications that were prepared but not delivered. Consumers use NotificationList IOC as specified in 3GPP TS 28.622 [7], clause 4.3.81 to fetch the missed notifications.
- Recover: When MnS Producer data becomes unreliable and later returns to reliable state, notifications are sent to inform MnS Consumer about the loss of reliability and its subsequent restoration.
  - Provisioning Management Service: notifyPotentialFaultyDataNodeTree and notifyDataNodeTreeSyncRecommended, as specified in clause 6.1.14
  - Fault Supervision Management Service: notifyPotentialFaultyAlarmList and notifyAlarmListRebuilt, as specified in clause 6.2.1.4
  - Additionally, operationalState/availabilityStatus in NtfSubscriptionControl IOC provide status on the subscription as specified in 3GPP TS 28.622 [7], clause 4.3.81, these indicate when the consumer needs to re-synchronise again (using notifyDataNodeTreeSyncRecommended or notifyAlarmListRebuilt).

### 6.11.3.2 Requirements

- REQ-rel-notif-1: The MnS Producer shall provide a mechanism for the MnS Consumer to detect missing or out-of-order notifications.
- REQ-rel-notif-2: The MnS Producer shall store generated notifications.
- REQ-rel-notif-3: The MnS Producer shall provide a mechanism for the MnS Consumer to retrieve stored notifications.
- REQ-rel-notif-4: The MnS Producer should inform the MnS Consumer if it detects that one or more notifications could not be properly prepared as per subscription.


### 6.11.3.3 Procedures

#### 6.11.3.3.1 Overview

The different mechanisms of Reliable notifications are realized through the following procedures. The procedure in the present clause is an example adding to the reader's understanding of the interactions for the corresponding Management Service. It outlines a possible flow and does not introduce new conformance requirements.

#### 6.11.3.3.2 Reliable notifications: Detection Procedure

The missing notification detection procedure is illustrated by Figure 6.11.3.3.2-1.



**Figure 6.11.3.3.2-1 Detection Procedure for Reliable Notifications**

Pre-condition:

- MnS Consumer has subscribed to Notification types.

Procedure:

1. MnS Producer sends subscribed Notification types to MnS Consumer over HTTP/TLS.
2. The MnS Producer updates the lastsequenceNumber attribute in the corresponding NtfSubscriptionControl instance with the latest sequence number used in sent notification.


Post-condition:

- The MnS Consumer detects any missed or out-of-order notifications by identifying gaps in the sequence numbers associated with a specific subscription.

#### 6.11.3.3.3 Reliable Notifications: Retrieval Procedure

The Retrieve procedure is illustrated by Figure 6.11.3.3.3-1,

### Reliable Notifications - Gap Detection & Recovery



**Figure 6.11.3.3.3-2 Retrieve Procedure for Reliable Notifications**

Pre-condition:

- MnS Consumer has detected missing subscribed notifications

Procedure:

1. When the MnS Consumer detects a gap in the sequence numbers of received notifications for a given subscription, it initiates the notification retrieval process.
2. The MnS Consumer retrieves the missing notifications using NotificationList IOC.

Post-condition:

- The MnS Consumer will reconcile the missed or out-of-order notifications based on the missing sequence numbers

#### 6.11.3.3.4 Reliable Notifications: Recover Procedure

The Retrieve procedure is as specified in clause 6.1.14 for the Provisioning Management Service notifications (notifyPotentialFaultyDataNodeTree and notifyDataNodeTreeSyncRecommended). For Fault Supervision Management Service (notifyPotentialFaultyAlarmList and notifyAlarmListRebuilt), it is as specified in clause 6.2.1.4.

---

## Annex A: Void

---

## Annex B: (informative) Guidelines and Example for stndDefined VES Events

### B.1: Guidelines for use of stndDefined VES for sending 3GPP-specified or O-RAN-specified O1 notifications

A stndDefined VES event, as specified in VES Event Listener Specification [18], allows a VES event to carry, as its payload, a notification specified by an SDO. In the case of O-RAN O1 Interface Specification, a harmonized stndDefined VES event carries either a 3GPP-specified O1 notification or an O-RAN-specified O1 notification as its payload.

3GPP has published an informative Annex B in 3GPP TS 28.532 [3] providing guidelines for the integration of 3GPP-specified notifications with VES. This annex expands on the information provided by 3GPP, including information on how to include O-RAN-specified O1 notifications in a VES stndDefined event.

When an O-RAN and 3GPP compliant ME supports VES stndDefined events for sending asynchronous notifications, a 3GPP-specified O1 notification, as defined by 3GPP, or an O-RAN-specified O1 notification, as defined by O-RAN, is included in the event.

A VES common event header, as defined by VES Event Listener Specification [18], is added to the notification.

In VES, the domain field in the common event header is used to route the event to the proper consumers and to map to a schema for the event payload. VES Event Listener Specification [18] added a new domain field enumeration value called stndDefined that indicates that the event is complying with a schema defined by a standards body.

An additional field was added to the VES common event header called stndDefinedNamespace, which contains a valid namespace as defined by the standards body. This field is only populated when the domain is stndDefined. 3GPP has defined four namespaces in 3GPP TS 28.532 [3] Annex B; namely 3GPP-Provisioning, 3GPP-Heartbeat, 3GPP-FaultSupervision and 3GPP-PerformanceAssurance. O-RAN has defined a namespace for the notifications it defines. Refer to clause 5.2.2 for details. A VES collector uses the stndDefinedNamespace, along with the stndDefined domain, to route the event to the correct consumer.

A stndDefined VES event has a field structure called stndDefinedFields, specified in VES Event Listener Specification [18]. This structure contains three properties:

- schemaReference (type = string, format = uri)
- data (JSON object which is identical to the 3GPP or O-RAN notification)
- stndDefinedFieldsVersion (type = string, format = enum)

The schemaReference, if present, is used to verify that the notification content is correct. 3GPP is publishing the notification schemas defined using OpenAPI, to a public repository, (<https://forge.3gpp.org/rep/sa5>) so that schema references can be included in the event. Likewise, O-RAN will define its notification schemas using OpenAPI and publish them in a public repository. This repository is still to be created.

The data element contains either a 3GPP-specified O1 notification, in JSON format, as specified in 3GPP TS 28.532 [3] or an O-RAN-specified O1 notification, in JSON format, as specified in O-RAN O1 Network Resource Model Specification [i.16].

The stndDefinedFieldsVersion provides the version of the stndDefinedFields structure, as defined by VES Event Listener Specification [18].

Clause B.2 provides an example of a stndDefined VES event for a new alarm notification.



## B.2: Example stndDefined VES event for a new alarm notification

The following example illustrates the population of a new alarm notification using a stndDefined VES event.

The VES Common Header as shown in the example below, contains:

- the domain set to stndDefined
- the stndDefinedNamespace set to 3GPP-FaultSupervision.

The stndDefinedFields structure as shown in the example below, contains:

- the 3GPP schema reference for the 3GPP fault notification type
- the data element which contains the full 3GPP notifyNewAlarm fault notification
- the version of the stndDefinedFields.

Mapping of DN to URI is described in 3GPP TS 32.158 [i.15]

| Mapping                      | DN (Distinguished Name)                        | URI part                            |
|------------------------------|------------------------------------------------|-------------------------------------|
| DN-prefix                    | "DC=operatorA.com,SubNetwork=south" (see note) | "south.SubNetwork.operatorA.com"    |
| LDN                          | "ManagedElement=1,GNBDUFunction=1"             | "/ManagedElement=1/GNBDUFunction=1" |
| NOTE: DC is Domain Component |                                                |                                     |

The value for href in the example below is derived according to the table above, mapping the Distinguished Name prefix (DN-prefix) and the Local Distinguished Name (LDN), respectively, to the authority component and the path component of the URI in order to be globally unique.


```
{
  "event": {
    "commonEventHeader": {
      "domain": "stndDefined",
      "eventId": "stndDefined-gNB-Nokia-000001",
      "eventName": "stndDefined-gNB-Nokia-ProcessingErrorAlarm-351",
      "lastEpochMicrosec": 1594909352208000,
      "priority": "Normal",
      "reportingEntityName": "NOKb5309",
      "sequence": 0,
      "sourceName": "NOKb5309",
      "startEpochMicrosec": 1594909352208000,
      "stndDefinedNamespace": "3GPP-FaultSupervision",
      "timeZoneOffset": "UTC-05:00",
      "version": "4.1",
      "vesEventListenerVersion": "7.2"
    },
    "stndDefinedFields": {
      "schemaReference": "https://forge.3gpp.org/rep/sa5/MnS/-/blob/Rel-18/OpenAPI/TS28111_FaultNrm.yaml#/components/schemas/NotifyNewAlarm",
      "data": {
        "href": "http://south.SubNetwork.operatorA.com/ManagedElement=1/GNBDUFunction=1",
        "notificationId": 123,
        "notificationType": "notifyNewAlarm",
        "eventTime": "2023-11-15T23:20:50.52-05:00",
        "systemDN": "DC=operatorA.com,SubNetwork=south,ManagedElement=1,MnSAgent=1",
        "probableCause": 351,
        "perceivedSeverity": "MAJOR",
        "specificProblem": 7052,
        "additionalText": "xyz",
        "additionalInformation": {
          "svc": "alarm-svc-1"
        },
        "alarmId": "15",
        "alarmType": "PROCESSING_ERROR_ALARM"
      },
      "stndDefinedFieldsVersion": "1.0"
    }
  }
}
```

```
        } // stdDefinedFields
    } //event
}
```

---

## Annex C: (informative) Streaming Trace Management Activation Example

Example with Management-based Trace Activation, Data Reporting and Deactivation for Streaming Trace follows. The sequence below is based on 3GPP specifications which are referred in clause 6.4.



**Figure C-1 : Streaming Trace Connection Establishment, Data Reporting and Deactivation Example**

#### Scenario:

- Provisioning Management Service Consumer activates/configures Trace Session on Trace MnS Producer. This will be accomplished using Provisioning Management services described in clause 6.1.
- Trace MnS Producer sends a notifyMOIChanges to indicate the new MOI is created. Steps 3-6 are optional when no connection to trace MnS consumer exist.
- Trace MnS Producer needs to establish a connection to the Trace MnS Consumer to set up a streaming connection (streams are active at this time between the Producer and Consumer). This is done using the establishStreamingConnection Operation via an HTTP POST request containing MetaData associated with this Trace Session.
- Trace MnS Consumer responds with an acknowledgement that contains the ConnectionID needed by the Trace MnS Producer when requesting that the connection be upgraded to a WebSocket to support streaming of the trace data.
- Trace MnS Producer requests the upgrade of the connection to a WebSocket using the ConnectionID and an HTTP GET operation.
- Trace MnS Consumer accepts the upgrade and WebSocket is established. WebSocket will remain connected until the last streaming trace session active on the Trace MnS Producer is ended.

NOTE: In this example, only one streaming trace session is active.

- Optionally addStream operation is used to add a stream to the trace connection.
- Trace MnS Producer starts trace session, waiting for triggering event to occur.
- Trace MnS Producer sends trace session start administrative message to Trace MnS Consumer.
- Heartbeat sending criteria are met. The criteria about when to send Trace stream heartbeat administrative message are implementation specific.
- Trace stream heartbeat administrative message is sent to Trace consumer repeatedly. Trace stream heartbeat administrative message is used for monitoring whether the trace session connection is alive and can be executed parallel to other loops.
- "start" triggering event detected.
- A new trace recording session is started on the Trace MnS Producer. Each trace recording session has a unique Trace Recording Session (TRS) Reference associated with it.
- Trace recording session start administrative message is sent from Trace MnS Producer to Trace MnS Consumer.
- While this trace record is active, and the reporting criteria are not fulfilled, the Trace MnS Producer collects trace data.
- When the reporting criteria are fulfilled, either timer expires or the buffer fills, or the buffer has data and the "stop" triggering event is detected, the Trace MnS Producer sends a trace data report to the Trace MnS Consumer containing trace record data for active recording sessions in a trace session. These records are the payload of the reportStreamData operation.
- The criteria for the trace recording session completion or stop occurs (call ends, etc.).
- The Trace MnS Producer stops collecting data for this trace recording session.
- Trace MnS Producer sends trace recording session stop administrative message to Trace MnS Consumer.
- Provisioning Management Service Consumer deactivates the trace via procedures defined in clause 6.1 of the present document. Deactivation means that the trace data collection ceases, and the Trace MnS Producer stops all active trace recording sessions and sends data that it has collected up to this point, if any, for each active trace recording to the Trace MnS Consumer.
- Trace MnS Producer initiates the termination of the trace session.

- For each active trace recording session, Trace MnS Producer initiates a Stop Trace Recording Session.
- Optionally if there are outstanding record(s) for this trace recording session that have not been streamed to the Trace MnS Consumer, Trace MnS Producer sends them as the payload of the reportStreamData operation.
- Trace MnS Producer informs the Trace MnS Consumer that this Trace Recording Session has ended by sending the trace record termination administrative message. The producer repeats this until all trace recording sessions for this trace session have been terminated.
- Trace MnS Producer sends the trace session stop administrative message to Trace MnS Consumer.
- Optionally the Trace MnS Producer sends the Trace MnS Consumer the deleteStream operation indicating that the stream has been removed in case the connection is used for multiple streams.
- Optionally when all active Trace Sessions between Trace MnS Producer and Trace MnS Consumer have ended, the WebSocket connection is to be torn down. Trace MnS Producer sends the Trace MnS Consumer the terminateSignalingConnection Operation which is a WebSocket close frame.
- Terminate connection.

## Annex D: (normative) Recommendation for UE Identifier Format in Trace Header

Specification 3GPP TS 32.423 [13] clause 5.2.2 defines *vendorExtension* IE in Trace Header as an Arraylist of String. The Trace Record Header should be encoded using GPB in Annex G of 3GPP TS 32.423 [13].

Several UE identifiers and node identifiers are identified as necessary for trace record correlation. Refer to O-RAN architecture description [15] clause 5.5 for detailed information.

To enable trace record correlation, a new map entry is defined for *vendor\_extension* to be used to send O-RAN UE/Node identifiers.

Defined TraceRecordHeader field vendor-extension is in following format:

```
map<string, string> vendor_extension = 10;
```

The map entry should be added for UE identifier and node identifiers is as below:

First string in the map entry: value = "oranUENodeIdentifiers"

Second string in the map entry: value = result of "print string" of message OranUEAndNodeIdentifiers

**NOTE:** The O-RAN defined map entry for O-RAN UE/Node identifiers "oranUENodeIdentifiers" can co-exist with other vendor defined vendor-extension map entries. O-RAN defined map entry "oranUENodeIdentifiers" can be add in any position in the *vendor\_extension* map.

```
message OranUEAndNodeIdentifiers {
  optional OranConnectedEntity connected_entity_id = 1;
  optional OranUEId            originator_ue_id = 2;
  optional OranUEId            connected_entity_ue_id = 3;
}
```

```
Message OranUEId{
  optional int64 amf_ue_ngap_id = 1;
  optional int64 ran_ue_ngap_id = 2;
  optional int64 mme_ue_slap_id = 3;
  optional int64 gnb_cu_ue_flap_id = 4;
  optional int64 gnb_cu_cp_ue_elap_id = 5;
  optional int64 gnb_cu_up_ue_elap_id = 6;
  optional int64 traced_ng_ran_node_ue_xnap_id = 7;
  optional int64 connected_ng_ran_node_ue_xnap_id = 8;
  optional int64 m_enb_ue_x2ap_id = 9;
  optional int64 c_rnti = 10;
}
```

```
Message OranConnectedEntity {
  oneof connected_entity_id {
    bytes      ng_connected_guami = 1;           // AMF ID of the connected AMF
    Guami      ng_connected_guami_decoded = 2;   // AMF ID of the connected AMF
    GlobalGnbId xn_connected_global_gnb_id = 3;  // ID of neighbouring gNB-CU-CP
    OranGlobalEnbId xn_connected_global_enb_id = 4; // ID of neighbouring ng-eNB node
    OranGlobalEnbId x2_connected_global_enb_id = 5; // ID of connected NSA eNB node
    bytes      s1_connected_mme = 6;           // ID of connected MME
    Gummei     s1_connected_mme_decoded = 7;    // ID of connected MME
    int64      f1_connected_du_id = 8;         // ID of connected gNB-DU
    int64      e1_connected_cup_id = 9;        // ID of connected gNB-CU-UP
  }
}
```

```
message GlobalEnbId {
  bytes plmn_identity = 1;
  int64 enb_id = 2;
}
```


```
Message Guami {
  bytes      plmn_identity = 1;
  string     amf_region_id = 2;
  string     amf_set_id = 3;
  string     amf_pointer = 4;
```

```
}  
  
Message Gummei {  
    bytes    plmn_identity =1;  
    string   mme_grp_id=2;  
    string   mme_code=3;  
}
```

Based on the value `nf_type` (for example, gNB-CU-CP, gNB-CU-UP, gNB-DU) in the `TraceRecordHeader`, different types of UE identifiers and node identifier can be reported. For detail, refer to O-RAN architecture description [15] clause 5.5.



## Annex E: (informative) Reliable Notifications – Detection & Retrieval Procedure example



**Figure E-1: Reliable notifications Detection & Retrieval Procedure example**

### Scenario:

- The MnS Consumer has an active subscription identified by subscriptionId = S1 and begins receiving notifications from the MnS Producer for this subscription.
- The MnS Producer sends a notification with sequence number =100 and subscriptionId = S1 to the MnS Consumer and updates the lastSequenceNumber = 100 in the NtfSubscriptionControl instance.
- The MnS Producer prepares and sends the next notifications seq=101 and seq=102 for subscriptionId = S1 and updates lastSequenceNumber accordingly.
- Due to delivery issues, these notifications do not reach the MnS Consumer, even though they were successfully generated by the MnS Producer.
- When the next notification with seq = 103 for subscriptionId = S1 is delivered, the MnS Consumer identifies that it has missed notifications, since it expected seq = 101 but instead received notification with seq = 103.
- A notification gap is detected for subscriptionId = S1, and the MnS Consumer will initiate retrieval of the missing notifications.
- The MnS Consumer will issue a NETCONF <get> request on the NotificationList IOC to retrieve stored notification entries.

- The MnS Producer returns a NETCONF <rpc-reply> containing the NotificationList with any notificationEntries available within the MnS Producer's retention window.

## Annex (informative): Change History

| Date       | Revision   | Description                                                                                                                                                                                                                                        |
|------------|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2019.03.18 | 0.01.00.00 | First draft of O-RAN OAM Interface Specification                                                                                                                                                                                                   |
| 2019.03.28 | 0.01.01.00 | Updates from review remarks received                                                                                                                                                                                                               |
| 2019.05.21 | 0.01.01.01 | Fault Supervision, Performance Assurance and File Management updates                                                                                                                                                                               |
| 2019.05.28 | 0.01.01.02 | References, Abbreviations, Definitions, Provisioning, Communication Surveillance, PNF Start Up and Registration updates                                                                                                                            |
| 2019.06.13 | 0.01.01.03 | Diagrams for File Management converted to UML, Performance Assurance UML, PNF Software Management Updates                                                                                                                                          |
| 2019.06.17 | 0.01.01.04 | Provisioning Updates                                                                                                                                                                                                                               |
| 2019.07.01 | 01.00      | Review Comments Addressed TSC approved copy                                                                                                                                                                                                        |
| 2019.09.27 | 02.00      | Updates for late review comments, additional CM notifications, NETCONF requirements and updated references to 3GPP SA5 Rel-16.                                                                                                                     |
| 2020.03.03 | 03.00      | Update Heartbeat Management Service. New clauses for Subscription Control, Streaming PM, O-RAN Defined PM Measurements and an Annex showing examples for using the specified template for O-RAN defined PM Measurements.                           |
| 2020.08.18 | 04.00      | Update Introductory Material, Provisioning, Fault Supervision, Performance Assurance, Trace Management, and Heartbeat Management to incorporate 3GPP Rel 16 CRs. Add Annex B for stdDefined event example and Annex C for Streaming Trace example. |
| 2020.08.31 | 04.00      | Update document with comments from WG1 review                                                                                                                                                                                                      |
| 2021.03.11 | 04.01      | Incorporate approved CRs to prepare for v05.00.<br><br>Update Provisioning with approved CR 10.<br><br>Update Fault Supervision with approved CR 11.                                                                                               |
| 2021.04.27 | 04.02      | Update Software Download with approved CR 13.                                                                                                                                                                                                      |
| 2021.05.24 | 04.03      | Incorporate approved Updates and Corrections CR 14<br><br>Updates to References, Security Protocols and Trace.                                                                                                                                     |
| 2021.06.21 | 04.04      | Incorporate approved YANG Module Discovery CR 15                                                                                                                                                                                                   |
| 2021.06.22 | 05.00      | O1v5 incorporating CRs from 04.01.00 through 04.04.00                                                                                                                                                                                              |

|            |          |                                                                                                                                                                                                                                                                                                                                                                                        |
|------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2021.10.25 | 06.00    | Incorporate approved CRs: PNF Reset CR 16, Performance Management CR 17, Cloudified NF Registration CR 18, Notify Alarm List Rebuilt CR 19, O1 Notifications CR 20 and References Updates CR 21.                                                                                                                                                                                       |
| 2022.03.15 | 07.00    | Incorporate approved CRs: PM Streaming Format Correction CR 22, 3GPP specified Notification VES format support CR 23, Annex C Streaming Trace Management CR 24, PNF Registration Notification CR 25, Rearrange PNF Reset Notification Requirements CR 26, Clarify counter naming requirement CR 27 and Notification capability CR 28.                                                  |
| 2022.07.18 | 08.00    | Incorporate approved CRs: O-RAN counter name clarification CR 29, File management update CR 30, O1 Notification CR 31, Plug and Connect uplift CR 32, UE Identifiers for Trace header CR 33 and CM Notifications uplift CR 34.<br><br>Editorial changes related to the copyright clarification.                                                                                        |
| 2022.08.31 | 08.00.01 | Incorporate approved CR 36 resolving outdated 3GPP references.                                                                                                                                                                                                                                                                                                                         |
| 2022.11.01 | 09.00.00 | Incorporate approved CRs: Alignment with 3GPP and editorial modifications CR37, PM file format for NR measurements CR38.<br><br>Editorial changes related to the new document naming format.<br><br>Editorial changes related to application of embedded O-RAN styles template.                                                                                                        |
| 2022.11.21 | 09.00.01 | Editorial CR39 introduced changes for alignment with ODR, O-RAN TS Template and ETSI PAS - re-arranged and re-numbered clauses. Removal of author information from the history table.                                                                                                                                                                                                  |
| 2023.01.31 | 09.00.02 | Incorporate approved CRs: UE Identifier schema CR40, Measurement job control clarification CR41 and File management correction CR42                                                                                                                                                                                                                                                    |
| 2023.03.06 | 10.00    | Incorporate approved CRs: Clean-up of 3GPP TS 28.532 reference CR43, Correction of 3GPP TS 28.533 reference CR44, O-RU change in O1 introduction CR45, Split of normative and informative references CR46, Clean-up references CR47, Clean-up of introduction CR48, Remove out of scope Fault Notification requirements CR49 and Clean-up Fault Supervision Control Requirements CR50. |
| 2023.07.11 | 11.00    | Incorporate approved CRs: Reference update to O-RAN internal specifications CR33, Normative language clean-up CR52.                                                                                                                                                                                                                                                                    |
| 2023.09.14 | 11.00.01 | Incorporate approved CR 53 clarifying the use of push-based file reporting for transfer of PM files.                                                                                                                                                                                                                                                                                   |
| 2023.10.11 | 11.00.02 | Incorporate approved CRs 54 fixing the PM use case reference and 55 updating the referenced 3GPP specifications versioning                                                                                                                                                                                                                                                             |
| 2023.10.30 | 12.00    | Incorporate approved CRs: SBMA terminology clean-up CR 56, Align Netconf server behaviour with 3GPP TS 28.532 CR 57, Update referenced specifications versioning CR 58, Security requirements alignment CR 59 and Heartbeat management capability clarification CR 60.                                                                                                                 |
| 2024.03.11 | 13.00    | Incorporate approved CRs: Correction of the stndDefined VES event examples CR 61, Alignment with the O1 consolidation WID CR 62, Alignment with 3GPP for non-specific references CR 63 and Notify Event addition CR 64.<br><br>Editorial changes (re-alignment of content between the Scope and Foreword clauses).                                                                     |

|            |          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2024.06.24 | 14.00    | Incorporate approved CRs: Removal of PM requirements (move to a dedicated TS) CR65, Add file preparation error notification for pull based scenario CR66, Add file preparation error notification for push based scenario CR67, Clarify the use of informative content (ETSI PAS triggered) CR68, Clarify O1 interface specification scope CR69, Fix editorial issue (ETSI PAS identified) in clause 6.5.4.3 CR70, File push clean-up CR71, Alarm history request requirements CR72, Align notification format across management services CR73, Add notifyAckStateChanged notification details CR74, ETSI EditHelp editorial corrections CR75 and 5G Performance Measurements clarification CR76. |
| 2024.10.02 | 14.00.01 | Incorporate approved CRs: Improving document consistency CR 77, Update of PNF Registration notification CR 78, General Requirements update CR 79, Editorial corrections CR 80, Alignment with 3GPP Rel-18 CR 81                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| 2024.11.04 | 14.00.02 | Incorporate approved CRs: Alignment of 3GPP references for Trace and NRM CR 82, Alignment of 3GPP references for PM CR 83, Correction in NtfSubscriptionControl CR 84, Alignment of 3GPP references for FM CR 85, Alignment of 3GPP references for CM CR 86.                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| 2024.11.21 | 15.00    | Incorporate approved CRs: Correction of VES event mapping CR 87, Fault Supervision MnS Stage 3 references update CR 88, Addressing PMCountGroup and CUCountGroup compatibility CR 89.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 2025.03.06 | 16.00    | Incorporate approved CR: Security Requirements CR 90.<br><br>Editorial changes (additional clean-up after CR 90 implementation).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 2025.07.09 | 17.00    | Incorporate approved CR: PNF and Cloudified NF registration notification CR 91.<br><br>Editorial changes (alignment with the latest TS template).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| 2025.11.18 | 18.00    | Incorporate approved CRs: Update the Fault Supervision for AlarmList states and reliability of Alarm Lists CR 92, Clarification in PNF registration notification CR 93, Alarm requirement clarification CR 94.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 2026.01.26 | 18.00.01 | Incorporate approved CRs: Align FM with 3GPP Rel-19 CR95, Introduce Data Node Tree Reliability Notifications CR96, Generic Management capability for missed/lost notifications CR97.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| 2026.01.27 | 18.00.02 | Resolve missing source code for UML diagrams (editorial fix).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 2026.03.05 | 19.00    | Incorporate approved CRs: Clarification of the Performance Data File Reporting method CR98, Correction of Annex D for TraceRecordHeader CR99, Addition of RRC reporting CR100, Logged and Immediate MDT configuration description correction CR101 and 3GPP Rel-19 alignment and clean-up CR102.                                                                                                                                                                                                                                                                                                                                                                                                  |