Think Python: Chapter 16-17

A function that doesn't modify any of the objects passed to it as arguments nor have any effect and does nothing except returning a value is termed a(n) _____ function.

A function that doesn't modify any of the objects passed to it as arguments nor have any effect and does nothing except returning a value is termed a(n) ______ function.

pure

Functions that DO modify objects received as parameters are termed

Functions that DO modify objects received as parameters are termed .

modifiers

The author of our textbook recommends writing _	functions
whenever it is reasonable, resorting to	only when one has
a compelling reason.	

The author of our textbook recommends writing _____ functions whenever it is reasonable, resorting to _____ only when one has a compelling reason.

pure, modifiers

A(n) _____ programming style involves writing pure functions whenever possible and modifiers only if there is a compelling advantage.

A(n) _____ programming style involves writing pure functions whenever possible and modifiers only if there is a compelling advantage.

functional

A(n) _____ is a requirement that should always be true during a program's execution.

A(n) _____ is a requirement that should always be true during a program's execution.

invariant

Methods are defined inside a(n) _____ definition.

Methods are defined inside a(n) _____ definition.

class

```
class Airedale:
  def diet results(dog):
      dog.weight *= .9
Charlotte = Airedale()
Charlotte.sex = "female"
Charlotte.age = 10.25
Charlotte.weight = 70
Charlotte.diet results()
print("Charlotte's weight goal post-diet is",
Charlotte.weight)
```

Charlotte's weight goal post-diet is 63.0

```
class Airedale:
    def diet_results(dog):
        dog.weight *= .9

Charlotte = Airedale()
Charlotte.sex = "female"
Charlotte.age = 10.25
Charlotte.weight = 70
Charlotte.diet results()
```

What is diet_results?
Where is it located?
Which type of dot notation is used to call it?

```
class Airedale:
    def diet_results(dog):
        dog.weight *= .9

Charlotte = Airedale()
Charlotte.sex = "female"
Charlotte.age = 10.25
Charlotte.weight = 70
Charlotte.diet results()
```

What is diet_results? A method
Where is it located? Inside the class definition
Which type of dot notation is used to call it?
Method syntax, the more common

```
class Airedale:
    def diet_results(self):
        self.weight *= .9

Charlotte = Airedale()
Charlotte.sex = "female"
Charlotte.age = 10.25
Charlotte.weight = 70
Charlotte.diet_results()
```

What's different here?

```
class Airedale:
  def diet results(self):
        self.weight *= .9
Charlotte = Airedale()
Charlotte.sex = "female"
Charlotte.age = 10.25
Charlotte.weight = 70
Charlotte.diet results()
What's different here?
--First parameter is named with convention of "self"
--Referring to attributes within the method requires the dot notation to use self, i.e., self.weight, instead of dog.weight as in the last example
```