Scan Report

January 26, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone "Coordinated Universal Time", which is abbreviated "UTC". The task was " hgdfdghgdgd". The scan started at Mon Jan 26 01:47:47 2026 UTC and ended at Mon Jan 26 14:04:13 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1 Result Overview **2**

2 Results per Host **2**

2.1 172.31.1.74 2

2.1.1 Critical 80/tcp 2

2.1.2 High 80/tcp 5

2.1.3 High 25/tcp 6

2.1.4 Medium 80/tcp 9

2.1.5 Medium 25/tcp 19

2.1.6 Low 80/tcp 25

2.1.7 Low general/icmp 26

2.1.8 Low general/tcp 27

2.1.9 Log 80/tcp 28

2.1.10 Log general/tcp 33

2.1.11 Log general/CPE-T 37

2.1.12 Log 25/tcp 37

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
172.31.1.74 nagios.trabalho_vulnnet	1	2	11	3	26	0
Total: 1	1	2	11	3	26	0

Vendor security updates are not trusted.
Overrides are off. Even when a result has an override, this report uses the actual threat of the result.
Information on overrides is included in the report.
Notes are included in the report.
This report might not show details of all issues that were found.
Issues with the threat level "Debug" are not shown.

This report contains all 43 results selected by the filtering described above. Before filtering there were 5586 results.

2 Results per Host

2.1 172.31.1.74

Host scan start	Mon Jan 26 08:38:21 2026 UTC
Host scan end	Mon Jan 26 10:27:50 2026 UTC

Service (Port)	Threat Level
80/tcp	Critical
80/tcp	High
25/tcp	High
80/tcp	Medium
25/tcp	Medium
80/tcp	Low
general/icmp	Low
general/tcp	Low
80/tcp	Log
general/tcp	Log
general/CPE-T	Log
25/tcp	Log

2.1.1 Critical 80/tcp

Critical (CVSS: 9.8)
NVT: Apache HTTP Server < 2.4.60 Multiple Vulnerabilities - Linux

Product detection result
`cpe:/a:apache:http_server:2.4.58`
`Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1`
`↪.0.117232)`

Summary
Apache HTTP Server is prone to multiple vulnerabilities.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 2.4.58
Fixed version:     2.4.60
Installation
path / port:       80/tcp
```

Solution:
Solution type: VendorFix
Update to version 2.4.60 or later.

Affected Software/OS
Apache HTTP Server version 2.4.59 and prior.

Vulnerability Insight
The following flaws exist:
- CVE-2024-36387: Denial of Service (DoS) by Null pointer in websocket over HTTP/2
- CVE-2024-38473: Proxy encoding problem
- CVE-2024-38474: Weakness with encoded question marks in backreferences
- CVE-2024-38475: Weakness in mod_rewrite when first segment of substitution matches filesystem path
- CVE-2024-38476: May use exploitable/malicious backend application output to run local handlers via internal redirect
- CVE-2024-38477: Crash resulting in DoS in mod_proxy via a malicious request
- CVE-2024-39573: mod_rewrite proxy handler substitution

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Apache HTTP Server < 2.4.60 Multiple Vulnerabilities - Linux`
OID:1.3.6.1.4.1.25623.1.0.114682
Version used: `2025-08-07T05:44:51Z`

Product Detection Result
Product: `cpe:/a:apache:http_server:2.4.58`

. . . continues on next page . . .

. . . continued from previous page . . .

Method: Apache HTTP Server Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.117232)

References

cve: CVE-2024-36387
cve: CVE-2024-38473
cve: CVE-2024-38474
cve: CVE-2024-38475
cve: CVE-2024-38476
cve: CVE-2024-38477
cve: CVE-2024-39573
cisa: Known Exploited Vulnerability (KEV) catalog
url: https://www.cisa.gov/known-exploited-vulnerabilities-catalog
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.60
cert-bund: WID-SEC-2025-1572
cert-bund: WID-SEC-2025-0818
cert-bund: WID-SEC-2025-0148
cert-bund: WID-SEC-2025-0143
cert-bund: WID-SEC-2024-3291
cert-bund: WID-SEC-2024-3199
cert-bund: WID-SEC-2024-1913
cert-bund: WID-SEC-2024-1504
dfn-cert: DFN-CERT-2025-1898
dfn-cert: DFN-CERT-2025-1808
dfn-cert: DFN-CERT-2025-0974
dfn-cert: DFN-CERT-2025-0854
dfn-cert: DFN-CERT-2025-0170
dfn-cert: DFN-CERT-2024-2841
dfn-cert: DFN-CERT-2024-2787
dfn-cert: DFN-CERT-2024-2736
dfn-cert: DFN-CERT-2024-2342
dfn-cert: DFN-CERT-2024-2214
dfn-cert: DFN-CERT-2024-2201
dfn-cert: DFN-CERT-2024-2180
dfn-cert: DFN-CERT-2024-2110
dfn-cert: DFN-CERT-2024-2017
dfn-cert: DFN-CERT-2024-1963
dfn-cert: DFN-CERT-2024-1920
dfn-cert: DFN-CERT-2024-1919
dfn-cert: DFN-CERT-2024-1911
dfn-cert: DFN-CERT-2024-1907
dfn-cert: DFN-CERT-2024-1893
dfn-cert: DFN-CERT-2024-1816
dfn-cert: DFN-CERT-2024-1811
dfn-cert: DFN-CERT-2024-1784
dfn-cert: DFN-CERT-2024-1741

. . . continues on next page . . .

. . . continued from previous page . . .

dfn-cert: DFN-CERT-2024-1699

[return to 172.31.1.74]

2.1.2 High 80/tcp

High (CVSS: 7.5)
NVT: Apache HTTP Server < 2.4.59 Multiple Vulnerabilities - Linux

Product detection result
cpe:/a:apache:http_server:2.4.58
Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1
↪.0.117232)

Summary
Apache HTTP Server is prone to multiple vulnerabilities.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 2.4.58
Fixed version:     2.4.59
Installation
path / port:       80/tcp
```

Solution:
Solution type: VendorFix
Update to version 2.4.59 or later.

Affected Software/OS
Apache HTTP Server version 2.4.58 and prior.

Vulnerability Insight
The following vulnerabilities exist:
- CVE-2023-38709: HTTP response splitting
- CVE-2024-24795: HTTP response splitting in multiple modules
- CVE-2024-27316: HTTP/2 DoS by memory exhaustion on endless continuation frames

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: Apache HTTP Server < 2.4.59 Multiple Vulnerabilities - Linux
OID:1.3.6.1.4.1.25623.1.0.152039
Version used: 2024-06-07T05:05:42Z

. . . continues on next page . . .

. . . continued from previous page . . .

Product Detection Result
Product: cpe:/a:apache:http_server:2.4.58
Method: Apache HTTP Server Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.117232)

References
cve: CVE-2023-38709
cve: CVE-2024-24795
cve: CVE-2024-27316
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.59
url: https://kb.cert.org/vuls/id/421644
url: https://nowotarski.info/http2-continuation-flood/
url: https://nowotarski.info/http2-continuation-flood-technical-details/
cert-bund: WID-SEC-2025-1529
cert-bund: WID-SEC-2024-1725
cert-bund: WID-SEC-2024-1643
cert-bund: WID-SEC-2024-1642
cert-bund: WID-SEC-2024-1504
cert-bund: WID-SEC-2024-1248
cert-bund: WID-SEC-2024-1226
cert-bund: WID-SEC-2024-0801
cert-bund: WID-SEC-2024-0789
dfn-cert: DFN-CERT-2025-2802
dfn-cert: DFN-CERT-2025-2658
dfn-cert: DFN-CERT-2025-2657
dfn-cert: DFN-CERT-2024-2900
dfn-cert: DFN-CERT-2024-2534
dfn-cert: DFN-CERT-2024-2076
dfn-cert: DFN-CERT-2024-1958
dfn-cert: DFN-CERT-2024-1853
dfn-cert: DFN-CERT-2024-1749
dfn-cert: DFN-CERT-2024-1697
dfn-cert: DFN-CERT-2024-1411
dfn-cert: DFN-CERT-2024-1335
dfn-cert: DFN-CERT-2024-1238
dfn-cert: DFN-CERT-2024-1031
dfn-cert: DFN-CERT-2024-1010
dfn-cert: DFN-CERT-2024-0964
dfn-cert: DFN-CERT-2024-0901
dfn-cert: DFN-CERT-2024-0890

[return to 172.31.1.74]

2.1.3 High 25/tcp

High (CVSS: 7.5)
NVT: Diffie-Hellman Ephemeral Key Exchange DoS Vulnerability (SSL/TLS, D(HE)ater)

Product detection result

```
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.
↪802067)
```

Summary

The remote SSL/TLS server is supporting Diffie-Hellman ephemeral (DHE) Key Exchange algorithms and thus could be prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
'DHE' cipher suites accepted by this service via the TLSv1.0 protocol:
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
'DHE' cipher suites accepted by this service via the TLSv1.1 protocol:
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
'DHE' cipher suites accepted by this service via the TLSv1.2 protocol:
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_AES_128_CBC_SHA256
TLS_DHE_RSA_WITH_AES_128_CCM
TLS_DHE_RSA_WITH_AES_128_CCM_8
TLS_DHE_RSA_WITH_AES_128_GCM_SHA256
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_AES_256_CBC_SHA256
TLS_DHE_RSA_WITH_AES_256_CCM
TLS_DHE_RSA_WITH_AES_256_CCM_8
TLS_DHE_RSA_WITH_AES_256_GCM_SHA384
TLS_DHE_RSA_WITH_ARIA_128_GCM_SHA256
TLS_DHE_RSA_WITH_ARIA_256_GCM_SHA384
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA256
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA256
TLS_DHE_RSA_WITH_CHACHA20_POLY1305_SHA256
```

Impact

. . . continues on next page . . .

. . . continued from previous page . . .

This vulnerability allows remote attackers (from the client side) to send arbitrary numbers that are actually not public keys, and trigger expensive server-side DHE modular-exponentiation calculations, also known as a D(HE)ater attack.
There could be an increase in CPU usage in the affected component. For OpenSSH, users may observe issues such as a slowdown in SSH connections.

Solution:
Solution type: Mitigation
- DHE key exchange should be disabled if no other mitigation mechanism can be used and either elliptic-curve variant of Diffie-Hellman (ECDHE) or RSA key exchange is supported by the clients. The fact that RSA key exchange is not forward secret should be considered.
- Limit the maximum number of concurrent connections in e.g. the configuration of the remote server. For Postfix this limit can be configured via 'smtpd_client_new_tls_session_rate_limit' option, for other products please refer to the manual of the product in question on configuration possibilities.

Vulnerability Insight
- CVE-2002-20001: The Diffie-Hellman Key Agreement Protocol allows remote attackers (from the client side) to send arbitrary numbers that are actually not public keys, and trigger expensive server-side DHE modular-exponentiation calculations, aka a D(HE)ater attack. The client needs very little CPU resources and network bandwidth. The attack may be more disruptive in cases where a client can require a server to select its largest supported key size. The basic attack scenario is that the client must claim that it can only communicate with DHE, and the server must be configured to allow DHE.
- CVE-2022-40735: The Diffie-Hellman Key Agreement Protocol allows use of long exponents that arguably make certain calculations unnecessarily expensive, because the 1996 van Oorschot and Wiener paper found that '(appropriately) short exponents' can be used when there are adequate subgroup constraints, and these short exponents can lead to less expensive calculations than for long exponents. This issue is different from CVE-2002-20001 because it is based on an observation about exponent size, rather than an observation about numbers that are not public keys. The specific situations in which calculation expense would constitute a server-side vulnerability depend on the protocol (e.g., TLS, SSH, or IKE) and the DHE implementation details. In general, there might be an availability concern because of server-side resource consumption from DHE modular-exponentiation calculations. Finally, it is possible for an attacker to exploit this vulnerability and CVE-2002-20001 together.
- CVE-2024-41996: Validating the order of the public keys in the Diffie-Hellman Key Agreement Protocol, when an approved safe prime is used, allows remote attackers (from the client side) to trigger unnecessarily expensive server-side DHE modular-exponentiation calculations. The client may cause asymmetric resource consumption. The basic attack scenario is that the client must claim that it can only communicate with DHE, and the server must be configured to allow DHE and validate the order of the public key.

Vulnerability Detection Method
Checks the supported cipher suites of the remote SSL/TLS server.
Details: `Diffie-Hellman Ephemeral Key Exchange DoS Vulnerability (SSL/TLS, D(HE)ater)`
OID:1.3.6.1.4.1.25623.1.0.117840

. . . continues on next page . . .

. . . continued from previous page . . .

Version used: 2024-10-03T05:05:33Z

Product Detection Result
Product: cpe:/a:ietf:transport_layer_security
Method: SSL/TLS: Report Supported Cipher Suites
OID: 1.3.6.1.4.1.25623.1.0.802067)

References
cve: CVE-2002-20001
cve: CVE-2022-40735
cve: CVE-2024-41996
url: https://dheatattack.gitlab.io/
url: https://dheatattack.gitlab.io/details/
url: https://www.researchgate.net/profile/Anton-Stiglic-2/publication/2401745_Se
↪curity_Issues_in_the_Diffie-Hellman_Key_Agreement_Protocol
url: https://github.com/Balasys/dheater
url: https://github.com/c0r0n3r/dheater
cert-bund: WID-SEC-2024-3056
cert-bund: WID-SEC-2023-1886
cert-bund: WID-SEC-2023-1352
cert-bund: WID-SEC-2022-2251
cert-bund: WID-SEC-2022-2000
cert-bund: CB-K22/0224
cert-bund: CB-K21/1276
dfn-cert: DFN-CERT-2025-3324
dfn-cert: DFN-CERT-2024-2847
dfn-cert: DFN-CERT-2024-2578
dfn-cert: DFN-CERT-2024-1671
dfn-cert: DFN-CERT-2023-1697
dfn-cert: DFN-CERT-2023-1332
dfn-cert: DFN-CERT-2022-2147
dfn-cert: DFN-CERT-2022-0437
dfn-cert: DFN-CERT-2021-2622

[return to 172.31.1.74]

2.1.4 Medium 80/tcp

Medium (CVSS: 5.8)
NVT: Apache HTTP Server 2.4.7 - 2.4.65 Authentication Bypass Vulnerability - Linux

Product detection result
cpe:/a:apache:http_server:2.4.58
Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1
↪.0.117232)

. . . continues on next page . . .

. . . continued from previous page . . .

Summary
Apache HTTP Server is prone to an authentication bypass vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 2.4.58
Fixed version:     2.4.66
Installation
path / port:       80/tcp
```

Solution:
Solution type: VendorFix
Update to version 2.4.66 or later.

Affected Software/OS
Apache HTTP Server version 2.4.7 through 2.4.65.

Vulnerability Insight
mod_userdir+suexec bypass via AllowOverride FileInfo vulnerability in Apache HTTP Server. Users with access to use the RequestHeader directive in htaccess can cause some CGI scripts to run under an unexpected userid.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Apache HTTP Server 2.4.7 - 2.4.65 Authentication Bypass Vulnerability - Linux`
OID:1.3.6.1.4.1.25623.1.0.125567
Version used: `2025-12-05T05:44:55Z`

Product Detection Result
Product: `cpe:/a:apache:http_server:2.4.58`
Method: `Apache HTTP Server Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.117232)

References

```
cve: CVE-2025-66200
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.66
url: https://www.openwall.com/lists/oss-security/2025/12/04/8
cert-bund: WID-SEC-2025-2750
dfn-cert: DFN-CERT-2025-3602
dfn-cert: DFN-CERT-2025-3581
dfn-cert: DFN-CERT-2025-3512
dfn-cert: DFN-CERT-2025-3405
```

Medium (CVSS: 5.0)
NVT: Apache HTTP Server 2.4.17 < 2.4.64 DoS Vulnerability - Linux

Product detection result
`cpe:/a:apache:http_server:2.4.58`
`Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1`
`↪.0.117232)`

Summary
Apache HTTP Server is prone to a denial of service (DoS) vulnerability via HTTP/2.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
```
Installed version: 2.4.58
Fixed version:     2.4.64
Installation
path / port:       80/tcp
```

Solution:
Solution type: VendorFix
Update to version 2.4.64 or later.

Affected Software/OS
Apache HTTP Server version 2.4.17 through 2.4.63.

Vulnerability Insight
Late release of memory after effective lifetime vulnerability in Apache HTTP Server.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Apache HTTP Server 2.4.17 < 2.4.64 DoS Vulnerability - Linux`
OID:1.3.6.1.4.1.25623.1.0.154915
Version used: `2025-07-11T15:43:14Z`

Product Detection Result
Product: `cpe:/a:apache:http_server:2.4.58`
Method: `Apache HTTP Server Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.117232)

References
`cve: CVE-2025-53020`
`url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.64`
`cert-bund: WID-SEC-2025-1850`
`cert-bund: WID-SEC-2025-1529`

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2025-2182
dfn-cert: DFN-CERT-2025-1860
```

Medium (CVSS: 5.0)
NVT: Apache HTTP Server < 2.4.64 Multiple Vulnerabilities - Linux

Product detection result

```
cpe:/a:apache:http_server:2.4.58
Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1
↪.0.117232)
```

Summary

Apache HTTP Server is prone to multiple vulnerabilities.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 2.4.58
Fixed version:     2.4.64
Installation
path / port:       80/tcp
```

Solution:

Solution type: VendorFix

Update to version 2.4.64 or later.

Affected Software/OS

Apache HTTP Server version 2.4.63 and prior.

Vulnerability Insight

The following flaws exist:

- CVE-2024-42516: HTTP response splitting
- CVE-2024-43204: SSRF with mod_headers setting Content-Type header
- CVE-2024-47252: mod_ssl error log variable escaping
- CVE-2025-49812: mod_ssl TLS upgrade attack

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.

Details: `Apache HTTP Server < 2.4.64 Multiple Vulnerabilities - Linux`

OID:1.3.6.1.4.1.25623.1.0.154909

Version used: `2025-07-11T15:43:14Z`

Product Detection Result

Product: `cpe:/a:apache:http_server:2.4.58`

. . . continues on next page . . .

. . . continued from previous page . . .

Method: Apache HTTP Server Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.117232)

References

```
cve: CVE-2024-42516
cve: CVE-2024-43204
cve: CVE-2024-47252
cve: CVE-2025-49812
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.64
cert-bund: WID-SEC-2026-0162
cert-bund: WID-SEC-2025-1850
cert-bund: WID-SEC-2025-1529
dfn-cert: DFN-CERT-2026-0205
dfn-cert: DFN-CERT-2025-2421
dfn-cert: DFN-CERT-2025-2403
dfn-cert: DFN-CERT-2025-2402
dfn-cert: DFN-CERT-2025-2373
dfn-cert: DFN-CERT-2025-2231
dfn-cert: DFN-CERT-2025-2182
dfn-cert: DFN-CERT-2025-1917
dfn-cert: DFN-CERT-2025-1860
```

Medium (CVSS: 5.0)
NVT: Apache HTTP Server 2.4.35 < 2.4.64 Access Control Bypass Vulnerability - Linux

Product detection result

```
cpe:/a:apache:http_server:2.4.58
Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1
↪.0.117232)
```

Summary

Apache HTTP Server is prone to an access control bypass vulnerability in mod_ssl.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 2.4.58
Fixed version:     2.4.64
Installation
path / port:       80/tcp
```

Solution:
Solution type: VendorFix
Update to version 2.4.64 or later.

. . . continues on next page . . .

. . . continued from previous page . . .

Affected Software/OS
Apache HTTP Server version 2.4.35 through 2.4.63.

Vulnerability Insight
In some mod_ssl configurations an access control bypass by trusted clients is possible using TLS 1.3 session resumption.
Configurations are affected when mod_ssl is configured for multiple virtual hosts, with each restricted to a different set of trusted client certificates (for example with a different SSLCACertificateFile/Path setting). In such a case, a client trusted to access one virtual host may be able to access another virtual host, if SSLStrictSNIVHostCheck is not enabled in either virtual host.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Apache HTTP Server 2.4.35 < 2.4.64 Access Control Bypass Vulnerability - Linux`
OID:1.3.6.1.4.1.25623.1.0.154911
Version used: `2025-07-11T15:43:14Z`

Product Detection Result
Product: `cpe:/a:apache:http_server:2.4.58`
Method: `Apache HTTP Server Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.117232)

References
```
cve: CVE-2025-23048
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.64
cert-bund: WID-SEC-2026-0162
cert-bund: WID-SEC-2025-1850
cert-bund: WID-SEC-2025-1529
dfn-cert: DFN-CERT-2026-0205
dfn-cert: DFN-CERT-2025-2421
dfn-cert: DFN-CERT-2025-2373
dfn-cert: DFN-CERT-2025-2231
dfn-cert: DFN-CERT-2025-2182
dfn-cert: DFN-CERT-2025-1860
```

Medium (CVSS: 5.0)
NVT: Apache HTTP Server 2.4.26 < 2.4.64 DoS Vulnerability - Linux

Product detection result
```
cpe:/a:apache:http_server:2.4.58
Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1
↪.0.117232)
```

. . . continues on next page . . .

. . . continued from previous page . . .

Summary
Apache HTTP Server is prone to a denial of service (DoS) vulnerability in mod_proxy_http2.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 2.4.58
Fixed version:     2.4.64
Installation
path / port:       80/tcp
```

Solution:
Solution type: VendorFix
Update to version 2.4.64 or later.

Affected Software/OS
Apache HTTP Server version 2.4.26 through 2.4.63.

Vulnerability Insight
In certain proxy configurations, a denial of service attack against Apache HTTP Server can be triggered by untrusted clients causing an assertion in mod_proxy_http2.
Configurations affected are a reverse proxy is configured for an HTTP/2 backend, with ProxyPreserveHost set to 'on'.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Apache HTTP Server 2.4.26 < 2.4.64 DoS Vulnerability - Linux`
OID:1.3.6.1.4.1.25623.1.0.154913
Version used: `2025-07-11T15:43:14Z`

Product Detection Result
Product: `cpe:/a:apache:http_server:2.4.58`
Method: `Apache HTTP Server Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.117232)

References

```
cve: CVE-2025-49630
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.64
cert-bund: WID-SEC-2025-1850
cert-bund: WID-SEC-2025-1529
dfn-cert: DFN-CERT-2025-2421
dfn-cert: DFN-CERT-2025-2345
dfn-cert: DFN-CERT-2025-2231
dfn-cert: DFN-CERT-2025-2182
```

. . . continues on next page . . .

. . . continued from previous page . . .

dfn-cert: DFN-CERT-2025-1860

Medium (CVSS: 4.8)
NVT: Cleartext Transmission of Sensitive Information via HTTP

Summary
The host / application transmits sensitive information (username, passwords) in cleartext via HTTP.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The following URLs requires Basic Authentication (URL:realm name):
http://nagios.trabalho_vulnnet/:"Nagios Access"

Impact
An attacker could use this situation to compromise or eavesdrop on the HTTP communication between the client and the server using a man-in-the-middle attack to get access to sensitive data like usernames or passwords.

Solution:
Solution type: Workaround
Enforce the transmission of sensitive data via an encrypted SSL/TLS connection. Additionally make sure the host / application is redirecting all users to the secured SSL/TLS connection before allowing to input sensitive data into the mentioned functions.

Affected Software/OS
Hosts / applications which doesn't enforce the transmission of sensitive data via an encrypted SSL/TLS connection.

Vulnerability Detection Method
Evaluate previous collected information and check if the host / application is not enforcing the transmission of sensitive data via an encrypted SSL/TLS connection.
The script is currently checking the following:
- HTTP Basic Authentication (Basic Auth)
- HTTP Forms (e.g. Login) with input field of type 'password'
Details: Cleartext Transmission of Sensitive Information via HTTP
OID:1.3.6.1.4.1.25623.1.0.108440
Version used: 2023-09-07T05:05:21Z

References
url: https://www.owasp.org/index.php/Top_10_2013-A2-Broken_Authentication_and_Se
↪ssion_Management
url: https://www.owasp.org/index.php/Top_10_2013-A6-Sensitive_Data_Exposure
url: https://cwe.mitre.org/data/definitions/319.html

Medium (CVSS: 4.3)
NVT: Apache HTTP Server < 2.4.66 SSI Vulnerability - Linux

Product detection result
`cpe:/a:apache:http_server:2.4.58`
`Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1`
`↪.0.117232)`

Summary
Apache HTTP Server is prone to a Server Side Includes (SSI) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 2.4.58
Fixed version:     2.4.66
Installation
path / port:       80/tcp
```

Solution:
Solution type: VendorFix
Update to version 2.4.66 or later.

Affected Software/OS
Apache HTTP Server prior to version 2.4.66.

Vulnerability Insight
Apache HTTP Server with SSI enabled and mod_cgid (but not mod_cgi) passes the shell-escaped query string to #exec cmd='...' directives.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Apache HTTP Server < 2.4.66 SSI Vulnerability - Linux`
OID:1.3.6.1.4.1.25623.1.0.125564
Version used: `2025-12-05T05:44:55Z`

Product Detection Result
Product: `cpe:/a:apache:http_server:2.4.58`
Method: `Apache HTTP Server Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.117232)

References
`cve: CVE-2025-58098`
`url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.66`
`url: https://www.openwall.com/lists/oss-security/2025/12/04/5`

. . . continues on next page . . .

. . . continued from previous page . . .

```
cert-bund: WID-SEC-2026-0153
cert-bund: WID-SEC-2025-2750
dfn-cert: DFN-CERT-2026-0027
dfn-cert: DFN-CERT-2026-0012
dfn-cert: DFN-CERT-2025-3602
dfn-cert: DFN-CERT-2025-3581
dfn-cert: DFN-CERT-2025-3512
dfn-cert: DFN-CERT-2025-3405
```

Medium (CVSS: 4.3)
NVT: Apache HTTP Server 2.4.x < 2.4.66 Improper Neutralization Vulnerability - Linux

Product detection result

```
cpe:/a:apache:http_server:2.4.58
Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1
↪.0.117232)
```

Summary

Apache HTTP Server is prone to an improper neutralization vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 2.4.58
Fixed version:     2.4.66
Installation
path / port:       80/tcp
```

Solution:

Solution type: VendorFix

Update to version 2.4.66 or later.

Affected Software/OS

Apache HTTP Server version 2.4.x prior to 2.4.66.

Vulnerability Insight

Improper neutralization of escape, meta, or control sequences vulnerability in Apache HTTP Server through environment variables set via the Apache configuration unexpectedly superseding variables calculated by the server for CGI programs.

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.

Details: `Apache HTTP Server 2.4.x < 2.4.66 Improper Neutralization Vulnerability - Linux` OID:1.3.6.1.4.1.25623.1.0.125566

. . . continues on next page . . .

. . . continued from previous page . . .

Version used: 2025-12-05T05:44:55Z

Product Detection Result
Product: cpe:/a:apache:http_server:2.4.58
Method: Apache HTTP Server Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.117232)

References
cve: CVE-2025-65082
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.66
url: https://www.openwall.com/lists/oss-security/2025/12/04/7
cert-bund: WID-SEC-2026-0155
cert-bund: WID-SEC-2025-2750
dfn-cert: DFN-CERT-2026-0214
dfn-cert: DFN-CERT-2025-3602
dfn-cert: DFN-CERT-2025-3581
dfn-cert: DFN-CERT-2025-3512
dfn-cert: DFN-CERT-2025-3405

[return to 172.31.1.74]

2.1.5 Medium 25/tcp

Medium (CVSS: 5.0)
NVT: Check if Mailserver answer to VRFY and EXPN requests

Summary
The Mailserver on this host answers to VRFY and/or EXPN requests.

Quality of Detection (QoD): 99%

Vulnerability Detection Result
'VRFY root' produces the following answer: 252 2.0.0 root

Solution:
Solution type: Workaround
Disable VRFY and/or EXPN on your Mailserver.
For postfix add 'disable_vrfy_command=yes' in 'main.cf'.
For Sendmail add the option 'O PrivacyOptions=goaway'.
It is suggested that, if you really want to publish this type of information, you use a mechanism that legitimate users actually know about, such as Finger or HTTP.

Vulnerability Insight

. . . continues on next page . . .

. . . continued from previous page . . .

VRFY and EXPN ask the server for information about an address. They are inherently unusable through firewalls, gateways, mail exchangers for part-time hosts, etc.

Vulnerability Detection Method
Details: `Check if Mailserver answer to VRFY and EXPN requests`
OID:1.3.6.1.4.1.25623.1.0.100072
Version used: `2023-10-31T05:06:37Z`

References
`url: http://cr.yp.to/smtp/vrfy.html`

Medium (CVSS: 5.0)
NVT: SSL/TLS: Known Untrusted / Dangerous Certificate Authority (CA) Detection

Product detection result
```
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Collect and Report Certificate Details (OID: 1.3.6.1.4.1.25
↪623.1.0.103692)
```

Summary
The service is using an SSL/TLS certificate from a known untrusted and/or dangerous certificate authority (CA).

Quality of Detection (QoD): 99%

Vulnerability Detection Result
```
The certificate of the remote service is signed by the following untrusted and/o
↪r dangerous CA:
Issuer: CN=localhost
Certificate details:
fingerprint (SHA-1)              | B2076F80E55087522A5CCA24219C2CA82659A8C2
fingerprint (SHA-256)            | 75EB153B9F5EF4FED193F04A8A539B3BD36E3367B0F307
↪FF4BFF66CDCB326FA0
issued by                        | CN=localhost
public key algorithm             | RSA
public key size (bits)           | 2048
serial                           | 448A1CBCC086DFFFDA32AACF50E6290DD95BCCA3
signature algorithm              | sha256WithRSAEncryption
subject                          | CN=localhost
subject alternative names (SAN)  | localhost
valid from                       | 2024-11-06 09:32:47 UTC
valid until                      | 2034-11-04 09:32:47 UTC
```

Impact

. . . continues on next page . . .

. . . continued from previous page . . .

An attacker could use this for man-in-the-middle (MITM) attacks, accessing sensible data and other attacks.

Solution:
Solution type: Mitigation
Replace the SSL/TLS certificate with one signed by a trusted CA.

Vulnerability Detection Method
The script reads the certificate used by the target host and checks if it was signed by a known untrusted and/or dangerous CA.
Details: `SSL/TLS: Known Untrusted / Dangerous Certificate Authority (CA) Detection`
OID:1.3.6.1.4.1.25623.1.0.113054
Version used: `2024-06-14T05:05:48Z`

Product Detection Result
Product: `cpe:/a:ietf:transport_layer_security`
Method: `SSL/TLS: Collect and Report Certificate Details`
OID: 1.3.6.1.4.1.25623.1.0.103692)

Medium (CVSS: 4.3)
NVT: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection

Product detection result
`cpe:/a:ietf:transport_layer_security:1.0`
`Detected by SSL/TLS: Version Detection (OID: 1.3.6.1.4.1.25623.1.0.105782)`

Summary
It was possible to detect the usage of the deprecated TLSv1.0 and/or TLSv1.1 protocol on this system.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
`In addition to TLSv1.2+ the service is also providing the deprecated TLSv1.0 and`
`↪ TLSv1.1 protocols and supports one or more ciphers. Those supported ciphers c`
`↪an be found in the 'SSL/TLS: Report Supported Cipher Suites' (OID: 1.3.6.1.4.1`
`↪.25623.1.0.802067) VT.`

Impact
An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection.
Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.

. . . continues on next page . . .

. . . continued from previous page . . .

Solution:
Solution type: Mitigation
It is recommended to disable the deprecated TLSv1.0 and/or TLSv1.1 protocols in favor of the TLSv1.2+ protocols.
Please see the references for more resources supporting you with this task.

Affected Software/OS
- All services providing an encrypted communication using the TLSv1.0 and/or TLSv1.1 protocols
- CVE-2023-41928: Kiloview P1 4G and P2 4G Video Encoder
- CVE-2024-41270: Gorush v1.18.4
- CVE-2025-3200: Multiple products from Wiesemann & Theis

Vulnerability Insight
The TLSv1.0 and TLSv1.1 protocols contain known cryptographic flaws like:
- CVE-2011-3389: Browser Exploit Against SSL/TLS (BEAST)
- CVE-2015-0204: Factoring Attack on RSA-EXPORT Keys Padding Oracle On Downgraded Legacy Encryption (FREAK)

Vulnerability Detection Method
Checks the used TLS protocols of the services provided by this system.
Details: `SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection`
OID:1.3.6.1.4.1.25623.1.0.117274
Version used: `2025-04-30T05:39:51Z`

Product Detection Result
Product: `cpe:/a:ietf:transport_layer_security:1.0`
Method: `SSL/TLS: Version Detection`
OID: 1.3.6.1.4.1.25623.1.0.105782)

References
`cve: CVE-2011-3389`
`cve: CVE-2015-0204`
`cve: CVE-2023-41928`
`cve: CVE-2024-41270`
`cve: CVE-2025-3200`
`url: https://ssl-config.mozilla.org`
`url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidel`
`↪ines/TG02102/BSI-TR-02102-1.html`
`url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/`
`↪TLS-Protokoll/TLS-Protokoll_node.html`
`url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/Technisch`
`↪eRichtlinien/TR03116/BSI-TR-03116-4.html`
`url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindes`
`↪tstandard_BSI_TLS_Version_2_4.html`

. . . continues on next page . . .

. . . continued from previous page . . .

```
url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org
url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters
↪-report-2014
url: https://datatracker.ietf.org/doc/rfc8996/
url: https://vnhacker.blogspot.com/2011/09/beast.html
url: https://web.archive.org/web/20201108095603/https://censys.io/blog/freak
url: https://certvde.com/en/advisories/VDE-2025-031/
url: https://gist.github.com/nyxfqq/cfae38fada582a0f576d154be1aeb1fc
url: https://advisories.ncsc.nl/advisory?id=NCSC-2024-0273
cert-bund: WID-SEC-2026-0180
cert-bund: WID-SEC-2023-1435
cert-bund: CB-K18/0799
cert-bund: CB-K16/1289
cert-bund: CB-K16/1096
cert-bund: CB-K15/1751
cert-bund: CB-K15/1266
cert-bund: CB-K15/0850
cert-bund: CB-K15/0764
cert-bund: CB-K15/0720
cert-bund: CB-K15/0548
cert-bund: CB-K15/0526
cert-bund: CB-K15/0509
cert-bund: CB-K15/0493
cert-bund: CB-K15/0384
cert-bund: CB-K15/0365
cert-bund: CB-K15/0364
cert-bund: CB-K15/0302
cert-bund: CB-K15/0192
cert-bund: CB-K15/0079
cert-bund: CB-K15/0016
cert-bund: CB-K14/1342
cert-bund: CB-K14/0231
cert-bund: CB-K13/0845
cert-bund: CB-K13/0796
cert-bund: CB-K13/0790
dfn-cert: DFN-CERT-2020-0177
dfn-cert: DFN-CERT-2020-0111
dfn-cert: DFN-CERT-2019-0068
dfn-cert: DFN-CERT-2018-1441
dfn-cert: DFN-CERT-2018-1408
dfn-cert: DFN-CERT-2016-1372
dfn-cert: DFN-CERT-2016-1164
dfn-cert: DFN-CERT-2016-0388
dfn-cert: DFN-CERT-2015-1853
dfn-cert: DFN-CERT-2015-1332
dfn-cert: DFN-CERT-2015-0884
dfn-cert: DFN-CERT-2015-0800
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2015-0758
dfn-cert: DFN-CERT-2015-0567
dfn-cert: DFN-CERT-2015-0544
dfn-cert: DFN-CERT-2015-0530
dfn-cert: DFN-CERT-2015-0396
dfn-cert: DFN-CERT-2015-0375
dfn-cert: DFN-CERT-2015-0374
dfn-cert: DFN-CERT-2015-0305
dfn-cert: DFN-CERT-2015-0199
dfn-cert: DFN-CERT-2015-0079
dfn-cert: DFN-CERT-2015-0021
dfn-cert: DFN-CERT-2014-1414
dfn-cert: DFN-CERT-2013-1847
dfn-cert: DFN-CERT-2013-1792
dfn-cert: DFN-CERT-2012-1979
dfn-cert: DFN-CERT-2012-1829
dfn-cert: DFN-CERT-2012-1530
dfn-cert: DFN-CERT-2012-1380
dfn-cert: DFN-CERT-2012-1377
dfn-cert: DFN-CERT-2012-1292
dfn-cert: DFN-CERT-2012-1214
dfn-cert: DFN-CERT-2012-1213
dfn-cert: DFN-CERT-2012-1180
dfn-cert: DFN-CERT-2012-1156
dfn-cert: DFN-CERT-2012-1155
dfn-cert: DFN-CERT-2012-1039
dfn-cert: DFN-CERT-2012-0956
dfn-cert: DFN-CERT-2012-0908
dfn-cert: DFN-CERT-2012-0868
dfn-cert: DFN-CERT-2012-0867
dfn-cert: DFN-CERT-2012-0848
dfn-cert: DFN-CERT-2012-0838
dfn-cert: DFN-CERT-2012-0776
dfn-cert: DFN-CERT-2012-0722
dfn-cert: DFN-CERT-2012-0638
dfn-cert: DFN-CERT-2012-0627
dfn-cert: DFN-CERT-2012-0451
dfn-cert: DFN-CERT-2012-0418
dfn-cert: DFN-CERT-2012-0354
dfn-cert: DFN-CERT-2012-0234
dfn-cert: DFN-CERT-2012-0221
dfn-cert: DFN-CERT-2012-0177
dfn-cert: DFN-CERT-2012-0170
dfn-cert: DFN-CERT-2012-0146
dfn-cert: DFN-CERT-2012-0142
dfn-cert: DFN-CERT-2012-0126
dfn-cert: DFN-CERT-2012-0123
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2012-0095
dfn-cert: DFN-CERT-2012-0051
dfn-cert: DFN-CERT-2012-0047
dfn-cert: DFN-CERT-2012-0021
dfn-cert: DFN-CERT-2011-1953
dfn-cert: DFN-CERT-2011-1946
dfn-cert: DFN-CERT-2011-1844
dfn-cert: DFN-CERT-2011-1826
dfn-cert: DFN-CERT-2011-1774
dfn-cert: DFN-CERT-2011-1743
dfn-cert: DFN-CERT-2011-1738
dfn-cert: DFN-CERT-2011-1706
dfn-cert: DFN-CERT-2011-1628
dfn-cert: DFN-CERT-2011-1627
dfn-cert: DFN-CERT-2011-1619
dfn-cert: DFN-CERT-2011-1482
```

[return to 172.31.1.74]

2.1.6 Low 80/tcp

Low (CVSS: 2.6)
NVT: Apache HTTP Server 2.4.30 - 2.4.65 Integer Overflow Vulnerability - Linux

Product detection result

```
cpe:/a:apache:http_server:2.4.58
Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1
↪.0.117232)
```

Summary

Apache HTTP Server is prone to an integer overflow vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 2.4.58
Fixed version:     2.4.66
Installation
path / port:       80/tcp
```

Solution:

Solution type: VendorFix

Update to version 2.4.66 or later.

. . . continues on next page . . .

. . . continued from previous page . . .

Affected Software/OS
Apache HTTP Server version 2.4.30 through 2.4.65.

Vulnerability Insight
An integer overflow in the case of failed ACME certificate renewal leads, after a number of failures (30 days in default configurations), to the backoff timer becoming 0. Attempts to renew the certificate then are repeated without delays until it succeeds.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Apache HTTP Server 2.4.30 - 2.4.65 Integer Overflow Vulnerability - Linux`
OID:1.3.6.1.4.1.25623.1.0.125565
Version used: `2025-12-05T05:44:55Z`

Product Detection Result
Product: `cpe:/a:apache:http_server:2.4.58`
Method: `Apache HTTP Server Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.117232)

References
```
cve: CVE-2025-55753
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.66
url: https://www.openwall.com/lists/oss-security/2025/12/04/4
cert-bund: WID-SEC-2025-2750
dfn-cert: DFN-CERT-2026-0218
dfn-cert: DFN-CERT-2026-0012
dfn-cert: DFN-CERT-2025-3581
dfn-cert: DFN-CERT-2025-3415
dfn-cert: DFN-CERT-2025-3405
```

[return to 172.31.1.74]

2.1.7 Low general/icmp

Low (CVSS: 2.1)
NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`The following response / ICMP packet has been received:`

. . . continues on next page . . .

. . . continued from previous page . . .

```
- ICMP Type: 14
- ICMP Code: 0
```

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: `ICMP Timestamp Reply Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: `2025-01-21T05:37:33Z`

References
`cve: CVE-1999-0524`
`url: https://datatracker.ietf.org/doc/html/rfc792`
`url: https://datatracker.ietf.org/doc/html/rfc2780`
`cert-bund: CB-K15/1514`
`cert-bund: CB-K14/0632`
`dfn-cert: DFN-CERT-2014-0658`

[return to 172.31.1.74]

2.1.8 Low general/tcp

Low (CVSS: 2.6)
NVT: TCP Timestamps Information Disclosure

Summary
The remote host implements TCP timestamps and therefore allows to compute the uptime.

. . . continues on next page . . .

. . . continued from previous page . . .

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
It was detected that the host implements RFC1323/RFC7323.
The following timestamps were retrieved with a delay of 1 seconds in-between:
Packet 1: 538113654
Packet 2: 538114762
```

Impact

A side effect of this feature is that the uptime of the remote host can sometimes be computed.

Solution:

Solution type: Mitigation

To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.
To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.
The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.
See the references for more information.

Affected Software/OS

TCP implementations that implement RFC1323/RFC7323.

Vulnerability Insight

The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

Vulnerability Detection Method

Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.
Details: `TCP Timestamps Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.80091
Version used: `2023-12-15T16:10:08Z`

References

```
url: https://datatracker.ietf.org/doc/html/rfc1323
url: https://datatracker.ietf.org/doc/html/rfc7323
url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/d
↪ownload/details.aspx?id=9152
url: https://www.fortiguard.com/psirt/FG-IR-16-090
```

[return to 172.31.1.74]

2.1.9 Log 80/tcp

Log (CVSS: 0.0)
NVT: HTTP Server Banner Enumeration

Summary
This script tries to detect / enumerate different HTTP server banner (e.g. from a frontend, backend or proxy server) by sending various different HTTP requests (valid and invalid ones).

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
It was possible to enumerate the following HTTP server banner(s):
Server banner                  | Enumeration technique
--------------------------------------------------------------------------------
↪-----------------
Server: Apache/2.4.58 (Ubuntu) | Invalid HTTP 00.5 GET request (non-existent HTT
↪P version) to '/'
```

Solution:

Log Method
Details: HTTP Server Banner Enumeration
OID:1.3.6.1.4.1.25623.1.0.108708
Version used: 2025-01-31T15:39:24Z

Log (CVSS: 0.0)
NVT: HTTP Security Headers Detection

Summary
All known security headers are being checked on the remote web server.
On completion a report will hand back whether a specific security header has been implemented (including its value and if it is deprecated) or is missing on the target.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Missing Headers                   | More Information
--------------------------------------------------------------------------------
↪--------------------------------------------------------------------------------
↪-----------------------------------------------
Content-Security-Policy           | https://owasp.org/www-project-secure-headers
↪/#content-security-policy
Cross-Origin-Embedder-Policy      | https://scotthelme.co.uk/coop-and-coep/, Not
↪e: This is an upcoming header
Cross-Origin-Opener-Policy        | https://scotthelme.co.uk/coop-and-coep/, Not
↪e: This is an upcoming header
Cross-Origin-Resource-Policy      | https://scotthelme.co.uk/coop-and-coep/, Not
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
↪e: This is an upcoming header
Document-Policy                   | https://w3c.github.io/webappsec-feature-poli
↪cy/document-policy#document-policy-http-header
Feature-Policy                    | https://owasp.org/www-project-secure-headers
↪/#feature-policy, Note: The Feature Policy header has been renamed to Permissi
↪ons Policy
Permissions-Policy                | https://w3c.github.io/webappsec-feature-poli
↪cy/#permissions-policy-http-header-field
Referrer-Policy                   | https://owasp.org/www-project-secure-headers
↪/#referrer-policy
Sec-Fetch-Dest                    | https://developer.mozilla.org/en-US/docs/Web
↪/HTTP/Headers#fetch_metadata_request_headers, Note: This is a new header suppo
↪rted only in newer browsers like e.g. Firefox 90
Sec-Fetch-Mode                    | https://developer.mozilla.org/en-US/docs/Web
↪/HTTP/Headers#fetch_metadata_request_headers, Note: This is a new header suppo
↪rted only in newer browsers like e.g. Firefox 90
Sec-Fetch-Site                    | https://developer.mozilla.org/en-US/docs/Web
↪/HTTP/Headers#fetch_metadata_request_headers, Note: This is a new header suppo
↪rted only in newer browsers like e.g. Firefox 90
Sec-Fetch-User                    | https://developer.mozilla.org/en-US/docs/Web
↪/HTTP/Headers#fetch_metadata_request_headers, Note: This is a new header suppo
↪rted only in newer browsers like e.g. Firefox 90
X-Content-Type-Options            | https://owasp.org/www-project-secure-headers
↪/#x-content-type-options
X-Frame-Options                   | https://owasp.org/www-project-secure-headers
↪/#x-frame-options
X-Permitted-Cross-Domain-Policies | https://owasp.org/www-project-secure-headers
↪/#x-permitted-cross-domain-policies
X-XSS-Protection                  | https://owasp.org/www-project-secure-headers
↪/#x-xss-protection, Note: Most major browsers have dropped / deprecated suppor
↪t for this header in 2020.
```

Solution:

Log Method

Details: `HTTP Security Headers Detection`
OID:1.3.6.1.4.1.25623.1.0.112081
Version used: `2025-03-21T15:40:43Z`

References

```
url: https://owasp.org/www-project-secure-headers/
url: https://owasp.org/www-project-secure-headers/#div-headers
url: https://securityheaders.com/
```

Log (CVSS: 0.0)
NVT: Services

Summary
This plugin performs service detection.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`A web server is running on this port`

Solution:

Vulnerability Insight
This plugin attempts to guess which service is running on the remote port(s). For instance, it searches for a web server which could listen on another port than 80 or 443 and makes this information available for other check routines.

Log Method
Details: `Services`
OID:1.3.6.1.4.1.25623.1.0.10330
Version used: `2025-03-05T05:38:53Z`

Log (CVSS: 0.0)
NVT: Nagios / Nagios Core Detection (HTTP)

Summary
HTTP based detection of Nagios / Nagios Core.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Detected Nagios / Nagios Core
Version:       unknown
Location:      /nagios
CPE:           cpe:/a:nagios:nagios
Concluded from version/product identification result:
Basic realm="Nagios
```

Solution:

Log Method
Details: `Nagios / Nagios Core Detection (HTTP)`
OID:1.3.6.1.4.1.25623.1.0.100186
Version used: `2025-09-11T05:38:37Z`

Log (CVSS: 0.0)
NVT: Web Application Scanning Consolidation / Info Reporting

Summary
The script consolidates and reports various information for web application (formerly called 'CGI') scanning.
This information is based on the following scripts / settings:
- HTTP-Version Detection (OID: 1.3.6.1.4.1.25623.1.0.100034)
- No 404 check (OID: 1.3.6.1.4.1.25623.1.0.10386)
- Web mirroring / webmirror.nasl (OID: 1.3.6.1.4.1.25623.1.0.10662)
- Directory Scanner / DDI_Directory_Scanner.nasl (OID: 1.3.6.1.4.1.25623.1.0.11032)
- The configured 'cgi_path' within the 'Scanner Preferences' of the scan config in use
- The configured 'Enable CGI scanning', 'Enable generic web application scanning' and 'Add historic /scripts and /cgi-bin to directories for CGI scanning' within the 'Global variable settings' of the scan config in use
If you think any of this information is wrong please report it to the referenced community forum.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The Hostname/IP "nagios.trabalho_vulnnet" was used to access the remote host.
Generic web application scanning is disabled for this host via the "Enable gener
↪ic web application scanning" option within the "Global variable settings" of t
↪he scan config in use.
Requests to this service are done via HTTP/1.1.
This service seems to be able to host PHP scripts.
This service seems to be able to host ASP scripts.
The User-Agent "Mozilla/5.0 [en] (X11, U; OpenVAS-VT <version replaced>)" was us
↪ed to access the remote host.
Historic /scripts and /cgi-bin are not added to the directories used for web app
↪lication scanning. You can enable this again with the "Add historic /scripts a
↪nd /cgi-bin to directories for CGI scanning" option within the "Global variabl
↪e settings" of the scan config in use.
The following files/directories require authentication and are tested (if enable
↪d) by the script "HTTP Brute Force Logins With Default Credentials (OID: 1.3.6
↪.1.4.1.25623.1.0.108041)":
http://nagios.trabalho_vulnnet/
The following directories were used for web application scanning:
http://nagios.trabalho_vulnnet/
While this is not, in and of itself, a bug, you should manually inspect these di
↪rectories to ensure that they are in compliance with company security standard
↪s
The following directories were excluded from web application scanning because th
↪e "Regex pattern to exclude directories from CGI scanning" setting of the VT "
↪Global variable settings" (OID: 1.3.6.1.4.1.25623.1.0.12288) for this scan was
↪: "/(index\.php|image|img|css|js$|js/|javascript|style|theme|icon|jquery|graph
↪ic|grafik|picture|bilder|thumbnail|media/|skins?/)"
http://nagios.trabalho_vulnnet/icons
```

. . . continues on next page . . .

. . . continued from previous page . . .

`http://nagios.trabalho_vulnnet/javascript`

Solution:

Log Method
Details: `Web Application Scanning Consolidation / Info Reporting`
OID:1.3.6.1.4.1.25623.1.0.111038
Version used: `2026-01-13T05:47:36Z`

References
`url: https://forum.greenbone.net/c/vulnerability-tests/7`

Log (CVSS: 0.0)
NVT: HTTP Server type and version

Summary
This script detects and reports the HTTP Server's banner which might provide the type and version of it.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The remote HTTP Server banner is:
Server: Apache/2.4.58 (Ubuntu)
```

Solution:

Log Method
Details: `HTTP Server type and version`
OID:1.3.6.1.4.1.25623.1.0.10107
Version used: `2023-08-01T13:29:10Z`

[return to 172.31.1.74]

2.1.10 Log general/tcp

Log (CVSS: 0.0)
NVT: Hostname Determination Reporting

Summary
The script reports information on how the hostname of the target was determined.

. . . continues on next page . . .

. . . continued from previous page . . .

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Hostname determination for IP 172.31.1.74:
Hostname|Source
nagios.trabalho_vulnnet|Reverse-DNS
```

Solution:

Log Method

Details: `Hostname Determination Reporting`
OID:1.3.6.1.4.1.25623.1.0.108449
Version used: `2022-07-27T10:11:28Z`

Log (CVSS: 0.0)
NVT: Apache HTTP Server Detection Consolidation

Summary

Consolidation of Apache HTTP Server detections.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Detected Apache HTTP Server
Version:       2.4.58
Location:      80/tcp
CPE:           cpe:/a:apache:http_server:2.4.58
Concluded from version/product identification result:
Server: Apache/2.4.58 (Ubuntu)
```

Solution:

Log Method

Details: `Apache HTTP Server Detection Consolidation`
OID:1.3.6.1.4.1.25623.1.0.117232
Version used: `2024-03-08T15:37:10Z`

References

`url: https://httpd.apache.org`

Log (CVSS: 0.0)
NVT: OS Detection Consolidation and Reporting

Summary
This script consolidates the OS information detected by several VTs and tries to find the best matching OS.
Furthermore it reports all previously collected information leading to this best matching OS. It also reports possible additional information which might help to improve the OS detection.
If any of this information is wrong or could be improved please consider to report these to the referenced community forum.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Best matching OS:
OS:           Ubuntu 24.04
Version:      24.04
CPE:          cpe:/o:canonical:ubuntu_linux:24.04
Found by VT:  1.3.6.1.4.1.25623.1.0.111067 (Operating System (OS) Detection (HTT
↪P))
Concluded from HTTP Server banner on port 80/tcp: Server: Apache/2.4.58 (Ubuntu)
Setting key "Host/runs_unixoide" based on this information
Other OS detections (in order of reliability):
OS:           Ubuntu
CPE:          cpe:/o:canonical:ubuntu_linux
Found by VT:  1.3.6.1.4.1.25623.1.0.111068 (Operating System (OS) Detection (SMT
↪P/POP3/IMAP))
Concluded from SMTP banner on port 25/tcp: 220 e98d4d9bfcb6 ESMTP Postfix (Ubunt
↪u)
```

Solution:

Log Method
Details: `OS Detection Consolidation and Reporting`
OID:1.3.6.1.4.1.25623.1.0.105937
Version used: `2026-01-21T05:50:46Z`

References
`url: https://forum.greenbone.net/c/vulnerability-tests/7`

Log (CVSS: 0.0)
NVT: IP Forwarding Enabled - Active Check

Summary
Checks if the remote host has IP forwarding enabled.

. . . continues on next page . . .

. . . continued from previous page . . .

Quality of Detection (QoD): 70%

Vulnerability Detection Result

```
It was possible to route a TCP packet through the target host and received an an
↪swer which means IP forwarding is enabled.
```

Solution:

Log Method

Sends a crafted Local Link Layer (LLL) frame and checks the response.
Details: `IP Forwarding Enabled - Active Check`
OID:1.3.6.1.4.1.25623.1.0.147205
Version used: `2021-12-03T08:27:06Z`

References

`cve: CVE-1999-0511`

Log (CVSS: 0.0)
NVT: Traceroute

Summary

Collect information about the network route and network distance between the scanner host and the target host.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Network route from scanner (172.30.0.2) to target (172.31.1.74):
172.30.0.2
172.31.1.74
Network distance between scanner and target: 2
```

Solution:

Vulnerability Insight

For internal networks, the distances are usually small, often less than 4 hosts between scanner and target. For public targets the distance is greater and might be 10 hosts or more.

Log Method

A combination of the protocols ICMP and TCP is used to determine the route. This method is applicable for IPv4 only and it is also known as 'traceroute'.
Details: `Traceroute`
OID:1.3.6.1.4.1.25623.1.0.51662
Version used: `2022-10-17T11:13:19Z`

[return to 172.31.1.74]

2.1.11 Log general/CPE-T

Log (CVSS: 0.0)
NVT: CPE Inventory

Summary
This routine uses information collected by other routines about CPE identities of operating systems, services and applications detected during the scan.
Note: Some CPEs for specific products might show up twice or more in the output. Background: After a product got renamed or a specific vendor was acquired by another one it might happen that a product gets a new CPE within the NVD CPE Dictionary but older entries are kept with the older CPE.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
172.31.1.74|cpe:/a:apache:http_server:2.4.58
172.31.1.74|cpe:/a:ietf:transport_layer_security:1.0
172.31.1.74|cpe:/a:ietf:transport_layer_security:1.1
172.31.1.74|cpe:/a:ietf:transport_layer_security:1.2
172.31.1.74|cpe:/a:ietf:transport_layer_security:1.3
172.31.1.74|cpe:/a:nagios:nagios
172.31.1.74|cpe:/a:postfix:postfix
172.31.1.74|cpe:/o:canonical:ubuntu_linux:24.04
```

Solution:

Log Method
Details: `CPE Inventory`
OID:1.3.6.1.4.1.25623.1.0.810002
Version used: `2022-07-27T10:11:28Z`

References
`url: https://nvd.nist.gov/products/cpe`

[return to 172.31.1.74]

2.1.12 Log 25/tcp

Log (CVSS: 0.0)
NVT: SSL/TLS: Untrusted Certificate Detection

. . . continues on next page . . .

. . . continued from previous page . . .

Summary
Checks and reports if a remote SSL/TLS service is using a certificate which is untrusted / the verification against the system wide trust store has failed.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
```
The remote SSL/TLS server is using the following certificate(s) which failed the
↪ verification against the system wide trust store (serial:issuer):
448A1CBCC086DFFFDA32AACF50E6290DD95BCCA3:CN=localhost (Server certificate)
```

Solution:

Log Method
Details: `SSL/TLS: Untrusted Certificate Detection`
OID:1.3.6.1.4.1.25623.1.0.117764
Version used: `2024-09-27T05:05:23Z`

Log (CVSS: 0.0)
NVT: SSL/TLS: Report Supported Cipher Suites

Summary
This routine reports all SSL/TLS cipher suites accepted by a service.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
```
'Strong' cipher suites accepted by this service via the TLSv1.0 protocol:
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_DH_anon_WITH_AES_256_CBC_SHA
'Medium' cipher suites accepted by this service via the TLSv1.0 protocol:
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_DH_anon_WITH_AES_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_ECDH_anon_WITH_AES_128_CBC_SHA
TLS_ECDH_anon_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_RSA_WITH_CAMELLIA_256_CBC_SHA
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
No 'Weak' cipher suites accepted by this service via the TLSv1.0 protocol.
No 'Null' cipher suites accepted by this service via the TLSv1.0 protocol.
'Anonymous' cipher suites accepted by this service via the TLSv1.0 protocol:
TLS_DH_anon_WITH_AES_128_CBC_SHA
TLS_DH_anon_WITH_AES_256_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA
TLS_ECDH_anon_WITH_AES_128_CBC_SHA
TLS_ECDH_anon_WITH_AES_256_CBC_SHA
'Strong' cipher suites accepted by this service via the TLSv1.1 protocol:
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_DH_anon_WITH_AES_256_CBC_SHA
'Medium' cipher suites accepted by this service via the TLSv1.1 protocol:
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_DH_anon_WITH_AES_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_ECDH_anon_WITH_AES_128_CBC_SHA
TLS_ECDH_anon_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_RSA_WITH_CAMELLIA_256_CBC_SHA
No 'Weak' cipher suites accepted by this service via the TLSv1.1 protocol.
No 'Null' cipher suites accepted by this service via the TLSv1.1 protocol.
'Anonymous' cipher suites accepted by this service via the TLSv1.1 protocol:
TLS_DH_anon_WITH_AES_128_CBC_SHA
TLS_DH_anon_WITH_AES_256_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA
TLS_ECDH_anon_WITH_AES_128_CBC_SHA
TLS_ECDH_anon_WITH_AES_256_CBC_SHA
'Strong' cipher suites accepted by this service via the TLSv1.2 protocol:
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_CHACHA20_POLY1305_SHA256
TLS_DH_anon_WITH_AES_256_CBC_SHA
TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305_SHA256
'Medium' cipher suites accepted by this service via the TLSv1.2 protocol:
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_AES_128_CBC_SHA256
TLS_DHE_RSA_WITH_AES_128_CCM
TLS_DHE_RSA_WITH_AES_128_CCM_8
TLS_DHE_RSA_WITH_AES_128_GCM_SHA256
```

. . . continues on next page . . .

. . . continued from previous page . . .

TLS_DHE_RSA_WITH_AES_256_CBC_SHA256
TLS_DHE_RSA_WITH_AES_256_CCM
TLS_DHE_RSA_WITH_AES_256_CCM_8
TLS_DHE_RSA_WITH_AES_256_GCM_SHA384
TLS_DHE_RSA_WITH_ARIA_128_GCM_SHA256
TLS_DHE_RSA_WITH_ARIA_256_GCM_SHA384
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA256
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA256
TLS_DH_anon_WITH_AES_128_CBC_SHA
TLS_DH_anon_WITH_AES_128_CBC_SHA256
TLS_DH_anon_WITH_AES_128_GCM_SHA256
TLS_DH_anon_WITH_AES_256_CBC_SHA256
TLS_DH_anon_WITH_AES_256_GCM_SHA384
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA256
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA256
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_ARIA_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_ARIA_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_CAMELLIA_128_CBC_SHA256
TLS_ECDHE_RSA_WITH_CAMELLIA_256_CBC_SHA384
TLS_ECDH_anon_WITH_AES_128_CBC_SHA
TLS_ECDH_anon_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA256
TLS_RSA_WITH_AES_128_CCM
TLS_RSA_WITH_AES_128_CCM_8
TLS_RSA_WITH_AES_128_GCM_SHA256
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA256
TLS_RSA_WITH_AES_256_CCM
TLS_RSA_WITH_AES_256_CCM_8
TLS_RSA_WITH_AES_256_GCM_SHA384
TLS_RSA_WITH_ARIA_128_GCM_SHA256
TLS_RSA_WITH_ARIA_256_GCM_SHA384
TLS_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_RSA_WITH_CAMELLIA_128_CBC_SHA256
TLS_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_RSA_WITH_CAMELLIA_256_CBC_SHA256

. . . continues on next page . . .

. . . continued from previous page . . .

```
No 'Weak' cipher suites accepted by this service via the TLSv1.2 protocol.
No 'Null' cipher suites accepted by this service via the TLSv1.2 protocol.
'Anonymous' cipher suites accepted by this service via the TLSv1.2 protocol:
TLS_DH_anon_WITH_AES_128_CBC_SHA
TLS_DH_anon_WITH_AES_128_CBC_SHA256
TLS_DH_anon_WITH_AES_128_GCM_SHA256
TLS_DH_anon_WITH_AES_256_CBC_SHA
TLS_DH_anon_WITH_AES_256_CBC_SHA256
TLS_DH_anon_WITH_AES_256_GCM_SHA384
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA256
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA256
TLS_ECDH_anon_WITH_AES_128_CBC_SHA
TLS_ECDH_anon_WITH_AES_256_CBC_SHA
'Strong' cipher suites accepted by this service via the TLSv1.3 protocol:
TLS_AES_256_GCM_SHA384
TLS_CHACHA20_POLY1305_SHA256
'Medium' cipher suites accepted by this service via the TLSv1.3 protocol:
TLS_AES_128_GCM_SHA256
No 'Weak' cipher suites accepted by this service via the TLSv1.3 protocol.
No 'Null' cipher suites accepted by this service via the TLSv1.3 protocol.
No 'Anonymous' cipher suites accepted by this service via the TLSv1.3 protocol.
```

Solution:

Vulnerability Insight
Notes:
- As the VT 'SSL/TLS: Check Supported Cipher Suites' (OID: 1.3.6.1.4.1.25623.1.0.900234) might run into a timeout the actual reporting of all accepted cipher suites takes place in this VT instead.
- SSLv2 ciphers are not getting reported as the protocol itself is deprecated, needs to be considered as weak and is reported separately as deprecated.

Log Method
Details: `SSL/TLS: Report Supported Cipher Suites`
OID:1.3.6.1.4.1.25623.1.0.802067
Version used: `2024-09-27T05:05:23Z`

Log (CVSS: 0.0)
NVT: SSL/TLS: Report Non Weak Cipher Suites

Product detection result
`cpe:/a:ietf:transport_layer_security`
`Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.`

. . . continues on next page . . .

. . . continued from previous page . . .

↪802067)

Summary
This routine reports all Non Weak SSL/TLS cipher suites accepted by a service.

Quality of Detection (QoD): 98%

Vulnerability Detection Result

```
'Non Weak' cipher suites accepted by this service via the TLSv1.0 protocol:
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_DH_anon_WITH_AES_128_CBC_SHA
TLS_DH_anon_WITH_AES_256_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_ECDH_anon_WITH_AES_128_CBC_SHA
TLS_ECDH_anon_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_RSA_WITH_CAMELLIA_256_CBC_SHA
'Non Weak' cipher suites accepted by this service via the TLSv1.1 protocol:
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_DH_anon_WITH_AES_128_CBC_SHA
TLS_DH_anon_WITH_AES_256_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_ECDH_anon_WITH_AES_128_CBC_SHA
TLS_ECDH_anon_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_RSA_WITH_CAMELLIA_256_CBC_SHA
'Non Weak' cipher suites accepted by this service via the TLSv1.2 protocol:
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_AES_128_CBC_SHA256
TLS_DHE_RSA_WITH_AES_128_CCM
```

. . . continues on next page . . .

. . . continued from previous page . . .

TLS_DHE_RSA_WITH_AES_128_CCM_8
TLS_DHE_RSA_WITH_AES_128_GCM_SHA256
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_AES_256_CBC_SHA256
TLS_DHE_RSA_WITH_AES_256_CCM
TLS_DHE_RSA_WITH_AES_256_CCM_8
TLS_DHE_RSA_WITH_AES_256_GCM_SHA384
TLS_DHE_RSA_WITH_ARIA_128_GCM_SHA256
TLS_DHE_RSA_WITH_ARIA_256_GCM_SHA384
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA256
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA256
TLS_DHE_RSA_WITH_CHACHA20_POLY1305_SHA256
TLS_DH_anon_WITH_AES_128_CBC_SHA
TLS_DH_anon_WITH_AES_128_CBC_SHA256
TLS_DH_anon_WITH_AES_128_GCM_SHA256
TLS_DH_anon_WITH_AES_256_CBC_SHA
TLS_DH_anon_WITH_AES_256_CBC_SHA256
TLS_DH_anon_WITH_AES_256_GCM_SHA384
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA256
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA256
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_ARIA_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_ARIA_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_CAMELLIA_128_CBC_SHA256
TLS_ECDHE_RSA_WITH_CAMELLIA_256_CBC_SHA384
TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305_SHA256
TLS_ECDH_anon_WITH_AES_128_CBC_SHA
TLS_ECDH_anon_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA256
TLS_RSA_WITH_AES_128_CCM
TLS_RSA_WITH_AES_128_CCM_8
TLS_RSA_WITH_AES_128_GCM_SHA256
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA256
TLS_RSA_WITH_AES_256_CCM
TLS_RSA_WITH_AES_256_CCM_8
TLS_RSA_WITH_AES_256_GCM_SHA384

. . . continues on next page . . .

. . . continued from previous page . . .

```
TLS_RSA_WITH_ARIA_128_GCM_SHA256
TLS_RSA_WITH_ARIA_256_GCM_SHA384
TLS_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_RSA_WITH_CAMELLIA_128_CBC_SHA256
TLS_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_RSA_WITH_CAMELLIA_256_CBC_SHA256
'Non Weak' cipher suites accepted by this service via the TLSv1.3 protocol:
TLS_AES_128_GCM_SHA256
TLS_AES_256_GCM_SHA384
TLS_CHACHA20_POLY1305_SHA256
```

Solution:

Log Method
Details: `SSL/TLS: Report Non Weak Cipher Suites`
OID:1.3.6.1.4.1.25623.1.0.103441
Version used: `2024-09-27T05:05:23Z`

Product Detection Result
Product: `cpe:/a:ietf:transport_layer_security`
Method: `SSL/TLS: Report Supported Cipher Suites`
OID: 1.3.6.1.4.1.25623.1.0.802067)

Log (CVSS: 0.0)
NVT: SSL/TLS: Report Medium Cipher Suites

Product detection result

```
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.
↪802067)
```

Summary
This routine reports all Medium SSL/TLS cipher suites accepted by a service.

Quality of Detection (QoD): 98%

Vulnerability Detection Result

```
'Medium' cipher suites accepted by this service via the TLSv1.0 protocol:
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_DH_anon_WITH_AES_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_ECDH_anon_WITH_AES_128_CBC_SHA
TLS_ECDH_anon_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_RSA_WITH_CAMELLIA_256_CBC_SHA
'Medium' cipher suites accepted by this service via the TLSv1.1 protocol:
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_DH_anon_WITH_AES_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_ECDH_anon_WITH_AES_128_CBC_SHA
TLS_ECDH_anon_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_RSA_WITH_CAMELLIA_256_CBC_SHA
'Medium' cipher suites accepted by this service via the TLSv1.2 protocol:
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_AES_128_CBC_SHA256
TLS_DHE_RSA_WITH_AES_128_CCM
TLS_DHE_RSA_WITH_AES_128_CCM_8
TLS_DHE_RSA_WITH_AES_128_GCM_SHA256
TLS_DHE_RSA_WITH_AES_256_CBC_SHA256
TLS_DHE_RSA_WITH_AES_256_CCM
TLS_DHE_RSA_WITH_AES_256_CCM_8
TLS_DHE_RSA_WITH_AES_256_GCM_SHA384
TLS_DHE_RSA_WITH_ARIA_128_GCM_SHA256
TLS_DHE_RSA_WITH_ARIA_256_GCM_SHA384
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA256
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA256
TLS_DH_anon_WITH_AES_128_CBC_SHA
TLS_DH_anon_WITH_AES_128_CBC_SHA256
TLS_DH_anon_WITH_AES_128_GCM_SHA256
TLS_DH_anon_WITH_AES_256_CBC_SHA256
TLS_DH_anon_WITH_AES_256_GCM_SHA384
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA
TLS_DH_anon_WITH_CAMELLIA_128_CBC_SHA256
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
TLS_DH_anon_WITH_CAMELLIA_256_CBC_SHA256
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_ARIA_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_ARIA_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_CAMELLIA_128_CBC_SHA256
TLS_ECDHE_RSA_WITH_CAMELLIA_256_CBC_SHA384
TLS_ECDH_anon_WITH_AES_128_CBC_SHA
TLS_ECDH_anon_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA256
TLS_RSA_WITH_AES_128_CCM
TLS_RSA_WITH_AES_128_CCM_8
TLS_RSA_WITH_AES_128_GCM_SHA256
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA256
TLS_RSA_WITH_AES_256_CCM
TLS_RSA_WITH_AES_256_CCM_8
TLS_RSA_WITH_AES_256_GCM_SHA384
TLS_RSA_WITH_ARIA_128_GCM_SHA256
TLS_RSA_WITH_ARIA_256_GCM_SHA384
TLS_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_RSA_WITH_CAMELLIA_128_CBC_SHA256
TLS_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_RSA_WITH_CAMELLIA_256_CBC_SHA256
'Medium' cipher suites accepted by this service via the TLSv1.3 protocol:
TLS_AES_128_GCM_SHA256
```

Solution:

Vulnerability Insight
Any cipher suite considered to be secure for only the next 10 years is considered as medium.

Log Method
Details: `SSL/TLS: Report Medium Cipher Suites`
OID:1.3.6.1.4.1.25623.1.0.902816
Version used: `2024-09-27T05:05:23Z`

Product Detection Result
Product: `cpe:/a:ietf:transport_layer_security`
Method: `SSL/TLS: Report Supported Cipher Suites`
OID: 1.3.6.1.4.1.25623.1.0.802067)

Log (CVSS: 0.0)
NVT: SSL/TLS: Report Perfect Forward Secrecy (PFS) Cipher Suites

Product detection result

```
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.
↪802067)
```

Summary

This routine reports all SSL/TLS cipher suites accepted by a service which are supporting Perfect Forward Secrecy (PFS).

Quality of Detection (QoD): 98%

Vulnerability Detection Result

```
Cipher suites supporting Perfect Forward Secrecy (PFS) are accepted by this serv
↪ice via the TLSv1.0 protocol:
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
Cipher suites supporting Perfect Forward Secrecy (PFS) are accepted by this serv
↪ice via the TLSv1.1 protocol:
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
Cipher suites supporting Perfect Forward Secrecy (PFS) are accepted by this serv
↪ice via the TLSv1.2 protocol:
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_AES_128_CBC_SHA256
TLS_DHE_RSA_WITH_AES_128_CCM
TLS_DHE_RSA_WITH_AES_128_CCM_8
TLS_DHE_RSA_WITH_AES_128_GCM_SHA256
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_AES_256_CBC_SHA256
TLS_DHE_RSA_WITH_AES_256_CCM
TLS_DHE_RSA_WITH_AES_256_CCM_8
TLS_DHE_RSA_WITH_AES_256_GCM_SHA384
TLS_DHE_RSA_WITH_ARIA_128_GCM_SHA256
TLS_DHE_RSA_WITH_ARIA_256_GCM_SHA384
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA256
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA256
TLS_DHE_RSA_WITH_CHACHA20_POLY1305_SHA256
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_ARIA_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_ARIA_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_CAMELLIA_128_CBC_SHA256
TLS_ECDHE_RSA_WITH_CAMELLIA_256_CBC_SHA384
TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305_SHA256
Cipher suites supporting Perfect Forward Secrecy (PFS) are accepted by this serv
↪ice via the TLSv1.3 protocol:
TLS_AES_128_GCM_SHA256
TLS_AES_256_GCM_SHA384
TLS_CHACHA20_POLY1305_SHA256
```

Solution:

Log Method
Details: `SSL/TLS: Report Perfect Forward Secrecy (PFS) Cipher Suites`
OID:1.3.6.1.4.1.25623.1.0.105018
Version used: `2024-09-30T08:38:05Z`

Product Detection Result
Product: `cpe:/a:ietf:transport_layer_security`
Method: `SSL/TLS: Report Supported Cipher Suites`
OID: 1.3.6.1.4.1.25623.1.0.802067)

Log (CVSS: 0.0)
NVT: SSL/TLS: Certificate - Self-Signed Certificate Detection

Product detection result
`cpe:/a:ietf:transport_layer_security`
`Detected by SSL/TLS: Collect and Report Certificate Details (OID: 1.3.6.1.4.1.25`
`↪623.1.0.103692)`

Summary
The SSL/TLS certificate on this port is self-signed.

Quality of Detection (QoD): 98%

. . . continues on next page . . .

. . . continued from previous page . . .

Vulnerability Detection Result

```
The certificate of the remote service is self signed.
Certificate details:
fingerprint (SHA-1)             | B2076F80E55087522A5CCA24219C2CA82659A8C2
fingerprint (SHA-256)           | 75EB153B9F5EF4FED193F04A8A539B3BD36E3367B0F307
↪FF4BFF66CDCB326FA0
issued by                       | CN=localhost
public key algorithm            | RSA
public key size (bits)          | 2048
serial                          | 448A1CBCC086DFFFDA32AACF50E6290DD95BCCA3
signature algorithm             | sha256WithRSAEncryption
subject                         | CN=localhost
subject alternative names (SAN) | localhost
valid from                      | 2024-11-06 09:32:47 UTC
valid until                     | 2034-11-04 09:32:47 UTC
```

Solution:

Log Method

Detects and reports if the issuer's distinguished name of the certificate is exactly the same as the subject's distinguished name.
Details: `SSL/TLS: Certificate - Self-Signed Certificate Detection`
OID:1.3.6.1.4.1.25623.1.0.103140
Version used: `2025-07-15T05:43:27Z`

Product Detection Result

Product: `cpe:/a:ietf:transport_layer_security`
Method: `SSL/TLS: Collect and Report Certificate Details`
OID: 1.3.6.1.4.1.25623.1.0.103692)

References

```
url: http://en.wikipedia.org/wiki/Self-signed_certificate
url: https://datatracker.ietf.org/doc/html/rfc5280#appendix-C.1
```

Log (CVSS: 0.0)
NVT: SSL/TLS: Certificate - Subject Common Name Does Not Match Server FQDN

Product detection result

```
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Collect and Report Certificate Details (OID: 1.3.6.1.4.1.25
↪623.1.0.103692)
```

. . . continues on next page . . .

. . . continued from previous page . . .

Summary
The SSL/TLS certificate contains a common name (CN) that does not match the hostname.

Quality of Detection (QoD): 98%

Vulnerability Detection Result

```
The certificate of the remote service contains a common name (CN) that does not
↪match the hostname "nagios.trabalho_vulnnet".
Certificate details:
fingerprint (SHA-1)             | B2076F80E55087522A5CCA24219C2CA82659A8C2
fingerprint (SHA-256)           | 75EB153B9F5EF4FED193F04A8A539B3BD36E3367B0F307
↪FF4BFF66CDCB326FA0
issued by                       | CN=localhost
public key algorithm            | RSA
public key size (bits)          | 2048
serial                          | 448A1CBCC086DFFFDA32AACF50E6290DD95BCCA3
signature algorithm             | sha256WithRSAEncryption
subject                         | CN=localhost
subject alternative names (SAN) | localhost
valid from                      | 2024-11-06 09:32:47 UTC
valid until                     | 2034-11-04 09:32:47 UTC
```

Solution:

Log Method
Details: `SSL/TLS: Certificate - Subject Common Name Does Not Match Server FQDN`
OID:1.3.6.1.4.1.25623.1.0.103141
Version used: `2024-06-14T05:05:48Z`

Product Detection Result
Product: `cpe:/a:ietf:transport_layer_security`
Method: `SSL/TLS: Collect and Report Certificate Details`
OID: 1.3.6.1.4.1.25623.1.0.103692)

Log (CVSS: 0.0)
NVT: Postfix SMTP Server Detection (SMTP)

Summary
SMTP based detection of Postfix.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Detected Postfix
Version:       unknown
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
Location:      25/tcp
CPE:           cpe:/a:postfix:postfix
Concluded from version/product identification result:
220 e98d4d9bfcb6 ESMTP Postfix (Ubuntu)
```

Solution:

Log Method
Details: `Postfix SMTP Server Detection (SMTP)`
OID:1.3.6.1.4.1.25623.1.0.111086
Version used: `2024-01-12T05:05:56Z`

References
`url: https://www.postfix.org/`

Log (CVSS: 0.0)
NVT: Services

Summary
This plugin performs service detection.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
An SMTP server is running on this port
Here is its banner :
220 e98d4d9bfcb6 ESMTP Postfix (Ubuntu)
```

Solution:

Vulnerability Insight
This plugin attempts to guess which service is running on the remote port(s). For instance, it searches for a web server which could listen on another port than 80 or 443 and makes this information available for other check routines.

Log Method
Details: `Services`
OID:1.3.6.1.4.1.25623.1.0.10330
Version used: `2025-03-05T05:38:53Z`

Log (CVSS: 0.0)
NVT: SMTP Server type and version

. . . continues on next page . . .

. . . continued from previous page . . .

Summary
This detects the SMTP Server's type and version by connecting to the server and processing the buffer received.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Remote SMTP server banner:
220 e98d4d9bfcb6 ESMTP Postfix (Ubuntu)
The remote SMTP server is announcing the following available ESMTP commands (EHL
↪O response) via an unencrypted connection:
8BITMIME, CHUNKING, DSN, ENHANCEDSTATUSCODES, ETRN, PIPELINING, SIZE 10240000, S
↪MTPUTF8, STARTTLS, VRFY
```

Solution:

Log Method
Details: `SMTP Server type and version`
OID:1.3.6.1.4.1.25623.1.0.10263
Version used: `2026-01-07T05:47:44Z`

Log (CVSS: 0.0)
NVT: SSL/TLS: SMTP 'STARTTLS' Command Detection

Summary
Checks if the remote SMTP server supports SSL/TLS with the 'STARTTLS' command.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The remote SMTP server supports SSL/TLS with the 'STARTTLS' command.
The remote SMTP server is announcing the following available ESMTP commands (EHL
↪O response) before sending the 'STARTTLS' command:
8BITMIME, CHUNKING, DSN, ENHANCEDSTATUSCODES, ETRN, PIPELINING, SIZE 10240000, S
↪MTPUTF8, STARTTLS, VRFY
The remote SMTP server is announcing the following available ESMTP commands (EHL
↪O response) after sending the 'STARTTLS' command:
8BITMIME, CHUNKING, DSN, ENHANCEDSTATUSCODES, ETRN, PIPELINING, SIZE 10240000, S
↪MTPUTF8, VRFY
```

Solution:

Log Method
Details: `SSL/TLS: SMTP 'STARTTLS' Command Detection`

. . . continues on next page . . .

. . . continued from previous page . . .

OID:1.3.6.1.4.1.25623.1.0.103118
Version used: 2023-10-31T05:06:37Z

References
url: https://tools.ietf.org/html/rfc3207

Log (CVSS: 0.0)
NVT: SSL/TLS: Version Detection

Summary
Enumeration and reporting of SSL/TLS protocol versions supported by a remote service.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The remote SSL/TLS service supports the following SSL/TLS protocol version(s):
TLSv1.0
TLSv1.1
TLSv1.2
TLSv1.3

Solution:

Log Method
Sends multiple connection requests to the remote service and attempts to determine the SSL/TLS protocol versions supported by the service from the replies.
Note: The supported SSL/TLS protocol versions included in the report of this VT are reported independently from the allowed / supported SSL/TLS ciphers.
Details: SSL/TLS: Version Detection
OID:1.3.6.1.4.1.25623.1.0.105782
Version used: 2024-09-27T05:05:23Z

Log (CVSS: 0.0)
NVT: SSL/TLS: Collect and Report Certificate Details

Summary
This script collects and reports the details of all SSL/TLS certificates.
This data will be used by other tests to verify server certificates.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
The following certificate details of the remote service were collected.
Certificate details:

. . . continues on next page . . .

. . . continued from previous page . . .

```
fingerprint (SHA-1)              | B2076F80E55087522A5CCA24219C2CA82659A8C2
fingerprint (SHA-256)            | 75EB153B9F5EF4FED193F04A8A539B3BD36E3367B0F307
↪FF4BFF66CDCB326FA0
issued by                        | CN=localhost
public key algorithm             | RSA
public key size (bits)           | 2048
serial                           | 448A1CBCC086DFFFDA32AACF50E6290DD95BCCA3
signature algorithm              | sha256WithRSAEncryption
subject                          | CN=localhost
subject alternative names (SAN)  | localhost
valid from                       | 2024-11-06 09:32:47 UTC
valid until                      | 2034-11-04 09:32:47 UTC
```

Solution:

Log Method
Details: SSL/TLS: Collect and Report Certificate Details
OID:1.3.6.1.4.1.25623.1.0.103692
Version used: 2024-09-27T05:05:23Z

Log (CVSS: 0.0)
NVT: SSL/TLS: Safe/Secure Renegotiation Support Status

Summary
Checks and reports if a remote SSL/TLS service supports safe/secure renegotiation.

Quality of Detection (QoD): 98%

Vulnerability Detection Result

```
Protocol Version | Safe/Secure Renegotiation Support Status
-------------------------------------------------------------------------------
↪-------------------------------------------------------------------------------
↪-------------------------------------
SSLv3            | Unknown, Reason: Scanner failed to negotiate an SSL/TLS conne
↪ction (Either the scanner or the remote host is probably not supporting / acce
↪pting this SSL/TLS protocol version).
TLSv1.0          | Enabled, Note: While the remote service announces the support
↪ of safe/secure renegotiation it still might not support / accept renegotiatio
↪n at all.
TLSv1.1          | Enabled, Note: While the remote service announces the support
↪ of safe/secure renegotiation it still might not support / accept renegotiatio
↪n at all.
TLSv1.2          | Enabled, Note: While the remote service announces the support
↪ of safe/secure renegotiation it still might not support / accept renegotiatio
↪n at all.
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
TLSv1.3          | Disabled (The TLSv1.3 protocol generally doesn't support rene
↪gotiation so this is always reported as 'Disabled')
```

Solution:

Log Method
Details: SSL/TLS: Safe/Secure Renegotiation Support Status
OID:1.3.6.1.4.1.25623.1.0.117757
Version used: 2024-09-27T05:05:23Z

References
url: https://www.gnutls.org/manual/html_node/Safe-renegotiation.html
url: https://wiki.openssl.org/index.php/TLS1.3#Renegotiation
url: https://datatracker.ietf.org/doc/html/rfc5746

[return to 172.31.1.74]