# Scan Report

January 26, 2026

**Summary**

This document reports on the results of an automatic security scan. All dates are displayed using the timezone "Coordinated Universal Time", which is abbreviated "UTC". The task was " hgdfdghgdgd". The scan started at Mon Jan 26 01:47:47 2026 UTC and ended at Mon Jan 26 14:04:13 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

## Contents

**1 Result Overview** **2**

**2 Results per Host** **2**

2.1 172.30.3.1 . . . . . 2

2.1.1 Critical 22/tcp . . . . . 2

2.1.2 High 22/tcp . . . . . 4

2.1.3 Medium 22/tcp . . . . . 15

2.1.4 Low general/tcp . . . . . 37

2.1.5 Low 22/tcp . . . . . 38

2.1.6 Low general/icmp . . . . . 41

2.1.7 Log general/tcp . . . . . 42

2.1.8 Log 22/tcp . . . . . 45

2.1.9 Log general/CPE-T . . . . . 49

# 1 Result Overview

| Host | Critical | High | Medium | Low | Log | False P. |
|---|---|---|---|---|---|---|
| 172.30.3.1<br>ssh-vuln-dos.trabalho_vulnnet | 1 | 6 | 12 | 4 | 11 | 0 |
| Total: 1 | 1 | 6 | 12 | 4 | 11 | 0 |

Vendor security updates are not trusted.
Overrides are off. Even when a result has an override, this report uses the actual threat of the result.
Information on overrides is included in the report.
Notes are included in the report.
This report might not show details of all issues that were found.
Issues with the threat level "Debug" are not shown.

This report contains all 34 results selected by the filtering described above. Before filtering there were 5586 results.

# 2 Results per Host

## 2.1 172.30.3.1

| | |
|---|---|
| Host scan start | Mon Jan 26 03:38:45 2026 UTC |
| Host scan end | Mon Jan 26 05:29:54 2026 UTC |

| Service (Port) | Threat Level |
|---|---|
| 22/tcp | Critical |
| 22/tcp | High |
| 22/tcp | Medium |
| general/tcp | Low |
| 22/tcp | Low |
| general/icmp | Low |
| general/tcp | Log |
| 22/tcp | Log |
| general/CPE-T | Log |

### 2.1.1 Critical 22/tcp

Critical (CVSS: 9.8)
NVT: OpenBSD OpenSSH < 9.3p2 RCE Vulnerability

**Product detection result**
`cpe:/a:openbsd:openssh:7.2p2`

. . . continues on next page . . .

. . . continued from previous page . . .

Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)

**Summary**
OpenBSD OpenSSH is prone to a remote code execution (RCE) vulnerability in OpenSSH's forwarded ssh-agent.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

```
Installed version: 7.2p2
Fixed version:     9.3p2
Installation
path / port:       22/tcp
```

**Solution:**
**Solution type:** VendorFix
Update to version 9.3p2 or later.

**Affected Software/OS**
OpenBSD OpenSSH prior to version 9.3p2.
The following conditions needs to be met:
- Exploitation requires the presence of specific libraries on the victim system.
- Remote exploitation requires that the agent was forwarded to an attacker-controlled system.

**Vulnerability Insight**
A condition where specific libraries loaded via ssh-agent(1)'s PKCS#11 support could be abused to achieve remote code execution via a forwarded agent socket.

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: OpenBSD OpenSSH < 9.3p2 RCE Vulnerability
OID:1.3.6.1.4.1.25623.1.0.104869
Version used: 2023-10-13T05:06:10Z

**Product Detection Result**
Product: cpe:/a:openbsd:openssh:7.2p2
Method: OpenSSH Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
cve: CVE-2023-38408
url: https://www.openssh.com/releasenotes.html#9.3p2
url: https://www.qualys.com/2023/07/19/cve-2023-38408/rce-openssh-forwarded-ssh-
↪agent.txt

. . . continues on next page . . .

. . . continued from previous page . . .

```
cert-bund: WID-SEC-2024-3195
cert-bund: WID-SEC-2024-1248
cert-bund: WID-SEC-2024-1082
cert-bund: WID-SEC-2024-0064
cert-bund: WID-SEC-2023-2679
cert-bund: WID-SEC-2023-2625
cert-bund: WID-SEC-2023-2240
cert-bund: WID-SEC-2023-1843
cert-bund: WID-SEC-2023-1819
dfn-cert: DFN-CERT-2026-0097
dfn-cert: DFN-CERT-2025-2802
dfn-cert: DFN-CERT-2024-1260
dfn-cert: DFN-CERT-2024-0491
dfn-cert: DFN-CERT-2023-2792
dfn-cert: DFN-CERT-2023-2179
dfn-cert: DFN-CERT-2023-1961
dfn-cert: DFN-CERT-2023-1920
dfn-cert: DFN-CERT-2023-1845
dfn-cert: DFN-CERT-2023-1773
dfn-cert: DFN-CERT-2023-1665
```

[ return to 172.30.3.1 ]

### 2.1.2 High 22/tcp

High (CVSS: 7.8)
NVT: OpenSSH <= 7.2p2 Privilege Escalation Vulnerability (May 2016)

**Product detection result**

```
cpe:/a:openbsd:openssh:7.2p2
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)
```

**Summary**

OpenSSH is prone to a privilege escalation vulnerability.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

```
Installed version: 7.2p2
Fixed version:     7.2p2-3
Installation
path / port:       22/tcp
```

**Impact**

. . . continues on next page . . .

. . . continued from previous page . . .

Successfully exploiting this issue will allow local users to gain privileges.

**Solution:**
**Solution type:** VendorFix
Update to version 7.2p2-3 or later.

**Affected Software/OS**
OpenSSH versions through 7.2p2.

**Vulnerability Insight**
The flaw exists due to an error in 'do_setup_env function' in the 'session.c' script in sshd which trigger a crafted environment for the /bin/login program when the UseLogin feature is enabled and PAM is configured to read .pam_environment files in user home directories.

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: `OpenSSH <= 7.2p2 Privilege Escalation Vulnerability (May 2016)`
OID:1.3.6.1.4.1.25623.1.0.807574
Version used: `2024-12-13T05:05:32Z`

**Product Detection Result**
Product: `cpe:/a:openbsd:openssh:7.2p2`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
`cve: CVE-2015-8325`
`url: https://people.canonical.com/~ubuntu-security/cve/2015/CVE-2015-8325.html`
`url: https://anongit.mindrot.org/openssh.git/commit/?id=85bdcd7c92fe7ff133bbc4e1`
`↪0a65c91810f88755`
`cert-bund: WID-SEC-2024-1053`
`cert-bund: CB-K17/1725`
`cert-bund: CB-K17/0055`
`cert-bund: CB-K17/0054`
`cert-bund: CB-K16/1837`
`cert-bund: CB-K16/1487`
`cert-bund: CB-K16/1485`
`cert-bund: CB-K16/1221`
`cert-bund: CB-K16/0684`
`cert-bund: CB-K16/0577`
`dfn-cert: DFN-CERT-2019-1408`
`dfn-cert: DFN-CERT-2017-1807`
`dfn-cert: DFN-CERT-2017-0060`
`dfn-cert: DFN-CERT-2017-0059`
`dfn-cert: DFN-CERT-2016-1943`

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2016-1576
dfn-cert: DFN-CERT-2016-1574
dfn-cert: DFN-CERT-2016-1243
dfn-cert: DFN-CERT-2016-0864
dfn-cert: DFN-CERT-2016-0733
dfn-cert: DFN-CERT-2016-0628
```

High (CVSS: 7.8)
NVT: OpenSSH < 7.4 Multiple Vulnerabilities (Jan 2017) - Linux

**Product detection result**

```
cpe:/a:openbsd:openssh:7.2p2
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)
```

**Summary**

OpenSSH is prone to multiple vulnerabilities.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

```
Installed version: 7.2p2
Fixed version:     7.4
Installation
path / port:       22/tcp
```

**Impact**

Successfully exploiting this issue allows local users to obtain sensitive private-key information, to gain privileges, conduct a senial-of-service condition and allows remote attackers to execute arbitrary local PKCS#11 modules.

**Solution:**

**Solution type:** VendorFix

Update to version 7.4 or later.

**Affected Software/OS**

OpenSSH versions before 7.4 on Linux.

**Vulnerability Insight**

Multiple flaws exist due to:
- An 'authfile.c' script does not properly consider the effects of realloc on buffer contents.
- The shared memory manager (associated with pre-authentication compression) does not ensure that a bounds check is enforced by all compilers.
- The sshd in OpenSSH creates forwarded Unix-domain sockets as root, when privilege separation is not used.

. . . continues on next page . . .

. . . continued from previous page . . .

- An untrusted search path vulnerability in ssh-agent.c in ssh-agent.
- NULL pointer dereference error due to an out-of-sequence NEWKEYS message.

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: `OpenSSH < 7.4 Multiple Vulnerabilities (Jan 2017) - Linux`
OID:1.3.6.1.4.1.25623.1.0.8103256
Version used: `2024-12-13T05:05:32Z`

**Product Detection Result**
Product: `cpe:/a:openbsd:openssh:7.2p2`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
```
cve: CVE-2016-10009
cve: CVE-2016-10010
cve: CVE-2016-10011
cve: CVE-2016-10012
cve: CVE-2016-10708
url: https://www.openssh.com/txt/release-7.4
url: http://www.securityfocus.com/bid/94968
url: http://www.securityfocus.com/bid/94972
url: http://www.securityfocus.com/bid/94977
url: http://www.securityfocus.com/bid/94975
url: http://www.openwall.com/lists/oss-security/2016/12/19/2
url: http://blog.swiecki.net/2018/01/fuzzing-tcp-servers.html
url: https://anongit.mindrot.org/openssh.git/commit/?id=28652bca29046f62c7045e93
↪3e6b931de1d16737
cert-bund: WID-SEC-2023-1996
cert-bund: CB-K18/0919
cert-bund: CB-K18/0591
cert-bund: CB-K18/0137
cert-bund: CB-K18/0041
cert-bund: CB-K17/2219
cert-bund: CB-K17/2112
cert-bund: CB-K17/1292
cert-bund: CB-K17/1061
cert-bund: CB-K17/0527
cert-bund: CB-K17/0377
cert-bund: CB-K17/0127
cert-bund: CB-K17/0041
cert-bund: CB-K16/1991
dfn-cert: DFN-CERT-2021-0776
dfn-cert: DFN-CERT-2019-1408
dfn-cert: DFN-CERT-2018-2259
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2018-2191
dfn-cert: DFN-CERT-2018-2068
dfn-cert: DFN-CERT-2018-1828
dfn-cert: DFN-CERT-2018-1568
dfn-cert: DFN-CERT-2018-1432
dfn-cert: DFN-CERT-2018-1112
dfn-cert: DFN-CERT-2018-1070
dfn-cert: DFN-CERT-2018-1068
dfn-cert: DFN-CERT-2018-0150
dfn-cert: DFN-CERT-2018-0046
dfn-cert: DFN-CERT-2017-2320
dfn-cert: DFN-CERT-2017-2208
dfn-cert: DFN-CERT-2017-1340
dfn-cert: DFN-CERT-2017-1096
dfn-cert: DFN-CERT-2017-0532
dfn-cert: DFN-CERT-2017-0386
dfn-cert: DFN-CERT-2017-0130
dfn-cert: DFN-CERT-2017-0042
dfn-cert: DFN-CERT-2016-2099
```

High (CVSS: 7.5)
NVT: OpenSSH < 7.3 DoS and User Enumeration Vulnerabilities - Linux

**Product detection result**

```
cpe:/a:openbsd:openssh:7.2p2
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)
```

**Summary**

OpenSSH is prone to denial of service (DoS) and user enumeration vulnerabilities.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

```
Installed version: 7.2p2
Fixed version:     7.3
Installation
path / port:       22/tcp
```

**Impact**

Successfully exploiting this issue allows remote attackers to cause a denial of service (crypt CPU consumption) and to enumerate users by leveraging the timing difference between responses when a large password is provided.

**Solution:**

**Solution type:** VendorFix

. . . continues on next page . . .

. . . continued from previous page . . .

Update to version 7.3 or later.

**Affected Software/OS**
OpenSSH versions before 7.3 on Linux.

**Vulnerability Insight**
Multiple flaws exist due to:
- The auth_password function in 'auth-passwd.c' script does not limit password lengths for password authentication.
- The sshd in OpenSSH, when SHA256 or SHA512 are used for user password hashing uses BLOWFISH hashing on a static password when the username does not exist and it takes much longer to calculate SHA256/SHA512 hash than BLOWFISH hash.

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: `OpenSSH < 7.3 DoS and User Enumeration Vulnerabilities - Linux`
OID:1.3.6.1.4.1.25623.1.0.809154
Version used: `2024-12-13T05:05:32Z`

**Product Detection Result**
Product: `cpe:/a:openbsd:openssh:7.2p2`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
`cve: CVE-2016-6515`
`cve: CVE-2016-6210`
`url: http://www.openssh.com/txt/release-7.3`
`url: http://www.securityfocus.com/bid/92212`
`url: http://seclists.org/fulldisclosure/2016/Jul/51`
`url: https://security-tracker.debian.org/tracker/CVE-2016-6210`
`url: http://openwall.com/lists/oss-security/2016/08/01/2`
`cert-bund: WID-SEC-2023-0450`
`cert-bund: WID-SEC-2023-0449`
`cert-bund: CB-K18/0041`
`cert-bund: CB-K17/2219`
`cert-bund: CB-K17/2112`
`cert-bund: CB-K17/1753`
`cert-bund: CB-K17/1349`
`cert-bund: CB-K17/1292`
`cert-bund: CB-K17/0055`
`cert-bund: CB-K16/1837`
`cert-bund: CB-K16/1629`
`cert-bund: CB-K16/1487`
`cert-bund: CB-K16/1485`

. . . continues on next page . . .

. . . continued from previous page . . .

```
cert-bund: CB-K16/1252
cert-bund: CB-K16/1221
cert-bund: CB-K16/1082
dfn-cert: DFN-CERT-2023-1920
dfn-cert: DFN-CERT-2019-1408
dfn-cert: DFN-CERT-2018-1828
dfn-cert: DFN-CERT-2018-1070
dfn-cert: DFN-CERT-2018-0046
dfn-cert: DFN-CERT-2017-2320
dfn-cert: DFN-CERT-2017-2208
dfn-cert: DFN-CERT-2017-1831
dfn-cert: DFN-CERT-2017-1407
dfn-cert: DFN-CERT-2017-1340
dfn-cert: DFN-CERT-2017-0060
dfn-cert: DFN-CERT-2016-1943
dfn-cert: DFN-CERT-2016-1729
dfn-cert: DFN-CERT-2016-1576
dfn-cert: DFN-CERT-2016-1574
dfn-cert: DFN-CERT-2016-1331
dfn-cert: DFN-CERT-2016-1243
dfn-cert: DFN-CERT-2016-1149
```

High (CVSS: 7.5)
NVT: Diffie-Hellman Ephemeral Key Exchange DoS Vulnerability (SSH, D(HE)ater)

**Product detection result**

```
cpe:/a:ietf:secure_shell_protocol
Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565
↪)
```

**Summary**

The remote SSH server is supporting Diffie-Hellman ephemeral (DHE) Key Exchange (KEX) algorithms and thus could be prone to a denial of service (DoS) vulnerability.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

```
The remote SSH server supports the following DHE KEX algorithm(s):
diffie-hellman-group14-sha1
diffie-hellman-group-exchange-sha256
```

**Impact**

This vulnerability allows remote attackers (from the client side) to send arbitrary numbers that are actually not public keys, and trigger expensive server-side DHE modular-exponentiation calculations, also known as a D(HE)ater attack.

. . . continues on next page . . .

. . . continued from previous page . . .

There could be an increase in CPU usage in the affected component. For OpenSSH, users may observe issues such as a slowdown in SSH connections.

**Solution:**
**Solution type:** Mitigation
- DHE key exchange should be disabled if no other mitigation mechanism can be used and either elliptic-curve variant of Diffie-Hellman (ECDHE) or RSA key exchange is supported by the clients. The fact that RSA key exchange is not forward secret should be considered.
- Limit the maximum number of concurrent connections in e.g. the configuration of the remote server. For OpenSSH this limit can be configured via the 'MaxStartups' option, for other products please refer to the manual of the product in question on configuration possibilities.

**Vulnerability Insight**
- CVE-2002-20001: The Diffie-Hellman Key Agreement Protocol allows remote attackers (from the client side) to send arbitrary numbers that are actually not public keys, and trigger expensive server-side DHE modular-exponentiation calculations, aka a D(HE)ater attack. The client needs very little CPU resources and network bandwidth. The attack may be more disruptive in cases where a client can require a server to select its largest supported key size. The basic attack scenario is that the client must claim that it can only communicate with DHE, and the server must be configured to allow DHE.
- CVE-2022-40735: The Diffie-Hellman Key Agreement Protocol allows use of long exponents that arguably make certain calculations unnecessarily expensive, because the 1996 van Oorschot and Wiener paper found that '(appropriately) short exponents' can be used when there are adequate subgroup constraints, and these short exponents can lead to less expensive calculations than for long exponents. This issue is different from CVE-2002-20001 because it is based on an observation about exponent size, rather than an observation about numbers that are not public keys. The specific situations in which calculation expense would constitute a server-side vulnerability depend on the protocol (e.g., TLS, SSH, or IKE) and the DHE implementation details. In general, there might be an availability concern because of server-side resource consumption from DHE modular-exponentiation calculations. Finally, it is possible for an attacker to exploit this vulnerability and CVE-2002-20001 together.
- CVE-2024-41996: Validating the order of the public keys in the Diffie-Hellman Key Agreement Protocol, when an approved safe prime is used, allows remote attackers (from the client side) to trigger unnecessarily expensive server-side DHE modular-exponentiation calculations. The client may cause asymmetric resource consumption. The basic attack scenario is that the client must claim that it can only communicate with DHE, and the server must be configured to allow DHE and validate the order of the public key.

**Vulnerability Detection Method**
Checks the supported KEX algorithms of the remote SSH server.
Details: `Diffie-Hellman Ephemeral Key Exchange DoS Vulnerability (SSH, D(HE)ater)`
OID:1.3.6.1.4.1.25623.1.0.117839
Version used: `2024-10-03T05:05:33Z`

**Product Detection Result**
Product: `cpe:/a:ietf:secure_shell_protocol`

. . . continues on next page . . .

. . . continued from previous page . . .

Method: SSH Protocol Algorithms Supported
OID: 1.3.6.1.4.1.25623.1.0.105565)

**References**

```
cve: CVE-2002-20001
cve: CVE-2022-40735
cve: CVE-2024-41996
url: https://dheatattack.gitlab.io/
url: https://dheatattack.gitlab.io/details/
url: https://www.researchgate.net/profile/Anton-Stiglic-2/publication/2401745_Se
↪curity_Issues_in_the_Diffie-Hellman_Key_Agreement_Protocol
url: https://github.com/Balasys/dheater
url: https://github.com/c0r0n3r/dheater
cert-bund: WID-SEC-2024-3056
cert-bund: WID-SEC-2023-1886
cert-bund: WID-SEC-2023-1352
cert-bund: WID-SEC-2022-2251
cert-bund: WID-SEC-2022-2000
cert-bund: CB-K22/0224
cert-bund: CB-K21/1276
dfn-cert: DFN-CERT-2025-3324
dfn-cert: DFN-CERT-2024-2847
dfn-cert: DFN-CERT-2024-2578
dfn-cert: DFN-CERT-2024-1671
dfn-cert: DFN-CERT-2023-1697
dfn-cert: DFN-CERT-2023-1332
dfn-cert: DFN-CERT-2022-2147
dfn-cert: DFN-CERT-2022-0437
dfn-cert: DFN-CERT-2021-2622
```

## High (CVSS: 7.4)
## NVT: OpenBSD OpenSSH <= 8.6 Command Injection Vulnerability

**Product detection result**

```
cpe:/a:openbsd:openssh:7.2p2
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)
```

**Summary**

OpenBSD OpenSSH is prone to a command injection vulnerability.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

```
Installed version: 7.2p2
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
Fixed version:      None
Installation
path / port:        22/tcp
```

**Impact**
Successful exploitation would allow an attacker to execute arbitrary code on the target machine.

**Solution:**
**Solution type:** WillNotFix
No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.

**Affected Software/OS**
OpenBSD OpenSSH through version 8.6 (initially reported for 8.3p1).

**Vulnerability Insight**
scp of OpenSSH allows command injection in spc.c via backtick characters in the destination argument.

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: `OpenBSD OpenSSH <= 8.6 Command Injection Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.113736
Version used: `2025-07-29T05:44:59Z`

**Product Detection Result**
Product: `cpe:/a:openbsd:openssh:7.2p2`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
```
cve: CVE-2020-15778
url: https://github.com/cpandya2909/CVE-2020-15778/
cert-bund: WID-SEC-2024-1082
cert-bund: WID-SEC-2023-1599
cert-bund: WID-SEC-2022-2413
cert-bund: WID-SEC-2022-1308
cert-bund: CB-K21/1268
dfn-cert: DFN-CERT-2024-1260
dfn-cert: DFN-CERT-2020-1691
```

High (CVSS: 7.0)
NVT: OpenSSH 6.2 <= 8.7 Privilege Escalation Vulnerability

**Product detection result**
`cpe:/a:openbsd:openssh:7.2p2`
`Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)`

**Summary**
OpenSSH is prone to a privilege scalation vulnerability in certain configurations.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

```
Installed version: 7.2p2
Fixed version:     8.8
Installation
path / port:       22/tcp
```

**Solution:**
**Solution type:** VendorFix
Update to version 8.8 or later.

**Affected Software/OS**
OpenSSH versions 6.2 through 8.7.

**Vulnerability Insight**
sshd failed to correctly initialise supplemental groups when executing an AuthorizedKeysCommand or AuthorizedPrincipalsCommand, where a AuthorizedKeysCommandUser or AuthorizedPrincipalsCommandUser directive has been set to run the command as a different user. Instead these commands would inherit the groups that sshd was started with.
Depending on system configuration, inherited groups may allow AuthorizedKeysCommand/AuthorizedPrincipalsCommand helper programs to gain unintended privilege.
Neither AuthorizedKeysCommand nor AuthorizedPrincipalsCommand are enabled by default in sshd_config.

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: `OpenSSH 6.2 <= 8.7 Privilege Escalation Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.117696
Version used: `2021-10-11T08:01:31Z`

**Product Detection Result**
Product: `cpe:/a:openbsd:openssh:7.2p2`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

. . . continues on next page . . .

. . . continued from previous page . . .

**References**

```
cve: CVE-2021-41617
url: https://www.openssh.com/txt/release-8.8
cert-bund: WID-SEC-2024-1082
cert-bund: WID-SEC-2023-1969
cert-bund: WID-SEC-2023-0426
cert-bund: WID-SEC-2022-1308
cert-bund: WID-SEC-2022-0676
cert-bund: WID-SEC-2022-0534
cert-bund: CB-K22/0310
cert-bund: CB-K22/0011
cert-bund: CB-K21/1268
cert-bund: CB-K21/1017
dfn-cert: DFN-CERT-2024-1260
dfn-cert: DFN-CERT-2024-0022
dfn-cert: DFN-CERT-2023-3218
dfn-cert: DFN-CERT-2023-3210
dfn-cert: DFN-CERT-2022-1571
dfn-cert: DFN-CERT-2022-0579
dfn-cert: DFN-CERT-2021-2586
dfn-cert: DFN-CERT-2021-2017
dfn-cert: DFN-CERT-2021-2015
```

[ return to 172.30.3.1 ]

### 2.1.3 Medium 22/tcp

Medium (CVSS: 6.8)
NVT: OpenBSD OpenSSH 6.8p1 - 9.9p1 MitM Vulnerability

**Product detection result**

```
cpe:/a:openbsd:openssh:7.2p2
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)
```

**Summary**

OpenBSD OpenSSH is prone to a man-in-the-middle (MitM) vulnerability.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

```
Installed version: 7.2p2
Fixed version:     9.9p2
Installation
```

. . . continues on next page . . .

. . . continued from previous page . . .

path / port: 22/tcp

**Solution:**
**Solution type:** VendorFix
Update to version 9.9p2 or later.

**Affected Software/OS**
OpenBSD OpenSSH versions 6.8p1 through 9.9p1.

**Vulnerability Insight**
ssh(1) in OpenSSH contained a logic error that allowed an on-path attacker (a.k.a MITM) to impersonate any server when the VerifyHostKeyDNS option is enabled. This option is off by default.

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: OpenBSD OpenSSH 6.8p1 - 9.9p1 MitM Vulnerability
OID:1.3.6.1.4.1.25623.1.0.114946
Version used: 2025-02-20T08:47:14Z

**Product Detection Result**
Product: cpe:/a:openbsd:openssh:7.2p2
Method: OpenSSH Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
cve: CVE-2025-26465
url: https://www.openssh.com/txt/release-9.9p2
url: https://www.openssh.com/security.html
url: https://www.qualys.com/2025/02/18/openssh-mitm-dos.txt
url: https://blog.qualys.com/vulnerabilities-threat-research/2025/02/18/qualys-t
↪ru-discovers-two-vulnerabilities-in-openssh-cve-2025-26465-cve-2025-26466
url: https://www.openwall.com/lists/oss-security/2025/02/18/1
url: https://www.openwall.com/lists/oss-security/2025/02/18/4
cert-bund: WID-SEC-2025-1439
cert-bund: WID-SEC-2025-1007
cert-bund: WID-SEC-2025-0394
dfn-cert: DFN-CERT-2026-0097
dfn-cert: DFN-CERT-2025-1201
dfn-cert: DFN-CERT-2025-1200
dfn-cert: DFN-CERT-2025-0993
dfn-cert: DFN-CERT-2025-0819
dfn-cert: DFN-CERT-2025-0470
dfn-cert: DFN-CERT-2025-0428

Medium (CVSS: 6.8)
NVT: OpenBSD OpenSSH <= 7.9 Multiple Vulnerabilities

**Product detection result**
`cpe:/a:openbsd:openssh:7.2p2`
`Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)`

**Summary**
OpenBSD OpenSSH is prone to multiple vulnerabilities.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

```
Installed version: 7.2p2
Fixed version:     8.0
Installation
path / port:       22/tcp
```

**Solution:**
**Solution type:** VendorFix
Update to version 8.0 or later.

**Affected Software/OS**
OpenBSD OpenSSH versions 7.9 and prior.

**Vulnerability Insight**
The following flaws exist:
- CVE-2018-20685: bypass of intended access restrictions in the scp client
- CVE-2019-6109, CVE-2019-6110: manipulation of the output in the scp client by a malicious server
- CVE-2019-6111: overwrite of arbitrary files in the scp client by a malicious server

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: `OpenBSD OpenSSH <= 7.9 Multiple Vulnerabilities`
OID:1.3.6.1.4.1.25623.1.0.117786
Version used: `2023-10-20T16:09:12Z`

**Product Detection Result**
Product: `cpe:/a:openbsd:openssh:7.2p2`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
`cve: CVE-2018-20685`

. . . continues on next page . . .

. . . continued from previous page . . .

```
cve: CVE-2019-6109
cve: CVE-2019-6110
cve: CVE-2019-6111
url: https://sintonen.fi/advisories/scp-client-multiple-vulnerabilities.txt
url: http://www.openwall.com/lists/oss-security/2019/04/18/1
cert-bund: WID-SEC-2024-1082
cert-bund: WID-SEC-2024-0872
cert-bund: WID-SEC-2023-1995
cert-bund: WID-SEC-2023-0561
cert-bund: CB-K19/0627
cert-bund: CB-K19/0312
cert-bund: CB-K19/0058
cert-bund: CB-K19/0037
dfn-cert: DFN-CERT-2024-1260
dfn-cert: DFN-CERT-2019-2157
dfn-cert: DFN-CERT-2019-1470
dfn-cert: DFN-CERT-2019-0970
dfn-cert: DFN-CERT-2019-0776
dfn-cert: DFN-CERT-2019-0563
dfn-cert: DFN-CERT-2019-0415
dfn-cert: DFN-CERT-2019-0357
dfn-cert: DFN-CERT-2019-0275
dfn-cert: DFN-CERT-2019-0136
dfn-cert: DFN-CERT-2019-0094
```

Medium (CVSS: 6.5)
NVT: OpenBSD OpenSSH < 9.6 Multiple Vulnerabilities (Terrapin Attack)

**Product detection result**

```
cpe:/a:openbsd:openssh:7.2p2
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)
```

**Summary**

OpenBSD OpenSSH is prone to multiple vulnerabilities.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

```
Installed version: 7.2p2
Fixed version:     9.6
Installation
path / port:       22/tcp
```

**Solution:**

**Solution type:** VendorFix

. . . continues on next page . . .

. . . continued from previous page . . .

Update to version 9.6 or later.
Note: Client and Server implementations need to run a fixed version to mitigate the Terrapin flaw.

**Affected Software/OS**
OpenBSD OpenSSH prior to version 9.6.

**Vulnerability Insight**
The following vulnerabilities exist:
- CVE-2023-48795: The SSH transport protocol with certain OpenSSH extensions allows remote attackers to bypass integrity checks such that some packets are omitted (from the extension negotiation message), and a client and server may consequently end up with a connection for which some security features have been downgraded or disabled, aka a 'Terrapin attack'.
- CVE-2023-51384: In ssh-agent certain destination constraints can be incompletely applied. When destination constraints are specified during addition of PKCS#11-hosted private keys, these constraints are only applied to the first key, even if a PKCS#11 token returns multiple keys.
- CVE-2023-51385: OS command injection might occur if a user name or host name has shell metacharacters, and this name is referenced by an expansion token in certain situations. For example, an untrusted Git repository can have a submodule with shell metacharacters in a user name or host name.

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: `OpenBSD OpenSSH < 9.6 Multiple Vulnerabilities (Terrapin Attack)`
OID:1.3.6.1.4.1.25623.1.0.118572
Version used: `2025-10-08T05:38:55Z`

**Product Detection Result**
Product: `cpe:/a:openbsd:openssh:7.2p2`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
`cve: CVE-2023-48795`
`cve: CVE-2023-51384`
`cve: CVE-2023-51385`
`url: https://www.openssh.com/txt/release-9.6`
`url: https://terrapin-attack.com`
`url: https://vin01.github.io/piptagole/ssh/security/openssh/libssh/remote-code-e`
`↪xecution/2023/12/20/openssh-proxycommand-libssh-rce.html`
`url: https://github.com/vin01/poc-proxycommand-vulnerable`
`cert-bund: WID-SEC-2025-0810`
`cert-bund: WID-SEC-2025-0168`
`cert-bund: WID-SEC-2025-0144`

. . . continues on next page . . .

. . . continued from previous page . . .

```
cert-bund: WID-SEC-2025-0139
cert-bund: WID-SEC-2024-3377
cert-bund: WID-SEC-2024-3320
cert-bund: WID-SEC-2024-3198
cert-bund: WID-SEC-2024-3195
cert-bund: WID-SEC-2024-3140
cert-bund: WID-SEC-2024-1913
cert-bund: WID-SEC-2024-1781
cert-bund: WID-SEC-2024-1701
cert-bund: WID-SEC-2024-1656
cert-bund: WID-SEC-2024-1655
cert-bund: WID-SEC-2024-1643
cert-bund: WID-SEC-2024-1642
cert-bund: WID-SEC-2024-1639
cert-bund: WID-SEC-2024-1637
cert-bund: WID-SEC-2024-1630
cert-bund: WID-SEC-2024-1474
cert-bund: WID-SEC-2024-1248
cert-bund: WID-SEC-2024-1228
cert-bund: WID-SEC-2024-1186
cert-bund: WID-SEC-2024-1082
cert-bund: WID-SEC-2024-0899
cert-bund: WID-SEC-2024-0892
cert-bund: WID-SEC-2024-0889
cert-bund: WID-SEC-2024-0885
cert-bund: WID-SEC-2024-0874
cert-bund: WID-SEC-2024-0869
cert-bund: WID-SEC-2024-0578
cert-bund: WID-SEC-2024-0564
cert-bund: WID-SEC-2024-0523
cert-bund: WID-SEC-2023-3182
cert-bund: WID-SEC-2023-3174
dfn-cert: DFN-CERT-2026-0097
dfn-cert: DFN-CERT-2025-3629
dfn-cert: DFN-CERT-2025-3272
dfn-cert: DFN-CERT-2025-2058
dfn-cert: DFN-CERT-2025-2037
dfn-cert: DFN-CERT-2025-1447
dfn-cert: DFN-CERT-2025-1177
dfn-cert: DFN-CERT-2025-1025
dfn-cert: DFN-CERT-2025-0660
dfn-cert: DFN-CERT-2025-0502
dfn-cert: DFN-CERT-2025-0294
dfn-cert: DFN-CERT-2025-0173
dfn-cert: DFN-CERT-2025-0165
dfn-cert: DFN-CERT-2025-0024
dfn-cert: DFN-CERT-2024-3171
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2024-2818
dfn-cert: DFN-CERT-2024-2759
dfn-cert: DFN-CERT-2024-2741
dfn-cert: DFN-CERT-2024-2682
dfn-cert: DFN-CERT-2024-2602
dfn-cert: DFN-CERT-2024-2573
dfn-cert: DFN-CERT-2024-2392
dfn-cert: DFN-CERT-2024-2210
dfn-cert: DFN-CERT-2024-2209
dfn-cert: DFN-CERT-2024-2194
dfn-cert: DFN-CERT-2024-2169
dfn-cert: DFN-CERT-2024-2048
dfn-cert: DFN-CERT-2024-2030
dfn-cert: DFN-CERT-2024-2028
dfn-cert: DFN-CERT-2024-1930
dfn-cert: DFN-CERT-2024-1895
dfn-cert: DFN-CERT-2024-1869
dfn-cert: DFN-CERT-2024-1868
dfn-cert: DFN-CERT-2024-1865
dfn-cert: DFN-CERT-2024-1862
dfn-cert: DFN-CERT-2024-1854
dfn-cert: DFN-CERT-2024-1846
dfn-cert: DFN-CERT-2024-1817
dfn-cert: DFN-CERT-2024-1794
dfn-cert: DFN-CERT-2024-1715
dfn-cert: DFN-CERT-2024-1698
dfn-cert: DFN-CERT-2024-1688
dfn-cert: DFN-CERT-2024-1655
dfn-cert: DFN-CERT-2024-1600
dfn-cert: DFN-CERT-2024-1443
dfn-cert: DFN-CERT-2024-1442
dfn-cert: DFN-CERT-2024-1413
dfn-cert: DFN-CERT-2024-1382
dfn-cert: DFN-CERT-2024-1380
dfn-cert: DFN-CERT-2024-1373
dfn-cert: DFN-CERT-2024-1260
dfn-cert: DFN-CERT-2024-1259
dfn-cert: DFN-CERT-2024-1108
dfn-cert: DFN-CERT-2024-1061
dfn-cert: DFN-CERT-2024-1029
dfn-cert: DFN-CERT-2024-1003
dfn-cert: DFN-CERT-2024-1000
dfn-cert: DFN-CERT-2024-0896
dfn-cert: DFN-CERT-2024-0779
dfn-cert: DFN-CERT-2024-0762
dfn-cert: DFN-CERT-2024-0744
dfn-cert: DFN-CERT-2024-0698
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2024-0633
dfn-cert: DFN-CERT-2024-0619
dfn-cert: DFN-CERT-2024-0618
dfn-cert: DFN-CERT-2024-0616
dfn-cert: DFN-CERT-2024-0597
dfn-cert: DFN-CERT-2024-0545
dfn-cert: DFN-CERT-2024-0526
dfn-cert: DFN-CERT-2024-0491
dfn-cert: DFN-CERT-2024-0480
dfn-cert: DFN-CERT-2024-0451
dfn-cert: DFN-CERT-2024-0440
dfn-cert: DFN-CERT-2024-0420
dfn-cert: DFN-CERT-2024-0388
dfn-cert: DFN-CERT-2024-0343
dfn-cert: DFN-CERT-2024-0306
dfn-cert: DFN-CERT-2024-0299
dfn-cert: DFN-CERT-2024-0285
dfn-cert: DFN-CERT-2024-0267
dfn-cert: DFN-CERT-2024-0251
dfn-cert: DFN-CERT-2024-0215
dfn-cert: DFN-CERT-2024-0211
dfn-cert: DFN-CERT-2024-0164
dfn-cert: DFN-CERT-2024-0154
dfn-cert: DFN-CERT-2024-0101
dfn-cert: DFN-CERT-2024-0092
dfn-cert: DFN-CERT-2024-0088
dfn-cert: DFN-CERT-2024-0067
dfn-cert: DFN-CERT-2024-0063
dfn-cert: DFN-CERT-2024-0062
dfn-cert: DFN-CERT-2024-0024
dfn-cert: DFN-CERT-2024-0022
dfn-cert: DFN-CERT-2024-0013
dfn-cert: DFN-CERT-2023-3219
dfn-cert: DFN-CERT-2023-3218
dfn-cert: DFN-CERT-2023-3210
dfn-cert: DFN-CERT-2023-3201
dfn-cert: DFN-CERT-2023-3200
dfn-cert: DFN-CERT-2023-3195
dfn-cert: DFN-CERT-2023-3193
dfn-cert: DFN-CERT-2023-3191
dfn-cert: DFN-CERT-2023-3185
dfn-cert: DFN-CERT-2023-3184
dfn-cert: DFN-CERT-2023-3183
dfn-cert: DFN-CERT-2023-3182
dfn-cert: DFN-CERT-2023-3175
```

Medium (CVSS: 5.9)
NVT: OpenBSD OpenSSH Information Disclosure Vulnerability (CVE-2020-14145)

**Product detection result**
`cpe:/a:openbsd:openssh:7.2p2`
`Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)`

**Summary**
OpenBSD OpenSSH is prone to an information disclosure vulnerability.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**
```
Installed version: 7.2p2
Fixed version:     8.5
Installation
path / port:       22/tcp
```

**Solution:**
**Solution type:** VendorFix
Update to version 8.5 or later.

**Affected Software/OS**
OpenBSD OpenSSH versions 5.7 through 8.4.

**Vulnerability Insight**
The client side in OpenSSH has an Observable Discrepancy leading to an information leak in the algorithm negotiation. This allows man-in-the-middle attackers to target initial connection attempts (where no host key for the server has been cached by the client).

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: `OpenBSD OpenSSH Information Disclosure Vulnerability (CVE-2020-14145)`
OID:1.3.6.1.4.1.25623.1.0.117785
Version used: `2021-11-22T14:03:31Z`

**Product Detection Result**
Product: `cpe:/a:openbsd:openssh:7.2p2`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
```
cve: CVE-2020-14145
url: http://www.openwall.com/lists/oss-security/2020/12/02/1
cert-bund: WID-SEC-2024-1591
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
cert-bund: WID-SEC-2024-1082
cert-bund: WID-SEC-2023-1969
cert-bund: WID-SEC-2023-1599
cert-bund: WID-SEC-2023-0068
cert-bund: CB-K20/0995
dfn-cert: DFN-CERT-2024-1260
dfn-cert: DFN-CERT-2020-2691
```

Medium (CVSS: 5.9)
NVT: Prefix Truncation Attacks in SSH Specification (Terrapin Attack)

**Product detection result**

```
cpe:/a:ietf:secure_shell_protocol
Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565
↪)
```

**Summary**

The remote SSH server is supporting an specific encryption algorithm or MAC. Parts of their SSH specification are vulnerable to a novel prefix truncation attack (a.k.a. Terrapin attack).

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

```
The remote SSH server supports the following possible affected client-to-server
↪encryption algorithm(s):
chacha20-poly1305@openssh.com
The remote SSH server supports the following possible affected server-to-client
↪encryption algorithm(s):
chacha20-poly1305@openssh.com
```

**Solution:**

**Solution type:** VendorFix

- Update OpenSSH to version 9.6 or later
- Update Apache MINA SSHD to version 2.12.0 or later
- For other products please contact the vendor for possible fixes / updates

Mitigation:

- To mitigate this protocol vulnerability, OpenSSH suggested a so-called 'strict kex' which alters the SSH handshake to ensure a Man-in-the-Middle attacker cannot introduce unauthenticated messages as well as convey sequence number manipulation across handshakes. Support for strict key exchange has been added to a variety of SSH implementations, including OpenSSH itself, PuTTY, libssh, and more.

Warning: To take effect, both the client and server must support this countermeasure.

As a stop-gap measure, peers may also (temporarily) disable the affected algorithms and use unaffected alternatives like AES-GCM instead until patches are available.

. . . continues on next page . . .

. . . continued from previous page . . .

**Affected Software/OS**
Systems supporting the following encryption algorithm and/or MACs:
- ChaCha20-Poly1305 (chacha20-poly1305@openssh.com) encryption algorithm
- CBC encryption algorithm and Encrypt-then-MAC (*-etm@openssh.com) MAC

**Vulnerability Insight**
Parts of the SSH specification are vulnerable to a novel prefix truncation attack (a.k.a. Terrapin attack), which allows a man-in-the-middle attacker to strip an arbitrary number of messages right after the initial key exchange, breaking SSH extension negotiation (RFC8308) in the process and thus downgrading connection security.

**Vulnerability Detection Method**
Checks the supported algorithms and MACs of the remote SSH server.
Note: This VT has a low QoD because mitigation is possible / available via software updates.
Details: `Prefix Truncation Attacks in SSH Specification (Terrapin Attack)`
OID:1.3.6.1.4.1.25623.1.0.114238
Version used: `2025-04-23T05:39:47Z`

**Product Detection Result**
Product: `cpe:/a:ietf:secure_shell_protocol`
Method: `SSH Protocol Algorithms Supported`
OID: 1.3.6.1.4.1.25623.1.0.105565)

**References**
`cve: CVE-2023-48795`
`cve: CVE-2024-41909`
`url: https://terrapin-attack.com`
`url: https://www.openssh.com/txt/release-9.6`
`url: https://lists.apache.org/thread/vwf1ot8wx1njyy8n19j5j2tcnjnozt3b`
`url: https://github.com/apache/mina-sshd/issues/445`
`url: https://github.com/apache/mina-sshd/pull/449`
`cert-bund: WID-SEC-2025-2359`
`cert-bund: WID-SEC-2025-0810`
`cert-bund: WID-SEC-2025-0168`
`cert-bund: WID-SEC-2025-0144`
`cert-bund: WID-SEC-2025-0139`
`cert-bund: WID-SEC-2024-3377`
`cert-bund: WID-SEC-2024-3320`
`cert-bund: WID-SEC-2024-3221`
`cert-bund: WID-SEC-2024-3198`
`cert-bund: WID-SEC-2024-3195`
`cert-bund: WID-SEC-2024-1913`
`cert-bund: WID-SEC-2024-1781`
`cert-bund: WID-SEC-2024-1701`
`cert-bund: WID-SEC-2024-1656`

. . . continues on next page . . .

. . . continued from previous page . . .

```
cert-bund: WID-SEC-2024-1655
cert-bund: WID-SEC-2024-1643
cert-bund: WID-SEC-2024-1642
cert-bund: WID-SEC-2024-1639
cert-bund: WID-SEC-2024-1637
cert-bund: WID-SEC-2024-1630
cert-bund: WID-SEC-2024-1474
cert-bund: WID-SEC-2024-1248
cert-bund: WID-SEC-2024-1228
cert-bund: WID-SEC-2024-1186
cert-bund: WID-SEC-2024-1082
cert-bund: WID-SEC-2024-0899
cert-bund: WID-SEC-2024-0892
cert-bund: WID-SEC-2024-0889
cert-bund: WID-SEC-2024-0885
cert-bund: WID-SEC-2024-0874
cert-bund: WID-SEC-2024-0869
cert-bund: WID-SEC-2024-0578
cert-bund: WID-SEC-2024-0564
cert-bund: WID-SEC-2024-0523
cert-bund: WID-SEC-2023-3174
dfn-cert: DFN-CERT-2026-0097
dfn-cert: DFN-CERT-2025-3629
dfn-cert: DFN-CERT-2025-3272
dfn-cert: DFN-CERT-2025-2941
dfn-cert: DFN-CERT-2025-2058
dfn-cert: DFN-CERT-2025-2037
dfn-cert: DFN-CERT-2025-1447
dfn-cert: DFN-CERT-2025-1177
dfn-cert: DFN-CERT-2025-1025
dfn-cert: DFN-CERT-2025-0660
dfn-cert: DFN-CERT-2025-0502
dfn-cert: DFN-CERT-2025-0294
dfn-cert: DFN-CERT-2025-0173
dfn-cert: DFN-CERT-2025-0165
dfn-cert: DFN-CERT-2025-0024
dfn-cert: DFN-CERT-2024-3171
dfn-cert: DFN-CERT-2024-2818
dfn-cert: DFN-CERT-2024-2759
dfn-cert: DFN-CERT-2024-2741
dfn-cert: DFN-CERT-2024-2602
dfn-cert: DFN-CERT-2024-2573
dfn-cert: DFN-CERT-2024-2392
dfn-cert: DFN-CERT-2024-2210
dfn-cert: DFN-CERT-2024-2209
dfn-cert: DFN-CERT-2024-2194
dfn-cert: DFN-CERT-2024-2169
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2024-2048
dfn-cert: DFN-CERT-2024-2030
dfn-cert: DFN-CERT-2024-2028
dfn-cert: DFN-CERT-2024-1930
dfn-cert: DFN-CERT-2024-1895
dfn-cert: DFN-CERT-2024-1869
dfn-cert: DFN-CERT-2024-1868
dfn-cert: DFN-CERT-2024-1865
dfn-cert: DFN-CERT-2024-1862
dfn-cert: DFN-CERT-2024-1854
dfn-cert: DFN-CERT-2024-1846
dfn-cert: DFN-CERT-2024-1817
dfn-cert: DFN-CERT-2024-1715
dfn-cert: DFN-CERT-2024-1698
dfn-cert: DFN-CERT-2024-1688
dfn-cert: DFN-CERT-2024-1655
dfn-cert: DFN-CERT-2024-1600
dfn-cert: DFN-CERT-2024-1443
dfn-cert: DFN-CERT-2024-1442
dfn-cert: DFN-CERT-2024-1413
dfn-cert: DFN-CERT-2024-1382
dfn-cert: DFN-CERT-2024-1380
dfn-cert: DFN-CERT-2024-1373
dfn-cert: DFN-CERT-2024-1260
dfn-cert: DFN-CERT-2024-1259
dfn-cert: DFN-CERT-2024-1108
dfn-cert: DFN-CERT-2024-1061
dfn-cert: DFN-CERT-2024-1029
dfn-cert: DFN-CERT-2024-1003
dfn-cert: DFN-CERT-2024-1000
dfn-cert: DFN-CERT-2024-0896
dfn-cert: DFN-CERT-2024-0779
dfn-cert: DFN-CERT-2024-0762
dfn-cert: DFN-CERT-2024-0744
dfn-cert: DFN-CERT-2024-0698
dfn-cert: DFN-CERT-2024-0633
dfn-cert: DFN-CERT-2024-0619
dfn-cert: DFN-CERT-2024-0618
dfn-cert: DFN-CERT-2024-0616
dfn-cert: DFN-CERT-2024-0597
dfn-cert: DFN-CERT-2024-0545
dfn-cert: DFN-CERT-2024-0526
dfn-cert: DFN-CERT-2024-0491
dfn-cert: DFN-CERT-2024-0451
dfn-cert: DFN-CERT-2024-0440
dfn-cert: DFN-CERT-2024-0420
dfn-cert: DFN-CERT-2024-0388
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2024-0343
dfn-cert: DFN-CERT-2024-0306
dfn-cert: DFN-CERT-2024-0299
dfn-cert: DFN-CERT-2024-0285
dfn-cert: DFN-CERT-2024-0267
dfn-cert: DFN-CERT-2024-0251
dfn-cert: DFN-CERT-2024-0215
dfn-cert: DFN-CERT-2024-0211
dfn-cert: DFN-CERT-2024-0164
dfn-cert: DFN-CERT-2024-0154
dfn-cert: DFN-CERT-2024-0101
dfn-cert: DFN-CERT-2024-0092
dfn-cert: DFN-CERT-2024-0088
dfn-cert: DFN-CERT-2024-0067
dfn-cert: DFN-CERT-2024-0063
dfn-cert: DFN-CERT-2024-0062
dfn-cert: DFN-CERT-2024-0024
dfn-cert: DFN-CERT-2024-0013
dfn-cert: DFN-CERT-2023-3219
dfn-cert: DFN-CERT-2023-3218
dfn-cert: DFN-CERT-2023-3210
dfn-cert: DFN-CERT-2023-3201
dfn-cert: DFN-CERT-2023-3200
dfn-cert: DFN-CERT-2023-3195
dfn-cert: DFN-CERT-2023-3193
dfn-cert: DFN-CERT-2023-3191
dfn-cert: DFN-CERT-2023-3185
dfn-cert: DFN-CERT-2023-3184
dfn-cert: DFN-CERT-2023-3183
dfn-cert: DFN-CERT-2023-3182
dfn-cert: DFN-CERT-2023-3175
```

Medium (CVSS: 5.3)
NVT: OpenSSH 'auth2-gss.c' User Enumeration Vulnerability - Linux

**Product detection result**

```
cpe:/a:openbsd:openssh:7.2p2
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)
```

**Summary**

OpenSSH is prone to a user enumeration vulnerability.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

. . . continues on next page . . .

. . . continued from previous page . . .

```
Installed version: 7.2p2
Fixed version:     None
Installation
path / port:       22/tcp
```

**Impact**
Successfully exploitation will allow a remote attacker to harvest valid user accounts, which may aid in brute-force attacks.

**Solution:**
**Solution type:** WillNotFix
No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.

**Affected Software/OS**
OpenSSH version 5.9 through 7.8.

**Vulnerability Insight**
The flaw exists in the 'auth-gss2.c' source code file of the affected software and is due to insufficient validation of an authentication request packet when the Guide Star Server II (GSS2) component is used on an affected system.

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: `OpenSSH 'auth2-gss.c' User Enumeration Vulnerability - Linux`
OID:1.3.6.1.4.1.25623.1.0.813888
Version used: `2021-05-28T07:06:21Z`

**Product Detection Result**
Product: `cpe:/a:openbsd:openssh:7.2p2`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
```
cve: CVE-2018-15919
url: https://bugzilla.novell.com/show_bug.cgi?id=1106163
url: https://seclists.org/oss-sec/2018/q3/180
cert-bund: WID-SEC-2024-1082
cert-bund: CB-K18/0885
dfn-cert: DFN-CERT-2024-1260
dfn-cert: DFN-CERT-2018-2293
dfn-cert: DFN-CERT-2018-2191
```

Medium (CVSS: 5.3)
NVT: OpenSSH < 7.6 'sftp-server' Security Bypass Vulnerability - Linux

**Product detection result**
`cpe:/a:openbsd:openssh:7.2p2`
`Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)`

**Summary**
OpenSSH is prone to a security bypass vulnerability.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

```
Installed version: 7.2p2
Fixed version:     7.6
Installation
path / port:       22/tcp
```

**Impact**
Successfully exploiting this issue allows local users to bypass certain security restrictions and perform unauthorized actions. This may lead to further attacks.

**Solution:**
**Solution type:** VendorFix
Update to version 7.6 or later.

**Affected Software/OS**
OpenSSH versions prior to 7.6 on Linux.

**Vulnerability Insight**
The flaw exists in the 'process_open' function in sftp-server.c script which does not properly prevent write operations in readonly mode.

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: `OpenSSH < 7.6 'sftp-server' Security Bypass Vulnerability - Linux`
OID:1.3.6.1.4.1.25623.1.0.812051
Version used: `2024-12-13T05:05:32Z`

**Product Detection Result**
Product: `cpe:/a:openbsd:openssh:7.2p2`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**

. . . continues on next page . . .

. . . continued from previous page . . .

```
cve: CVE-2017-15906
url: https://www.openssh.com/txt/release-7.6
url: http://www.securityfocus.com/bid/101552
url: https://github.com/openbsd/src/commit/a6981567e8e
cert-bund: WID-SEC-2024-1082
cert-bund: CB-K20/0041
cert-bund: CB-K18/0137
cert-bund: CB-K17/2126
cert-bund: CB-K17/2014
cert-bund: CB-K17/2002
dfn-cert: DFN-CERT-2024-1260
dfn-cert: DFN-CERT-2019-0362
dfn-cert: DFN-CERT-2018-2554
dfn-cert: DFN-CERT-2018-2191
dfn-cert: DFN-CERT-2018-2068
dfn-cert: DFN-CERT-2018-1828
dfn-cert: DFN-CERT-2018-1568
dfn-cert: DFN-CERT-2018-0150
dfn-cert: DFN-CERT-2017-2217
dfn-cert: DFN-CERT-2017-2100
dfn-cert: DFN-CERT-2017-2093
```

Medium (CVSS: 5.3)
NVT: OpenSSH < 7.8 User Enumeration Vulnerability - Linux

**Product detection result**

```
cpe:/a:openbsd:openssh:7.2p2
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)
```

**Summary**

OpenSSH is prone to a user enumeration vulnerability.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

```
Installed version: 7.2p2
Fixed version:     7.8
Installation
path / port:       22/tcp
```

**Impact**

Successfully exploitation will allow remote attacker to test whether a certain user exists or not (username enumeration) on a target OpenSSH server.

**Solution:**

. . . continues on next page . . .

. . . continued from previous page . . .

**Solution type:** VendorFix
Update to version 7.8 or later.

**Affected Software/OS**
OpenSSH versions 7.7 and prior.

**Vulnerability Insight**
The flaw is due to not delaying bailout for an invalid authenticating user until after the packet containing the request has been fully parsed, related to auth2-gss.c, auth2-hostbased.c, and auth2-pubkey.c

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: `OpenSSH < 7.8 User Enumeration Vulnerability - Linux`
OID:1.3.6.1.4.1.25623.1.0.813864
Version used: `2024-12-13T05:05:32Z`

**Product Detection Result**
Product: `cpe:/a:openbsd:openssh:7.2p2`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
```
cve: CVE-2018-15473
url: https://0day.city/cve-2018-15473.html
url: https://github.com/openbsd/src/commit/779974d35b4859c07bc3cb8a12c74b43b0a7d
↪1e0
cert-bund: WID-SEC-2024-1082
cert-bund: CB-K20/0041
cert-bund: CB-K18/1031
cert-bund: CB-K18/0873
dfn-cert: DFN-CERT-2024-1260
dfn-cert: DFN-CERT-2021-2178
dfn-cert: DFN-CERT-2020-2189
dfn-cert: DFN-CERT-2020-0228
dfn-cert: DFN-CERT-2019-2046
dfn-cert: DFN-CERT-2019-0857
dfn-cert: DFN-CERT-2019-0362
dfn-cert: DFN-CERT-2018-2293
dfn-cert: DFN-CERT-2018-2259
dfn-cert: DFN-CERT-2018-2191
dfn-cert: DFN-CERT-2018-1806
dfn-cert: DFN-CERT-2018-1696
```

Medium (CVSS: 5.3)
NVT: OpenSSH Information Disclosure Vulnerability (CVE-2016-20012)

**Product detection result**
`cpe:/a:openbsd:openssh:7.2p2`
`Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)`

**Summary**
OpenBSD OpenSSH is prone to an information disclosure vulnerability.

**Quality of Detection (QoD):** 50%

**Vulnerability Detection Result**

```
Installed version: 7.2p2
Fixed version:     None
Installation
path / port:       22/tcp
```

**Solution:**
**Solution type:** WillNotFix
No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.

**Affected Software/OS**
All currently OpenSSH versions are known to be affected.

**Vulnerability Insight**
OpenSSH allows remote attackers, who have a suspicion that a certain combination of username and public key is known to an SSH server, to test whether this suspicion is correct. This occurs because a challenge is sent only when that combination could be valid for a login session.

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: `OpenSSH Information Disclosure Vulnerability (CVE-2016-20012)`
OID:1.3.6.1.4.1.25623.1.0.117777
Version used: `2022-11-24T10:18:54Z`

**Product Detection Result**
Product: `cpe:/a:openbsd:openssh:7.2p2`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
`cve: CVE-2016-20012`

. . . continues on next page . . .

. . . continued from previous page . . .

```
url: https://github.com/openssh/openssh-portable/pull/270
url: https://rushter.com/blog/public-ssh-keys/
url: https://utcc.utoronto.ca/~cks/space/blog/tech/SSHKeysAreInfoLeak
cert-bund: WID-SEC-2024-1082
cert-bund: WID-SEC-2024-0229
cert-bund: CB-K21/0979
dfn-cert: DFN-CERT-2024-1260
```

Medium (CVSS: 5.0)
NVT: OpenBSD OpenSSH < 9.2 Unspecified Vulnerability

**Product detection result**

```
cpe:/a:openbsd:openssh:7.2p2
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)
```

**Summary**

OpenBSD OpenSSH is prone to an unspecified vulnerability.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

```
Installed version: 7.2p2
Fixed version:     9.2
Installation
path / port:       22/tcp
```

**Solution:**

**Solution type:** VendorFix

Update to version 9.2 or later.

**Affected Software/OS**

OpenBSD OpenSSH prior to version 9.2.

**Vulnerability Insight**

If the CanonicalizeHostname and CanonicalizePermittedCNAMEs options were enabled, and the system/libc resolver did not check that names in DNS responses were valid, then use of these options could allow an attacker with control of DNS to include invalid characters (possibly including wildcards) in names added to known_hosts files when they were updated. These names would still have to match the CanonicalizePermittedCNAMEs allow-list, so practical exploitation appears unlikely.

**Vulnerability Detection Method**

Checks if a vulnerable version is present on the target host.

Details: `OpenBSD OpenSSH < 9.2 Unspecified Vulnerability`

. . . continues on next page . . .

. . . continued from previous page . . .

OID:1.3.6.1.4.1.25623.1.0.104512
Version used: 2025-01-21T05:37:33Z

**Product Detection Result**
Product: cpe:/a:openbsd:openssh:7.2p2
Method: OpenSSH Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
url: https://www.openssh.com/releasenotes.html#9.2
url: https://www.openwall.com/lists/oss-security/2023/02/02/3

Medium (CVSS: 5.0)
NVT: OpenBSD OpenSSH < 9.3 Unspecified Vulnerability

**Product detection result**
cpe:/a:openbsd:openssh:7.2p2
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)

**Summary**
OpenBSD OpenSSH is prone to an unspecified vulnerability.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**
Installed version: 7.2p2
Fixed version: 9.3
Installation
path / port: 22/tcp

**Solution:**
**Solution type:** VendorFix
Update to version 9.3 or later.

**Affected Software/OS**
OpenBSD OpenSSH prior to version 9.3.

**Vulnerability Insight**
ssh(1): Portable OpenSSH provides an implementation of the getrrsetbyname(3) function if the standard library does not provide it, for use by the VerifyHostKeyDNS feature. A specifically crafted DNS response could cause this function to perform an out-of-bounds read of adjacent stack data, but this condition does not appear to be exploitable beyond denial-of-service to the ssh(1) client.

. . . continues on next page . . .

. . . continued from previous page . . .

The getrrsetbyname(3) replacement is only included if the system's standard library lacks this function and portable OpenSSH was not compiled with the ldns library (–with-ldns). getrrsetbyname(3) is only invoked if using VerifyHostKeyDNS to fetch SSHFP records.This problem was found by the Coverity static analyzer.

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: `OpenBSD OpenSSH < 9.3 Unspecified Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.104635
Version used: `2025-01-21T05:37:33Z`

**Product Detection Result**
Product: `cpe:/a:openbsd:openssh:7.2p2`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
`url: https://www.openssh.com/releasenotes.html#9.3`
`url: https://www.openwall.com/lists/oss-security/2023/03/15/8`

Medium (CVSS: 4.0)
NVT: OpenBSD OpenSSH < 9.1 Multiple Vulnerabilities

**Product detection result**
`cpe:/a:openbsd:openssh:7.2p2`
`Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)`

**Summary**
OpenBSD OpenSSH is prone to multiple vulnerabilities.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**
```
Installed version: 7.2p2
Fixed version:     9.1
Installation
path / port:       22/tcp
```

**Solution:**
**Solution type:** VendorFix
Update to version 9.1 or later.

**Affected Software/OS**

. . . continues on next page . . .

. . . continued from previous page . . .

OpenBSD OpenSSH prior to version 9.1.

**Vulnerability Insight**
The following vulnerabilities exist:
- A one-byte overflow in SSH- banner processing in ssh-keyscan.
- A double free() in error path of file hashing step in signing/verify code in ssh-keygen.
- A double-free in error path in ssh-keysign.

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: `OpenBSD OpenSSH < 9.1 Multiple Vulnerabilities`
OID:1.3.6.1.4.1.25623.1.0.127244
Version used: `2025-01-21T05:37:33Z`

**Product Detection Result**
Product: `cpe:/a:openbsd:openssh:7.2p2`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
`url: https://www.openssh.com/releasenotes.html#9.1`

[ return to 172.30.3.1 ]

### 2.1.4 Low general/tcp

Low (CVSS: 2.6)
NVT: TCP Timestamps Information Disclosure

**Summary**
The remote host implements TCP timestamps and therefore allows to compute the uptime.

**Quality of Detection (QoD):** 80%

**Vulnerability Detection Result**
```
It was detected that the host implements RFC1323/RFC7323.
The following timestamps were retrieved with a delay of 1 seconds in-between:
Packet 1: 415935276
Packet 2: 415936405
```

**Impact**
A side effect of this feature is that the uptime of the remote host can sometimes be computed.

**Solution:**

. . . continues on next page . . .

. . . continued from previous page . . .

**Solution type:** Mitigation
To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.
To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.
The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.
See the references for more information.

**Affected Software/OS**
TCP implementations that implement RFC1323/RFC7323.

**Vulnerability Insight**
The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

**Vulnerability Detection Method**
Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.
Details: `TCP Timestamps Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.80091
Version used: `2023-12-15T16:10:08Z`

**References**
`url: https://datatracker.ietf.org/doc/html/rfc1323`
`url: https://datatracker.ietf.org/doc/html/rfc7323`
`url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/d`
`↪ownload/details.aspx?id=9152`
`url: https://www.fortiguard.com/psirt/FG-IR-16-090`

[ return to 172.30.3.1 ]

### 2.1.5 Low 22/tcp

Low (CVSS: 2.6)
NVT: Weak MAC Algorithm(s) Supported (SSH)

**Product detection result**
`cpe:/a:ietf:secure_shell_protocol`
`Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565`
`↪)`

**Summary**

. . . continues on next page . . .

. . . continued from previous page . . .

The remote SSH server is configured to allow / support weak MAC algorithm(s).

**Quality of Detection (QoD):** 80%

**Vulnerability Detection Result**

```
The remote SSH server supports the following weak client-to-server MAC algorithm
↪(s):
umac-64-etm@openssh.com
umac-64@openssh.com
The remote SSH server supports the following weak server-to-client MAC algorithm
↪(s):
umac-64-etm@openssh.com
umac-64@openssh.com
```

**Solution:**
**Solution type:** Mitigation
Disable the reported weak MAC algorithm(s).

**Vulnerability Detection Method**
Checks the supported MAC algorithms (client-to-server and server-to-client) of the remote SSH server.
Currently weak MAC algorithms are defined as the following:
- MD5 based algorithms
- 96-bit based algorithms
- 64-bit based algorithms
- 'none' algorithm

Details: `Weak MAC Algorithm(s) Supported (SSH)`
OID:1.3.6.1.4.1.25623.1.0.105610
Version used: `2024-06-14T05:05:48Z`

**Product Detection Result**
Product: `cpe:/a:ietf:secure_shell_protocol`
Method: `SSH Protocol Algorithms Supported`
OID: 1.3.6.1.4.1.25623.1.0.105565)

**References**
`url: https://www.rfc-editor.org/rfc/rfc6668`
`url: https://www.rfc-editor.org/rfc/rfc4253#section-6.4`

Low (CVSS: 2.4)
NVT: OpenBSD OpenSSH < 10.1 Multiple Vulnerabilities

**Product detection result**
`cpe:/a:openbsd:openssh:7.2p2`

. . . continues on next page . . .

. . . continued from previous page . . .

Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)

**Summary**
OpenBSD OpenSSH is prone to multiple vulnerabilities.

**Quality of Detection (QoD):** 30%

**Vulnerability Detection Result**

```
Installed version: 7.2p2
Fixed version:     10.1
Installation
path / port:       22/tcp
```

**Solution:**
**Solution type:** VendorFix
Update to version 10.1 or later.

**Affected Software/OS**
OpenBSD OpenSSH versions prior to 10.1.

**Vulnerability Insight**
The following flaws exist:
- CVE-2025-61984: 'ssh' allows control characters in usernames that originate from certain possibly untrusted sources, potentially leading to code execution when a ProxyCommand is used. The untrusted sources are the command line and %-sequence expansion of a configuration file. (A configuration file that provides a complete literal username is not categorized as an untrusted source.)
- CVE-2025-61985: 'ssh' allows the '\0' character in an ssh:// URI, potentially leading to code execution when a ProxyCommand is used.

**Vulnerability Detection Method**
Checks if a vulnerable version is present on the target host.
Details: OpenBSD OpenSSH < 10.1 Multiple Vulnerabilities
OID:1.3.6.1.4.1.25623.1.0.119134
Version used: 2025-10-08T05:38:55Z

**Product Detection Result**
Product: cpe:/a:openbsd:openssh:7.2p2
Method: OpenSSH Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.108577)

**References**
cve: CVE-2025-61984
cve: CVE-2025-61985

. . . continues on next page . . .

. . . continued from previous page . . .

```
url: https://www.openssh.com/txt/release-10.1
url: https://www.openssh.com/security.html
url: https://www.openwall.com/lists/oss-security/2025/10/06/1
url: https://dgl.cx/2025/10/bash-a-newline-ssh-proxycommand-cve-2025-61984#_
cert-bund: WID-SEC-2025-2212
dfn-cert: DFN-CERT-2026-0218
dfn-cert: DFN-CERT-2025-3384
dfn-cert: DFN-CERT-2025-2768
```

[ return to 172.30.3.1 ]

### 2.1.6 Low general/icmp

Low (CVSS: 2.1)
NVT: ICMP Timestamp Reply Information Disclosure

**Summary**
The remote host responded to an ICMP timestamp request.

**Quality of Detection (QoD):** 80%

**Vulnerability Detection Result**

```
The following response / ICMP packet has been received:
- ICMP Type: 14
- ICMP Code: 0
```

**Impact**
This information could theoretically be used to exploit weak time-based random number generators in other services.

**Solution:**
**Solution type:** Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

**Vulnerability Insight**
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

**Vulnerability Detection Method**
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.

. . . continues on next page . . .

. . . continued from previous page . . .

Details: ICMP Timestamp Reply Information Disclosure
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: 2025-01-21T05:37:33Z

**References**
cve: CVE-1999-0524
url: https://datatracker.ietf.org/doc/html/rfc792
url: https://datatracker.ietf.org/doc/html/rfc2780
cert-bund: CB-K15/1514
cert-bund: CB-K14/0632
dfn-cert: DFN-CERT-2014-0658

[ return to 172.30.3.1 ]

### 2.1.7 Log general/tcp

Log (CVSS: 0.0)
NVT: Hostname Determination Reporting

**Summary**
The script reports information on how the hostname of the target was determined.

**Quality of Detection (QoD):** 80%

**Vulnerability Detection Result**
Hostname determination for IP 172.30.3.1:
Hostname|Source
ssh-vuln-dos.trabalho_vulnnet|Reverse-DNS

**Solution:**

**Log Method**
Details: Hostname Determination Reporting
OID:1.3.6.1.4.1.25623.1.0.108449
Version used: 2022-07-27T10:11:28Z

Log (CVSS: 0.0)
NVT: IP Forwarding Enabled - Active Check

**Summary**
Checks if the remote host has IP forwarding enabled.

**Quality of Detection (QoD):** 70%

. . . continues on next page . . .

. . . continued from previous page . . .

**Vulnerability Detection Result**

```
It was possible to route a TCP packet through the target host and received an an
↪swer which means IP forwarding is enabled.
```

**Solution:**

**Log Method**

Sends a crafted Local Link Layer (LLL) frame and checks the response.
Details: `IP Forwarding Enabled - Active Check`
OID:1.3.6.1.4.1.25623.1.0.147205
Version used: `2021-12-03T08:27:06Z`

**References**

`cve: CVE-1999-0511`

Log (CVSS: 0.0)
NVT: OS Detection Consolidation and Reporting

**Summary**

This script consolidates the OS information detected by several VTs and tries to find the best matching OS.
Furthermore it reports all previously collected information leading to this best matching OS. It also reports possible additional information which might help to improve the OS detection.
If any of this information is wrong or could be improved please consider to report these to the referenced community forum.

**Quality of Detection (QoD):** 80%

**Vulnerability Detection Result**

```
Best matching OS:
OS:           Ubuntu 16.04
Version:      16.04
CPE:          cpe:/o:canonical:ubuntu_linux:16.04
Found by VT:  1.3.6.1.4.1.25623.1.0.105586 (Operating System (OS) Detection (SSH
↪ Banner))
Concluded from SSH banner on port 22/tcp: SSH-2.0-OpenSSH_7.2p2 Ubuntu-4ubuntu2.
↪1
Setting key "Host/runs_unixoide" based on this information
```

**Solution:**

**Log Method**

Details: `OS Detection Consolidation and Reporting`

. . . continues on next page . . .

. . . continued from previous page . . .

OID:1.3.6.1.4.1.25623.1.0.105937
Version used: 2026-01-21T05:50:46Z

**References**
url: https://forum.greenbone.net/c/vulnerability-tests/7

Log (CVSS: 0.0)
NVT: OpenSSH Detection Consolidation

**Summary**
Consolidation of OpenSSH detections.

**Quality of Detection (QoD):** 80%

**Vulnerability Detection Result**

```
Detected OpenSSH Server
Version:       7.2p2
Location:      22/tcp
CPE:           cpe:/a:openbsd:openssh:7.2p2
Concluded from version/product identification result:
SSH-2.0-OpenSSH_7.2p2 Ubuntu-4ubuntu2.1
```

**Solution:**

**Log Method**
Details: OpenSSH Detection Consolidation
OID:1.3.6.1.4.1.25623.1.0.108577
Version used: 2024-12-13T05:05:32Z

**References**
url: https://www.openssh.com/

Log (CVSS: 0.0)
NVT: Traceroute

**Summary**
Collect information about the network route and network distance between the scanner host and the target host.

**Quality of Detection (QoD):** 80%

**Vulnerability Detection Result**

```
Network route from scanner (172.30.0.2) to target (172.30.3.1):
172.30.0.2
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
172.30.3.1
Network distance between scanner and target: 2
```

**Solution:**

**Vulnerability Insight**
For internal networks, the distances are usually small, often less than 4 hosts between scanner and target. For public targets the distance is greater and might be 10 hosts or more.

**Log Method**
A combination of the protocols ICMP and TCP is used to determine the route. This method is applicable for IPv4 only and it is also known as 'traceroute'.
Details: `Traceroute`
OID:1.3.6.1.4.1.25623.1.0.51662
Version used: `2022-10-17T11:13:19Z`

[ return to 172.30.3.1 ]

### 2.1.8 Log 22/tcp

Log (CVSS: 0.0)
NVT: SSH Protocol Versions Supported

**Summary**
Identification of SSH protocol versions supported by the remote SSH Server. Also reads the corresponding fingerprints from the service.

**Quality of Detection (QoD):** 95%

**Vulnerability Detection Result**

```
The remote SSH Server supports the following SSH Protocol Versions:
1.99
2.0
SSHv2 Fingerprint(s):
ecdsa-sha2-nistp256: eb:11:4c:fb:ce:22:57:53:af:9d:88:4d:39:03:89:3f
ssh-ed25519: 83:33:aa:e2:17:12:85:ba:42:a3:3c:16:ae:96:5b:a8
ssh-rsa: 7f:ac:9f:fd:5b:22:0c:f1:4f:25:0e:80:58:44:06:54
```

**Solution:**

**Log Method**
The following versions are tried: 1.33, 1.5, 1.99 and 2.0.
Details: `SSH Protocol Versions Supported`

. . . continues on next page . . .

. . . continued from previous page . . .

OID:1.3.6.1.4.1.25623.1.0.100259
Version used: 2024-06-17T08:31:37Z

Log (CVSS: 0.0)
NVT: SSH Protocol Algorithms Supported

**Summary**
This script detects which algorithms are supported by the remote SSH service.

**Quality of Detection (QoD):** 80%

**Vulnerability Detection Result**

```
The following options are supported by the remote SSH service:
kex_algorithms:
curve25519-sha256@libssh.org,ecdh-sha2-nistp256,ecdh-sha2-nistp384,ecdh-sha2-nis
↪tp521,diffie-hellman-group-exchange-sha256,diffie-hellman-group14-sha1
server_host_key_algorithms:
ssh-rsa,rsa-sha2-512,rsa-sha2-256,ecdsa-sha2-nistp256,ssh-ed25519
encryption_algorithms_client_to_server:
chacha20-poly1305@openssh.com,aes128-ctr,aes192-ctr,aes256-ctr,aes128-gcm@openss
↪h.com,aes256-gcm@openssh.com
encryption_algorithms_server_to_client:
chacha20-poly1305@openssh.com,aes128-ctr,aes192-ctr,aes256-ctr,aes128-gcm@openss
↪h.com,aes256-gcm@openssh.com
mac_algorithms_client_to_server:
umac-64-etm@openssh.com,umac-128-etm@openssh.com,hmac-sha2-256-etm@openssh.com,h
↪mac-sha2-512-etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64@openssh.com,uma
↪c-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1
mac_algorithms_server_to_client:
umac-64-etm@openssh.com,umac-128-etm@openssh.com,hmac-sha2-256-etm@openssh.com,h
↪mac-sha2-512-etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64@openssh.com,uma
↪c-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1
compression_algorithms_client_to_server:
none,zlib@openssh.com
compression_algorithms_server_to_client:
none,zlib@openssh.com
```

**Solution:**

**Log Method**
Details: SSH Protocol Algorithms Supported
OID:1.3.6.1.4.1.25623.1.0.105565
Version used: 2026-01-21T05:50:46Z

Log (CVSS: 0.0)
NVT: SSH Server type and version

**Summary**
This detects the SSH Server's type and version by connecting to the server and processing the buffer received.

**Quality of Detection (QoD):** 80%

**Vulnerability Detection Result**

```
Remote SSH server banner: SSH-2.0-OpenSSH_7.2p2 Ubuntu-4ubuntu2.1
Remote SSH supported authentication: password,publickey
Remote SSH text/login banner: (not available)
This is probably (a):
- OpenSSH
Concluded from remote connection attempt with credentials:
Login:    OpenVASVT
Password: OpenVASVT
```

**Solution:**

**Vulnerability Insight**
This information gives potential attackers additional information about the system they are attacking. Versions and Types should be omitted where possible.

**Log Method**
Details: `SSH Server type and version`
OID:1.3.6.1.4.1.25623.1.0.10267
Version used: `2025-11-13T05:40:19Z`

Log (CVSS: 0.0)
NVT: Services

**Summary**
This plugin performs service detection.

**Quality of Detection (QoD):** 80%

**Vulnerability Detection Result**
`An ssh server is running on this port`

**Solution:**

**Vulnerability Insight**

. . . continues on next page . . .

. . . continued from previous page . . .

This plugin attempts to guess which service is running on the remote port(s). For instance, it searches for a web server which could listen on another port than 80 or 443 and makes this information available for other check routines.

**Log Method**
Details: `Services`
OID:1.3.6.1.4.1.25623.1.0.10330
Version used: `2025-03-05T05:38:53Z`

Log (CVSS: 0.0)
NVT: PQC Key Exchange (KEX) Algorithm(s) Missing (SSH)

**Product detection result**
`cpe:/a:ietf:secure_shell_protocol`
`Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565 ↪)`

**Summary**
The remote SSH server is configured to NOT allow / support at least ONE Post-Quantum Cryptography (PQC) key exchange (KEX) algorithm(s).

**Quality of Detection (QoD):** 80%

**Vulnerability Detection Result**
`The remote SSH server is NOT supporting at least ONE PQC KEX algorithm.`

**Impact**
The connection may be vulnerable to 'store now, decrypt later' attacks.

**Solution:**
**Solution type:** Mitigation
Update the remote SSH server to a version supporting PQC KEX algorithms (e.g. OpenSSH 8.9 or later) and enable relevant PQC KEX algorithms accordingly.
Please see the references/manual of the remote SSH server and/or contact the vendor of it for more support.

**Log Method**
Checks the (previously collected) supported KEX algorithms of the remote SSH server.
Currently the following PQC KEX algorithms are defined / getting used for this check:
- sntrup761x25519-sha512@openssh.com
- sntrup761x25519-sha512
- mlkem768x25519-sha256
- sntrup4591761x25519-sha512@tinyssh.org
- ecdh-nistp256-kyber-512r3-sha256-d00@openquantumsafe.org

. . . continues on next page . . .

. . . continued from previous page . . .

- ecdh-nistp384-kyber-768r3-sha384-d00@openquantumsafe.org
- ecdh-nistp521-kyber-1024r3-sha512-d00@openquantumsafe.org
- x25519-kyber-512r3-sha256-d00@amazon.com
- mlkem1024nistp384-sha384
- mlkem768nistp256-sha256
- curve25519-frodokem1344-sha512@ssh.com
- ecdh-nistp521-kyber1024-sha512@ssh.com

Details: `PQC Key Exchange (KEX) Algorithm(s) Missing (SSH)`
OID:1.3.6.1.4.1.25623.1.0.119214
Version used: `2025-10-31T05:40:56Z`

**Product Detection Result**
Product: `cpe:/a:ietf:secure_shell_protocol`
Method: `SSH Protocol Algorithms Supported`
OID: 1.3.6.1.4.1.25623.1.0.105565)

**References**
`url: https://openssh.com/pq.html`
`url: https://quantumcomputingreport.com/openssh-10-0-introduces-default-post-qua`
`↪ntum-key-exchange-algorithm/`
`url: https://www.nist.gov/news-events/news/2024/08/nist-releases-first-3-finaliz`
`↪ed-post-quantum-encryption-standards`
`url: https://csrc.nist.gov/News/2024/postquantum-cryptography-fips-approved`
`url: https://www.forescout.com/blog/post-quantum-cryptography-the-real-risks-of-`
`↪not-adopting-it/`

[ return to 172.30.3.1 ]

### 2.1.9 Log general/CPE-T

Log (CVSS: 0.0)
NVT: CPE Inventory

**Summary**
This routine uses information collected by other routines about CPE identities of operating systems, services and applications detected during the scan.
Note: Some CPEs for specific products might show up twice or more in the output. Background: After a product got renamed or a specific vendor was acquired by another one it might happen that a product gets a new CPE within the NVD CPE Dictionary but older entries are kept with the older CPE.

**Quality of Detection (QoD):** 80%

**Vulnerability Detection Result**
`172.30.3.1|cpe:/a:ietf:secure_shell_protocol:2.0`

. . . continues on next page . . .

. . . continued from previous page . . .

172.30.3.1|cpe:/a:openbsd:openssh:7.2p2
172.30.3.1|cpe:/o:canonical:ubuntu_linux:16.04

**Solution:**

**Log Method**
Details: CPE Inventory
OID:1.3.6.1.4.1.25623.1.0.810002
Version used: 2022-07-27T10:11:28Z

**References**
url: https://nvd.nist.gov/products/cpe

[ return to 172.30.3.1 ]