<u>Dense CNN with Self-Attention for Time-</u> <u>Domain Speech Enhancement</u>

Ashutosh Pandey, DeLiang Wang

Outline

- Introduction
- Methodology
- Architecture
- Experiments
- Conclusion

Introduction

When the voice is polluted by background noise, not only the magnitude will be affected, but also the phase will also change, but the risk of adjusting the phase is extremely high, and it is very likely that the voice quality will become very bad.

Introduction

On the other hand, when processing signals in the time domain, the magnitude and phase can be changed together, and it is safer than processing the phase in the frequency domain.

Therefore, this paper proposes a time-domain speech enhancement model that combines Dense CNN and Self Attention, and uses a new loss function that simultaneously constrains speech and background sounds.

Methodology


```
U-Net

+
Dense Net


+
Sub-pixel Convolution

+
Self Attention
```


Input




U-Net



Dense Net



Methodology Sub-pixel Convolution



Self Attention

Causal: Softmax(Mask(QK^T))V

Non Causal: Softmax(QK^T)V

Loss

• Time-Domain Loss

$$\mathcal{L}_T(s,\hat{s}) = MSE(s,\hat{s})$$

• STFT Magnitude Loss


$$\mathcal{L}_{SM}(s,\hat{s}) = MAE(mag(s), mag(\hat{s}))$$

• Time-frequency Loss


$$\mathcal{L}_{TF}(s,\hat{s}) = \alpha \mathcal{L}_{T} + (1-\alpha) \mathcal{L}_{SM}$$

• Phase Constrained Magnitude Loss


$$\mathcal{L}_{PCM}(s,\hat{s}) = 0.5\mathcal{L}_{SM}(s,\hat{s}) + 0.5\mathcal{L}_{SM}(n,x-\hat{s})$$




Architecture




1 x 3 Conv




Architecture Self Attention Shape



Architecture Self Attention Shape



Dense Net Conv






- Sample rate: 16kHz
- Hamming window
 - size: 512
 - ∘ stride: 256
- Optimizer: Adam

Data Set

- 語音:WSJ0 SI-84 dataset
- 訓練用噪音: <u>10000 non-speech sounds from</u> <u>Sound Ideas</u>
- 測試用噪音: <u>babble and cafeteria noises from</u> <u>an Auditec CD</u>




	M	etric		STOI									
7	Test	nois	e		Bal	oble		Cafeteria					
Tes	st S	NR (dB)	-5	0	5	Avg.	-5	0	5	Avg.		
	Mixture				70.5	81.3	70.1	57.1	69.7	81.0	69.2		
	1	×	×	76.7	88.0	93.2	86.0	76.4	87.8	92.9	85.7		
	2	×	×	81.6	91.3	95.0	89.3	80.5	90.2	94.3	88.3		
Causal	2	✓	×	83.5	91.9	95.2	90.2	81.4	90.5	94.5	88.8		
Cal	2	✓	✓	84.9	92.2	95.3	90.8	82.1	90.7	94.6	89.1		
	2	×	1	85.3	92.3	95.4	91.0	82.3	90.8	94.7	89.3		
	1	×	1	83.9	91.8	95.2	90.3	81.0	90.3	94.5	88.6		
al	3	X	×	84.7	92.5	95.7	90.9	83.1	91.4	95.0	89.8		
ıns	3	✓	×	86.6	92.9	95.7	91.7	84.1	91.7	95.0	90.3		
ိုင်	3	✓	1	87.9	93.5	96.0	92.4	85.0	92.0	95.2	90.8		
Non-causal	3	×	✓	87.9	93.5	96.1	92.5	85.0	92.1	95.3	90.8		
Z	1	×	✓	83.7	91.5	95.2	90.1	80.1	89.8	94.3	88.1		
	m	Dil.	Att.										

	M	etric		PESQ									
-	Test noise				Bal	oble		Cafeteria					
Tes	st S	NR (dB)	-5	0	5	Avg.	-5	0	5	Avg.		
	Mixture				1.82	2.12	1.83	1.46	1.77	2.12	1.78		
	1	×	×	1.90	2.39	2.76	2.35	2.02	2.49	2.84	2.45		
	2	×	×	2.13	2.70	3.08	2.64	2.17	2.68	3.05	2.63		
Causal	2	✓	×	2.23	2.75	3.12	2.70	2.21	2.70	3.07	2.66		
Cal	2	✓	✓	2.30	2.77	3.14	2.74	2.23	2.71	3.08	2.67		
•	2	×	✓	2.34	2.81	3.17	2.77	2.24	2.72	3.09	2.68		
	1	×	1	2.23	2.72	3.09	2.68	2.15	2.62	3.01	2.59		
al	3	X	X	2.37	2.88	3.22	2.82	2.34	2.82	3.16	2.77		
ıns	3	✓	×	2.53	2.96	3.24	2.91	2.44	2.88	3.19	2.84		
-C5	3	✓	✓	2.61	3.02	3.32	2.98	2.47	2.91	3.24	2.87		
Non-causal	3	×	✓	2.61	3.04	3.33	2.99	2.45	2.91	3.23	2.86		
Z	1	×	✓	2.24	2.71	3.09	2.68	2.13	2.59	2.98	2.57		
	m	Dil.	Att.										

	M	etric		SNR									
	Test noise				Bal	bble		Cafeteria					
Tes	st S	NR (dB)	-5	0	5	Avg.	-5	0	5	Avg.		
	Mi	xture		-5.0	0.0	5.0	0	-5.0	0.0	5.0	0.0		
	1	×	×	5.5	9.9	13.4	9.6	6.5	10.4	13.4	10.1		
	2	×	×	7.4	11.5	14.7	11.2	7.7	11.4	14.4	11.2		
ısa	2	✓	×	7.7	11.8	15.0	11.5	7.9	11.5	14.5	11.3		
Causal	2	✓	✓	8.2	12.0	15.1	11.8	8.2	11.7	14.7	11.5		
	2	×	1	8.5	12.1	15.1	11.9	8.2	11.7	14.7	11.5		
	1	×	1	7.9	11.8	15.0	11.6	7.9	11.5	14.5	11.3		
al	3	X	X	8.2	12.2	15.2	11.9	8.3	11.8	14.7	11.6		
ıns	3	✓	×	9.1	12.5	15.3	12.3	8.7	12.0	14.8	11.8		
ိုင်	3	✓	✓	9.6	12.9	15.7	12.7	8.9	12.2	15.0	12.0		
Non-causal	3	×	✓	9.6	12.9	15.8	12.8	8.9	12.3	15.1	12.1		
Z	1	×	✓	8.3	12.0	15.2	11.8	7.8	11.4	14.6	11.3		
	m	Dil.	Att.										

ch	3	le?	Metric	STOI									
0.0	Approach Causal?	tim	Test Noise		Bab	ble		Cafeteria					
Idd		Real-time	Test SNR	-5 db	0 dB	5 dB	AVG	-5 dB	0 dB	5 dB	AVG		
A		Re	Mixture	58.4	70.5	81.3	70.1	57.1	69.7	81.0	69.2		
a)	X	X	BLSTM [12]	77.4	85.8	91.0	84.7	76.1	84.7	90.5	83.7		
b)	×	×	GRN [13]	80.2	88.9	93.4	87.5	79.4	88.0	92.9	86.8		
	✓	✓	GCRN [19]	82.4	90.9	94.8	89.4	79.1	89.3	94.0	87.5		
c)	$ \times $	×	NC-GCRN [19]	87.0	93.0	95.6	91.9	84.1	91.7	95.1	90.3		
	✓	×	SEGAN-T [20]	81.5	90.3	94.1	88.6	79.8	89.5	93.5	87.6		
	✓	×	AECNN-SM [24]	82.6	91.5	95.1	89.7	81.1	90.7	94.5	88.8		
	✓	✓	TCNN [25]	82.8	91.3	94.8	89.6	80.6	89.8	94.0	88.1		
	✓	✓	DCN-T	85.3	92.3	95.4	91.0	82.3	90.8	94.7	89.3		
(d)	✓	✓	DCN-SM	85.2	92.7	95.8	91.2	82.5	91.3	95.1	89.6		
	/	✓	DCN-PCM	85.1	92.7	95.8	91.2	82.5	91.3	95.1	89.6		
	$ \times $	×	NC-DCN-T	87.9	93.5	96.1	92.5	85.0	92.1	95.3	90.8		
	$ \times $	×	NC-DCN-SM	89.1	94.2	96.5	93.3	85.8	92.9	95.8	91.5		
	X	×	NC-DCN-PCM	89.0	94.3	96.6	93.3	85.6	93.0	95.9	91.5		

ch	[5]	le?	Metric				PE	SQ			
Coa	sal?	al-time	Test Noise		Bab	ble		Cafeteria			
Approach	Caus	al-	Test SNR	-5 db	0 dB	5 dB	AVG	-5 dB	0 dB	5 dB	AVG
A		Re	Mixture	1.56	1.82	2.12	1.83	1.46	1.77	2.12	1.78
a)	X	X	BLSTM [12]	1.97	2.37	2.69	2.34	2.01	2.38	2.51	2.30
b)	×	×	GRN [13]	2.16	2.63	2.97	2.59	2.23	2.62	2.96	2.60
c)	✓	✓	GCRN [19]	2.17	2.70	3.07	2.65	2.10	2.60	2.99	2.56
()	$ \times $	×	NC-GCRN [19]	2.53	2.96	3.25	2.91	2.40	2.85	3.17	2.81
	✓	×	SEGAN-T [20]	2.11	2.62	2.97	2.57	2.15	2.61	2.94	2.57
	/	×	AECNN-SM [24]	2.21	2.80	3.17	2.73	2.23	2.76	3.12	2.70
	✓	✓	TCNN [25]	2.18	2.70	3.06	2.65	2.14	2.62	2.98	2.58
	✓	√	DCN-T	2.34	2.81	3.17	2.77	2.24	2.72	3.09	2.68
(d)	✓	✓	DCN-SM	2.35	2.93	3.31	2.86	2.33	2.85	3.22	2.80
	/	✓	DCN-PCM	2.31	2.91	3.30	2.84	2.29	2.82	3.22	2.78
	$ \times $	×	NC-DCN-T	2.61	3.04	3.33	2.99	2.45	2.91	3.23	2.86
	$ \times $	×	NC-DCN-SM	2.75	3.19	3.46	3.13	2.61	3.07	3.37	3.02
	X	×	NC-DCN-PCM	2.71	3.18	3.48	3.12	2.56	3.07	3.39	3.01



Demo

https://web.cse.ohiostate.edu/~wang.77/pnl/demo/PandeyDCN.html

Conclusion

- This paper proposes a time-domain-based DCN model with a time-frequency loss function to obtain good results in the task of speech enhancement.
- Although SM loss has good results in the evaluation indicators of STOI and PESQ, when judged by human ears, the effect of PCM loss is closer to clean speech.

Conclusion

- The author mentioned that DNN-based speech enhancement methods are not easy to generalize to speech that has not been learned.
- Time domain loss can help improve SNR, and frequency domain loss can improve scores on STOI and PESQ.