<u>Dense CNN with Self-Attention for Time-</u> <u>Domain Speech Enhancement</u>

Ashutosh Pandey, DeLiang Wang

Outline

- Introduction
- Methodology
- Architecture
- Experiments
- Conclusion

Introduction

When the voice is polluted by background noise, not only the magnitude will be affected, but also the phase will also change, but the risk of adjusting the phase is extremely high, and it is very likely that the voice quality will become very bad.

Introduction

On the other hand, when processing signals in the time domain, the magnitude and phase can be changed together, and it is safer than processing the phase in the frequency domain.

Therefore, this paper proposes a time-domain speech enhancement model that combines Dense CNN and Self Attention, and uses a new loss function that simultaneously constrains speech and background sounds.

Methodology


```
U-Net

+
Dense Net


+
Sub-pixel Convolution

+
Self Attention
```


Input




U-Net



Dense Net



Methodology Sub-pixel Convolution



Self Attention

Causal: Softmax(Mask(QK^T))V

Non Causal: Softmax(QK^T)V

Loss

• Time-Domain Loss

$$\mathcal{L}_T(s,\hat{s}) = MSE(s,\hat{s})$$

• STFT Magnitude Loss


$$\mathcal{L}_{SM}(s,\hat{s}) = MAE(mag(s), mag(\hat{s}))$$

• Time-frequency Loss


$$\mathcal{L}_{TF}(s,\hat{s}) = \alpha \mathcal{L}_{T} + (1-\alpha) \mathcal{L}_{SM}$$

Phase Constrained Magnitude Loss


$$\mathcal{L}_{PCM}(s,\hat{s}) = 0.5\mathcal{L}_{SM}(s,\hat{s}) + 0.5\mathcal{L}_{SM}(n,x-\hat{s})$$




Architecture



1 x 3 Conv




Architecture Self Attention Shape



Architecture Self Attention Shape

Dense Net Conv






- Sample rate: 16kHz
- Hamming window
 - size: 512
 - ∘ stride: 256
- Optimizer: Adam


Data Set

- 語音:WSJ0 SI-84 dataset
- 訓練用噪音:
- 測試用噪音:



	M	etric		STOI							PESQ								SNR								
	Test	noise	e	Babble Cafeteria							Bal	oble		Cafeteria				Babble				Cafeteria					
Te	est S	NR (d	dB)	-5	0	5	Avg.	-5	0	5	Avg.	-5	0	5	Avg.	-5	0	5	Avg.	-5	0	5	Avg.	-5	0	5	Avg.
	Mixture			58.4	70.5	81.3	70.1	57.1	69.7	81.0	69.2	1.56	1.82	2.12	1.83	1.46	1.77	2.12	1.78	-5.0	0.0	5.0	0	-5.0	0.0	5.0	0.0
Causal	1	X	×	76.7	88.0	93.2	86.0	76.4	87.8	92.9	85.7	1.90	2.39	2.76	2.35	2.02	2.49	2.84	2.45	5.5	9.9	13.4	9.6	6.5	10.4	13.4	10.1
	2	×	×	81.6	91.3	95.0	89.3	80.5	90.2	94.3	88.3	2.13	2.70	3.08	2.64	2.17	2.68	3.05	2.63	7.4	11.5	14.7	11.2	7.7	11.4	14.4	11.2
	2	✓	×	83.5	91.9	95.2	90.2	81.4	90.5	94.5	88.8	2.23	2.75	3.12	2.70	2.21	2.70	3.07	2.66	7.7	11.8	15.0	11.5	7.9	11.5	14.5	11.3
	2	✓	✓	84.9	92.2	95.3	90.8	82.1	90.7	94.6	89.1	2.30	2.77	3.14	2.74	2.23	2.71	3.08	2.67	8.2	12.0	15.1	11.8	8.2	11.7	14.7	11.5
	2	×	✓	85.3	92.3	95.4	91.0	82.3	90.8	94.7	89.3	2.34	2.81	3.17	2.77	2.24	2.72	3.09	2.68	8.5	12.1	15.1	11.9	8.2	11.7	14.7	11.5
	1	×	✓	83.9	91.8	95.2	90.3	81.0	90.3	94.5	88.6	2.23	2.72	3.09	2.68	2.15	2.62	3.01	2.59	7.9	11.8	15.0	11.6	7.9	11.5	14.5	11.3
Te	3	X	×	84.7	92.5	95.7	90.9	83.1	91.4	95.0	89.8	2.37	2.88	3.22	2.82	2.34	2.82	3.16	2.77	8.2	12.2	15.2	11.9	8.3	11.8	14.7	11.6
Non-causal	3	✓	×	86.6	92.9	95.7	91.7	84.1	91.7	95.0	90.3	2.53	2.96	3.24	2.91	2.44	2.88	3.19	2.84	9.1	12.5	15.3	12.3	8.7	12.0	14.8	11.8
	3	✓	✓	87.9	93.5	96.0	92.4	85.0	92.0	95.2	90.8	2.61	3.02	3.32	2.98	2.47	2.91	3.24	2.87	9.6	12.9	15.7	12.7	8.9	12.2	15.0	12.0
	3	×	✓	87.9	93.5	96.1	92.5	85.0	92.1	95.3	90.8	2.61	3.04	3.33	2.99	2.45	2.91	3.23	2.86	9.6	12.9	15.8	12.8	8.9	12.3	15.1	12.1
	1	×	✓	83.7	91.5	95.2	90.1	80.1	89.8	94.3	88.1	2.24	2.71	3.09	2.68	2.13	2.59	2.98	2.57	8.3	12.0	15.2	11.8	7.8	11.4	14.6	11.3
	m	Dil.	Att.																								

		· -	D. C. a. a. a.					CTOI							DE	00			
Approach	13] je	Metric	STOI								PESQ							
	Causal	-time	Test Noise		Bab	ble		Cafeteria				Babble				Cafeteria			
		E	Test SNR	-5 db	0 dB	5 dB	AVG	-5 dB	0 dB	5 dB	AVG	-5 db	0 dB	5 dB	AVG	-5 dB	0 dB	5 dB	AVG
		Re	Mixture	58.4	70.5	81.3	70.1	57.1	69.7	81.0	69.2	1.56	1.82	2.12	1.83	1.46	1.77	2.12	1.78
a)	X	×	BLSTM [12]	77.4	85.8	91.0	84.7	76.1	84.7	90.5	83.7	1.97	2.37	2.69	2.34	2.01	2.38	2.51	2.30
b)	×	X	GRN [13]	80.2	88.9	93.4	87.5	79.4	88.0	92.9	86.8	2.16	2.63	2.97	2.59	2.23	2.62	2.96	2.60
	1	1	GCRN [19]	82.4	90.9	94.8	89.4	79.1	89.3	94.0	87.5	2.17	2.70	3.07	2.65	2.10	2.60	2.99	2.56
c)	×	×	NC-GCRN [19]	87.0	93.0	95.6	91.9	84.1	91.7	95.1	90.3	2.53	2.96	3.25	2.91	2.40	2.85	3.17	2.81
	1	X	SEGAN-T [20]	81.5	90.3	94.1	88.6	79.8	89.5	93.5	87.6	2.11	2.62	2.97	2.57	2.15	2.61	2.94	2.57
	✓	×	AECNN-SM [24]	82.6	91.5	95.1	89.7	81.1	90.7	94.5	88.8	2.21	2.80	3.17	2.73	2.23	2.76	3.12	2.70
	✓	✓	TCNN [25]	82.8	91.3	94.8	89.6	80.6	89.8	94.0	88.1	2.18	2.70	3.06	2.65	2.14	2.62	2.98	2.58
	✓	✓	DCN-T	85.3	92.3	95.4	91.0	82.3	90.8	94.7	89.3	2.34	2.81	3.17	2.77	2.24	2.72	3.09	2.68
(d)	✓	✓	DCN-SM	85.2	92.7	95.8	91.2	82.5	91.3	95.1	89.6	2.35	2.93	3.31	2.86	2.33	2.85	3.22	2.80
	✓	✓	DCN-PCM	85.1	92.7	95.8	91.2	82.5	91.3	95.1	89.6	2.31	2.91	3.30	2.84	2.29	2.82	3.22	2.78
	×	×	NC-DCN-T	87.9	93.5	96.1	92.5	85.0	92.1	95.3	90.8	2.61	3.04	3.33	2.99	2.45	2.91	3.23	2.86
	×	×	NC-DCN-SM	89.1	94.2	96.5	93.3	85.8	92.9	95.8	91.5	2.75	3.19	3.46	3.13	2.61	3.07	3.37	3.02
	X	×	NC-DCN-PCM	89.0	94.3	96.6	93.3	85.6	93.0	95.9	91.5	2.71	3.18	3.48	3.12	2.56	3.07	3.39	3.01



Demo

```
https://web.cse.ohio-
state.edu/~wang.77/pnl/demo/PandeyDCN.html
```

Conclusion

- This paper proposes a time-domain-based DCN model with a time-frequency loss function to obtain good results in the task of speech enhancement.
- Although SM loss has good results in the evaluation indicators of STOI and PESQ, when judged by human ears, the effect of PCM loss is closer to clean speech.

Conclusion

- The author mentioned that DNN-based speech enhancement methods are not easy to generalize to speech that has not been learned.
- Time domain loss can help improve SNR, and frequency domain loss can improve scores on STOI and PESQ.