

Dynamic Resonance Rooting: A Computational Framework for Complex Adaptive Systems

Christopher Woodyard
Vers3Dynamics

Abstract--Dynamic Resonance Rooting (DRR) is a computational framework for studying complex adaptive systems through resonance detection, directed rooting analysis, and normalized resonance-depth diagnostics. DRR analyzes time-indexed observables to identify persistent modal structure, estimate candidate lead-lag relationships among variables, and summarize stability-related evidence using spectral concentration, temporal persistence, phase coherence, and amplitude stability. The framework connects nonlinear dynamics, spectral analysis, information-theoretic influence diagnostics, state-space review, and reproducible research software. Its reference implementation provides Python modules for resonance detection, rooting, depth scoring, state-space diagnostics, reporting, validation-readiness artifacts, and deterministic benchmark examples. A reproduced coupled-oscillator benchmark detects a 12.5 Hz target frequency with zero frequency error and recovers the expected $\text{dim}_0 \rightarrow \text{dim}_1$ lag relation. Additional extension paths are specified for spectral-state propagation, multi-agent belief coherence, and online depth-weight governance. DRR is intended for hypothesis generation, monitoring design, and model-review workflows; domain conclusions require independent validation.

Index Terms--complex adaptive systems, resonance detection, transfer entropy, lead-lag analysis, state-space diagnostics, reproducible research, model-risk review.

I. INTRODUCTION

Complex adaptive systems (CAS) often exhibit structure that is visible before it is reducible to a single linear explanation. Their behavior can include nonlinear feedback, emergent order, adaptation, path dependence, and abrupt regime transitions. These properties make CAS scientifically valuable but methodologically difficult: a descriptive account may identify patterns without quantifying them, while a narrow model may impose assumptions that erase the very dynamics under study.

DRR addresses this gap by connecting observed dynamic signatures to candidate drivers or stability anchors. It is framed as a pipeline that starts from time-indexed observables, extracts resonant structure, estimates directed lead-lag roots, scores the depth of the resulting pattern, and exports evidence that can be reproduced and reviewed.

The framework is implemented in public research software. The repository gives DRR a computational surface with modules, tests, examples, documentation, and an explicit review boundary. The software does not validate DRR for operational use by itself. It does, however, make assumptions, calculations, and outputs inspectable, which is a prerequisite for scientific refinement.

The contributions are precise operational meanings for resonance, rooting, and resonance depth; a structure that separates theory, computation, validation, and limitations; a mapping from DRR concepts to the reference implementation; a conservative validation agenda that avoids unsupported causal or supervisory claims; and an extension path for spectral-state propagation, belief coherence, and adaptive depth weighting.

II. BACKGROUND AND PROBLEM STATEMENT

A. Complex Adaptive Systems

CAS analysis is challenged by nonlinearity, delayed feedback, high-dimensional coupling, and changing state spaces. Standard linear correlation can miss directional or lagged relationships; purely mechanistic models can be underidentified; and black-box prediction can be hard to interpret. DRR therefore targets an intermediate role: it organizes diagnostic evidence for hypothesis generation, monitoring design, and model review.

The framework inherits ideas from nonlinear dynamics, spectral analysis, information-theoretic influence measures, early-warning indicators, and state-space modeling. Its central claim is not that every CAS is literally an oscillator. Rather, many CAS emit time-series traces in which dominant modes, persistence, coherence, and lagged coupling are informative about the current regime and its stability.

B. Analytical Gap

The core analytical gap is the lack of a single reproducible workflow that jointly asks: which modes are persistent, which variables appear to lead or respond, how stable is the detected structure, and what evidence is available for independent review?

DRR addresses this gap only when its outputs remain diagnostic. A high rooting score is a lead-lag candidate, not proof that one variable causes another. A high resonance-depth score indicates coherent and persistent modal evidence under the chosen window and transformation, not universal resilience. These boundaries are essential to making the framework credible.

III. DYNAMIC RESONANCE ROOTING FRAMEWORK

A. Inputs and Notation

Let X in $\mathbb{R}^{(T \times n)}$ denote a time-indexed matrix with T observations and n variables. Each column x_i is treated as an observable trace. Optional preprocessing may include interpolation, differencing, log differencing, standardization, and time-delay embedding. The output is a set of resonance records, a directed rooting matrix, per-dimension depth scores, and review artifacts.

The recommended DRR workflow is intentionally modular so that domain experts can replace a component without replacing the whole framework. For example, FFT may be replaced by Welch power spectral density for noisy signals, lagged correlation may be replaced by transfer entropy when available, and state-space diagnostics may be omitted when the data do not support them.




Fig. 1. DRR pipeline integrated with the reference implementation.

B. Resonance Detection

A resonance is defined operationally as a persistent modal structure detected in an observable trace or reconstructed state. In the implementation, supported detection methods include FFT, Welch power spectral density, and Markov-state persistence. The resonance record stores dominant frequency candidates, peak magnitudes or state persistence information, confidence metadata, and the spectrum used for review.

This definition avoids metaphorical ambiguity. Resonance does not need to mean physical vibration; it means a reviewable recurrent mode under an explicit detection method. The interpretation of that mode remains domain-specific.

C. Rooting Analysis

Rooting is defined as the estimation of directed lead-lag structure among observables. For each ordered pair (i, j), DRR searches lags and assigns a score to the evidence that x_i precedes x_j . The current repository uses deterministic lagged correlation by default and transfer entropy when the optional backend is available. Surrogate p-values and significant-edge records make the result auditable.

Rooting should be read as diagnostic influence evidence, not causal identification. DRR reports should therefore avoid phrases such as proves control, proves causality, or predicts policy. The correct language is that DRR detects candidate lead-lag structure whose scientific meaning requires independent validation.

D. Resonance Depth

Resonance depth is a normalized composite score for the stability and coherence of a detected mode. The current software implementation computes four components: spectral concentration S, temporal persistence P, phase coherence C, and amplitude stability A. The composite is clipped to [0, 1] and reported with component details and a simple confidence interval:

$$D = \text{clip}_{[0,1]}(0.35*S + 0.25*P + 0.25*C + 0.15*A)$$

This formula should be treated as a versioned design choice rather than a universal law. Its value is that it exposes what is being rewarded: concentrated spectral power, persistence over windows, coherent phase behavior, and stable amplitude.

IV. SOFTWARE INTEGRATION

The GitHub repository at <https://github.com/topherchris420/dynamic-resonance-rooting> serves as the reference implementation for this manuscript. The package, named `drf-framework`, exposes a Python API centered on `DynamicResonanceRooting`. The inspected main-branch checkout was commit 7da497a.

The software turns key terms into executable interfaces. `ResonanceDetector` implements FFT, Welch, and Markov-state detection. `RootingAnalyzer` estimates directed lead-lag scores and reports the backend used. `DepthCalculator` computes the composite resonance-depth metric. State-space utilities attach transition, measurement, covariance, likelihood, stability, and impulse-response diagnostics. Reporting utilities serialize results into JSON, Markdown, CSV, plots, and reviewer-readable summaries.

The current repository test suite was run after inspection: 43/43 tests passed. This does not constitute domain validation, but it supports the implementation-readiness claim for the reference software surface.

DRR Concept	Operational Meaning	Repository Surface
Resonance	Persistent modal/state structure detected from a signal.	<code>ResonanceDetector</code> ; <code>detect_resonances</code>
Rooting	Directed lead-lag evidence between variables.	<code>RootingAnalyzer</code> ; <code>analyze_influence_network</code>
Depth	Composite stability and coherence score in [0, 1].	<code>DepthCalculator</code> ; <code>calculate_resonance_depths</code>
State-space review	Diagnostic transition and impulse-response summaries.	<code>state_space.py</code>
Validation readiness	Model-risk cards, event backtests, shadow logs.	<code>validation.py</code> ; <code>supervision.py</code>

Table I. Mapping from DRR concepts to repository modules.

A. Minimal Research Workflow

A typical workflow loads a numeric matrix, initializes `DynamicResonanceRooting` with an embedding dimension, time delay, and sampling rate, and calls `analyze_system`. In multivariate mode, the result contains resonance records, resonance-depth details, agent belief states, an optional influence network, rooting-analysis records, and optional state-space diagnostics.

Software integration should be cited as a research artifact, not as empirical proof. The repository contributes reproducibility, inspection, and extension capacity; scientific claims still require benchmark expansion, domain-specific data, and external review.

B. Reproduction Artifact

The reproduction harness evaluates a synthetic coupled-oscillator benchmark with a known target frequency and known directed lag. A live run reports exact frequency recovery at 12.5 Hz, zero frequency error, a resonance depth of 0.9043, and detection of the expected edge `dim_0 -> dim_1` at lag 2 using lagged correlation.

Metric	Reproduced Value
Benchmark	Known-frequency coupled oscillator
Target and detected frequency	12.5 Hz and 12.5 Hz
Frequency error	0.0 Hz
Expected edge	<code>dim_0 -> dim_1</code>
Expected lag	2 samples
Rooting method	<code>lagged_correlation</code>
Resonance depth	0.9042969836929234
Depth components	S=0.9566, P=0.7788, C=0.9884, A=0.8512

Table II. Repository reproduction result (DRR composite v1).

V. VALIDATION, LIMITATIONS, AND GOVERNANCE

A central requirement for DRR is sharp limitation language. DRR outputs diagnostic evidence. They do not establish causality, domain truth, supervisory findings, clinical conclusions, or operational decisions. Any high-stakes use requires independent conceptual-soundness review, implementation verification, outcomes analysis, benchmark comparison, ongoing monitoring, and governance approval for a specific intended use.

A validation program should proceed in layers. Synthetic benchmarks should vary noise, lag, coupling strength, sampling rate, missingness, and regime shifts. Semi-synthetic benchmarks should inject known oscillatory and directed structures into real background signals. Domain benchmarks should compare DRR against simpler baselines and accepted methods. Finally, shadow-mode deployment should record analyst reviews without allowing DRR outputs to affect decisions.

The reference implementation already supports part of this program through deterministic examples, expected artifacts, model-risk cards, event backtests, shadow-review logs, and explainability summaries. These artifacts are central because they bridge an analytical proposal and a reviewable research method.

VI. APPLICATION PATTERNS

In physical and biological systems, DRR can be used to summarize dominant modes, phase coherence, and candidate coupling paths before deeper mechanistic modeling. In policy and supervisory analytics, DRR can help prioritize questions about recurring metric patterns, peer-group differences, and lagged observables while preserving a strict boundary between diagnostic evidence and policy judgment.

For AI and multi-agent systems, DRR offers a way to monitor oscillatory behavior, coordination loops, or delayed responses in high-dimensional traces. Its usefulness will depend on careful feature design, stable sampling, and independent checks that detected modes are not artifacts of logging cadence or preprocessing.

Across all domains, the recommended posture is the same: use DRR to ask better questions, not to replace domain science. The framework is most defensible when paired with transparent preprocessing, sensitivity analysis, baseline comparisons, and reviewer-facing caveats.

VII. DISCUSSION AND FUTURE WORK

DRR is strongest when it narrows from an all-purpose theory of CAS to a reproducible diagnostic framework. The software integration supports this focus by showing exactly where resonance, rooting, depth, state-space diagnostics, and validation artifacts live. The next research step is benchmark expansion.

Future work should formalize the statistical properties of the depth score, compare rooting methods across controlled datasets, add rolling-window transition studies, evaluate robustness under noise and missing data, and document failure modes. Future versions should also separate the stable core from experimental extensions such as transfer entropy backends, QBist belief updates, neural operators, or domain-specific dashboards.

VIII. EXTENSION PATH

Three extension paths can widen what the depth composite represents without changing the default `dr_r_composite_v1` behavior. They should remain additive and opt-in until benchmarked across controlled data, null surrogates, and domain-specific holdouts.

A. Spectral-State Propagation

A spectral-state propagator would score one-block-ahead predictability in the Fourier domain. Its fidelity N can be calibrated against phase-randomized surrogates rather than an arbitrary threshold. This guards against accidental overlap leakage and keeps the score interpretable as structure beyond a null spectral baseline.

$$N = \text{clip}_{[0,1]}(1 - r_t / r_{\text{null}})$$

B. Belief Coherence

A population layer can track whether independently seeded estimators converge on similar belief states when observing the same resonance-depth stream. Belief coherence B is defined as one minus mean pairwise Jensen-Shannon divergence across the population.

$$B = 1 - \text{mean}_{\{i < j\}} \text{JSD}(p_i || p_j)$$

C. Depth-Weight Governance

A depth governor can learn event-informed weights while preserving the published `v1` weights as a shrinkage prior. With limited event evidence, the prior dominates; as labeled outcomes accumulate, the online component can receive more weight.

$$\lambda = \lambda_{\text{bda0}} / (\lambda_{\text{bda0}} + n_{\text{events}})$$

$$w = \lambda_{\text{bda0}} * w_{\text{prior}} + (1 - \lambda_{\text{bda0}}) * w_{\text{online}}$$

Extension	Adds	Validation Gate
Spectral-state propagation	Predictability beyond phase-randomized nulls.	Noise, leakage, and regime-shift tests.
Belief coherence	Cross-estimator agreement signal.	Calibration across seeds and windows.
Depth governor	Event-informed adaptive weights.	Holdout labels and no-lookahead checks.

Table III. Extension path and validation gates.

IX. CONCLUSION

Dynamic Resonance Rooting is best understood as a computational framework for organizing resonance, lead-lag, and stability diagnostics in complex adaptive systems. The framework is defined operationally, grounded in a public Python implementation, bounded by reviewable limitations, and paired with a concrete validation agenda. Extension paths for nonlinear predictability, belief coherence, and adaptive weighting can broaden the framework, but they should remain opt-in until independently benchmarked. This structure can support research discussion, software review, and future empirical validation without overstating what the current evidence proves.

REFERENCES

- [1] J. H. Holland, *Adaptation in Natural and Artificial Systems*. Cambridge, MA, USA: MIT Press, 1992.
- [2] M. Mitchell, *Complexity: A Guided Tour*. New York, NY, USA: Oxford University Press, 2009.
- [3] S. H. Strogatz, *Nonlinear Dynamics and Chaos*, 2nd ed. Boulder, CO, USA: Westview Press, 2015.
- [4] F. Takens, Detecting strange attractors in turbulence, in *Dynamical Systems and Turbulence*, Warwick 1980, D. Rand and L.-S. Young, Eds. Berlin, Germany: Springer, 1981, pp. 366-381.
- [5] P. Welch, The use of fast Fourier transform for the estimation of power spectra, *IEEE Trans. Audio Electroacoust.*, vol. 15, no. 2, pp. 70-73, 1967.
- [6] T. Schreiber, Measuring information transfer, *Phys. Rev. Lett.*, vol. 85, no. 2, pp. 461-464, 2000.
- [7] M. Scheffer et al., Early-warning signals for critical transitions, *Nature*, vol. 461, pp. 53-59, 2009.
- [8] V. Dakos et al., Methods for detecting early warnings of critical transitions in time series, *PLOS ONE*, vol. 7, no. 7, 2012.
- [9] R. E. Kalman, A new approach to linear filtering and prediction problems, *J. Basic Eng.*, vol. 82, no. 1, pp. 35-45, 1960.
- [10] E. N. Lorenz, Deterministic nonperiodic flow, *J. Atmos. Sci.*, vol. 20, no. 2, pp. 130-141, 1963.
- [11] R. M. May, Simple mathematical models with very complicated dynamics, *Nature*, vol. 261, pp. 459-467, 1976.
- [12] H. Kantz and T. Schreiber, *Nonlinear Time Series Analysis*, 2nd ed. Cambridge, U.K.: Cambridge University Press, 2004.
- [13] E. Bradley and H. Kantz, Nonlinear time-series analysis revisited, *Chaos*, vol. 25, no. 9, 2015.
- [14] C. Woodyard, *Dynamic Resonance Rooting Framework*, GitHub repository, 2026. [Online]. Available: <https://github.com/topherchris420/dynamic-resonance-rooting>.
- [15] C. Woodyard, *Dynamic Resonance Rooting*, source PDF `ssm-5285993.pdf`, 2025.
- [16] C. E. Fuchs and R. Schack, Quantum-Bayesian coherence, *Rev. Mod. Phys.*, vol. 85, no. 4, pp. 1693-1715, 2013.
- [17] Z. Li et al., Fourier neural operator for parametric partial differential equations, in *Proc. Int. Conf. Learning Representations*, 2021.