294. Flip Game II

Medium 380 34 Add to List Share

You are playing the following Flip Game with your friend: Given a string that contains only these two characters: `+` and `-`, you and your friend take turns to flip two **consecutive** `"++"` into `"--"`. The game ends when a person can no longer make a move and therefore the other person will be the winner.

Write a function to determine if the starting player can guarantee a win.

Example:

```
Input: s = "++++"
Output: true
Explanation: The starting player can guarantee a win by flipping the middle "++" to become "+--+".
```

Follow up:
Derive your algorithm's runtime complexity.

Accepted 52,141 Submissions 104,605

Seen this question in a real interview before? Yes No

Contributor

Companies

Related Topics

Similar Questions

Java

Autocomplete

```
class Solution {
    public boolean canWin(String s) {
        if (s == null || s.length() < 2) return false;
        char[] ss = s.toCharArray();
        return canWin();
    }
    boolean canWin() {
        for (int is = 0; is <= len-2; ++is) {
            if (ss[is] == '+' && ss[is+1] == '+') {
                ss[is] = '-'; ss[is+1] = '-';
                boolean wins = !canWin();
                ss[is] = '+'; ss[is+1] = '+';
                if (wins) return true;
            }
        }
        return false;
    }
}
```

Need more space? Try using full screen mode! Got it!

Your previous code was restor

Consol... Contribute