1058. Minimize Rounding Error to Meet Target

Medium 63 59 Add to List Share

Given an array of prices `[p1,p2...,pn]` and a `target`, round each price `pi` to `Roundi(pi)` so that the rounded array `[Round1(p1),Round2(p2)...,Roundn(pn)]` sums to the given `target`. Each operation `Roundi(pi)` could be either `Floor(pi)` or `Ceil(pi)`.

Return the string `"-1"` if the rounded array is impossible to sum to `target`. Otherwise, return the smallest rounding error, which is defined as Σ |$Round_i(p_i)$ - (p_i)| for i from 1 to n, as a string with three places after the decimal.

Example 1:

```
Input: prices = ["0.700","2.800","4.900"], target = 8
Output: "1.000"
Explanation:
Use Floor, Ceil and Ceil operations to get (0.7 - 0) + (3 - 2.8) +
(5 - 4.9) = 0.7 + 0.2 + 0.1 = 1.0 .
```

Example 2:

```
Input: prices = ["1.500","2.500","3.500"], target = 10
Output: "-1"
Explanation:
It is impossible to meet the target.
```

Note:

1. `1 <= prices.length <= 500`.
2. Each string of prices `prices[i]` represents a real number which is between 0 and 1000 and has exactly 3 decimal places.
3. `target` is between 0 and 1000000.

Accepted 2,850 | Submissions 6,837

Seen this question in a real interview before? Yes No

Contributor 

Companies

```
class Solution {
    public String
minimizeError(String[]
int target) {

    }
}
```

Console