Question 1

Not yet answered

Marked out of 1.00

While inserting the elements 71, 65, 84, 69, 67, 83 in an empty binary search tree (BST) in the sequence shown, the element in the lowest level is

Select one:

- a. 67
- b. 69
- c. 83
- d. 65

Question 2

Not yet answered

Marked out of 1.00

Pick the best statement for the below program:

```
#include<stdio.h>

void fun(int n)
{
int idx;
int arr1[n] = {0};
int arr2[n];

for (idx=0; idx<n; idx++)
arr2[idx] = 0;
}

int main()
{
fun(4);
return 0;
}
```

Select one:

- a. Definition of both arr1 and arr2 is incorrect because variable is used to specify the size of array. That's why compile error.
- b. Initialization of arr1 is incorrect. arr1 can't be initialized due to its size being specified as variable. That's why compile error.
- c. Apart from definition of arr1 arr2, initialization of arr1 is also incorrect. arr1 can't be initialized due to its size being specified as variable. That's why compile error.
- d. No compile error. The program would define and initializes both arrays to ZERO.

Question 3

Not yet answered

Marked out of 1.00

Given:

```
3. class Test {
4. public static void main(String [] args) {
5. printAll(args);
6. }
7. public static void printAll(String[] lines) {
8. for(int i=0;i<lines.length;i++){
9. System.out.println(lines[i]);
10. Thread.currentThread().sleep(1000);
11. } } }
```

The static method Thread.currentThread() returns a reference to the currently executing Thread object.

What is the result of this code?

Select one:

- **a. Each String in the array lines will print, and there is no guarantee there will be a pause because currentThread() may not retrieve this thread**
- **b. This code will not compile**
- **c. Each String in the array lines will print, with no pause in between because this method is not executed in a Thread**
- **d. Each String in the array lines will print, with exactly a 1-second pause between lines**
- **e. Each String in the lines array will print, with at least a one-second pause between lines**

Question **4**

Not yet answered

Marked out of 1.00

Choose the correct option to fill the ?1 and ?2 so that the program prints an input string in reverse order.
Assume that the input string is terminated by a new line character.

```
#include <stdio.h>
void wrt_it (void);
int main (void)
{
printf("Enter Text");
printf ("\n");
wrt_ it();
printf ("\n");
return 0;
}
void wrt_it (void)
{
int c;
if (?1)
wrt_it();
?2
}
```

Select one:

- **a. ?1 is (c = getchar()); ! = '\n'**
  ?2 is getchar(c);
- **b. ?1 is getchar() ! = '\n'**
  ?2 is getchar(c);
- **c. ?1 is c! = '\n'**
  ?2 is putchar(c);
- **d. ?1 is (c = getchar()) ! = '\n'**
  ?2 is putchar(c);

Question 5

Not yet answered

Marked out of 1.00

Given:

```
3. class MyThread extends Thread {
4. public static void main(String [] args) {
5. MyThread t = new MyThread();
6. Thread x = new Thread(t);
7. x.start();
8. }
9. public void run() {
10. for(int i=0;i<3;++i) {
11. System.out.print(i + "..");
12. } } }
```

What is the result of this code?

Select one:

- **a. Compilation fails**
- **b. 0..1..2..**
- **c. 1..2..3..**
- **d. 0..1..2..3..**
- **e. An exception occurs at runtime**

Question 6

Not yet answered

Marked out of 1.00

Given:

```
1. public class TestObj {
2. public static void main(String[] args) {
3. Object o = new Object() {
4. public boolean equals(Object obj) {
5. return true;
6. }
7. }
8. System.out.println(o.equals("Fred"));
9. }
10. }
```

What is the result?

Select one:

- **a. Compilation fails because of an error on line 3**
- **b. fred**
- **c. Compilation fails because of an error on a line other than 3, 4, or 8**
- **d. true**
- **e. Compilation fails because of an error on line 8**
- **f. Compilation fails because of an error on line 4**
- **g. An exception occurs at runtime**

Question 7

Not yet answered

Marked out of 1.00

Assume you have a class that holds two private variables: a and b.
Which of the following pairs can prevent concurrent access problems in that class? (Choose all that apply.)

Select one or more:

- [ ] **a. public synchronized int read(){return a+b;}**
public synchronized void set(int a, int b){this.a=a;this.b=b;}

- [ ] **b. public int read(){synchronized(this){return a+b;}}**
public void set(int a, int b){synchronized(this){this.a=a;this.b=b;}}

- [ ] **c. public synchronized(this) int read(){return a+b;}**
public synchronized(this) void set(int a, int b){this.a=a;this.b=b;}

- [ ] **d. public int read(){synchronized(a){return a+b;}}**
public void set(int a, int b){synchronized(b){this.a=a;this.b=b;}}

- [ ] **e. public int read(){return a+b;}**
public void set(int a, int b){this.a=a;this.b=b;}

- [ ] **f. public int read(){synchronized(a){return a+b;}}**
public void set(int a, int b){synchronized(a){this.a=a;this.b=b;}}

Question 8

Not yet answered

Marked out of 1.00

```
#include <iostream>
using namespace std;
class sample1
{
float i, j;
};
class sample2
{
int x, y;
public:
sample2 (int a, int b)
{
x = a;
y = b;
}
int result()
{
return x + y;
}
};
int main ()
{
sample1 d;
sample2 * padd;
padd = (sample2*) &d;
cout<< padd->result();
return 0;
}
```

Select one:

- **a. 20**
- **b. random number**
- **c. runtime error**
- **d. runtime error or random number**

Question **9**

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

class base {
int arr[10];
};

class b1: virtual public base { };

class b2: virtual public base { };

class derived: public b1, public b2 {};

int main(void)
{
cout << sizeof(derived);
return 0;
}
```

Select one:

- **a. 0**
- **b. 48**
- **c. 4**
- **d. 80**

Question **10**

Not yet answered

Marked out of 1.00

```
class Mycpp
{
int Mycpp()
{
cout<<"Constructor";
return 0;
}
};
int main()
{
Mycpp obj;
return 0;
}
```

Select one:

- **a. 0**
- **b. Compilation Error**
- **c. Constructor**
- **d. Runtime Error**

Question **11**

Not yet answered

Marked out of 1.00

Which are true about a method-local inner class? (Choose all that apply.)

Select one or more:

- ☐ **a. It must be marked final**
- ☐ **b. It can be marked public**
- ☐ **c. It can access private members of the enclosing class**
- ☐ **d. It can be marked static**
- ☐ **e. It can be marked abstract**

Question **12**

Not yet answered

Marked out of 1.00

Output of following program under the assumption that numbers are stored in 2's complement form.

```
#include<stdio.h>
int main()
{
printf("%c\n", ~('C' * -1));
return 0;
}
```

Select one:

- ○ **a. C**
- ○ **b. A**
- ○ **c. Compiler Error**
- ○ **d. B**

Question **13**

Not yet answered

Marked out of 1.00

Given a method declared as
public static <E extends Number> List<E> process(List<E> nums)

A programmer wants to use this method like this
// INSERT DECLARATIONS HERE
output = process(input);

Which pairs of declarations could be placed at // INSERT DECLARATIONS HERE to allow the code to compile? (Choose all that apply.)

Select one or more:

- ☐ **a. List<Integer> input = null;**
  List<Integer> output = null;
- ☐ **b. List<Number> input = null;**
  List<Number> output = null;
- ☐ **c. ArrayList<Integer> input = null;**
  ArrayList<Integer> output = null;
- ☐ **d. ArrayList<Integer> input = null;**
  List<Number> output = null;
- ☐ **e. List<Number> input = null;**
  ArrayList<Integer> output = null;
- ☐ **f. ArrayList<Integer> input = null;**
  List<Integer> output = null;
- ☐ **g. None of the above**

Question **14**

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

class base {
int arr[10];
};

class b1: public base { };

class b2: public base { };

class derived: public b1, public b2 {};

int main(void)
{
cout << sizeof(derived);
return 0;
}
```

Select one:

- **a. 80**
- **b. 0**
- **c. 4**
- **d. 40**

Question **15**

Not yet answered

Marked out of 1.00

The seven elements A, B, C, D, E, F and G are pushed onto a stack in reverse order, i.e., starting from G.
The stack is popped five times and each element is inserted into a queue.
Two elements are deleted from the queue and pushed back onto the stack. Now, one element is popped from the stack.
The popped item is _____.

Select one:

- **a. A**
- **b. B**
- **c. F**
- **d. G**

Question **16**

Not yet answered

Marked out of 1.00

Pick the best statement for the below program:

```
#include<stdio.h>

int size = 4;
int arr[size];

int main()
{
if(arr[0])
printf("Initialized to ZERO");
else
printf("Not initialized to ZERO");

return 0;
}
```

Select one:

- **a. No compile error and it'll print either "Initialized to ZERO" or "Not initialized to ZERO" depending on what value is present at arr[0] at a particular run of the program.**
- **b. No compile error and it'll print "Not initialized to ZERO".**
- **c. Compile error because size of arr has been defined using variable outside any function.**
- **d. No compile error and it'll print "Initialized to ZERO".**

Question **17**

Not yet answered

Marked out of 1.00

Pick the best statement for the following program snippet:

```
#include <stdio.h>

int main()
{
int var; /*Suppose address of var is 2000 */

void *ptr = &var;
*ptr = 5;
printf("var=%d and *ptr=%d",var,*ptr);
1
return 0;
}
```

Select one:

- **a. It will print "var=5 and *ptr=5"**
- **b. It will print "var=5 and *ptr=XYZ" where XYZ is some random address**
- **c. Compile error**
- **d. It will print "var=5 and *ptr=2000"**

Question **18**

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;
void Execute(int &x, int y = 200)
{
int TEMP = x + y;
x+= TEMP;
if(y!=200)
cout<<TEMP<<x<<y<<"--";
}
int main()
{
int A=50, B=20;
cout<<A<<B<<"--";
Execute(A,B);
cout<<A<<B<<"--";
return 0;
}
```

Select one:

- **a. 5020--70120200--5020**
- **b. 5020--5020--**
- **c. 5020--7012020--12020--**
- **d. 5020--7050200--5020--**

Question **19**

Not yet answered

Marked out of 1.00

Given:

```
1. public class HorseTest {
2. public static void main(String[] args) {
3. class Horse {
4. public String name;
5. public Horse(String s) {
6. name = s;
7. }
8. }
9. Object obj = new Horse("Zippo");
10. System.out.println(obj.name);
11. }
12. }
```

What is the result?

Select one:

- **a. Compilation fails because of an error on line 3**
- **b. Compilation fails because of an error on line 10**
- **c. Zippo**
- **d. An exception occurs at runtime at line 10**
- **e. Compilation fails because of an error on line 9**

Question **20**

Not yet answered

Marked out of 1.00

Which collection class(es) allows you to grow or shrink its size and provides indexed access to
its elements, but whose methods are not synchronized? (Choose all that apply.)

Select one or more:

- ☐ **a. java.util.Vector**
- ☐ **b. java.util.HashSet**
- ☐ **c. java.util.ArrayList**
- ☐ **d. java.util.LinkedHashSet**
- ☐ **e. java.util.List**
- ☐ **f. java.util.PriorityQueue**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=11636)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved. Version 4.2

/