Question 1

Not yet answered

Marked out of 1.00

Which of the following overloaded functions are NOT allowed in C++?

1) Function declarations that differ only in the return type

```
int fun(int x, int y);
void fun(int x, int y);
```

2) Functions that differ only by static keyword in return type

```
int fun(int x, int y);
static int fun(int x, int y);
```

3)Parameter declarations that differ only in a pointer * versus an array []

```
int fun(int *ptr, int n);
int fun(int ptr[], int n);
```

4) Two parameter declarations that differ only in their default arguments

```
int fun( int x, int y);
int fun( int x, int y = 10);
```

Select one:

- a. **All except 1)**
- b. **All except 2)**
- c. **All except 2 and 4**
- d. **All of the above**

Question **2**

Not yet answered

Marked out of 1.00

Given two files:

```
1. package pkgA;
2. public class Foo {
3. int a = 5;
4. protected int b = 6;
5. public int c = 7;
6. }
```

```
3. package pkgB;
4. import pkgA.*;
5. public class Baz {
6. public static void main(String[] args) {
7. Foo f = new Foo();
8. System.out.print(" " + f.a);
9. System.out.print(" " + f.b);
10. System.out.print(" " + f.c);
11. }
12. }
```

What is the result? (Choose all that apply.)

Select one or more:

- ☐ **a. Compilation fails with an error on line 8**
- ☐ **b. Compilation fails with an error on line 7**
- ☐ **c. 5 followed by an exception**
- ☐ **d. Compilation fails with an error on line 9**
- ☐ **e. 5 6 7**
- ☐ **f. Compilation fails with an error on line 10**

Question 3

Not yet answered

Marked out of 1.00

Given:

```
1. enum Animals {
2. DOG("woof"), CAT("meow"), FISH("burble");
3. String sound;
4. Animals(String s) { sound = s; }
5. }
6. class TestEnum {
7. static Animals a;
8. public static void main(String [] args) {
9. System.out.println(a.DOG.sound + " " + a.FISH.sound);
10. }
11. }
```

What is the result?

Select one:

- **a. Multiple compilation errors**
- **b. Compilation fails due to an error on line 9**
- **c. Compilation fails due to an error on line 4**
- **d. Compilation fails due to an error on line 3**
- **e. woof burble**
- **f. Compilation fails due to an error on line 2**

Question **4**

Not yet answered

Marked out of 1.00

Choose the best statement with respect to following three program snippets in C Language

```
/*Program Snippet 1 with for loop*/
for (i = 0; i < 10; i++)
{
/*statement1*/
continue;
/*statement2*/
}

/*Program Snippet 2 with while loop*/
i = 0;
while (i < 10)
{
/*statement1*/
continue;
/*statement2*/
i++;
}

/*Program Snippet 3 with do-while loop*/
i = 0;
do
{
/*statement1*/
continue;
/*statement2*/
i++;
}while (i < 10);
```

Select one:

- **a. continue can't be used with all the three loops in C.**
- **b. None of the above is correct.**
- **c. All the loops are equivalent i.e. any of the three can be chosen and they all will perform exactly same.**
- **d. After hitting the continue; statement in all the loops, the next expression to be executed would be controlling expression (i.e. i < 10) in all the 3 loops.**

Question **5**

Not yet answered

Marked out of 1.00

Which of the following is true in CPP?

Select one:

- **a. Static methods cannot be overloaded.**
- **b. Non-static data members can be accessed by static methods.**
- **c. Static methods can only access static members (data and methods)**
- **d. Static data members can only be accessed by static methods.**

Question 6

Not yet answered

Marked out of 1.00

What does below SQL statement describe?

SELECT CustomerName, Address + ‘, ‘ + City + ‘, ‘ + Country AS Address
FROM Customers;

Select one:

- **a. Alias named Address column will be created and under this Address, City and Country will be printed as combined statement.**
- **b. All of these are wrong**
- **c. Alias named Address will be created for Country columns**
- **d. Alias named Address column will be created and under this all CustomerName, address, city and country will be printed as combined statement**

Question 7

Not yet answered

Marked out of 1.00

output of the following in C

```
#include <stdio.h>
int main()
{
const int x;
x = 10;
printf("%d", x);
return 0;
}
```

Select one:

- **a. Compiler Error**
- **b. 10**
- **c. Runtime Error**
- **d. 0**

Question 8

Not yet answered

Marked out of 1.00

Generalization is a

Select one:

- **a. none of these**
- **b. has a relationship**
- **c. is a relationship**
- **d. depends on scenario**

Question **9**

Not yet answered

Marked out of 1.00

Which of the following is aggregate function in SQL?

Select one:

- **a. Avg**
- **b. Ordered by**
- **c. distinct**
- **d. Select**

Question **10**

Not yet answered

Marked out of 1.00

What can be requested from any object of the class to affect behavior?

Select one:

- **a. instance**
- **b. attribute**
- **c. operation**
- **d. object**

Question **11**

Not yet answered

Marked out of 1.00

Which is called as a virtual table in SQL?

Select one:

- **a. INNER JOIN**
- **b. VIEW**
- **c. None of these**
- **d. JOIN**

Question
12

Not yet answered

Marked out of 1.00

A typical "switch" body looks as follows:

```
switch (controlling_expression)
{
case label1:
/*label1 statements*/
break;
case label2:
/*label1 statements*/
break;
default:
/*Default statements*/
}
```

Which of the following statement is not correct statement?

Select one:

- **a. "switch" body can have the "default" label at first i.e. before all the other "case" labels. It would still compile.**
- **b. "switch" body may not have any "case" label at all and it would still compile.**
- **c. "switch" body may contain more than one "case" labels where the label value of these "case" is same and it would still compile.**
  If "switch" controlling expression results in this "case" label value, the "case" which is placed first would be executed.
- **d. "switch" body may not have the "default" label and it would still compile.**
- **e. "switch" body may not have any "break" statement and it would still compile.**

Question **13**

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

int &fun()
{
int x = 10;
return x;
}
int main()
{
fun() = 30;
cout << fun();
return 0;
}
```

Select one:

- **a. May cause runtime error**
- **b. May cause compiler error**
- **c. 0**
- **d. Always works fine.**

Question **14**

Not yet answered

Marked out of 1.00

Interaction diagram captures the behavior of a _____

Select one:

- **a. None of these**
- **b. Multiple Use case**
- **c. Single Use case**
- **d. Only selected Use cases**

Question **15**

Not yet answered

Marked out of 1.00

In the context of the following printf() in C, pick the best statement.

```
i) printf("%d",8);
ii) printf("%d",090);
iii) printf("%d",00200);
iv) printf("%d",0007000);
```

Select one:

- **a. Only i), iii) and iv) would compile successfully. They will print 8, 128 and 3584 respectively.**
- **b. All i), ii), iii) and iv) would compile successfully and they will print 8, 90, 200 & 7000 respectively.**
- **c. Only i) would compile. And it will print 8.**
- **d. Both i) and ii) would compile. i) will print 8 while ii) will print 90**

Question 16

Not yet answered

Marked out of 1.00

Which of the following allows objects to change type within the subtyping structure

Select one:

- **a. Static classification**
- **b. Dynamic classification**
- **c. Depends on the scenario**
- **d. None of these**

Question 17

Not yet answered

Marked out of 1.00

Suppose that in a C program snippet, followings statements are used.

i) sizeof(int);
ii) sizeof(int*);
iii) sizeof(int**);

Assuming size of pointer is 4 bytes and size of int is also 4 bytes, pick the most correct answer from the given options.

Select one:

- **a. i), ii) and iii) would compile successfully but the size of each would be different and would be decided at run time.**
- **b. i), ii) and iii) would compile successfully and size of each would be same i.e. 4**
- **c. ii) and iii) would result in compile error but i) would compile and result in size as 4.**
- **d. Only i) would compile successfully and it would return size as 4.**

Question 18

Not yet answered

Marked out of 1.00

Logical operators used in SQL are

Select one:

- **a. $,|,!**
- **b. AND, OR , NOT**
- **c. &&, ||, !**
- **d. None of these**

Question **19**

Not yet answered

Marked out of 1.00

Given:

```
1. class Voop {
2. public static void main(String[] args) {
3. doStuff(1);
4. doStuff(1,2);
5. }
6. // insert code here
7. }
```

Which, inserted independently at line 6, will compile? (Choose all that apply.)

Select one or more:

- ☐ **a. static void doStuff(int... doArgs, int y) { }**
- ☐ **b. static void doStuff(int... doArgs) { }**
- ☐ **c. static void doStuff(int[] doArgs) { }**
- ☐ **d. static void doStuff(int x, int... doArgs) { }**
- ☐ **e. static void doStuff(int doArgs...) { }**

Question **20**

Not yet answered

Marked out of 1.00

Which method names follow the JavaBeans standard? (Choose all that apply.)

Select one or more:

- ☐ **a. deleteRep**
- ☐ **b. addSize**
- ☐ **c. getCust**
- ☐ **d. isColorado**
- ☐ **e. putDimensions**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=10338)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved. Version 4.2

/