Question 1

Not yet answered

Marked out of 1.00

Which statement(s) are true? (Choose all that apply.)

Select one or more:

- ☐ **a. Cohesion is the OO principle most closely associated with making sure that classes know about other classes only through their APIs**
- ☐ **b. Cohesion is the OO principle most closely associated with making sure that a class is designed with a single, well-focused purpose**
- ☐ **c. Cohesion is the OO principle most closely associated with allowing a single object to be seen as having many types**
- ☐ **d. Cohesion is the OO principle most closely associated with hiding implementation details**

Question 2

Not yet answered

Marked out of 1.00

Given:

```
class Clidder {
private final void flipper() { System.out.println("Clidder"); }
}
public class Clidlet extends Clidder {
public final void flipper() { System.out.println("Clidlet"); }
public static void main(String [] args) {
new Clidlet().flipper();
} }
```

What is the result?

Select one:

- ◯ **a. Clidlet**
- ◯ **b. Clidder Clidlet**
- ◯ **c. Clidlet Clidder**
- ◯ **d. Compilation fails**
- ◯ **e. Clidder**

Question **3**

Not yet answered

Marked out of 1.00

Given:

```
3. class Dog {
4. public void bark() { System.out.print("woof "); }
5. }
6. class Hound extends Dog {
7. public void sniff() { System.out.print("sniff "); }
8. public void bark() { System.out.print("howl "); }
9. }
10. public class DogShow {
11. public static void main(String[] args) { new DogShow().go(); }
12. void go() {
13. new Hound().bark();
14. ((Dog) new Hound()).bark();
15. ((Dog) new Hound()).sniff();
16. }
17. }
```

What is the result? (Choose all that apply.)

Select one or more:

- ☐ **a. Compilation fails with an error at line 15**
- ☐ **b. howl woof followed by an exception**
- ☐ **c. howl howl followed by an exception**
- ☐ **d. howl woof sniff**
- ☐ **e. Compilation fails with an error at line 14**
- ☐ **f. howl howl sniff**

Question **4**

Not yet answered

Marked out of 1.00

Which of the following is NOT a type of SQL constraint?

Select one:

- ○ **a. ALTERNATE KEY**
- ○ **b. PRIMARY KEY**
- ○ **c. UNIQUE**
- ○ **d. FOREIGN KEY**

Question **5**

Not yet answered

Marked out of 1.00

Which of the following concepts provides facility of using object of one class inside another class?

Select one:

- ○ **a. Encapsulation**
- ○ **b. Inheritance**
- ○ **c. Composition**
- ○ **d. Abstraction**

Question 6

Not yet answered

Marked out of 1.00

Given:

1. ClassA has a ClassD
2. Methods in ClassA use public methods in ClassB
3. Methods in ClassC use public methods in ClassA
4. Methods in ClassA use public variables in ClassB

Which is most likely true? (Choose the most likely.)

Select one or more:

- [ ] **a. ClassA has weak encapsulation**
- [ ] **b. ClassC is tightly coupled to ClassA**
- [ ] **c. ClassB has weak encapsulation**
- [ ] **d. ClassD has low cohesion**
- [ ] **e. ClassB has strong encapsulation**

Question 7

Not yet answered

Marked out of 1.00

You have run an SQL statement that asked the DBMS to display data in a table named USER_TABLES.
The results include columns of data labeled "TableName," "NumberOfColumns" and "PrimaryKey."

You are looking at _____ .

Select one:

- ◯ **a. user data.**
- ◯ **b. indexes**
- ◯ **c. A report**
- ◯ **d. Metadata**

Question **8**

Not yet answered

Marked out of 1.00

Suppose someone writes increment macro (i.e. which increments the value by one) in following ways:

#define INC1(a) ((a)+1)

#define INC2 (a) ((a)+1)

#define INC3(a) ((a) + 1)

#define INC4 (a) ((a) + 1)

Pick the correct statement for the above macros.

Select one:

- **a. Only INC1 and INC2 are correct.**
- **b. Only INC1 is correct.**
- **c. Only INC1 and INC3 are correct.**
- **d. All (i.e. INC1, INC2, INC3 and INC4) are correct.**

Question **9**

Not yet answered

Marked out of 1.00

In a class, a public operation is shown by

Select one:

- **a. -**
- **b. +**
- **c. #**
- **d. ?**

Question **10**

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

int operate (int a, int b)
{
        return (a * b);
}

float operate (float a, float b)
{
        return (a/b);
}

int main()
{
        int x=5, y=2;
        float n=5.0, m=2.0;
        cout << operate(x,y) <<"\t";
    cout << operate (n,m);
    return 0;
}
```

Select one:

- **a. 10 2.5**
- **b. Compile Time Error Ambiguity in Function Call**
- **c. 5.0 2.5**
- **d. 10.0 5.0**
- **e. 10.0 5**

Question **11**

Not yet answered

Marked out of 1.00

In the description of a class, a protected operation is shown by

Select one:

- **a. -**
- **b. ?**
- **c. +**
- **d. #**

Question **12**

Not yet answered

Marked out of 1.00

The average case occurs in the Linear Search Algorithm when:

Select one:

- **a. The item to be searched is in some where middle of the Array**
- **b. The item to be searched is in the last of the array**
- **c. The item to be searched is either in the last or not in the array**
- **d. The item to be searched is not in the array**

Question 13

Not yet answered

Marked out of 1.00

In the following program snippet, both s1 and s2 would be variables of structure type defined as below and there won't be any compilation issue. typedef struct Student { int rollno; int total; } Student; Student s1; struct Student s2;

Select one:

- **a. None of these**
- **b. FALSE**
- **c. Compiler Dependent**
- **d. TRUE**

Question 14

Not yet answered

Marked out of 1.00

What does fun2() do in general?

```
int fun(int x, int y)
{
   if (y == 0)   return 0;
   return (x + fun(x, y-1));
}

int fun2(int a, int b)
{
   if (b == 0) return 1;
   return fun(a, fun2(a, b-1));
}
```

Select one:

- **a. x+x*y**
- **b. x^y**
- **c. x*y**
- **d. y^x**

Question **15**

Not yet answered

Marked out of 1.00

Given:

```
3. public class Redwood extends Tree {
4. public static void main(String[] args) {
5. new Redwood().go();
6. }
7. void go() {
8. go2(new Tree(), new Redwood());
9. go2((Redwood) new Tree(), new Redwood());
10. }
11. void go2(Tree t1, Redwood r1) {
12. Redwood r2 = (Redwood)t1;
13. Tree t2 = (Tree)r1;
14. }
15. }
16. class Tree { }
```

What is the result? (Choose all that apply.)

Select one or more:

- ☐ **a. Compilation fails with an error at line 13**
- ☐ **b. Compilation fails with an error at line 8**
- ☐ **c. Compilation fails with an error at line 12**
- ☐ **d. The code compiles and runs with no output**
- ☐ **e. An exception is thrown at runtime**
- ☐ **f. Compilation fails with an error at line 9**

Question **16**

Not yet answered

Marked out of 1.00

Which view addresses the performance, scalability and throughput of the system?

Select one:

- ○ **a. Process**
- ○ **b. Design**
- ○ **c. Implementation**
- ○ **d.**
  Use Case

Question **17**

Not yet answered

Marked out of 1.00

Consider the following code snippet for checking whether a number is power of 2 or not.

```
/* Incorrect function to check if x is power of 2*/

bool isPowerOfTwo (unsigned int x)
{
  return (!(x&(x-1)));
}
```

What is wrong with above function?

Select one:

- **a. It does not work for x = 0**
- **b. It does not work for x = 1**
- **c. It does reverse of what is required**
- **d. It works perfectly fine for all values of x.**

Question **18**

Not yet answered

Marked out of 1.00

Given the following,

```
1. class X { void do1() { } }
2. class Y extends X { void do2() { } }
3.
4. class Chrome {
5. public static void main(String [] args) {
6. X x1 = new X();
7. X x2 = new Y();
8. Y y1 = new Y();
9. // insert code here
10. }
11. }
```

Which, inserted at line 9, will compile? (Choose all that apply.)

Select one or more:

- **a. (Y)x2.do2();**
- **b. x2.do2();**
- **c. ((Y)x2).do2();**
- **d. None of the above statements will compile**

Question **19**

Not yet answered

Marked out of 1.00

The pre-order and post order traversal of a Binary Tree generates the same output. The tree can have maximum

Select one:

- **a. Any number of nodes**
- **b. Two nodes**
- **c. One node**
- **d. Three nodes**

Question **20**

Not yet answered

Marked out of 1.00

```
#include<stdio.h>

int foo(int a)
{
 printf("%d",a);
 return 0;
}

int main()
{
 foo;
 return 0;
}
```

Select one:

- **a. It'll result in compile error because foo is used without parentheses.**
- **b. No compile error and ZERO (i.e. 0) would be passed to foo function. This would make foo to be executed with output 0.**
- **c. No compile error but foo function wouldn't be executed. The program wouldn't print anything.**
- **d. No compile error and some garbage value would be passed to foo function. This would make foo to be executed with output "garbage integer".**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=10476)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved. Version 4.2

/