Question 1

Not yet answered

Marked out of 1.00

Find out the correct statement for the following program.

```
#include <stdio.h>

int * gPtr;

int main()
{
int * lPtr = NULL;

if(gPtr == lPtr)
{
printf("Equal!");
}
else
{
printf("Not Equal");
}

return 0;
}
```

Select one:

- **a. Segmentation fault**
- **b. Since gPtr isn't initialized in the program, it'll print sometimes Equal and at other times Not Equal.**
- **c. It'll always print Equal.**
- **d. It'll always print Not Equal.**

Question 2

Not yet answered

Marked out of 1.00

Pick the best statement for the below:

```
int arr[50] = {0,1,2,[47]=47,48,49};
```

Select one:

- **a. Segementation fault**
- **b. This is allowed in C as per standard.**
- **c. This isn't allowed in C and it'll give compile error**
- **d. None of these**

Question 3

Not yet answered

Marked out of 1.00

Pick the best statement for the below program:

```
#include<stdio.h>
int main()
{
struct {int a[2], b;} arr[] = {[0].a = {1}, [1].a = {2}, [0].b = 1, [1].b = 2};

printf("%d %d %d and",arr[0].a[0],arr[0].a[1],arr[0].b);
printf("%d %d %d\n",arr[1].a[0],arr[1].a[1],arr[1].b);

return 0;
}
```

Select one:

- **a. Compile error because struct type (containing two fields i.e. an array of int and an int) has been specified along with the definition of array arr[] of this struct type.**
- **b. No compile error and two elements of arr[] would be defined and initialized. Output would be "1 X 1 and 2 X 2" where X is some garbage random number.**
- **c. No compile error and two elements of arr[] would be defined and initialized. Output would be "1 0 1 and 2 0 2".**
- **d. Compile error because of incorrect syntax for initialization of array arr[].**

Question 4

Not yet answered

Marked out of 1.00

```
#include<stdio.h>

void print(int n)
{
if (n > 4000)
return;
printf("%d ", n);
print(2*n);
printf("%d ", n);
}

int main()
{
print(1000);
getchar();
return 0;
}
```

Select one:

- **a. 1000 2000 4000 4000 2000 1000**
- **b. 1000 2000 4000**
- **c. 1000 2000 4000 2000 1000**
- **d. 1000 2000 2000 1000**

Question 5

Not yet answered

Marked out of 1.00

Number of comparisons required for an unsuccessful search of an element in a sequential search, organized, fixed length, symbol table of length L is

Select one:

- **a. L/2**
- **b. L**
- **c. 2L**
- **d. (L+1)/2**

Question 6

Not yet answered

Marked out of 1.00

Output of following program? Assume that the size of char is 1 byte and size of int is 4 bytes, and there is no alignment done by the compiler.

```
#include<iostream>
#include<stdlib.h>
using namespace std;

template<class T, class U>
class A {
T x;
U y;
static int count;
};

int main() {
A<char, char> a;
A<int, int> b;
cout << sizeof(a) << endl;
cout << sizeof(b) << endl;
return 0;
}
```

Select one:

- **a. Compiler Error: There can not be more than one template arguments.**
- **b. 2**
  8
- **c. 6**
  12
- **d. 8**
  8

Question 7

Not yet answered

Marked out of 1.00

Would destructor be called, if yes, then due to which vector?

```
#include <iostream>
#include <vector>
using namespace std;

class a
{
public :
~a()
{
cout << "destroy";
}
};
int main()
{
vector <a*> *v1 = new vector<a*>;
vector <a> *v2 = new vector<a>;
return 0;
}
```

Select one:

- **a. v2**
- **b. v1**
- **c. no destructor call**
- **d. v1 and v2**

Question 8

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;
int main ()
{
int cin;
cin >> cin;
cout << "cin" << cin;
return 0;
}
```

Select one:

- **a. cin+input**
- **b. Runtime error**
- **c. cin+junk value/0**
- **d. error in using cin keyword**

Question **9**

Not yet answered

Marked out of 1.00

A member function can always access the data in _____ , (in C++).

Select one:

- **a. the private part of its class**
- **b. the class of which it is member**
- **c. the object of which it is a member**
- **d. the public part of its class**

Question **10**

Not yet answered

Marked out of 1.00

Given:

```
3. public class Tenor extends Singer {
4. public static String sing() { return "fa"; }
5. public static void main(String[] args) {
6. Tenor t = new Tenor();
7. Singer s = new Tenor();
8. System.out.println(t.sing() + " " + s.sing());
9. }
10. }
11. class Singer { public static String sing() { return "la"; } }
```

What is the result?

Select one:

- **a. fa la**
- **b. Compilation fails**
- **c. fa fa**
- **d. An exception is thrown at runtime**
- **e. la la**

Question **11**

Not yet answered

Marked out of 1.00

Given:

```
3. class Alpha {
4. static String s = " ";
5. protected Alpha() { s += "alpha "; }
6. }
7. class SubAlpha extends Alpha {
8. private SubAlpha() { s += "sub "; }
9. }
10. public class SubSubAlpha extends Alpha {
11. private SubSubAlpha() { s += "subsub "; }
12. public static void main(String[] args) {
13. new SubSubAlpha();
14. System.out.println(s);
15. }
16. }
```

What is the result?

Select one:

- **a. subsub**
- **b. sub subsub**
- **c. alpha sub subsub**
- **d. Compilation fails**
- **e. alpha subsub**
- **f. An exception is thrown at runtime**

Question **12**

Not yet answered

Marked out of 1.00

Given:

```
3. class Building {
4. Building() { System.out.print("b "); }
5. Building(String name) {
6. this(); System.out.print("bn " + name);
7. }
8. }
9. public class House extends Building {
10. House() { System.out.print("h "); }
11. House(String name) {
12. this(); System.out.print("hn " + name);
13. }
14. public static void main(String[] args) { new House("x "); }
15. }
```

What is the result?

Select one:

- **a. b bn x h hn x**
- **b. bn x b h hn x**
- **c. Compilation fails**
- **d. bn x h hn x**
- **e. h hn x**
- **f. hn x h**
- **g. b h hn x**
- **h. b hn x h**

Question **13**

Not yet answered

Marked out of 1.00

Given:

```
3. class Mammal {
4. String name = "furry ";
5. String makeNoise() { return "generic noise"; }
6. }
7. class Zebra extends Mammal {
8. String name = "stripes ";
9. String makeNoise() { return "bray"; }
10. }
11. public class ZooKeeper {
12. public static void main(String[] args) { new ZooKeeper().go(); }
13. void go() {
14. Mammal m = new Zebra();
15. System.out.println(m.name + m.makeNoise());
16. }
17. }
```

What is the result?

Select one:

- **a. furry bray**
- **b. stripes bray**
- **c. furry generic noise**
- **d. stripes generic noise**
- **e. An exception is thrown at runtime**
- **f. Compilation fails**

Question **14**

Not yet answered

Marked out of 1.00

You're designing a new online board game in which Floozels are a type of Jammers,
Jammers can have Quizels,
Quizels are a type of Klakker,
and Floozels can have several Floozets.

Which of the following fragments represent this design? (Choose all that apply.)

Select one or more:

☐ **a. import java.util.*;**
interface Klakker { }
class Jammer { Set<Quizel> q; }
class Quizel implements Klakker { }
public class Floozel extends Jammer { List<Floozet> f; }
interface Floozet { }

☐ **b. import java.util.*;**
class Floozet { }
class Quizel implements Klakker { }
class Jammer { List<Quizel> q; }
interface Klakker { }
class Floozel extends Jammer { List<Floozet> f; }

☐ **c. import java.util.*;**
class Klakker { Set<Quizel> q; }
class Quizel extends Klakker { }
class Jammer { List<Floozel> f; }
class Floozet extends Floozel { }
public class Floozel { Set<Klakker> k; }

☐ **d. import java.util.*;**
interface Jammer extends Quizel { }
interface Klakker { }
interface Quizel extends Klakker { }
interface Floozel extends Jammer, Floozet { }
interface Floozet { }

Question **15**

Not yet answered

Marked out of 1.00

In the relational model, relationships between relations or tables are created by using:

Select one:

◯ **a. candidate keys.**

◯ **b. foreign keys.**

◯ **c. determinants.**

◯ **d. composite keys.**

Question **16**

Not yet answered

Marked out of 1.00

SQL views can be used to hide:

Select one:

- **a. None of these**
- **b. complicated SQL syntax only.**
- **c. columns and rows only.**
- **d. Both columns and rows as well as complicated SQL syntax can be hidden by an SQL view.**

Question **17**

Not yet answered

Marked out of 1.00

Which of the following is NOT a basic element of all versions of the E-R model?

Select one:

- **a. Relationships**
- **b. Entities**
- **c. Attributes**
- **d. Primary keys**

Question **18**

Not yet answered

Marked out of 1.00

How many tables may be included with a join?

Select one:

- **a. Two**
- **b. Three**
- **c. All of these**
- **d. One**

Question **19**

Not yet answered

Marked out of 1.00

A _____ is a physical element that exists at run time and represents a computational resource.

Select one:

- **a. Object**
- **b. Node**
- **c. Interface**
- **d. Component**

Question **20**

Not yet answered

Marked out of 1.00

A use case diagram is used to model _____ of a system.

Select one:

- **a. Interface**
- **b. Behavior**
- **c. State**
- **d. Structure**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=10622)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved.

Version 4.2