Question 1

Not yet answered

Marked out of 1.00

Consider the following Employee table

ID salary DeptName
1 10000 EC
2 40000 EC
3 30000 CS
4 40000 ME
5 50000 ME
6 60000 ME
7 70000 CS

How many rows are there in the result of following query?

```
SELECT E.ID
FROM Employee E
WHERE EXISTS (SELECT E2.salary
FROM Employee E2
WHERE E2.DeptName = 'CS'
AND E.salary > E2.salary)
```

Select one:

- a. 5
- b. 0
- c. 4
- d. 6

Question 2

Not yet answered

Marked out of 1.00

Output of following C program?

```
#include<stdio.h>
int main()
{
int i = 0;
for (printf("1st\n"); i < 2 && printf("2nd\n"); ++i && printf("3rd\n"))
{
printf("*\n");
}
return 0;
}
```

Select one:

- **a. 1st**
  2nd
  *****
  3rd
  2nd
  *****
- **b. 1st**
  2nd
  3rd
  *****
  2nd
  3rd
- **c. 1st**
  2nd
  *****
  3rd
  2nd
  *****
  3rd
- **d. 1st**
  2nd
  3rd
  *****
  1st
  2nd
  3rd

Question 3

Not yet answered

Marked out of 1.00

Write the output of the following C program

```
#include <stdio.h>

int main (void)
{
int shifty;
shifty = 0570;
shifty = shifty >>4;
shifty = shifty <<6;
printf("the value of shifty is %o",shifty);
}
```

Select one:

- **a. the value of shifty is 2700**
- **b. the value of shifty is 4300**
- **c. the value of shifty is 5700**
- **d. the value of shifty is 15c0**

Question 4

Not yet answered

Marked out of 1.00

Which are true? (Choose all that apply.)

Select one or more:

- **a. When a thread is waiting as a result of wait(), it releases its lock**
- **b. The notifyAll() method must be called from a synchronized context**
- **c. To call wait(), an object must own the lock on the thread**
- **d. The difference between notify() and notifyAll() is that notifyAll() notifies all waiting threads, regardless of the object they're waiting on**
- **e. The notify() method causes a thread to immediately release its lock**
- **f. The notify() method is defined in class java.lang.Thread**

Question 5

Not yet answered

Marked out of 1.00

What will be the output of following code ?

```
#include <iostream>
using namespace std;

class Animal
{
public :
int legs = 4;
};

class Dog : Animal
{
public:
int tail = 1;
};

int main()
{
Dog d;
cout << d.legs;
cout << d.tail;
}
```

Select one:

- **a. 44**
- **b. 40**
- **c. 41**
- **d. Error**

Question 6

Not yet answered

Marked out of 1.00

Given:
1. public class WaitTest {
2. public static void main(String [] args) {
3. System.out.print("1 ");
4. synchronized(args){
5. System.out.print("2 ");
6. try {
7. args.wait();
8. }
9. catch(InterruptedException e){}
10. }
11. System.out.print("3 ");
12. } }
What is the result of trying to compile and run this program?

Select one:

- **a. 1 2**
- **b. It will fail to compile because it has to be synchronized on the this object**
- **c. 1 2 3**
- **d. 1 3**
- **e. At runtime, it throws an IllegalMonitorStateException when trying to wait**
- **f. It fails to compile because the IllegalMonitorStateException of wait() is not dealt with in line 7**

Question 7

Not yet answered

Marked out of 1.00

Given:

```
public abstract class AbstractTest {
public int getNum() {
return 45;
}
public abstract class Bar {
public int getNum() {
return 38;
}
}
public static void main(String[] args) {
AbstractTest t = new AbstractTest() {
public int getNum() {
return 22;
}
};
AbstractTest.Bar f = t.new Bar() {
public int getNum() {
return 57;
}
};
System.out.println(f.getNum() + " " + t.getNum());
} }
```

What is the result?

Select one:

- **a. 45 38**
- **b. An exception occurs at runtime**
- **c. 57 22**
- **d. 45 57**
- **e. Compilation fails**

Question 8

Not yet answered

Marked out of 1.00

Predict the output of the below program:

```
#include <stdio.h>
int main()
{
int i = 3;
switch(i)
{
printf("Outside ");
case 1: printf("Hello");
break;
case 2: printf("World");
break;
defau1t: printf("Welcome");
}
return 0;
}
```

Select one:

- **a. Outside Welcome**
- **b. None of these**
- **c. Nothing gets printed**
- **d. HelloWorld**

Question 9

Not yet answered

Marked out of 1.00

Assume the following method is properly synchronized and called from a thread A on an object B:

wait(2000);

After calling this method, when will the thread A become a candidate to get another turn at the CPU?

Select one:

- **a. After the lock on B is released, or after two seconds**
- **b. Two seconds after lock B is released**
- **c. Two seconds after object B is notified**
- **d. After object B is notified, or after two seconds**

Question 10

Not yet answered

Marked out of 1.00

A company maintains records of sales made by its salespersons and pays them commission based on each individual's total sales made in a year. This data is maintained in a table with following schema:
salesinfo = (salespersonid, totalsales, commission)
In a certain year, due to better business results, the company decides to further reward its salespersons by enhancing the commission paid to them as per the following formula:
If commission < = 50000, enhance it by 2%
If 50000 < commission < = 100000, enhance it by 4%
If commission > 100000, enhance it by 6%
The IT staff has written three different SQL scripts to calculate enhancement for each slab, each of these scripts is to run as a separate transaction as follows:

T1

```
Update salesinfo
Set commission = commission * 1.02
Where commission < = 50000;
```

T2

```
Update salesinfo
Set commission = commission * 1.04
Where commission > 50000 and commission is < = 100000;
```

T3

```
Update salesinfo
Set commission = commission * 1.06
Where commission > 100000;
```

Which of the following options of running these transactions will update the commission of all salespersons correctly

Select one:

- **a. Execute T3 followed by T2 followed by T1**
- **b. Execute T1 followed by T2 followed by T3**
- **c. Execute T2, followed by T3; T1 running concurrently throughout**
- **d. Execute T3 followed by T2; T1 running concurrently throughout**

Question 11

Not yet answered

Marked out of 1.00

The following three 'C' language statements is equivalent to which single statement?
y=y+1;
z=x+y;
x=x+1

Select one:

- **a. z = (x++) + (y++);**
- **b. z = (x++) + (++y);**
- **c. z = x + y + 2;**
- **d. z = (x++) + (++y) + 1;**

Question 12

Not yet answered

Marked out of 1.00

Given:
3. import java.util.*;
4. public class Mixup {
5. public static void main(String[] args) {
6. Object o = new Object();
7. // insert code here
8. s.add("o");
9. s.add(o);
10. }
11. }

And these three fragments:

I. Set s = new HashSet();
II. TreeSet s = new TreeSet();
III. LinkedHashSet s = new LinkedHashSet();

When fragments I, II, or III are inserted, independently, at line 7, which are true?
(Choose all that apply.)

Select one or more:

- **a. Fragment III executes without exception**
- **b. Fragment III compiles**
- **c. Fragment I compiles**
- **d. Fragment I executes without exception**
- **e. Fragment II executes without exception**
- **f. Fragment II compiles**

Question 13

Not yet answered

Marked out of 1.00

Given the proper import statement(s), and

```
13. PriorityQueue<String> pq = new PriorityQueue<String>();
14. pq.add("2");
15. pq.add("4");
16. System.out.print(pq.peek() + " ");
17. pq.offer("1");
18. pq.add("3");
19. pq.remove("1");
20. System.out.print(pq.poll() + " ");
21. if(pq.remove("2")) System.out.print(pq.poll() + " ");
22. System.out.println(pq.poll() + " " + pq.peek());
```

What is the result?

Select one:

- **a. Compilation fails**
- **b. 2 2 3 3 3**
- **c. 2 2 3 4**
- **d. 4 3 3 4**
- **e. 4 3 3 3 3**
- **f. 2 2 3 3 4**
- **g. An exception is thrown at runtime**
- **h. 2 2 3 3**

Question **14**

Not yet answered

Marked out of 1.00

What will be the output of following code?

```
#include <iostream>
using namespace std;

class A
{
int x;
};

class B : public A
{
public:
void show()
{
x=10;
cout << x;
}
};

int main()
{
B b;
b.show();
return 0;
}
```

Select one:

- **a. 0**
- **b. error**
- **c. garbage value**
- **d. 10**

Question 15

Not yet answered

Marked out of 1.00

What will be the output of following code?

```
#include <iostream>
using namespace std;

class Base
{
public:
Base() { cout << "Base"; }
};

class Derived : public Base
{
public:
Derived(int i) { cout << i; }
};

int main()
{
Derived d2(10);
return 0;
}
```

Select one:

- **a. 10Base**
- **b. Base10**
- **c. error**
- **d. 10**

Question 16

Not yet answered

Marked out of 1.00

Given:

```
3. public class Tour {
4. public static void main(String[] args) {
5. Cathedral c = new Cathedral();
6. // insert code here
7. s.go();
8. }
9. }
10. class Cathedral {
11. class Sanctum {
12. void go() { System.out.println("spooky"); }
13. }
14. }
```

Which, inserted independently at line 6, compile and produce the output "spooky"? (Choose all that apply.)

Select one or more:

- ☐ **a. Sanctum s = c.new Sanctum();**
- ☐ **b. c.Sanctum s = Cathedral.new Sanctum();**
- ☐ **c. Cathedral.Sanctum s = Cathedral.new Sanctum();**
- ☐ **d. Cathedral.Sanctum s = c.new Sanctum();**
- ☐ **e. c.Sanctum s = c.new Sanctum();**

Question 17

Not yet answered

Marked out of 1.00

What does the following program do when the input is unsigned 16-bit integer?

```
#include
main( )
{
unsigned int num;
int i;
scanf ("%u", &num);
for ( i = 0; i<16; i++)
{
printf (“%d”, (num << i & 1 << 15 ) ? 1:0);
}
}
```

Quiz-01-07-2020 (http://classroom.teleuniv.com/mod/quiz/view.php?id=684)

Select one:

- **a. It prints all odd bits from num**
- **b. It prints binary equivalent of num**
- **c. None of the above**
- **d. It prints all even bits from num**

Question 18

Not yet answered

Marked out of 1.00

In ..... inheritance, the base classes are constructed in the order in which they appear in the deceleration of the derived class.

Select one:

- **a. hierarchical**
- **b. multilevel**
- **c. multipath**
- **d. multiple**

Question **19**

Not yet answered

Marked out of 1.00

Predict the output of the following program:

```
#include <stdio.h>
int main()
{
const int check = 20;
const int arr[] = {10, 20, 30};
switch (check)
{
case arr[0]: printf("Hello ");
case arr[1]: printf("World ");
case arr[2]: printf("Welcome ");
}
return 0;
}
```

Select one:

- **a. World Welcome**
- **b. Compile-time error**
- **c. Hello**
- **d. Welcome**

Question **20**

Not yet answered

Marked out of 1.00

Consider the followng realtions :

Students
Roll No Student Name
1 Raj
2 Rohit
3 Raj

(Roll No is Primary Key)

Performance
Roll No Course Marks
1 Math 80
1 English 70
2 Math 75
3 English 80
2 Physics 65
3 Math 80

Here in Performance table Roll No is a foreing key and Course is a Primay Key

```
SELECT S. Student_Name, sum(P.Marks)
FROM Student S, Performance P
WHERE S.Roll_No = P.Roll_No
GROUP BY S.Student_Name
```

The number of rows that will be returned by the SQL query is _____

Select one:

- **a. 1**
- **b. 0**
- **c. 3**
- **d. 2**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=11708)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved. Version 4.2