Question 1

Not yet answered

Marked out of 1.00

If size of an integer is 4 bytes what will be the output of the following program ?

```
#include<stdio.h>
int main() {
int arr[]={11,12,13,14,15};
printf(" %d %d %d ", sizeof(arr),sizeof(*arr),sizeof(arr[0]));
return 0;
}
```

Select one:

- **a. 20 20 4**
- **b. 4 4 20**
- **c. 4 4 4** (selected)
- **d. 20 4 4**

Question 2

Not yet answered

Marked out of 1.00

Which of the following is the correct output for the program given below ?

```
#include<stdio.h>
int main() {
int arr[3] = {2,3,4};
char *p;
p=(char *)arr;
printf(" %d ",*p);
p=p+1;
printf(" %d ", *p);
return 0;
}
```

Select one:

- **a. 2 3**
- **b. Garbage Values**
- **c. 1 0**
- **d. 2 0**

Question 3

Not yet answered

Marked out of 1.00

output of the Below CPP Code

```
#include<iostream>
using namespace std;

int main() {
bool b = 32;
int i = false;
cout<<endl<<b<<endl<<i;

int j = b+b;
bool k = b+b;
cout<<endl<<j<<endl<<k<<endl;
return 0;

}
```

Select one:

- **a. 1**
  0
  2
  1
- **b. 32**
  0
  64
  1
- **c. 1**
  0
  1
  0
- **d. Compilation Fails**

Question 4

Not yet answered

Marked out of 1.00

Which of the following is the correct output for the C program given below ?

```
#include<stdio.h>
int main()
{
extern int i;
i=20;
printf(" %lu ", sizeof(i));
return 0;
}
```

Select one:

- **a. 2**
- **b. Would vary from compiler to compiler**
- **c. Compilation fails**
- **d. 4**

Question 5

Not yet answered

Marked out of 1.00

How long will the for loop get executed ?

```
#include<stdio.h>
int main() {
int i;
for(;scanf("%d",&i);printf("%d\n",i));
}
```

Select one:

- **a. The for loop would get executed only once.**
- **b. The for loop would not get executed at all.**
- **c. The for loop would get executed infinite times**
- **d. The for loop would get executed 5 times**

Question 6

Not yet answered

Marked out of 1.00

Given the scenario: This class is intended to allow users to write a series of messages,
so that each message is identified with a timestamp and the name of the thread that wrote the message:

```
public class Logger {
private StringBuilder contents = new StringBuilder();
public void log(String message) {
contents.append(System.currentTimeMillis());
contents.append(": ");
contents.append(Thread.currentThread().getName());
contents.append(message);
contents.append("\n");
}
public String getContents() { return contents.toString(); }
}
```

How can we ensure that instances of this class can be safely used by multiple threads?

Select one:

- **a. Synchronize the log() method only**
- **b. Synchronize both log() and getContents()**
- **c. Replacing StringBuilder with StringBuffer will make this class thread-safe**
- **d. This class is already thread-safe**
- **e. Synchronize the getContents() method only**
- **f. This class cannot be made thread-safe**

Question 7

Not yet answered

Marked out of 1.00

what would be the equivalent pointer expression for referrring the array element a[i][j][k][l];

Select one:

- **a. *a[i][j][k][l]*(*(*(a+i)+j)+k)+l)*(*(*(a+i)+j)+k)+l)**
- **b. *(*(*(a+i)+j)+k)+l)**
- **c. ***a**
- **d. *(*(*(*(a+i)+j)+k)+l)**

Question 8

Not yet answered

Marked out of 1.00

Given:

```
3. public class Car {
4. class Engine {
5. // insert code here
6. }
7. public static void main(String[] args) {
8. new Car().go();
9. }
10. void go() {
11. new Engine();
12. }
13. void drive() { System.out.println("hi"); }
14. }
```

Which, inserted independently at line 5, produce the output "hi"? (Choose all that apply.)

Select one or more:

- **a. Engine() { this.drive(); }**
- **b. Engine() { Car.this.drive(); }**
- **c. { this.drive(); }**
- **d. { this.Car.this.drive(); }**
- **e. Engine() { Car.drive(); }**
- **f. { Car.drive(); }**
- **g. { Car.this.drive(); }**

Question 9

Not yet answered

Marked out of 1.00

output of the Below CPP Code

```
#include<iostream>
using namespace std;

int main() {

char *str1 = "My Cat Pat ";
char *str2= str1;
cout<<endl<<str1<<endl<<str2;

*str1='B';
cout<<endl<<str1<<endl<<str2;

*str2='P';
cout<<endl<<str1<<endl<<str2;
return 0;
}
```

Select one:

- **a. My Cat Pat**
  My Cat Pat
  By Cat Pat
  My Cat Pat
  By Cat Pat
  Py Cat Pat
- **b. My Cat Pat**
  My Cat Pat
  By Cat Pat
  By Cat Pat
  Py Cat Pat
  Py Cat Pat
- **c. My Cat Pat**
  My Cat Pat
  My Cat Pat
  My Cat Pat
  My Cat Pat
  My Cat Pat
- **d. Compilation fails**
- **e. Segementaion fault**

Question **10**

Not yet answered

Marked out of 1.00

Given:

```
3. import java.util.*;
4. class Turtle {
5. int size;
6. public Turtle(int s) { size = s; }
7. public boolean equals(Object o) { return (this.size == ((Turtle)o).size); }
8. // insert code here
9. }
10. public class TurtleTest {
11. public static void main(String[] args) {
12. LinkedHashSet<Turtle> t = new LinkedHashSet<Turtle>();
13. t.add(new Turtle(1)); t.add(new Turtle(2)); t.add(new Turtle(1));
14. System.out.println(t.size());
15. }
16. }
```

And these two fragments:

I. public int hashCode() { return size/5; }

II. // no hashCode method declared

If fragment I or II is inserted, independently, at line 8, which are true? (Choose all that apply.)

Select one or more:

- ☐ **a. If fragment II is inserted, the output is 3**
- ☐ **b. If fragment I is inserted, compilation fails**
- ☐ **c. If fragment II is inserted, compilation fails**
- ☐ **d. If fragment II is inserted, the output is 2**
- ☐ **e. If fragment I is inserted, the output is 3**
- ☐ **f. If fragment I is inserted, the output is 2**

Question 11

Not yet answered

Marked out of 1.00

Given:

```
3. public class City {
4. class Manhattan {
5. void doStuff() throws Exception { System.out.print("x "); }
6. }
7. class TimesSquare extends Manhattan {
8. void doStuff() throws Exception { }
9. }
10. public static void main(String[] args) throws Exception {
11. new City().go();
12. }
13. void go() throws Exception { new TimesSquare().doStuff(); }
14. }
```

What is the result?

Select one:

- **a. Compilation fails due only to an error on line 10**
- **b. Compilation fails due only to an error on line 4**
- **c. Compilation fails due only to an error on line 13**
- **d. x x**
- **e. Compilation fails due to multiple errors**
- **f. x**
- **g. Compilation fails due only to an error on line 7**
- **h. No output is produced**

Question 12

Not yet answered

Marked out of 1.00

output of the below cpp code

```
#include<iostream>
using namespace std;

const int i =10;

int main() {
const int i =20;
cout<<i<<" "<<::i<<" ";

cout<<&i<<" "<<&::i<<" ";
cout<<"end of main";
return 0;
}
```

Select one:

- **a. Segmentation fault**
- **b. 20 10 followed by junk values followed by end of main**
- **c. Compilation fails**
- **d. 20 10 20 10 end of main**
- **e. None of these**

Question 13

Not yet answered

Marked out of 1.00

output of the Below CPP Code

```
#include<iostream>
using namespace std;

int main() {

int str1(43);
cout<<endl<<str1;
return 0;
}
```

Select one:

- **a. None of these**
- **b. 43**
- **c. Compilation fails**
- **d. Segmentation fault**

Question 14

Not yet answered

Marked out of 1.00

output of the following c code

```
#include<stdio.h>
int main() {
char *cptr, c;
void *vptr,v;
c=10,v=0;
cptr=&c;
vptr=&v;
printf(" %d %d ", *cptr,*vptr);
return 0;
}
```

Select one:

- **a. Segementation fault**
- **b. GarbageValue GarbageValue**
- **c. 10 0**
- **d. Compilation fails**

Question 15

Not yet answered

Marked out of 1.00

Given:

```
public static synchronized void main(String[] args) throws
InterruptedException {
Thread t = new Thread();
t.start();
System.out.print("X");
t.wait(10000);
System.out.print("Y");
}
```

What is the result of this code?

Select one:

- a. **The code does not compile**
- b. **It prints X and exits**
- c. **It prints XY with a 10000-second delay between X and Y**
- d. **An exception is thrown at runtime**
- e. **It prints XY with a 10-second delay between X and Y**
- f. **It prints X and never exits**
- g. **It prints XY and exits almost immeditately**

Question 16

Not yet answered

Marked out of 1.00

Given the proper import statement(s), and:

```
13. TreeSet<String> s = new TreeSet<String>();
14. TreeSet<String> subs = new TreeSet<String>();
15. s.add("a"); s.add("b"); s.add("c"); s.add("d"); s.add("e");
16.
17. subs = (TreeSet)s.subSet("b", true, "d", true);
18. s.add("g");
19. s.pollFirst();
20. s.pollFirst();
21. s.add("c2");
22. System.out.println(s.size() +" "+ subs.size());
```

Which are true? (Choose all that apply.)

Select one or more:

- a. **The size of subs is 3**
- b. **The size of s is 4**
- c. **An exception is thrown at runtime**
- d. **The size of s is 7**
- e. **The size of s is 5**
- f. **The size of subs is 1**
- g. **The size of subs is 2**
- h. **The size of subs is 4**

Question 17

Not yet answered

Marked out of 1.00

output of the below CPP Code

```
#include<iostream>
using namespace std;

int i =20;
int main() {
int i = 5;
cout<<i<<endl<<::i<<endl;
{
int i=10;
cout<<i<<endl<<::i;
}
return 0;
}
```

Select one:

- **a. compilation error**
- **b. 5**
  20
  10
  20
- **c. 5**
  10
  10
  20
- **d. 5**
  20
  10
  5

Question **18**

Not yet answered

Marked out of 1.00

Given:

```
5. class A { void m() { System.out.println("outer"); } }
6.
7. public class TestInners {
8. public static void main(String[] args) {
9. new TestInners().go();
10. }
11. void go() {
12. new A().m();
13. class A { void m() { System.out.println("inner"); } }
14. }
15. class A { void m() { System.out.println("middle"); } }
16. }
```

What is the result?

Select one:

- **a. outer**
- **b. inner**
- **c. An exception is thrown at runtime**
- **d. Compilation fails**
- **e. middle**

Question **19**

Not yet answered

Marked out of 1.00

Given:

```
3. public class Navel {
4. private int size = 7;
5. private static int length = 3;
6. public static void main(String[] args) {
7. new Navel().go();
8. }
9. void go() {
10. int size = 5;
11. System.out.println(new Gazer().adder());
12. }
13. class Gazer {
14. int adder() { return size * length; }
15. }
16. }
```

What is the result?

Select one:

- **a. 21**
- **b. An exception is thrown at runtime**
- **c. 15**
- **d. Compilation fails due to multiple errors**
- **e. Compilation fails due only to an error on line 5**
- **f. Compilation fails due only to an error on line 4**

Question **20**

Not yet answered

Marked out of 1.00

output of the Below CPP Code

```
#include<iostream>
using namespace std;

int main()
{
char *p="what a day";
char *q=p;
cout<<p<<endl<<q;
q="its a good day";
cout<<p<<endl<<q;
return 0;
}
```

Select one:

- **a. compilation fails**
- **b. what a day**
  what a day
  its a good day
  its a good day
- **c. what a day**
  what a day
  what a day
  its a good day
- **d. segementation fault**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=11879)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved.

Version 4.2

/