Question 1

Not yet answered

Marked out of 1.00

What are entity classes?

Select one:

- a. None of these
- b. Classes that contain data.
- c. Classes that represent something or some concept in the application domain.
- d. Classes that contain persistent data.

Question 2

Not yet answered

Marked out of 1.00

To evaluate an expression without any embedded function calls:

Select one:

- a. As many stacks as the height of the expression tree are needed
- b. A Turing machine is needed in the general case
- c. One stack is enough
- d. Two stacks are needed

Question 3

Not yet answered

Marked out of 1.00

Which of these is the correct set of analysis class stereotypes in standard UML?

Select one:

- a. None of these
- b. Interface, sequence and entity.
- c. Boundary, control and entity.
- d. Interface, control and entity.

Question **4**

Not yet answered

Marked out of 1.00

Given:

```
3. class Dozens {
4. int[] dz = {1,2,3,4,5,6,7,8,9,10,11,12};
5. }
6. public class Eggs {
7. public static void main(String[] args) {
8. Dozens [] da = new Dozens[3];
9. da[0] = new Dozens();
10. Dozens d = new Dozens();
11. da[1] = d;
12. d = null;
13. da[1] = null;
14. // do stuff
15. }
16. }
```

Which two are true about the objects created within main(), and eligible for garbage collection when line 14 is reached?

Select one or more:

- ☐ **a. Four objects were created**
- ☐ **b. Three objects are eligible for GC**
- ☐ **c. Two objects are eligible for GC**
- ☐ **d. Five objects were created**
- ☐ **e. Zero objects are eligible for GC**
- ☐ **f. One object is eligible for GC**
- ☐ **g. Three objects were created**
- ☐ **h. None of these**

Question **5**

Not yet answered

Marked out of 1.00

_____ data are continuous and take continuous values.

Select one:

- ○ **a. Both Analog and Digital**
- ○ **b. None of these**
- ○ **c. Analog only**
- ○ **d. Digital only**

Question 6

Not yet answered

Marked out of 1.00

Pick the best statement for the below program In C:

```
#include<stdio.h>
int main()
{
union {int i1; int i2;} myVar = {.i2 =100};
printf("%d %d",myVar.i1, myVar.i2);
return 0;
}
```

Select one:

- **a. None of these**
- **b. No compile error and it'll print "100 100".**
- **c. Compile error due to incorrect syntax of initialization.**
- **d. No compile error and it'll print "0 100".**

Question 7

Not yet answered

Marked out of 1.00

```
#include <iostream>
using namespace std;

template <int i>
void fun()
{
i = 20;
cout << i;
}

int main()
{
fun<10>();
return 0;
}
```

Select one:

- **a. None of these**
- **b. 20**
- **c. Compiler Error**
- **d. 10**

Question **8**

Not yet answered

Marked out of 1.00

The following postfix expression with single digit operands is evaluated using a stack:

8 2 3 ^ / 2 3 * + 5 1 * -

Note that ^ is the exponentiation operator.

The top two elements of the stack after the first * is evaluated are:

Select one:

- **a. 6, 1**
- **b. 5, 7**
- **c. 3, 2**
- **d. 1, 5**

Question 9

Not yet answered

Marked out of 1.00

Pick the best statement for the following program snippet:

```
#include<stdio.h>

void foo(void)
{
static int staticVar;
staticVar++;
printf("foo: %d\n",staticVar);
}

void bar(void)
{
static int staticVar;
staticVar++;
printf("bar: %d\n",staticVar);
}

int main()
{
foo(), bar(), foo();
return 0;
}
```

Select one:

- **a. Compile error because same static variable name is used in both foo and bar.**
  Since these static variables retain their values even after function is over, same name can't be used in both the functions.
- **b. Compile error because semicolon isn't used while calling foo() and bar() in side main function.**
- **c. No compile error and only one copy of staticVar would be used across both the functions and that's why final value of that single staticVar would be 3.**
- **d. No compile error and separate copies of staticVar would be used in both the functions.**
  That's why staticVar in foo() would be 2 while staticVar in bar() would be 1.

Question 10

Not yet answered

Marked out of 1.00

Given an Prefix convert to Postfix

Prefix : *+AB-CD

Select one:

- **a. AB*CD-+**
- **b. AB+CD-***
- **c. AB+CD*-**
- **d. AB-CD+***

Question 11

Not yet answered

Marked out of 1.00

Can static functions be virtual?
Will the following program compile?

```
#include<iostream>
using namespace std;

class Test
{
public:
virtual static void fun() { }
};
```

Select one:

- a. No
- b. Yes
- c. None of these
- d. Will compile followed by a Segmentation fault

Question 12

Not yet answered

Marked out of 1.00

_____ is the process of converting digital data to a digital signal.

Select one:

- a. None of these
- b. Line coding
- c. Block coding
- d. Scrambling

Question 13

Not yet answered

Marked out of 1.00

Predict the output of following C program, assume that a character takes 1 byte and pointer takes 4 bytes.

```
#include <stdio.h>
int main()
{
char *str1 = "HelloKmit";
char str2[] = "HelloKmit";

printf("sizeof(str1) = %d, sizeof(str2) = %d", sizeof(str1), sizeof(str2));

return 0;
}
```

Select one:

- a. sizeof(str1) = 4, sizeof(str2) = 4
- b. sizeof(str1) = 4, sizeof(str2) = 10
- c. sizeof(str1) = 10, sizeof(str2) = 10
- d. sizeof(str1) = 10, sizeof(str2) = 4

Question **14**

Not yet answered

Marked out of 1.00

Predict the output of following C program

```
int main()
{
char a[2][3][3] = {'h','e','l','l','o','k','m','i','t'};
printf("%s ", **a);
return 0;
}
```

Select one:

- **a. hellokmit**
- **b. Runtime Error**
- **c. Compiler Error**
- **d. hellokmit followed by garbage characters**

Question **15**

Not yet answered

Marked out of 1.00

Data can be _____.

Select one:

- **a. Digital only**
- **b. Analog only**
- **c. Both Analog and Digital**
- **d. None of these**

Question 16

Not yet answered

Marked out of 1.00

Given:

```
3. public class Bertha {
4. static String s = "";
5. public static void main(String[] args) {
6. int x = 4; Boolean y = true; short[] sa = {1,2,3};
7. doStuff(x, y);
8. doStuff(x);
9. doStuff(sa, sa);
10. System.out.println(s);
11. }
12. static void doStuff(Object o) { s += "1"; }
13. static void doStuff(Object... o) { s += "2"; }
14. static void doStuff(Integer... i) { s += "3"; }
15. static void doStuff(Long L) { s += "4"; }
16. }
```

What is the result?

Select one:

- **a. 232**
- **b. 332**
- **c. 212**
- **d. 312**
- **e. 334**
- **f. Compilation fails**
- **g. 234**

Question 17

Not yet answered

Marked out of 1.00

Predict the output of the following CPP Program

```
#include <iostream>
using namespace std;

class Test {
static int count;
int id;
public:
Test() {
count++;
id = count;
cout << "Constructing object number " << id << endl;
if(id == 4)
throw 4;
}
~Test() { cout << "Destructing object number " << id << endl; }
};

int Test::count = 0;

int main() {
try {
Test array[5];
} catch(int i) {
cout << "Caught " << i << endl;
}
}
```

Select one:

- a. **Constructing object number 1**
  Constructing object number 2
  Constructing object number 3
  Constructing object number 4
  Destructing object number 3
  Destructing object number 2
  Destructing object number 1
  Caught 4
- b. **Constructing object number 1**
  Constructing object number 2
  Constructing object number 3
  Constructing object number 4
  Destructing object number 1
  Destructing object number 2
  Destructing object number 3
  Destructing object number 4
  Caught 4
- c. **Constructing object number 1**
  Constructing object number 2
  Constructing object number 3
  Constructing object number 4
  Destructing object number 4
  Destructing object number 3

Destructing object number 2
Destructing object number 1
Caught 4

○ **d. Constructing object number 1**
Constructing object number 2
Constructing object number 3
Constructing object number 4
Destructing object number 1
Destructing object number 2
Destructing object number 3
Caught 4

Question **18**

Not yet answered

Marked out of 1.00

Given:

```
3. public class Ouch {
4. static int ouch = 7;
5. public static void main(String[] args) {
6. new Ouch().go(ouch);
7. System.out.print(" " + ouch);
8. }
9. void go(int ouch) {
10. ouch++;
11. for(int ouch = 3; ouch < 6; ouch++)
12. ;
13. System.out.print(" " + ouch);
14. }
15. }
```

What is the result?

Select one:

○ **a. 8 7**

○ **b. An exception is thrown at runtime**

○ **c. 5 7**

○ **d. 8 8**

○ **e. Compilation fails**

○ **f. 5 8**

Question **19**

Not yet answered

Marked out of 1.00

What do boundary classes represent?

Select one:

○ **a. None of these**

○ **b. People who will use the system.**

○ **c. Customers and suppliers of the business.**

○ **d. Interaction between the system and its actors.**

Question **20**

Not yet answered

Marked out of 1.00

Conver the following infix to postfix expression

a+b*(c^d-e)^(f+g*h)-i

Select one:

- **a. abcd^e-fgh*+^*+i-**
- **b. abcd-e^fgh+**^+i-**
- **c. abc^de-fgh+*^*+i-**
- **d. abcd^ef-gh*^+*i+-**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=10822)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved.