Question 1

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;
union test
{
test()
{
cout<<"Test called ";
}
~test() {
cout<<"Test Des called ";
}
}t[2];
int main()
{

}
```

Select one:

- **a. Segmentation fault**
- **b. Compilation fails**
- **c. Test called Test Des called Test called Test Des called**
- **d. Compiles but prints nothing**
- **e. Test called Test called Test Des called Test Des called**

Question 2

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

struct emp{
char name [20];
int age;
};

union uemp{
char name [20];
int age;
};


int main()
{
struct emp e = {"Pinky",25};
union uemp ue;
ue=e;
cout<<ue.name<<ue.age;
}
```

Select one:

- **a. Compilation fails**
- **b. Segmentation fault/run time error**
- **c. Garbage Value followed by Garbage value**
- **d. Pinky 25**

Question 3

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;


int i = 5;

int main()
{
int i = 10;
{
int i = 20;
cout<< i <<" "<< ::i << " "<<::(::i);
}
}
```

Select one:

- **a. 20 10 10**
- **b. 20 10 followed by run time error**
- **c. 20 10 5**
- **d. 20 5 5**
- **e. Compilation fails**

Question 4

Not yet answered

Marked out of 1.00

Given:

```
3. import java.util.*;
4. public class Magellan {
5. public static void main(String[] args) {
6. TreeMap<String, String> myMap = new TreeMap<String, String>();
7. myMap.put("a", "apple"); myMap.put("d", "date");
8. myMap.put("f", "fig"); myMap.put("p", "pear");
9. System.out.println("1st after mango: " + // sop 1
10. myMap.higherKey("f"));
11. System.out.println("1st after mango: " + // sop 2
12. myMap.ceilingKey("f"));
13. System.out.println("1st after mango: " + // sop 3
14. myMap.floorKey("f"));
15. SortedMap<String, String> sub = new TreeMap<String, String>();
16. sub = myMap.tailMap("f");
17. System.out.println("1st after mango: " + // sop 4
18. sub.firstKey());
19. }
20. }
```

Which of the System.out.println statements will produce the output 1st after mango: p?
(Choose all that apply.)

Select one:

- **a. None; compilation fails**
- **b. sop 3**
- **c. sop 2**
- **d. None; an exception is thrown at runtime**
- **e. sop 4**
- **f. sop 1**

Question 5

Not yet answered

Marked out of 1.00

```
#include<stdio.h>
int main() {
enum status {pass,fail,atkt};
enum status stud1,stud2,stud3;
stud1=pass;
stud2=atkt;
stud3=fail;
printf(" %d %d %d ", stud1, stud2,stud3);
return 0;
}
```

Select one:

- **a. 1 2 3**
- **b. 0 2 1**
- **c. pass atkt fail**
- **d. 0 1 2**
- **e. 1 3 2**

Question 6

Not yet answered

Marked out of 1.00

which of the following set of statements is correct ?

Select one:

- **a. typedef long a;**
  extern int a c;
- **b. typedef long a;**
  extern a c;
- **c. None of these**
- **d. typedef long a;**
  extern a int c;

Question 7

Not yet answered

Marked out of 1.00

Consider the following code snippet :

```
struct data1
{
int i;
float f;
};
struct data2
{
char name[10];
double d;
};
```

what is the correct way of declaring a union info which would share space amongst structure data1 and data2 ?

Select one:

- a. **None of these**
- b. **union info**
  {
  struct data2 y;
  };
- c. **union info**
  {
  struct data1 x;
  struct data2 y;
  };
- d. **union info**
  {
  struct data1 x;
  };

Question 8

Not yet answered

Marked out of 1.00

Which of the following is not a user-defined data type ?

Select one:

- a. **union stud**
  {
  int age;
  char name [20];
  }
- b. **struct book**
  {
  char name [10];
  }
- c. **enum day {Sun,Mon,Tue};**
- d. **long int i = 100;**

Question 9

Not yet answered

Marked out of 1.00

Given:

```
class MyThread extends Thread {
MyThread() {
System.out.print(" MyThread");
}
public void run() { System.out.print(" bar"); }
public void run(String s) { System.out.print(" baz"); }
}
public class TestThreads {
public static void main (String [] args) {
Thread t = new MyThread() {
public void run() { System.out.print(" foo"); }
};
t.start();
} }
```

What is the result?

Select one:

- **a. foo bar baz**
- **b. MyThread bar**
- **c. foo bar**
- **d. Compilation fails**
- **e. An exception is thrown at runtime**
- **f. bar foo**
- **g. MyThread foo**
- **h. foo**

Question 10

Not yet answered

Marked out of 1.00

Given:

```
3. import java.util.*;
4. class Business { }
5. class Hotel extends Business { }
6. class Inn extends Hotel { }
7. public class Travel {
8. ArrayList<Hotel> go() {
9. // insert code here
10. }
11. }
```

Which, inserted independently at line 9, will compile? (Choose all that apply.)

Select one:

- **a. return new ArrayList<Business>();**
- **b. return new ArrayList<Hotel>();**
- **c. return new ArrayList<Inn>();**
- **d. return new ArrayList<Object>();**

Question 11

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

const int i = 57;

int main()
{
const int i = 89;
cout<<i<<" "<<::i<<endl;
cout<<&i<<" "<<&::i;
return 0;
}
```

Select one:

- **a. 89 57**
  GarbageValue GarbageValue
- **b. Compilation fails**
- **c. GarbageValue GarbageValue**
  GarbageValue GarbageValue
- **d. 89 57**
  address followed by address

Question 12

Not yet answered

Marked out of 1.00

```
3. import java.util.*;
4. public class Pockets {
5. public static void main(String[] args) {
6. String[] sa = {"nickel", "button", "key", "lint"};
7. Sorter s = new Sorter();
8. for(String s2: sa) System.out.print(s2 + " ");
9. Arrays.sort(sa,s);
10. System.out.println();
11. for(String s2: sa) System.out.print(s2 + " ");
12. }
13. class Sorter implements Comparator<String> {
14. public int compare(String a, String b) {
15. return b.compareTo(a);
16. }
17. }
18. }
```

What is the result?

Select one:

- **a. button key lint nickel**
  nickel lint key button
- **b. nickel button key lint**
  nickel lint key button
- **c. nickel button key lint**
  button key lint nickel
- **d. An exception is thrown at runtime**
- **e. Compilation fails**
- **f. nickel button key lint**
  nickel button key lint

Question 13

Not yet answered

Marked out of 1.00

output of the following C Code

```
#include<stdio.h>

struct emp
{
char name[20];
int age;
};

void f(struct emp);

int main(){
struct emp e ={34,"Scott"};
f(e);
return 0;
}

void f(struct emp e)
{
printf(" %s %d ", e.name,e.age);
}
```

Select one:

- **a. 34 Scott**
- **b. Garbage value followed by garbage value**
- **c. Scott 34**
- **d. Garbage Value followed by 34**

Question 14

Not yet answered

Marked out of 1.00

Given:

```
public class TwoThreads {
static Thread laurel, hardy;
public static void main(String[] args) {
laurel = new Thread() {
public void run() {
System.out.println("A");
try {
hardy.sleep(1000);
} catch (Exception e) {
System.out.println("B");
}
System.out.println("C");
}
};
hardy = new Thread() {
public void run() {
System.out.println("D");
try {
laurel.wait();
} catch (Exception e) {
System.out.println("E");
}
System.out.println("F");
}
};
laurel.start();
hardy.start();
}
}
```

Which letters will eventually appear somewhere in the output? (Choose all that apply.)

Select one or more:

- ☐ **a. D**
- ☐ **b. The answer cannot be reliably determined**
- ☐ **c. A**
- ☐ **d. E**
- ☐ **e. F**
- ☐ **f. B**
- ☐ **g. The code does not compile**
- ☐ **h. C**

Question 15

Not yet answered

Marked out of 1.00

Given:

```
public class ThreadDemo {
synchronized void a() { actBusy(); }
static synchronized void b() { actBusy(); }
static void actBusy() {
try { Thread.sleep(1000); }
catch (InterruptedException e) {}
}
public static void main(String[] args) {
final ThreadDemo x = new ThreadDemo();
final ThreadDemo y = new ThreadDemo();
Runnable runnable = new Runnable() {
public void run() {
int option = (int) (Math.random() * 4);
switch (option) {
case 0: x.a(); break;
case 1: x.b(); break;
case 2: y.a(); break;
case 3: y.b(); break;
} }
};
Thread thread1 = new Thread(runnable);
Thread thread2 = new Thread(runnable);
thread1.start();
thread2.start();
} }
```

Which of the following pairs of method invocations could NEVER be executing at the same time?
(Choose all that apply.)

Select one or more:

- ☐ **a. x.a() in thread1, and y.b() in thread2**
- ☐ **b. x.b() in thread1, and x.b() in thread2**
- ☐ **c. x.a() in thread1, and y.a() in thread2**
- ☐ **d. x.a() in thread1, and x.b() in thread2**
- ☐ **e. x.a() in thread1, and x.a() in thread2**
- ☐ **f. x.b() in thread1, and y.b() in thread2**
- ☐ **g. x.b() in thread1, and y.a() in thread2**
- ☐ **h. x.b() in thread1, and x.a() in thread2**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=11886)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved.