Question 1

Not yet answered

Marked out of 1.00

Consider the following three C functions :

```
[PI]
int * g (void)
{
int x= 10;
return (&x);
}

[P2]
int * g (void)
{
int * px;
*px= 10;
return px;
}

[P3]
int *g (void)
{
int *px;
px = (int *) malloc (sizeof(int));
*px= 10;
return px;
}
```

Which of the above three functions are likely to cause problems with pointers?

Select one:

- **a. Only P3**
- **b. P1, P2 and P3**
- **c. Only P1 and P2**
- **d. Only P1 and P3**

Question 2

Not yet answered

Marked out of 1.00

Assume that the size of char is 1 byte and negatives are stored in 2's complement form

```
#include<stdio.h>
int main()
{
char c = 125;
c = c+10;
printf("%d", c);
return 0;
}
```

Select one:

- **a. -121**
- **b. +INF**
- **c. 135**
- **d. -8**

Question 3

Not yet answered

Marked out of 1.00

```
#include <stdio.h>
int fun()
{
static int num = 16;
return num--;
}

int main()
{
for(fun(); fun(); fun())
printf("%d ", fun());
return 0;
}
```

Select one:

- **a. Infinite loop**
- **b. 14 11 8 5 2**
- **c. 15 12 8 5 2**
- **d. 13 10 7 4 1**

Question **4**

Not yet answered

Marked out of 1.00

```
# include <stdio.h>
int main()
{
int i = 0;
for (i=0; i<20; i++)
{
switch(i)
{
case 0:
i += 5;
case 1:
i += 2;
case 5:
i += 5;
default:
i += 4;
break;
}
printf("%d ", i);
}
return 0;
}
```

Select one:

- **a. 5 10 15 20**
- **b. 7 12 17 22**
- **c. 16 21**
- **d. Compiler Error**

Question **5**

Not yet answered

Marked out of 1.00

Which of the following is true about exception handling in C++?

1) There is a standard exception class like Exception class in Java.
2) All exceptions are unchecked in C++, i.e., compiler doesn't check if the exceptions are caught or not.
3) In C++, a function can specify the list of exceptions that it can throw using comma separated list like following.

void fun(int a, char b) throw (Exception1, Exception2, ..)

Select one:

- **a. 1 and 2**
- **b. 1 and 3**
- **c. 2 and 3**
- **d. 1, 2 and 3**

Question 6

Not yet answered

Marked out of 1.00

```
#include <iostream>
using namespace std;

struct sec
{
int a;
char b;
};

int main()
{
struct sec s ={25,50};
struct sec *ps =(struct sec *)&s;
cout << ps->a << ps->b;
return 0;
}
```

Select one:

- **a. 253**
- **b. 252**
- **c. 252**
- **d. 254**

Question 7

Not yet answered

Marked out of 1.00

Which of the followings is/are automatically added to every class, if we do not write our own.

Select one:

- **a. Copy Constructor**
- **b. All of the mentioned**
- **c. A constructor without any parameter**
- **d. Assignment Operator**

Question 8

Not yet answered

Marked out of 1.00

What is the general syntax for accessing the namespace variable?

Select one:

- **a. namespace,operator**
- **b. namespace#operator**
- **c. namespace::operator**
- **d. namespace$operator**

Question **9**

Not yet answered

Marked out of 1.00

What will be the output of the following C++ code?

```
#include <iostream>
using namespace std;

namespace first
{
int var = 5;
}

namespace second
{
double var = 3.1416;
}

int main ()
{
int a;
a = first::var + second::var;
cout << a;
return 0;
}
```

Select one:

- **a. 8**
- **b. 8.31416**
- **c. 9**
- **d. compile time error**

Question **10**

Not yet answered

Marked out of 1.00

What will be the output of the following C++ code?

```
#include <iostream>
using namespace std;

namespace first
{
int x = 5;
int y = 10;
}

namespace second
{
double x = 3.1416;
double y = 2.7183;
}

int main ()
{
using first::x;
using second::y;
bool a, b;
a = x > y;
b = first::y < second::x;
cout << a << b;
return 0;
}
```

Select one:

- **a. 00**
- **b. 10**
- **c. 01**
- **d. 11**

Question **11**

Not yet answered

Marked out of 1.00

Given:

```
1. class Comp2 {
2. public static void main(String[] args) {
3. float f1 = 2.3f;
4. float[][] f2 = {{42.0f}, {1.7f, 2.3f}, {2.6f, 2.7f}};
5. float[] f3 = {2.7f};
6. Long x = 42L;
7. // insert code here
8. System.out.println("true");
9. }
10. }
```

And the following five code fragments:

```
F1. if(f1 == f2)
F2. if(f1 == f2[2][1])
F3. if(x == f2[0][0])
F4. if(f1 == f2[1,1])
F5. if(f3 == f2[2])
```

What is true?

Select one:

- **a. Three of them will compile, only one will be true**
- **b. Two of them will compile, two will be true**
- **c. Two of them will compile, only one will be true**
- **d. One of them will compile, only one will be true**
- **e. Three of them will compile, exactly three will be true**
- **f. Three of them will compile, exactly two will be true**

Question 12

Not yet answered

Marked out of 1.00

Given:

```
class Fork {
public static void main(String[] args) {
if(args.length == 1 | args[1].equals("test")) {
System.out.println("test case");
} else {
System.out.println("production " + args[0]);
}
}
}
```

And the command-line invocation:
java Fork live2

What is the result?

Select one:

- **a. Compilation fails**
- **b. test case live2**
- **c. An exception is thrown at runtime**
- **d. test case**
- **e. production live2**

Question 13

Not yet answered

Marked out of 1.00

Given:

```
class Feline {
public static void main(String[] args) {
Long x = 42L;
Long y = 44L;
System.out.print(" " + 7 + 2 + " ");
System.out.print(foo() + x + 5 + " ");
System.out.println(x + y + foo());
}
static String foo() { return "foo"; }
}
```

What is the result?

Select one:

- **a. 72 foo47 4244foo**
- **b. 9 foo47 86foo**
- **c. 72 foo425 4244foo**
- **d. 72 foo47 86foo**
- **e. Compilation fails**
- **f. 9 foo425 86foo**
- **g. 9 foo425 4244foo**
- **h. 9 foo47 4244foo**
- **i. 72 foo425 86foo**

Question **14**

Not yet answered

Marked out of 1.00

Given:

```
3. public class Twisty {
4. { index = 1; }
5. int index;
6. public static void main(String[] args) {
7. new Twisty().go();
8. }
9. void go() {
10. int [][] dd = {{9,8,7}, {6,5,4}, {3,2,1,0}};
11. System.out.println(dd[index++][index++]);
12. }
13. }
```

What is the result? (Choose all that apply.)

Select one:

- **a. 2**
- **b. 1**
- **c. 8**
- **d. 4**
- **e. 6**
- **f. An exception is thrown at runtime**
- **g. Compilation fails**

Question **15**

Not yet answered

Marked out of 1.00

Given:

```
3. public class McGee {
4. public static void main(String[] args) {
5. Days d1 = Days.TH;
6. Days d2 = Days.M;
7. for(Days d: Days.values()) {
8. if(d.equals(Days.F)) break;
9. d2 = d;
10. }
11. System.out.println((d1 == d2)?"same old" : "newly new");
12. }
13. enum Days {M, T, W, TH, F, SA, SU};
14. }
```

What is the result?

Select one:

- **a. Compilation fails due only to an error on line 11**
- **b. same old**
- **c. Compilation fails due only to an error on line 7**
- **d. Compilation fails due to multiple errors**
- **e. newly new**
- **f. Compilation fails due only to an error on line 13**
- **g. Compilation fails due only to an error on line 8**

Question **16**

Not yet answered

Marked out of 1.00

An IPv4 address consists of _____ bits.

Select one:

- **a. 64**
- **b. 32**
- **c. 4**
- **d. 8**

Question **17**

Not yet answered

Marked out of 1.00

An IPv6 address can have up to _____ colons.

Select one:

- **a. 8**
- **b. 4**
- **c. none of these**
- **d. 7**

Question **18**

Not yet answered

Marked out of 1.00

An IPv6 address can have up to _____ hexadecimal digits.

Select one:

- **a. none of these**
- **b. 8**
- **c. 32**
- **d. 16**

Question **19**

Not yet answered

Marked out of 1.00

Which is the correct UML definition of a collaboration?

Select one:

- **a. None of these**
- **b. A collaboration describes objects that share functionality.**
- **c. A collaboration describes the messages between objects.**
- **d. A collaboration describes the structure of instances playing roles in a behaviour and their relationships.**

Question **20**

Not yet answered

Marked out of 1.00

An interaction sequence diagram drawn during analysis differs from one drawn during design which of the following ways?

Select one:

- **a. It does not include boundary objects.**
- **b. It normally does not include design objects or detailed specifications of message signatures.**
- **c. It does not include control objects.**
- **d. None of these**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=11013)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved. Version 4.2

/