Question 1

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

class base
{
public:
virtual void disp(){
cout<<"\nin base :: disp ";
}
};


class derived1 : virtual public base
{
public:
virtual void disp(){
cout<<"\nin dervied1 :: disp ";
}
};

class derived2 : virtual public base
{
public:
virtual void disp(){
cout<<"\nin dervied2 :: disp ";
}
};


class derived3 : public derived1 , public derived2
{
public:
void disp(){
cout<<"\nin dervied3 :: disp ";
derived1::disp();
}
};




int main(){
base *b;
derived1 d1;
b = &d1;
b->disp();

derived2 d2;
b=&d2;
b->disp();

derived3 d3;
b=&d3;
b->disp();
return 0;
}
```

Select one:

- a. **in dervied1 :: disp**
  in dervied2 :: disp
  in dervied3 :: disp
  in dervied1 :: disp
- b. **in dervied1 :: disp**
  in dervied3 :: disp
  in dervied2 :: disp
  in dervied3 :: disp
- c. **Segmentation fault**
- d. **Compilation fails**

Question 2

Not yet answered

Marked out of 1.00

which of the following statement should be used to obtain a remainder after dividing 3.14 by 2.1 ?

Select one:

- a. **rem=3.14%2.1;**
- b. **rem = 3.14 mod 2.1**
- c. **rem = modf(3.14,2.1);**
- d. **we cannot obtain the remainder in floating point division**
- e. **rem = fmod(3.14,2.1);**

Question 3

Not yet answered

Marked out of 1.00

```
#include<stdio.h>
int main() {
int i = 1;
for( ; ;)
{
printf(" %d ", i++);
if(i > 10) break;

}
return 0;
}
```

Select one:

- a. **There should be a condition in the for loop**
- b. **The for loop should be replaced by a while loop**
- c. **No error**
- d. **The two semicolons should be removed**

Question 4

Not yet answered

Marked out of 1.00

Given:

```
1. // insert code here
2. class StatTest {
3. public static void main(String[] args) {
4. System.out.println(Integer.MAX_VALUE);
5. }
6. }
```

Which, inserted independently at line 1, compiles? (Choose all that apply.)

Select one or more:

- [ ] **a. import static java.lang.Integer.*;**
- [ ] **b. import static java.lang.Integer.*_VALUE;**
- [ ] **c. import static java.lang;**
- [ ] **d. import static java.lang.Integer.MAX_VALUE;**
- [ ] **e. None of the above statements are valid import syntax**
- [ ] **f. import static java.lang.Integer;**

Question 5

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

class Student
{
public:
int age;
int rno;
Student(int age,int rno)
{
this->age= age;
this->rno = rno;
}
void change()
{
age = 40;
rno = 80;
}
};

int main(){

const Student s(10,15);
s.change();
std::cout<<s.age<<" "<<s.rno;

}
```

Select one:

- **a. Segmentation fault**
- **b. 10 15**
- **c. Compilation fails**
- **d. 40 80**

Question 6

Not yet answered

Marked out of 1.00

Which of the following is correct about err used in the declaration given below ?

typedef enum error { warning, test,exception} err;

Select one:

- **a. It is a typedef for enum error**
- **b. It is a variable of type enum error**
- **c. It is a structure**
- **d. The statement is erroneous**
- **e. It is one of the elements of enum error**

Question 7

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

class index
{
public:
index() { count = 0; }
index(int c) { count = c; }

protected :
int count;
public:
void display() {
std::cout<<count<<" ";
}
void operator ++() {
count++;
}
};

class index1 : public index{
public :
void operator --(){
count--;
}

};


int main(){
index1 i;
++i;
++i;
i.display();
--i;
i.display();
return 0;
}
```

Select one:

- **a. 2 1**
- **b. 2 2**
- **c. Segmentation fault**
- **d. Compilation error**

Question 8

Not yet answered

Marked out of 1.00

Given:

```
3. public class Leader implements Runnable {
4. public static void main(String[] args) {
5. Thread t = new Thread(new Leader());
6. t.start();
7. System.out.print("m1 ");
8. t.join();
9. System.out.print("m2 ");
10. }
11. public void run() {
12. System.out.print("r1 ");
13. System.out.print("r2 ");
14. }
15. }
```

Which are true? (Choose all that apply.)

Select one or more:

- ☐ **a. The output could be m1 r1 r2 m2**
- ☐ **b. The output could be m1 r1 m2 r2**
- ☐ **c. The output could be r1 r2 m1 m2**
- ☐ **d. The output could be m1 m2 r1 r2**
- ☐ **e. Compilation fails**
- ☐ **f. An exception is thrown at runtime**

Question 9

Not yet answered

Marked out of 1.00

Given:

```
import static java.lang.System.*;
class _ {
static public void main(String... __A_V_) {
String $ = "";
for(int x=0; ++x < __A_V_.length; )
$ += __A_V_[x];
out.println($);
}
}
```

And the command line:
java _ - A .
What is the result?

Select one or more:

- [ ] **a. -A**
- [ ] **b. -A.**
- [ ] **c. An exception is thrown at runtime**
- [ ] **d. Compilation fails**
- [ ] **e. _-A.**
- [ ] **f. _A.**
- [ ] **g. A.**

Question 10

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

int main(){
int a=5,b=6,c=7,d=8;
int *pa,*pb,*pc,*pd;
pa=&a;
pb=&b;
pc=&c;
pd=&d;
int *arr[]={pa,pb,pc,pd};
for(int i=0;i<4;i++)
cout<<*arr[i]<<" ";
}
```

Select one:

- ○ **a. Compilation fails**
- ○ **b. 5 6 7 8**
- ○ **c. 4 Address gets printed**
- ○ **d. Segmentation fault**

Question 11

Not yet answered

Marked out of 1.00

what will be the output of the following C Program

the array begins at the location 1008

```
#include<stdio.h>
int main() {
int a[2][3][4] = { {19,2,3,4},{5,6,7,8},{9,1,1,2},{2,1,4,7},{6,7,8,9},{9,8,7,6}};
printf(" %d %d %d %d", a,*a,**a,***a);
return 0;
}
```

Select one:

- **a. 1008 1008 1008 1008**
- **b. 19 19 19 19**
- **c. 1008 19 19 19**
- **d. 1008 1008 1008 19**
- **e. Compilation fails**

Question 12

Not yet answered

Marked out of 1.00

Given:

```
3. import java.util.*;
4. class Dog { int size; Dog(int s) { size = s; } }
5. public class FirstGrade {
6. public static void main(String[] args) {
7. TreeSet<Integer> i = new TreeSet<Integer>();
8. TreeSet<Dog> d = new TreeSet<Dog>();
9.
10. d.add(new Dog(1)); d.add(new Dog(2)); d.add(new Dog(1));
11. i.add(1); i.add(2); i.add(1);
12. System.out.println(d.size() + " " + i.size());
13. }
14. }
```

What is the result?

Select one:

- **a. Compilation fails**
- **b. 1 2**
- **c. An exception is thrown at runtime**
- **d. 3 3**
- **e. 3 2**
- **f. 2 2**
- **g. 2 3**

Question 13

Not yet answered

Marked out of 1.00

Given:
3. import java.util.*;
4. public class GeoCache {
5. public static void main(String[] args) {
6. String[] s = {"map", "pen", "marble", "key"};
7. Othello o = new Othello();
8. Arrays.sort(s,o);
9. for(String s2: s) System.out.print(s2 + " ");
10. System.out.println(Arrays.binarySearch(s, "map"));
11. }
12. static class Othello implements Comparator<String> {
13. public int compare(String a, String b) { return b.compareTo(a); }
14. }
15. }

Which are true? (Choose all that apply.)

Select one or more:

- ☐ **a. An exception is thrown at runtime**
- ☐ **b. The output will contain "key map marble pen"**
- ☐ **c. The output will contain a 1**
- ☐ **d. The output will contain "pen marble map key"**
- ☐ **e. The output will contain a –1**
- ☐ **f. Compilation fails**
- ☐ **g. The output will contain a 2**

Question 14

Not yet answered

Marked out of 1.00

what will be the output of the following program?

```
#include<stdio.h>
int main() {
int i = 4;
switch(i)
{
default :
printf(" apple ");
case 1 : printf(" orange "); break;
case 2 : printf(" grapes "); break;
case 3 : printf(" mango ");
}
return 0;
}
```

Select one:

- ○ **a. None of these**
- ○ **b. Compilation fails**
- ○ **c. apple orange**
- ○ **d. apple**

Question **15**

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

int main(){

bool x(true);
std::cout<<x;

}
```

Select one:

- **a. 1**
- **b. true**
- **c. compilation error**
- **d. Segmentation fault**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=12004)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved. Version 4.2