Question 1

Not yet answered

Marked out of 1.00

output of the following C code

Assume the sizes are given as below

int- 4 bytes
float - 4 bytes
double - 8 bytes
char - 1 bytes
long double - 16 bytes

```
#include<stdio.h>
int main()
{
printf(" %lu %lu %lu ", sizeof(3.14f),sizeof(3.14),sizeof(3.14l));
}
```

Select one:

- **a. 4 8 16**
- **b. 4 8 12**
- **c. 4 4 4**
- **d. 4 8 8**

Question 2

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

class sample
{
static int count ;
public:
sample() {
count++;
}
static void showcount() {
cout<<" "<<count;
}

};

int sample::count=0;

int main()
{

sample s;
sample::showcount();
sample s2;
sample::showcount();
sample s3;
sample::showcount();

return 0;
}
```

Select one:

- **a. 2 2 2**
- **b. 3 3 3**
- **c. 1 2 3**
- **d. 0 1 2**
- **e. Compilation fails**

Question 3

Not yet answered

Marked out of 1.00

Which of the following statements are correct about an if-else statement in a C Program ?

Select one or more:

- **a. Nested if-else statements are allowed.**
- **b. if we use an if it is compulsory to use an else**
- **c. Every if-else statement can be replaced by an equivalent statement using ?: operators**
- **d. Multiple statements in an else block are allowed**
- **e. Multiple statements in an if block are allowed**

Question 4

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

int i=3;

class parent
{
protected:
int i;
public:
parent() {
i=2;
cout<<" "<<i;
}
};

class child:public parent
{
int i;
public:

child():parent() {
i=1;
cout<<" "<<i;
cout<<" "<<parent::i;
cout<<" "<<::i;
}
};


int main()
{

child c;
return 0;
}
```

Select one:

- **a. 2 2 2 3**
- **b. 1 1 2 3**
- **c. 2 1 2 3**
- **d. Compilation fails**

Question 5

Not yet answered

Marked out of 1.00

```
#include<stdio.h>
int main()
{
int i = 1;
if(!i)
printf("\n Recursion ends here ");
else
{
i=0;
printf("\n Recursion continues here ");
main();
}
return 0;
}
```

Select one:

- **a. Recursion continues here**
- **b. Recursion ends here**
  Recursion continues here
- **c. Recursion ends here**
- **d. Recursion continues here**
  Recursion ends here
- **e. The Code prints Recursion continues here**
  Recursion continues here (till the stack over flows)

Question 6

Not yet answered

Marked out of 1.00

output of the following java code

```
public class Main {
public static void main (String[] args) {
double d = 10.0/-0;
if(d==Double.POSITIVE_INFINITY)
System.out.println("Positive Infinity");
else
System.out.println("Negative Infinity");
}
}
```

Select one:

- **a. Negative Infinity**
- **b. Runtime exception**
- **c. Compilation fails**
- **d. Positive Infinity**

Question 7

Not yet answered

Marked out of 1.00

Output of the following CPP Code

Assume the size of int as 4 bytes

```
#include<iostream>
using namespace std;
class parent
{
int i;
};
class child : public parent
{
int j;
};

int main()
{
cout<<sizeof(parent)<<" "<<sizeof(child)<<" ";
parent p;
child c;
cout<<sizeof(p)<<" "<<sizeof(c);
return 0;
}
```

Select one:

- **a. 8 8 8 8**
- **b. 4 8 4 8**
- **c. 1 1 1 1**
- **d. 4 4 4 4**

Question 8

Not yet answered

Marked out of 1.00

Given:
3. import java.util.*;
4. public class Antique {
5. public static void main(String[] args) {
6. List<String> myList = new ArrayList<String>();
7. assert (args.length > 0);
8. System.out.println("still static");
9. }
10. }

Which sets of commands (javac followed by java) will compile and run without exception or error? (Choose all that apply.)

Select one or more:

- ☐ **a. javac -source 1.6 Antique.java**
  java -ea Antique
- ☐ **b. javac -source 1.4 Antique.java**
  java Antique
- ☐ **c. javac Antique.java**
  java -ea Antique
- ☐ **d. javac Antique.java**
  java Antique
- ☐ **e. javac -source 6 Antique.java**
  java Antique

Question 9

Not yet answered

Marked out of 1.00

```
public class Main {

public static void main (String[] args) {
int [] a ={1};
Main m = new Main();
m.increment(a);
System.out.println(a[a.length-1]);

}
void increment(int [] j){
j[j.length-1]++;
}
}
```

Select one:

- ◯ **a. Compiles and runs printing out 2**
- ◯ **b. An ArrayIndexOutOfBounds Exception at runtime**
- ◯ **c. Compiles and runs printing out 1**
- ◯ **d. Compile error**

Question **10**

Not yet answered

Marked out of 1.00

The binary equivalent of 5.375 is

Select one:

- **a. 101.101110111**
- **b. None of these**
- **c. 101.011**
- **d. 101011**

Question **11**

Not yet answered

Marked out of 1.00

output of the following code

```
#include<stdio.h>
int main() {
int x=10,y=20;
if(!(!x) && x)
printf("x=%d\n",x);
else
printf("y=%d\n",y);
return 0;
}
```

Select one:

- **a. x=0**
- **b. x=1**
- **c. x=10**
- **d. y=20**
- **e. x=-10**

Question 12

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

class parent
{
public:
virtual void display()=0;
};
class child:public parent
{
private:
virtual void display() =0; // Line A
};
class child2 : child // Line B
{
public:
void display()
{
cout<<"display called";
}
};


int main()
{
child2 c;
c.display();
return 0;
}
```

Select one:

- **a. Compiles fine and prints display called**
- **b. Compilation fails at Line B**
- **c. Compilation fails at Line A**
- **d. Compilation fails at Both Line A and Line B**

Question 13

Not yet answered

Marked out of 1.00

Given two files:

```
1. package pkgA;
2. public class Foo {
3. int a = 5;
4. protected int b = 6;
5. }
```

```
1. package pkgB;
2. import pkgA.*;
3. public class Fiz extends Foo {
4. public static void main(String[] args) {
5. Foo f = new Foo();
6. System.out.print(" " + f.a);
7. System.out.print(" " + f.b);
8. System.out.print(" " + new Fiz().a);
9. System.out.println(" " + new Fiz().b);
10. }
11. }
```

What is the result? (Choose all that apply.)

Select one or more:

- ☐ **a. 5 6 5 6**
- ☐ **b. Compilation fails with an error on line 6**
- ☐ **c. 5 6 followed by an exception**
- ☐ **d. Compilation fails with an error on line 7**
- ☐ **e. Compilation fails with an error on line 8**

Question 14

Not yet answered

Marked out of 1.00

```
#include<iostream>
#include<string.h>
using namespace std;
class parent
{
public:
int i=10;
char s[10]="sachin";
parent()
{
i=20;
strcpy(s,"scott");

}
parent(int i,char s[10])
{
this->i=i;
strcpy(this->s,s);
}
};

int main()
{
parent p(30,"shyam");
cout<<p.i<<" "<<p.s;
return 0;
}
```

Select one:

- **a. 10 saching**
- **b. 30 shyam**
- **c. 20 scott**
- **d. Compilation fails**

Question **15**

Not yet answered

Marked out of 1.00

Given the default classpath:
/foo

And this directory structure:

foo
|
test
|
xcom
|--A.class
|--B.java

And these two files:

```
package xcom;
public class A { }
```

```
package xcom;
public class B extends A { }
```

Which allows B.java to compile? (Choose all that apply.)

Select one or more:

- ☐ **a. Set the current directory to xcom then invoke javac -classpath . B.java**
- ☐ **b. Set the current directory to test then invoke javac -classpath xcom:. B.java**
- ☐ **c. Set the current directory to xcom then invoke javac B.java**
- ☐ **d. Set the current directory to test then invoke javac -classpath . xcom/B.java**
- ☐ **e. Set the current directory to test then invoke javac -classpath xcom B.java**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=12574)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved. Version 4.2

/