Question 1

Not yet answered

Marked out of 1.00

```
void main()
{
fork() ; fork() ; printf ("yes");
}
```

If we execute this core segment, how many times the string yes will be printed ?

Select one:

- **a. 4 times**
- **b. Only once**
- **c. 2 times**
- **d. 8 times**

Question 2

Not yet answered

Marked out of 1.00

Which of the following is incorrect in C++ ?

(1)When we write overloaded function we must code the function for each usage.
(2)When we write function template we code the function only once.
(3)It is difficult to debug macros
(4)Templates are more efficient than macros

Select one:

- **a. All are correct**
- **b. (1) and (2)**
- **c. (1), (2) and (3)**
- **d. (3) and (4)**

Question 3

Not yet answered

Marked out of 1.00

Output of the following C Code

```
#include<stdio.h>
int main()
{
typedef int i;
i a = 0;
printf("%d", a);
return 0;
}
```

Select one:

- **a. 0**
- **b. 1**
- **c. Compiler Error**
- **d. Runtime Error**

Question 4

Not yet answered

Marked out of 1.00

IN CPP, When one object reference variable is assigned to another object reference variable then

Select one:

- **a. it is illegal to assign one object reference variable to another object reference variable.**
- **b. a copy of the object is created.**
- **c. a copy of the reference is created.**
- **d. a copy of the reference is not created.**

Question 5

Not yet answered

Marked out of 1.00

Which of the following is an appropriate way of managing complex behaviour on an interaction sequence diagram?

Select one:

- **a. Some objects are omitted from the diagram to reduce the complexity.**
- **b. A group of objects can be represented by a single lifeline.**
- **c. Some messages are omitted to reduce the complexity.**
- **d. None of these**

Question 6

Not yet answered

Marked out of 1.00

What is the time complexity of fun()?

```
int fun(int n)
{
int count = 0;
for (int i = 0; i < n; i++)
for (int j = i; j > 0; j--)
count = count + 1;
return count;
}
```

Select one:

- **a. Theta (n^2)**
- **b. Theta (n*Logn)**
- **c. Theta (nLognLogn)**
- **d. Theta (n)**

Question **7**

Not yet answered

Marked out of 1.00

What is meant by the term ‘thread of control’ in the context of concurrent behaviour?

Select one:

- **a. None of these**
- **b. A thread of control is the mechanism that controls concurrent behaviour.**
- **c. A thread of control is an execution pathway that may occur simultaneously with other execution pathways.**
- **d. A thread of control is a weak part of the control system.**

Question **8**

Not yet answered

Marked out of 1.00

A computer has 1000 K of main memory.

The jobs arrive and finish in the sequence

Job 1 requiring 200 K arrives
Job 2 requiring 350 K arrives
Job 3 requiring 300 K arrives
Job 1 finishes
Job 4 requiring 120 K arrives
Job 5 requiring 150 K arrives
Job 6 requiring 80 K arrives

Among best fit and first fit, which performs better for this sequence?

Select one:

- **a. First fit**
- **b. Best fit**
- **c. Both perform the same**
- **d. None of the above**

Question 9

Not yet answered

Marked out of 1.00

Given:

```
3. public class Spock {
4. public static void main(String[] args) {
5. int mask = 0;
6. int count = 0;
7. if( ((5<7) || (++count < 10)) | mask++ < 10 ) mask = mask + 1;
8. if( (6 > 8) ^ false) mask = mask + 10;
9. if( !(mask > 1) && ++count > 1) mask = mask + 100;
10. System.out.println(mask + " " + count);
11. }
12. }
```

Which two answers are true about the value of mask and the value of count at line 10?
(Choose two.)

Select one or more:

- ☐ **a. count is greater than 0**
- ☐ **b. mask is 2**
- ☐ **c. count is 0**
- ☐ **d. mask is 0**
- ☐ **e. mask is greater than 10**
- ☐ **f. mask is 1**
- ☐ **g. mask is 10**

Question **10**

Not yet answered

Marked out of 1.00

```
#include <iostream>
using namespace std;

class A
{
public:
virtual void fun() { cout << "A::fun() "; }
};

class B: public A
{
public:
void fun() { cout << "B::fun() "; }
};

class C: public B
{
public:
void fun() { cout << "C::fun() "; }
};

int main()
{
B *bp = new C;
bp->fun();
return 0;
}
```

Select one:

- **a. C::fun()**
- **b. A::fun()**
- **c. None of these**
- **d. Compilation fails**
- **e. B::fun()**

Question 11

Not yet answered

Marked out of 1.00

output of the following C code

```
int main()
{
char a[2][3][3] = {'s','t','a','y','h','o','m','e'};
printf("%s ", **a);
return 0;
}
```

Select one:

- **a. stayhome followed by garbage characters**
- **b. Runtime Error**
- **c. Compiler Error**
- **d. stayhome**

Question 12

Not yet answered

Marked out of 1.00

Given:

```
4. public class SpecialOps {
5. public static void main(String[] args) {
6. String s = "";
7. Boolean b1 = true;
8. Boolean b2 = false;
9. if((b2 = false) | (21%5) > 2) s += "x";
10. if(b1 || (b2 = true)) s += "y";
11. if(b2 == true) s += "z";
12. System.out.println(s);
13. }
14. }
```

Which are true? (Choose all that apply.)

Select one:

- **a. Compilation fails**
- **b. y will be included in the output**
- **c. z will be included in the output**
- **d. An exception is thrown at runtime**
- **e. x will be included in the output**

Question **13**

Not yet answered

Marked out of 1.00

output of the following C Code

```
#include<stdio.h>
int main()
{
int n;
for (n = 9; n!=0; n--)
printf("n = %d", n--);
return 0;
}
```

What is the output?

Select one:

- **a. 9 8 7 6 5 4 3 2 1**
- **b. 9 7 5 3 1**
- **c. Infinite Loop**
- **d. 9 7 5 3**

Question **14**

Not yet answered

Marked out of 1.00

Given:

```
class Plane {
static String s = "-";
public static void main(String[] args) {
new Plane().s1();
System.out.println(s);
}
void s1() {
try { s2(); }
catch (Exception e) { s += "c"; }
}
void s2() throws Exception {
s3(); s += "2";
s3(); s += "2b";
}
void s3() throws Exception {
throw new Exception();
} }
```

What is the result?

Select one:

- **a. -c2**
- **b. -c22b**
- **c. -2c**
- **d. -c**
- **e. Compilation fails**
- **f. -**
- **g. -2c2b**
- **h. -2c2bc**

Question **15**

Not yet answered

Marked out of 1.00

Collaboration diagrams differ from interaction sequence diagrams in the following way?

Select one:

- **a. Collaboration diagrams only show the collaboration and not the sequence in which the messages are sent.**
- **b. Collaboration diagrams show the links between the objects.**
- **c. None of these**
- **d. Collaboration diagrams cannot show the design detail that can be shown on a sequence diagram.**

Question **16**

Not yet answered

Marked out of 1.00

Which of the following is a disadvantage of collaboration diagrams?

Select one:

- **a. A collaboration diagram cannot include guard conditions.**
- **b. None of these**
- **c. A collaboration diagram can only be used during analysis.**
- **d. A collaboration diagram is difficult to read if there are many messages between two objects.**

Question **17**

Not yet answered

Marked out of 1.00

Given:

try { int x = Integer.parseInt("two"); }

Which could be used to create an appropriate catch block? (Choose all that apply.)

Select one or more:

- **a. IllegalStateException**
- **b. IllegalArgumentException**
- **c. ClassCastException**
- **d. NumberFormatException**
- **e. ArrayIndexOutOfBoundsException**
- **f. ExceptionInInitializerError**

Question **18**

Not yet answered

Marked out of 1.00

Given:

```
3. interface Vessel { }
4. interface Toy { }
5. class Boat implements Vessel { }
6. class Speedboat extends Boat implements Toy { }
7. public class Tree {
8. public static void main(String[] args) {
9. String s = "0";
10. Boat b = new Boat();
11. Boat b2 = new Speedboat();
12. Speedboat s2 = new Speedboat();
13. if((b instanceof Vessel) && (b2 instanceof Toy)) s += "1";
14. if((s2 instanceof Vessel) && (s2 instanceof Toy)) s += "2";
15. System.out.println(s);
16. }
17. }
```

What is the result?

Select one:

- **a. Compilation fails**
- **b. 012**
- **c. 0**
- **d. 01**
- **e. 02**
- **f. An exception is thrown at runtime**

Question **19**

Not yet answered

Marked out of 1.00

What happens in C++ when an exception is thrown and not caught anywhere like following program.

```
#include <iostream>
using namespace std;

int fun() throw (int)
{
throw 10;
}

int main() {

fun();

return 0;
}
```

Select one:

- **a. Abnormal program termination**
- **b. None of these**
- **c. Program doesn't print anything and terminates normally**
- **d. Compiler error**

Question **20**

Not yet answered

Marked out of 1.00

What is the output of below C program?

```
#include <stdio.h>
int foo(int* a, int* b)
{
int sum = *a + *b;
*b = *a;
return *a = sum - *b;
}
int main()
{
int i = 0, j = 1, k = 2, l;
l = i++ || foo(&j, &k);
printf("%d %d %d %d", i, j, k, l);
return 0;
}
```

Select one:

- **a. 1 2 2 1**
- **b. 1 2 2 2**
- **c. 1 1 2 1**
- **d. 1 2 1 1**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=11105)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved. Version 4.2