Question 1

Not yet answered

Marked out of 1.00

Consider the schema
Sailors(sid, sname, rating, age) with the following data

sid sname rating age
22 Dustin 7 45
29 Borg 1 33
31 Pathy 8 55
32 Robert 8 25
58 Raghu 10 17
64 Herald 7 35
71 Vishnu 10 16
74 King 9 35
85 Archer 3 26
84 Bob 3 64
96 Flinch 3 17

For the query

SELECT S.rating, AVG(S.age) AS avgage FROM Sailors S
Where S.age >= 18
GROUP BY S.rating
HAVING 1 < (SELECT COUNT(*) FROM Sailors S2 where S.rating = S2.rating)

The number of rows returned is

Select one:

- **a. 6**
- **b. 3**
- **c. 5**
- **d. 4**

Question 2

Not yet answered

Marked out of 1.00

```
public class Main
{
String pearl(String s)
{
return s.substring(0,1); //Line A
}
public static void main(String [] args )
{
Main m = new Main();
char c = 4 * 4; //Line B
String str="Bead";

str=m.pearl(str);
System.out.println(Byte.parseByte(str,c)); // Line C
}
}
```

Select one:

- **a. Compilation fails at Line B only**
- **b. Compilation fails at Line C only**
- **c. Compilation fails at all the three lines (Line A, Line B and Line C)**
- **d. Runtime exception**
- **e. Compilation fails at Line A only**
- **f. Compiles fine and prints some number**

Question 3

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

class Sample
{
private:
int x,y;
public:
void sample();
void display();
};
void Sample::sample()
{
cin>>x>>y;
}
void Sample::display()
{
cout<<x<<" "<<y;
}
int main()
{
Sample s1;
s1.sample();
s1.display();
return 0;
}
```

Select one:

- **a. Segmentation fault**
- **b. Compilation fails**
- **c. Compiles but prints nothing**
- **d. Reads two numbers and prints two numbers**

Question 4

Not yet answered

Marked out of 1.00

```
public class Test
{
public static void main(String [] args )
{
Integer x = new Integer(256);
System.out.println(x.byteValue());
}
}
```

Select one:

- **a. Prints 127**
- **b. Prints 0**
- **c. Runtime error**
- **d. Compilation fails**
- **e. Prints 256**

Question 5

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

class Sample
{
private:
int x,y;
public:
void read();
void display();
};
void Sample::read()
{
cin>>x>>y;
}
void Sample::display()
{
cout<<x<<" "<<y;
}
int main()
{
Sample *s1;
s1 =(Sample *)malloc(sizeof(Sample)); // Line A
s1->read();
s1->display();
return 0;
}
```

Select one:

- **a. the code will work if and only if replaced Line A to s1=new Sample;**
- **b. reads two numbers and prints two numbers**
- **c. What ever changes you make the code will not compile at all**
- **d. the code will work if and only if replaced Line A to s1 = (Sample)new Sample;**

Question 6

Not yet answered

Marked out of 1.00

```
#include<stdio.h>
int main()
{
char ch;
if((ch=printf("")))
printf("if block");
else;
printf("else block");
}
```

Select one:

- **a. if block else block**
- **b. Compilation fails**
- **c. Prints Nothing**
- **d. if block**
- **e. else block**

Question 7

Not yet answered

Marked out of 1.00

In SQL, _____ is an Aggregate function.

Select one:

- **a. MODIFY**
- **b. SELECT**
- **c. CREATE**
- **d. AVG**

Question 8

Not yet answered

Marked out of 1.00

Consider the following tables

employee

empid empname managerid deptid salary dob
11 Ram 0 1 40000 01-01-1991
12 Murali 0 2 35000 21-02-1987
13 Tarang 1 1 30000 25-08-1989
15 Lisa 2 2 42000 31-05-1992
27 Fatima 2 1 39000 17-04-1990

Department

Deptid DeptName
1 IT
2 Admin

What is the outut of below SQL Query?

```
SELECT * FROM EMPLOYEE E
WHERE 2 = (SELECT COUNT(DISTINCT E1.SALARY)
FROM EMPLOYEE E1
WHERE E1.SALARY > E.SALARY)
```

Select one:

- **a. Two distinct salary of employees**
- **b. Employee with second highest salary**
- **c. Third highest salary**
- **d. Second Highest salary**

Question 9

Not yet answered

Marked out of 1.00

```
#include<stdio.h>
int main()
{
int i=1;
switch(i)
{
printf("one");
case 1 : printf("zero"); break;
case 2 : printf("two"); break;
}
}
```

Select one:

- **a. zero**
- **b. None of these**
- **c. one**
- **d. one zero**
- **e. Compilation fails**

Question 10

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

class Sample
{
private:
int x,y;
public:
void read();
void show(Sample s);
};
void Sample::read()
{
cin>>x>>y;
}

void show(Sample s)
{
cout<<s.x<<" "<<s.y;
}
int main()
{
Sample s2;
s2.read();
show(s2);
return 0;
}
```

In order to make the code compile we should mark the show(Sample s) in the class Sample as

Select one:

- **a. const**
- **b. inline**
- **c. static**
- **d. friend**

Question 11

Not yet answered

Marked out of 1.00

If you think the following CPP code works fine and if the rno entered is 15 and marks entered is 95 what will be the output ?

```
#include <iostream>
using namespace std;

class Student
{
private:
int rno,marks;
public:
Student(int r = 0, int i =0)
{
rno = r; marks = i;
}
friend ostream & operator << (ostream &MyCout, const Student &c);
friend istream & operator >> (istream &MyCin, Student &c);
};

ostream & operator << (ostream &MyCout, const Student &c)
{
MyCout << c.rno;
MyCout << " " << c.marks << endl;
return MyCout;
}

istream & operator >> (istream &MyCin, Student &c)
{

MyCin >> c.rno;
MyCin >> c.marks;
return MyCin;
}

int main()
{
Student s1;
cin >> s1;
cout << s1;
return 0;
}
```

Select one:

- **a. Compilation fails**
- **b. Compiles fine but prints Nothing**
- **c. 15 95**
- **d. Segmentation fault**
- **e. None of these**

Question 12

Not yet answered

Marked out of 1.00

```
#include<stdio.h>
#define PAT(a,b) ((a)>(b))?(a):(b);

int main()
{
int a=10,b=5;
int k=0;
k=PAT(++a,b++);
printf(" %d %d %d ", a,b,k);
return 0;
}
```

Select one:

- **a. 12 6 12**
- **b. Compilation fails**
- **c. 12 6 Garbage Value**
- **d. 11 5 Garbage Value**
- **e. 11 5 11**

Question 13

Not yet answered

Marked out of 1.00

```
public class Test
{
public static void main(String [] args ) {
byte a = 10;
Byte b = new Byte(a);
Byte c = new Byte(11);
System.out.println(b.compareTo(c));
}
}
```

Select one:

- **a. Runtime error**
- **b. Runs and prints 0**
- **c. Runs and prints false**
- **d. Runs and prints -1**
- **e. Runs and prints 1**
- **f. Compiletime error**

Question **14**

Not yet answered

Marked out of 1.00

```
#include<stdio.h>

int main() {
char i=0;
for(i=5 && i >=-1;++i;i>0)
printf(" %d\n ", i);
printf(" \n");
return 0;

}
```

Select one:

- **a. 1 2 3 4 .... 125 126 -127 -126....-1**
- **b. 0 1 2 3 4 5**
- **c. compiles fine but prints nothing**
- **d. 1 2 3 4 .... 126 127 -128 -127 ..... -2 -1**
- **e. Compilation fails**
- **f. None of these**

Question **15**

Not yet answered

Marked out of 1.00

```
public class Main
{
public static void main(String [] args ) {
StringBuffer a="Hello";
StringBuffer b = a.append(" World");
System.out.println(b);
}
}
```

Select one:

- **a. World**
- **b. Hello**
- **c. Hello World**
- **d. Compilation fails**
- **e. Run time exception**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=13055)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved. Version 4.2

/