Question 1

Not yet answered

Marked out of 1.00

Output of following C program?

```
#include <stdio.h>
int f1() { printf ("hello"); return 1;}
int f2() { printf ("welcome"); return 1;}

int main()
{
int p = f1() + f2();
return 0;
}
```

Select one:

- **a. hellowelcome**
- **b. Compiler Error**
- **c. welcomehello**
- **d. Compiler Dependent**

Question 2

Not yet answered

Marked out of 1.00

Given:
3. public class Gotcha {
4. public static void main(String[] args) {
5. // insert code here
6.
7. }
8. void go() {
9. go();
10. }
11. }

And given the following three code fragments:

I. new Gotcha().go();

II. try { new Gotcha().go(); }
catch (Error e) { System.out.println("ouch"); }

III. try { new Gotcha().go(); }
catch (Exception e) { System.out.println("ouch"); }

When fragments I - III are added, independently, at line 5, which are true? (Choose all that apply.)

Select one or more:

- ☐ **a. All will complete normally**
- ☐ **b. They will all compile**
- ☐ **c. None will complete normally**
- ☐ **d. Some will not compile**
- ☐ **e. Only one will complete normally**
- ☐ **f. Two of them will complete normally**

Question 3

Not yet answered

Marked out of 1.00

Predict the output of following C program, assume that a character takes 1 byte and pointer takes 4 bytes.

```
#include <stdio.h>
int main()
{
char *str1 = "helloworld";
char str2[] = "helloworld";
char *str3='K';

printf("sizeof(str1) = %d, sizeof(str2) = %d, sizeof(str3) = %d ", sizeof(str1),
sizeof(str2),sizeof(str3));

return 0;
}
```

Select one:

- **a. sizeof(str1) = 4, sizeof(str2) = 11, sizeof(str3) = 4**
- **b. sizeof(str1) = 4, sizeof(str2) = 4, sizeof(str3) = 1**
- **c. sizeof(str1) = 11, sizeof(str2) = 11, sizeof(str3) = 1**
- **d. sizeof(str1) = 11, sizeof(str2) = 4, sizeof(str3) = 4**

Question 4

Not yet answered

Marked out of 1.00

What is the output of the following program?

```
#include<iostream>
using namespace std;

class Base {
public:
void f() {
cout<<"Base\n";
}
};

class Derived:private Base {
public:
void f() {
cout<<"Derived\n";
}
};
main() {
Base *p = new Derived();
p->f();
}
```

Select one:

- **a. Base**
- **b. Derived**
- **c. None of the above.**
- **d. Compile error**

Question 5

Not yet answered

Marked out of 1.00

Given:

```
3. public class Wind {
4. public static void main(String[] args) {
5. foreach:
6. for(int j=0; j<5; j++) {
7. for(int k=0; k< 3; k++) {
8. System.out.print(" " + j);
9. if(j==3 && k==1) break foreach;
10. if(j==0 || j==2) break;
11. }
12. }
13. }
14. }
```

What is the result?

Select one:

- **a. Compilation fails**
- **b. 1 1 1 3 3**
- **c. 1 1 1 3 3 4 4 4**
- **d. 0 1 2 3**
- **e. 0 1 1 1 2 3 3 4 4 4**
- **f. 0 1 1 1 2 3 3**

Question 6

Not yet answered

Marked out of 1.00

In SQL, relations can contain null values, and comparisons with null values are treated as unknown.

Suppose all comparisons with a null value are treated as false.
Which of the following pairs is not equivalent?

Select one:

- **a. x < 5, not(x = 5)**
- **b. x = 5, not (not (x = 5)**
- **c. None of the above**
- **d. x = 5, x > 4 and x < 6, where x is an integer**

Question 7

Not yet answered

Marked out of 1.00

Predict the output of following C program

```
#include <stdio.h>
int main()
{
char a = '\012';

printf("%d", a);

return 0;
}
```

Select one:

- a. **Empty**
- b. **10**
- c. **12**
- d. **Compiler Error**

Question 8

Not yet answered

Marked out of 1.00

Given:

```
3. public class OverAndOver {
4. static String s = "";
5. public static void main(String[] args) {
6. try {
7. s += "1";
8. throw new Exception();
9. } catch (Exception e) { s += "2";
10. } finally { s += "3"; doStuff(); s += "4";
11. }
12. System.out.println(s);
13. }
14. static void doStuff() { int x = 0; int y = 7/x; }
15. }
```

What is the result?

Select one:

- a. **Compilation fails**
- b. **13**
- c. **An exception is thrown with no other output**
- d. **1234 followed by an exception**
- e. **123 followed by an exception**
- f. **1234**
- g. **123**
- h. **12**

Question 9

Not yet answered

Marked out of 1.00

Consider the following relational schema:

employee(empId, empName, empDept)
customer(custId, custName, salesRepId, rating)

salesRepId is a foreign key referring to empId of the employee relation.
Assume that each employee makes a sale to at least one customer.

What does the following query return?

```
SELECT empName
FROM employee E
WHERE NOT EXISTS ( SELECT custId
FROM customer C
WHERE C.salesRepId = E.empId
AND C.rating <> 'GOOD');
```

Select one:

- **a. Names of all the employees with at most one of their customers having a 'GOOD' rating.**
- **b. Names of all the employees with none of their customers having a 'GOOD' rating.**
- **c. Names of all the employees with at least one of their customers having a 'GOOD' rating.**
- **d. Names of all the employees with all their customers having a 'GOOD' rating.**

Question 10

Not yet answered

Marked out of 1.00

Given:

```
3. public class Clumsy {
4. public static void main(String[] args) {
5. int j = 7;
6. assert(++j > 7);
7. assert(++j > 8): "hi";
8. assert(j > 10): j=12;
9. assert(j==12): doStuff();
10. assert(j==12): new Clumsy();
11. }
12. static void doStuff() { }
13. }
```

Which are true? (Choose all that apply.)

Select one:

- **a. Compilation fails due to an error on line 7**
- **b. Compilation fails due to an error on line 8**
- **c. Compilation fails due to an error on line 9**
- **d. Compilation fails due to an error on line 10**
- **e. Compilation fails due to an error on line 6**
- **f. Compilation succeeds**

Question 11

Not yet answered

Marked out of 1.00

What is the output of the following program?

```
#include<iostream>
using namespace std;

void main() {
char s[] = "Fine";
*s = 'N';

cout<<s<<endl;
}
```

Select one:

- a. **Fine**
- b. **Runtime error**
- c. **Compile error**
- d. **Nine**

Question 12

Not yet answered

Marked out of 1.00

In an inventory management system implemented at a trading corporation, there are several tables designed to hold all the information.
Amongst these, the following two tables hold information on which items are supplied by which suppliers,
and which warehouse keeps which items along with the stock-level of these items.

Supply = (supplierid, itemcode)
Inventory = (itemcode, warehouse, stocklevel)

For a specific information required by the management, following SQL query has been written

```
Select distinct STMP.supplierid
From Supply as STMP
Where not unique (Select ITMP.supplierid
From Inventory, Supply as ITMP
Where STMP.supplierid = ITMP.supplierid
And ITMP.itemcode = Inventory.itemcode
And Inventory.warehouse = 'Nagpur');
```

For the warehouse at Nagpur, this query will find all suppliers who

Select one:

- a. **supply exactly one item**
- b. **supply one or more items**
- c. **supply two or more items**
- d. **do not supply any item**

Question **13**

Not yet answered

Marked out of 1.00

Given:

```
1. public class Frisbee {
2. // insert code here
3. int x = 0;
4. System.out.println(7/x);
5. }
6. }
```

And given the following four code fragments:
I. public static void main(String[] args) {
II. public static void main(String[] args) throws Exception {
III. public static void main(String[] args) throws IOException {
IV. public static void main(String[] args) throws RuntimeException {

If the four fragments are inserted independently at line 4, which are true? (Choose all that apply.)

Select one:

- **a. All four will compile and execute and throw an exception**
- **b. When considering fragments II, III, and IV, of those that will compile, adding a try/catch block around line 6 will cause compilation to fail**
- **c. Some, but not all, will compile and execute without exception**
- **d. All four will compile and execute without exception**
- **e. Some, but not all, will compile and execute and throw an exception**

Question **14**

Not yet answered

Marked out of 1.00

A class can contain objects of other classes and this phenomenon is called_____ .

Select one:

- **a. Object Association**
- **b. Relationship**
- **c. None of these**
- **d. Containership**

Question **15**

Not yet answered

Marked out of 1.00

Given:

```
2. class MyException extends Exception { }
3. class Tire {
4. void doStuff() { }
5. }
6. public class Retread extends Tire {
7. public static void main(String[] args) {
8. new Retread().doStuff();
9. }
10. // insert code here
11. System.out.println(7/0);
12. }
13. }
```

And given the following four code fragments:

```
I. void doStuff() {
II. void doStuff() throws MyException {
III. void doStuff() throws RuntimeException {
IV. void doStuff() throws ArithmeticException {
```

When fragments I - IV are added, independently, at line 10, which are true? (Choose all that apply.)

Select one or more:

- ☐ **a. None will compile**
- ☐ **b. They will all compile**
- ☐ **c. None of those that compile will throw an exception at runtime**
- ☐ **d. All of those that compile will throw an exception at runtime**
- ☐ **e. Some, but not all, will compile**
- ☐ **f. Only some of those that compile will throw an exception at runtime**

Question **16**

Not yet answered

Marked out of 1.00

Consider the relation account (customer, balance) where customer is a primary key and there are no null values.

We would like to rank customers according to decreasing balance.

The customer with the largest balance gets rank 1. ties are not broke but ranks are skipped:
if exactly two customers have the largest balance they each get rank 1 and rank 2 is not assigned

Query1:
select A.customer, count(B.customer)
from account A, account B
where A.balance <=B.balance
group by A.customer

Query2:
select A.customer, 1+count(B.customer)
from account A, account B
where A.balance < B.balance
group by A.customer

Consider these statements about Query1 and Query2.

1. Query1 will produce the same row set as Query2 for some but not all databases.
2. Both Query1 and Query2 are correct implementation of the specification
3. Query1 is a correct implementation of the specification but Query2 is not
4. Neither Query1 nor Query2 is a correct implementation of the specification
5. Assigning rank with a pure relational query takes less time than scanning in decreasing balance order assigning ranks using ODBC.

Which two of the above statements are correct?

Select one:

- **a. 1 and 3**
- **b. 2 and 5**
- **c. 3 and 5**
- **d. 1 and 4**

Question **17**

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;
int x = 1;
void fun()
{
int x = 2;
{
int x = 3;
cout << x << endl;
cout << ::x << endl;
}
}
int main()
{
fun();
return 0;
}
```

Select one:

- **a. 2 3**
- **b. 3 1**
- **c. 3 3**
- **d. 0 3**

Question **18**

Not yet answered

Marked out of 1.00

```
#include <stdio.h>
int main()
{
if (sizeof(int) > -1)
printf("Yes");
else
printf("No");
return 0;
}
```

Select one:

- **a. No**
- **b. Yes**
- **c. Compiler Error**
- **d. Runtime Error**

Question **19**

Not yet answered

Marked out of 1.00

In the following CPP program f() is overloaded.?

```
#include<iostream>
using namespace std;
void f(unsigned int x) {
cout<<"one "<<x;
}
void f(signed int x) {
cout<<"two "<<x;
}
int main() {
f(20);
return 1;
}
```

Select one:

- **a. Run time error/Segmentation fault**
- **b. two 20**
- **c. one 20**
- **d. Compilation fails**

Question **20**

Not yet answered

Marked out of 1.00

Predict the output of the following program:

```
#include <stdio.h>
int main()
{
char str[] = "%d %c", arr[] = "GreatQuee";
printf(str, 0[arr], 2[arr + 3]);
return 0;
}
```

Select one:

- **a. Compile-time error**
- **b. 71 81**
- **c. G Q**
- **d. 71 Q**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=11322)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved. Version 4.2

/