Question 1

Not yet answered

Marked out of 1.00

what is the output of the following C Code

```
#include <stdio.h>
int main()
{
int i=5;
const int j = 3;
switch(i)
{
case 1 : printf("one "); break;
case j+2 : printf("Three ");
case 5: printf(" five "); break;
}
return 0;
}
```

Select one:

- **a. five**
- **b. Three five**
- **c. Segmentation fault**
- **d. Compilation fails**

Question 2

Not yet answered

Marked out of 1.00

```
#include <stdio.h>
int main()
{
char ch='A';
printf(" %c ", ch>='A' && ch<='Z' ? ch+'a'-'A':ch);
printf(" %c ", ch >='A' && ch <='Z' ?ch: ch +'a'-'A');
return 0;
}
```

Select one:

- **a. Segmentation fault**
- **b. a A**
- **c. A a**
- **d. A A**
- **e. Compilation fails**
- **f. a a**

Question 3

Not yet answered

Marked out of 1.00

Output of the following C Code

```
#include <stdio.h>
int m2(int x)
{
return x*x;
}
int m1(int a, int b)
{
return (m2(11));
}

int main()
{
printf(" %d ", m1(10,20));
return 0;
}
```

Select one:

- **a. 11**
- **b. 121**
- **c. Segmentation fault**
- **d. Compilation fails**

Question 4

Not yet answered

Marked out of 1.00

```
#include <stdio.h>
int fun(int,int);
typedef int (*pf) (int,int);
int proc(pf,int,int);


int main()
{
printf(" %d ", proc(fun,6,6));
return 0;
}
int fun(int a,int b)
{
return (a==b);
}
int proc(pf p, int a, int b)
{
return ((*p)(a,b));
}
```

Select one:

- **a. -1**
- **b. 1**
- **c. 6**
- **d. 0**

Question 5

Not yet answered

Marked out of 1.00

Output of the following C Code

```
#include <stdio.h>
int main()
{
printf(" %c ", "zyxwvutsrqpo"[4]);
return 0;
}
```

Select one:

- **a. Compilation fails**
- **b. v**
- **c. s**
- **d. 118**
- **e. w**

Question 6

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

template<class T,class S,class Z> void fun(T a,S b,Z c)
{
cout<<a<<" "<<b<<" "<<c;
}

class Sample
{
int i;
public:
Sample() {i=100;}

friend ostream & operator << (ostream &MyCout, const Sample &c){
MyCout<<c.i<<" ";
}

};

int main()
{
int i=10;
char c='T';
Sample S;
fun(i,c,S);
}
```

Select one:

- **a. 10 T Garbage Value**
- **b. None of these**
- **c. 10 T 100**
- **d. Compilation fails**
- **e. Segmentation fault**

Question 7

Not yet answered

Marked out of 1.00

Output of the below CPP Code

```
#include<string.h>
#include<iostream>
using namespace std;

class Sample
{
int i;
public:
class ErrClass
{ public:
char str[50];
ErrClass(const char *s)
{
strcpy(str,s);
}

};
void fun(int a,int b)
{
int c;
if(b==0)
throw ErrClass("This is a Divison Error ");
else
{
c=a/b;
cout<<c<<" ";
}
}
};
int main()
{
try {
Sample S;
S.fun(20,5);
S.fun(2,0);
}
catch(Sample::ErrClass e)
{
cout<<e.str<<endl;
}
catch(char *st)
{
cout<<st<<" exception caught ";
}
return 0;
}
```

Select one:

- **a. 4 This is a Divison Error**
- **b. Segmentation fault**

- c. Compilation fails
- d. 4 This is a Divison Error exception caught
- e. 4 followed by Segmentation fault

Question 8

Not yet answered

Marked out of 1.00

output of the below cpp code

assume the size of int as 4 bytes

```
#include<string.h>
#include<iostream>
using namespace std;

class Sample
{
public :
int i : 10;
int j : 5;
Sample()
{
i=3;
j=4;
}

};
int main()
{
Sample s;
cout<<sizeof(s);
return 0;
}
```

Select one:

- a. 8 bytes
- b. None of these
- c. 15 bits
- d. 4 bytes

Question 9

Not yet answered

Marked out of 1.00

output of the below java called

```
interface A {
void m1();
}
class Main
{
A a;
void m2()
{
a=new A()
{
public void m1(){
System.out.println("m1 called");
}
};
}
public static void main(String [] args)
{
Main m = new Main();
m.a.m1();
}

}
```

Select one:

- **a. Compilation fails**
- **b. NoSuchMethodException at runtime**
- **c. NullPointer exception at runtime**
- **d. m1 called**

Question 10

Not yet answered

Marked out of 1.00

IF start is called again on a dead thread, which exception is thrown

Select one:

- **a. IllegalMonitorStateException**
- **b. InterruptedException**
- **c. None of these**
- **d. IllegalThreadStateException**

Question 11

Not yet answered

Marked out of 1.00

```
class C1
{
static class C2
{
static int i;
}
public static void main(String args[])
{
System.out.println(C1.C2.i);
}
}
```

Select one:

- **a. 0**
- **b. Runtime Exception**
- **c. Garbage Value**
- **d. Compilation fails**

Question 12

Not yet answered

Marked out of 1.00

what does the below mysql trigger do

```
create trigger t1 before UPDATE on sailors
for each row
begin
if new.age>60 then
set new.age=old.age;
else
set new.age=new.age;
end if;
end;
$
```

Select one:

- **a. the way of creating the trigger is not correct here**
- **b. None of these**
- **c. it only checks if the sailor table has age column or not**
- **d. updates the sailor table age column to the value 60 for all rows**

Question 13

Not yet answered

Marked out of 1.00

Given the following table Managers with (Id,Name,Salary) as the columns what will be the
rows of the Managers table after the below query has been executed

Query –

```
DELETE M1
From managers M1, managers M2
Where M2.Name = M1.Name AND M1.Id>M2.Id;
```

Managers –
Id Name Salary
1 Harpreet 20000
2 Ravi 30000
3 Vinay 10000
4 Ravi 30000
5 Harpreet 20000
6 Vinay 10000
7 Rajeev 40000
8 Vinay 10000
9 Ravi 30000
10 Sanjay 50000

Select one:

- **a.**
  Id Name Salary
  1 Harpreet 20000
  2 Ravi 30000
  3 Vinay 10000
  4 Ravi 30000
  5 Harpreet 20000
  6 Vinay 10000
  7 Rajeev 40000
  8 Vinay 10000
  9 Ravi 30000
  10 Sanjay 50000
- **b. None of these**
- **c. Id Name Salary**
  1 Harpreet 20000
  2 Ravi 30000
  3 Vinay 10000
  7 Rajeev 40000
  10 Sanjay 50000
- **d.**
  Id Name Salary
  5 Harpreet 20000
  6 Vinay 10000
  7 Rajeev 40000
  9 Ravi 30000
  10 Sanjay 50000

Question **14**

Not yet answered

Marked out of 1.00

Unit testing is done by:

Select one:

- **a. None of the mentioned**
- **b. Developers**
- **c. Customers**
- **d. Users**

Question **15**

Not yet answered

Marked out of 1.00

System testing is a

Select one:

- **a. Black box testing**
- **b. Grey box testing**
- **c. White box testing**
- **d. Both a and b**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=14015)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved. Version 4.2