Question 1

Not yet answered

Marked out of 1.00

Given:

```
import java.io.*;
public class TestSer {
public static void main(String[] args) {
SpecialSerial s = new SpecialSerial();
try {
ObjectOutputStream os = new ObjectOutputStream(
new FileOutputStream("myFile"));
os.writeObject(s); os.close();
System.out.print(++s.z + " ");
ObjectInputStream is = new ObjectInputStream(
new FileInputStream("myFile"));
SpecialSerial s2 = (SpecialSerial)is.readObject();
is.close();
System.out.println(s2.y + " " + s2.z);
} catch (Exception x) {System.out.println("exc"); }
}
}
```

```
class SpecialSerial implements Serializable {
transient int y = 7;
static int z = 9;
}
```

Which are true? (Choose all that apply.)

Select one or more:

- ☐ **a. In order to alter the standard deserialization process you would implement the readObject() method in SpecialSerial**
- ☐ **b. The output is 10 0 10**
- ☐ **c. The output is 10 0 9**
- ☐ **d. In order to alter the standard deserialization process you would implement the defaultReadObject() method in SpecialSerial**
- ☐ **e. The output is 10 7 10**
- ☐ **f. Compilation fails**
- ☐ **g. The output is 10 7 9**

Question 2

Not yet answered

Marked out of 1.00

Output of the following CPP Code

```
#include<iostream>
using namespace std;

class Base {
private:
int i, j;
public:
Base(int _i = 0, int _j = 0): i(_i), j(_j) { }
};
class Derived: public Base {
public:
void show(){
cout<<" i = "<<i<<" j = "<<j;
}
};
int main(void) {
Derived d;
d.show();
return 0;
}
```

Select one:

- a. **None of these**
- b. **i = 0 j = 0**
- c. **Compiler Error: i and j are private in Base**
- d. **Compiler Error: Could not call constructor of Base**

Question 3

Not yet answered

Marked out of 1.00

Output of the following C Code

```
#include<stdio.h>
int main()
{
typedef int *i;
int j = 10;
i *a = &j;
printf("%d", **a);
return 0;
}
```

Select one:

- a. **Compiler Error**
- b. **0**
- c. **10**
- d. **Garbage Value**

Question **4**

Not yet answered

Marked out of 1.00

What is the output of the following C Code

```
#include<stdio.h>
void crazy(int n,int a,int b)
{
if (n <= 0) return;
crazy(n-1, a, b+n);
printf("%d %d %d\n",n,a,b);
crazy(n-1, b, a+n);
}

int main()
{
crazy(3,4,5);
return 0;
}
```

Select one:

- **a. 3 4 5**
  1 5 9
  2 5 7
  1 7 7
- **b. 3 4 5**
  1 4 10
  2 4 8
  1 8 6
  1 5 9
  2 5 7
  1 7 7
- **c. 1 4 10**
  2 4 8
  1 8 6
  3 4 5
  1 5 9
  2 5 7
  1 7 7
- **d. 1 4 10**
  2 4 8
  1 8 6
  3 4 5

Question 5

Not yet answered

Marked out of 1.00

Given:

```
3. import java.io.*;
4. public class ReadingFor {
5. public static void main(String[] args) {
6. String s;
7. try {
8. FileReader fr = new FileReader("myfile.txt");
9. BufferedReader br = new BufferedReader(fr);
10. while((s = br.readLine()) != null)
11. System.out.println(s);
12. br.flush();
13. } catch (IOException e) { System.out.println("io error"); }
16. }
17. }
```

And given that myfile.txt contains the following two lines of data:

```
ab
cd
```

What is the result?

Select one:

- **a. ab**
- **b. a**
  b
  c
  d
- **c. Compilation fails**
- **d. abcd**
- **e. ab**
  cd

Question 6

Not yet answered

Marked out of 1.00

Consider the C function given below.

```
int f(int j)
{
static int i = 50;
int k;
if (i == j)
{
printf("something");
k = f(i);
return 0;
}
else return 0;
}
```

Which one of the following is TRUE?

Select one:

- **a. The function returns 0 when j = 50.**
- **b. The function returns 0 for all values of j.**
- **c. The function prints the string something for all values of j.**
- **d. The function will exhaust the runtime stack or run into an infinite loop when j = 50**

Question 7

Not yet answered

Marked out of 1.00

In _____, the bodies of the two loops are merged together to form a single loop provided that they do not make any references to each other.

Select one:

- **a. Loop jamming**
- **b. Loop concatenation**
- **c. Strength reduction**
- **d. Loop unrolling**

Question **8**

Not yet answered

Marked out of 1.00

The following table has two attributes A and C where A is the primary key and C is the foreign key referencing A with on-delete cascade.

A	C
2	4
3	4
4	3
5	2
7	2
9	5
6	4

The set of all tuples that must be additionally deleted to preserve referential integrity when the tuple (2,4) is deleted is:

Select one:

- **a. (3,4) and (6,4)**
- **b. (5,2) and (7,2)**
- **c. (3,4), (4,3) and (6,4)**
- **d. (5,2), (7,2) and (9,5)**

Question 9

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

class Base1
{
public:
char c;
};

class Base2
{
public:
int c;
};

class Derived: public Base1, public Base2
{
public:
void show() { cout << c; }
};

int main(void)
{
Derived d;
d.show();
return 0;
}
```

Select one:

- **a. None of these**
- **b. Compiler Error in “cout << c;"**
- **c. Compiler Error in “class Derived: public Base1, public Base2”**
- **d. Garbage Value**

Question 10

Not yet answered

Marked out of 1.00

Given:

```
class TKO {
public static void main(String[] args) {
String s = "-";
Integer x = 343;
long L343 = 343L;
if(x.equals(L343)) s += ".e1 ";
if(x.equals(343)) s += ".e2 ";
Short s1 = (short)((new Short((short)343)) / (new Short((short)49)));
if(s1 == 7) s += "=s ";
if(s1 < new Integer(7+1)) s += "fly ";
System.out.println(s);
} }
```

Which of the following will be included in the output String s? (Choose all that apply.)

Select one or more:

- ☐ **a. .e1**
- ☐ **b. None of the above**
- ☐ **c. .e2**
- ☐ **d. Compilation fails**
- ☐ **e. An exception is thrown at runtime**
- ☐ **f. fly**
- ☐ **g. =s**

Question 11

Not yet answered

Marked out of 1.00

Output of the following C Code

```
#include<stdio.h>
int main()
{
float x = 0.1;
if ( x == 0.1 )
printf("IF");
else if (x == 0.1f)
printf("ELSE IF");
else
printf("ELSE");
}
```

Select one:

- ○ **a. ELSE IF**
- ○ **b. ELSE**
- ○ **c. Compilation fails**
- ○ **d. IF**

Question **12**

Not yet answered

Marked out of 1.00

what is the output of the below C code

```
#include<stdio.h>
#include<string.h>

int main()
{
char p[] = "helloworld";
char t;
int i, j;
for(i=0,j=strlen(p)-1; i<j; i++)
{
t = p[i];
p[i] = p[j-i];
p[j-i] = t;
}
printf("%s", p);
return 0;
}
```

Select one:

- **a. Nothing is printed on the screen**
- **b. helloworld**
- **c. Segementation fault**
- **d. dlrowolleh**
- **e. delloworlh**

Question **13**

Not yet answered

Marked out of 1.00

Given:

```
3. public class Theory {
4. public static void main(String[] args) {
5. String s1 = "abc";
6. String s2 = s1;
7. s1 += "d";
8. System.out.println(s1 + " " + s2 + " " + (s1==s2));
9.
10. StringBuffer sb1 = new StringBuffer("abc");
11. StringBuffer sb2 = sb1;
12. sb1.append("d");
13. System.out.println(sb1 + " " + sb2 + " " + (sb1==sb2));
14. }
15. }
```

Which are true? (Choose all that apply.)

Select one or more:

- ☐ **a. Compilation fails**
- ☐ **b. The second line of output is abcd abcd true**
- ☐ **c. The first line of output is abc abc false**
- ☐ **d. The first line of output is abc abc true**
- ☐ **e. The second line of output is abcd abcd false**
- ☐ **f. The second line of output is abcd abc false**
- ☐ **g. The first line of output is abcd abc false**

Question **14**

Not yet answered

Marked out of 1.00

```
#include <iostream>
using namespace std;

int main()
{
try {
throw "10";
}
catch (char *excp) {
cout << "Caught " << excp;
}
catch (...) {
cout << "Default Exception\n";
}
return 0;
}
```

Select one:

- **a. Default Exception**
- **b. Compilation fails**
- **c. Segmentation fault**
- **d. Caught 10**

Question **15**

Not yet answered

Marked out of 1.00

The relation book (title, price) contains the titles and prices of different books. Assuming that no two books have the same price, what does the following SQL query list?

```
select title
from book as B
where (select count(*)
from book as T
where T.price > B.price) < 5
```

Select one:

- **a. Titles of the five most expensive books**
- **b. Title of the fifth most inexpensive book**
- **c. Titles of the four most expensive books**
- **d. Title of the fifth most expensive book**

Question **16**

Not yet answered

Marked out of 1.00

Output of the following C Code

```
# include <stdio.h>
int main()
{
int i = 0;
for (i=0; i<20; i++)
{
switch(i)
{
case 0:
i += 5;
case 1:
i += 2;
case 5:
i += 5;
default:
i += 4;
break;
}
printf("%d ", i);
}
return 0;
}
```

Select one:

- **a. Compiler Error**
- **b. 16 21**
- **c. 7 12 17 22**
- **d. 5 10 15 20**

Question 17

Not yet answered

Marked out of 1.00

Consider the below C++ program.

```
#include<iostream>
using namespace std;

class A
{
public:
A(){ cout <<"1";}
A(const A &obj){ cout <<"2";}
};

class B: virtual A
{
public:
B(){cout <<"3";}
B(const B & obj){cout<<"4";}
};

class C: virtual A
{
public:
C(){cout<<"5";}
C(const C & obj){cout <<"6";}
};

class D:B,C
{
public:
D(){cout<<"7";}
D(const D & obj){cout <<"8";}
};

int main()
{
D d1;
D d(d1);
}
```

Which of the below is not printed?

Select one:

- **a. 4**
- **b. 6**
- **c. All of these are not printed**
- **d. 2**

Question **18**

Not yet answered

Marked out of 1.00

Given:

```
import java.io.*;
class Keyboard { }
public class Computer implements Serializable {
private Keyboard k = new Keyboard();
public static void main(String[] args) {
Computer c = new Computer();
c.storeIt(c);
}
void storeIt(Computer c) {
try {
ObjectOutputStream os = new ObjectOutputStream(
new FileOutputStream("myFile"));
os.writeObject(c);
os.close();
System.out.println("done");
} catch (Exception x) {System.out.println("exc"); }
}
}
```

What is the result? (Choose all that apply.)

Select one:

- **a. Exactly one object is serialized**
- **b. Compilation fails**
- **c. Exactly two objects are serialized**
- **d. exc**
- **e. done**

Question 19

Not yet answered

Marked out of 1.00

Given:

```
import java.io.*;
class Player {
Player() { System.out.print("p"); }
}
class CardPlayer extends Player implements Serializable {
CardPlayer() { System.out.print("c"); }
public static void main(String[] args) {
CardPlayer c1 = new CardPlayer();
try {
FileOutputStream fos = new FileOutputStream("play.txt");
ObjectOutputStream os = new ObjectOutputStream(fos);
os.writeObject(c1);
os.close();
FileInputStream fis = new FileInputStream("play.txt");
ObjectInputStream is = new ObjectInputStream(fis);
CardPlayer c2 = (CardPlayer) is.readObject();
is.close();
} catch (Exception x ) { }
}
}
```

What is the result?

Select one:

- **a. An exception is thrown at runtime**
- **b. pc**
- **c. pcpc**
- **d. pcp**
- **e. Compilation fails**
- **f. pcc**

Question **20**

Not yet answered

Marked out of 1.00

Output of the following C Code

```
#include<stdio.h>

void dynamic(int s, ...)
{
printf("%d ", s);
}

int main()
{
dynamic(2, 4, 6, 8);
dynamic(3, 6, 9);
return 0;
}
```

Select one:

- **a. 4 3**
- **b. 3 2**
- **c. 2 3**
- **d. Compiler Error**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=11368)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved.