Question 1

Not yet answered

Marked out of 1.00

What will be the output of the following c code

```
#include<stdio.h>

int main()
{
typedef int LONG;
LONG a = 4;
LONG b = 68;
float c = 0;
c=b;
b+=a;
printf(" %d %f ", b, c);

return 1;
}
```

Select one:

- **a. 72 68.000000**
- **b. 72.000000 68**
- **c. 68.000000 72.000000**
- **d. Compilation fails**

Question 2

Not yet answered

Marked out of 1.00

output of the below cpp code

```
#include<string.h>
#include<iostream>
using namespace std;

class sample
{
int rno=55;
int marks = 100;
char name[25]="Shiva";
public :
sample() {
rno= 95;
marks = 85;
strcpy(name,"Arjun");


}
void display()
{
cout<<rno<<" "<<name<<" "<<marks;
}
};

int main()
{
sample s;
s.display();
return 1;
}
```

Select one:

- a. **95 Arjun 85**
- b. **55 Shiva 100**
- c. **Compilation fails**
- d. **Segmentation fault**

Question 3

Not yet answered

Marked out of 1.00

Project Risk Factor is considered in ?

Select one:

- a. **Iterative enhancement model**
- b. **Prototyping Model**
- c. **Waterfall Model**
- d. **Spiral Model**

Question 4

Not yet answered

Marked out of 1.00

what is the output of the java code

```
class A extends Thread
{
public void run(){
System.out.print("A ");
}
}

class Main{
public static void main(String [] args)
{
A a = new A();
a.run();
a.start();
}
}
```

Select one:

- **a. None of these**
- **b. Results in "IllegalThreadStateException"**
- **c. Compilation fails**
- **d. A**
- **e. A A**

Question 5

Not yet answered

Marked out of 1.00

In the Spiral model, ‘risk analysis’ is performed

Select one:

- **a. In the first loop**
- **b. In the first and second loop**
- **c. In every loop**
- **d. Before using spiral model**

Question 6

Not yet answered

Marked out of 1.00

output of the below cpp code

```
#include<iostream>
using namespace std;

class sample
{
public :
sample() { cout<<"sample called " ; }
};

class demo:public sample
{
public :
void display() { ::sample(); cout<<" display called "; }
};

int main()
{
demo d;
d.display();
return 1;
}
```

Select one:

- **a. Segmention fault**
- **b. Compilation fails**
- **c. sample called sample called display called**
- **d. sample called display called**

Question 7

Not yet answered

Marked out of 1.00

what is the output of the java code

```
class Main{
public void m1(Object o1)
{
System.out.println("Object");
}
public void m1(String str)
{
System.out.println("String");
}
public void m1(StringBuffer sb)
{
System.out.println("String Buffer");
}

public static void main(String [] args)
{
new Main().m1("Hello");
}
}
```

Select one:

- **a. Object**
- **b. String**
- **c. Compilation Fails**
- **d. String Buffer**

Question 8

Not yet answered

Marked out of 1.00

output of the below cpp code

```
#include<iostream>
using namespace std;

class sample
{
private:
int i;
public :
virtual void display() { }
};

class example
{
int i;
public :
void display() { }
};

class demo
{
public: void display() { }
};

int main()
{
cout<<sizeof(sample)<<" ";
cout<<sizeof(demo)<<" ";
cout<<sizeof(example);
return 1;
}
```

Select one:

- **a. 8 4 1**
- **b. 8 1 4**
- **c. 8 8 8**
- **d. 8 4 4**

Question 9

Not yet answered

Marked out of 1.00

what will be the output of the program(Test.c) if it is executed from the command line as shown below

Test 1 2 3

```
#include<stdio.h>
#include<stdlib.h>
int main(int argc,char *argv[])
{
int i,j=0;
for(i=0;i<argc;i++)
j=j+atoi(argv[i]);
printf(" %d ", j);
return 0;
}
```

Select one:

- **a. 6**
- **b. Compilation error**
- **c. 1 2 3**
- **d. "123"**

Question 10

Not yet answered

Marked out of 1.00

If an int is 4 bytes wide then which of the following is the correct output for the program given below ?

```
#include<stdio.h>
void fun(char **);
int main()
{
char *argv[]={"hello","doing","good","everyone"};
fun(argv);
}
void fun(char **p)
{
char *t;
t=(p+sizeof(int))[-1];
printf(" %s ", t);
}
```

Select one:

- **a. good**
- **b. Compilation fails**
- **c. everyone**
- **d. Segmentation fault**
- **e. hello**
- **f. doing**

Question 11

Not yet answered

Marked out of 1.00

what is the output of the java code

```
class Main extends Exception implements Runnable{

public void run() { }

public static void main(String [] args)
{
Main m = new Main();
Thread t = new Thread(m);
t.start();
t.setPriority(-1);
}

}
```

Select one:

- **a. Compiles fine and prints nothing**
- **b. Compialtion fails**
- **c. None of these**
- **d. Results in IllegalArgumentException**

Question 12

Not yet answered

Marked out of 1.00

What should be the empty line in the following code should be filled to make the code work and print 20

```
#include<stdio.h>

int check(int,int);

int main()
{
int c;
c=check(10,20);
printf(" %d ",c);
}

int check(int i,int j)
{
int *q,*p;
p=&i;
q=&j;
// _________
}
```

Select one:

- **a. return i >= 45 ? *q:*p;**
- **b. i >= 45 ? return(*p):return(*q);**
- **c. None of these**
- **d. return i >= 45 ? *p:*q;**
- **e. i >= 45 ? return(*q):return(*p);**

Question **13**

Not yet answered

Marked out of 1.00

what is the output of the java code

```
class Main{
private String get(String str)
{
try {
throw new Exception();

}
catch(Exception e)
{
return null;
}
}
public static void main(String [] args)
{
try {
System.out.println(new Main().get("Hello"));

}catch(Exception e)
{
System.out.println("Exception ");

}
}

}
```

Select one:

- **a. Compilation fails**
- **b. Compiles fine and prints null**
- **c. None of these**
- **d. Compiles fine but prints nothing**
- **e. Results in NullPointerException**

Question 14

Not yet answered

Marked out of 1.00

output of the followint C code

```
#include<stdio.h>

int main()
{
int i=32,j=0x20,k,l,m;
k=i|j;
l=i&j;
m=k^i;
printf(" %d %d %d %d %d ", i, j, k, l,m);
return 1;
}
```

Select one:

- **a. 0 0 0 0 0**
- **b. 0 32 32 32 32**
- **c. 32 32 32 32 0**
- **d. 32 32 32 32 32**

Question 15

Not yet answered

Marked out of 1.00

Consider the following schema:

Emp (Empcode, Name, Sex, Salary, Deptt)

A simple SQL query is executed as follows:

```
SELECT Deptt FROM Emp
WHERE sex = 'M'
GROUP by Dept
Having avg (Salary) > {select avg (Salary) from Emp}
```

The output will be

Select one:

- **a. Average salary of male employee is less than the average salary of the organization**
- **b. Average salary of male employee is the average salary of the organization**
- **c. Average salary of male employee is more than the average salary of the organization**
- **d. Average salary of male employee is equal to the average salary of the organization**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=14869)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved.