## Question 1

Not yet answered

Marked out of 1.00

Given:

```
3. import java.text.*;
4. public class Slice {
5. public static void main(String[] args) {
6. String s = "987.123456";
7. double d = 987.123456d;
8. NumberFormat nf = NumberFormat.getInstance();
9. nf.setMaximumFractionDigits(5);
10. System.out.println(nf.format(d) + " ");
11. try {
12. System.out.println(nf.parse(s));
13. } catch (Exception e) { System.out.println("got exc"); }
14. }
15. }
```

Which are true? (Choose all that apply.)

Select one or more:

- ☐ **a. The output is 987.12345 987.123456**
- ☐ **b. The try/catch block is unnecessary**
- ☐ **c. The invocation of parse() must be placed within a try/catch block**
- ☐ **d. The code compiles and runs without exception**
- ☐ **e. The output is 987.12346 987.12345**
- ☐ **f. The output is 987.12346 987.123456**
- ☐ **g. The output is 987.12345 987.12345**

## Question 2

Not yet answered

Marked out of 1.00

Output of the following C Code

```
#include <stdio.h>

int i=3;
void main(int k)
{
if(i==0)
{
k=0;
return;
}
else
{
k=i;
k--;
main(--i);
}
printf(" %d ", k);
}
```

Select one:

- **a. 0 1 2**
- **b. 0**
- **c. 2 1**
- **d. 2 1 0**
- **e. Compilation fails**

Question 3

Not yet answered

Marked out of 1.00

what is the output of the following cpp code

```
#include <iostream>
using namespace std;

int top =3;
class base
{
protected:
int top;
public:
base()
{
top=2;
cout<<top<<" ";
}
};

class derived :public base
{
private :
int top;
public :
derived():base()
{
top=1;
cout<<top<<" ";
cout<<base::top<<" ";
cout<<::top<<" ";
}
};
int main()
{
derived d1;
return 1;

}
```

Select one:

- a. **2 1 2 3**
- b. **1 2 3 2**
- c. **None of these**
- d. **2 2 1 2**

Question **4**

Not yet answered

Marked out of 1.00

```
#include <stdio.h>
int var = 20;
int main()
{
int var = var;
printf("%d ", var);
return 0;
}
```

Select one:

- **a. Compiler Error**
- **b. 20**
- **c. Segmentation fault**
- **d. Garbage Value/0**
- **e. None of these**

Question **5**

Not yet answered

Marked out of 1.00

Each time a defect gets detected and fixed, the reliability of a software product

Select one:

- **a. decreases**
- **b. remains constant**
- **c. cannot say anything**
- **d. increases**

Question **6**

Not yet answered

Marked out of 1.00

Are the following two sets of statements are same in CPP:

Assume sample is a class and s1 and s2 are objects

```
sample s1;
s1=s2;
```

and

```
sample s1=s2;
```

Select one:

- **a. None of these**
- **b. Same**
- **c. Not Same**
- **d. Depends on the Compiler**

Question 7

Not yet answered

Marked out of 1.00

Given:
public static void before() {
Set set = new TreeSet();
set.add("2");
set.add(3);
set.add("1");
Iterator it = set.iterator();
while (it.hasNext())
System.out.print(it.next() + " ");
}
Which statements are true?

Select one:

- **a. The before() method will not compile**
- **b. The before() method will print 1 2 3**
- **c. The before() method will throw an exception at runtime**
- **d. The before() method will print three numbers, but the order cannot be determined**
- **e. The before() method will print 1 2**

Question 8

Not yet answered

Marked out of 1.00

output of the following cpp code

```
#include <iostream>
using namespace std;

void fun(int i)
{
cout<<i+10;
}
void fun(int &i)
{
cout<<i+20;
}
int main()
{
int i=40;
fun(i);
return 1;
}
```

Select one:

- **a. 50**
- **b. Compilation fails**
- **c. 40**
- **d. 60**

Question 9

Not yet answered

Marked out of 1.00

Output of the following C Code

```
#include <stdio.h>

int main()
{
float arr[5] = {12.5, 10.0, 13.5, 90.5, 0.5};
float *ptr1 = &arr[0];
float *ptr2 = ptr1 + 3;

printf("%f ", *ptr2);
printf("%d", ptr2 - ptr1);

return 0;
}
```

Select one:

- **a. 90.500000 3**
- **b. 10.000000 12**
- **c. 0.500000 3**
- **d. 90.500000 12**

Question **10**

Not yet answered

Marked out of 1.00

Given:

```
3. import java.io.*;
4. public class Talker {
5. public static void main(String[] args) {
6. Console c = System.console();
7. String u = c.readLine("%s", "username: ");
8. System.out.println("hello " + u);
9. String pw;
10. if(c != null && (pw = c.readPassword("%s", "password: ")) != null)
11. // check for valid password
12. }
13. }
```

If line 6 creates a valid Console object, and if the user enters fred as a username and 1234 as a
password, what is the result? (Choose all that apply.)

Select one or more:

- ☐ **a. username:**
  **password:**
- ☐ **b. An exception is thrown at runtime**
- ☐ **c. username: fred**
  **password:**
- ☐ **d. Compilation fails**
- ☐ **e. username: fred**
  **password: 1234**

Question **11**

Not yet answered

Marked out of 1.00

Assume a class D that is privately derived from class B.

Which of the following can an object of class D located in main() access ?

Select one:

- ◯ **a. Public Members of D**
- ◯ **b. Protected Members of D**
- ◯ **c. Private Members of D**
- ◯ **d. Protected Members of B**
- ◯ **e. private members of B**
- ◯ **f. public Members of B**

Question 12

Not yet answered

Marked out of 1.00

Output of the following C Code

```
#include <stdio.h>
char str1[100];

char *fun(char str[])
{
static int i = 0;
if (*str)
{
fun(str+1);
str1[i] = *str;
i++;
}
return str1;
}

int main()
{
char str[] = "C was Developed by Dennis";
printf("%s", fun(str));
return 0;
}
```

Select one:

- a. **sinneD yb depoleveD saw C**
- b. **Segmentation Fault**
- c. **C was Developed by Dennis**
- d. **Nothing is printed on screen**

Question 13

Not yet answered

Marked out of 1.00

Output of the following C Code
Assume the size of integer is 4 bytes

```
#include <stdio.h>
struct bits
{
int i : 10;
int j : 20;
}b;

int main()
{
printf(" %ld ", sizeof(b));
return 1;
}
```

Select one:

- **a. 8**
- **b. 120**
- **c. 30**
- **d. 4**

Question **14**

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;
class A
{
public:
A()
{
cout<<"A Constructor "; }
};
class B
{
public:
B()
{
cout<<"B Constructor "; }
};
class C:public B,virtual public A
{
public:
C()
{
cout<<"C Constructor "; }
};
int main()
{
C a;
return 1;
}
```

Select one:

- **a. None of these**
- **b. A ConstructorB ConstructorC Constructor**
- **c. B ConstructorA Constructor C Constructor**
- **d. Illegal to specify virtual in derivation of class**

Question **15**

Not yet answered

Marked out of 1.00

Which statements are true about comparing two instances of the same class, given that the
equals() and hashCode() methods have been properly overridden? (Choose all that apply.)

Select one or more:

- ☐ **a. If the equals() method returns true, the hashCode() comparison == might return false**
- ☐ **b. If the hashCode() comparison == returns true, the equals() method must return true**
- ☐ **c. If the hashCode() comparison != returns true, the equals() method might return true**
- ☐ **d. If the hashCode() comparison == returns true, the equals() method might return true**
- ☐ **e. If the equals() method returns false, the hashCode() comparison == might return true**

Question **16**

Not yet answered

Marked out of 1.00

```
3. import java.util.*;
4. public class Looking {
5. public static void main(String[] args) {
6. String input = "1 2 a 3 45 6";
7. Scanner sc = new Scanner(input);
8. int x = 0;
9. do {
10. x = sc.nextInt();
11. System.out.print(x + " ");
12. } while (x!=0);
13. }
14. }
```

What is the result?

Select one:

- ◯ **a. 1 2**
- ◯ **b. 1 2 3 4 5 6**
- ◯ **c. 1 2 followed by an exception**
- ◯ **d. 1 2 3 45 6**
- ◯ **e. Compilation fails**
- ◯ **f. 1 2 a 3 45 6**

Question 17

Not yet answered

Marked out of 1.00

```
public static void main(String[] args) {
// INSERT DECLARATION HERE
for (int i = 0; i <= 10; i++) {
List<Integer> row = new ArrayList<Integer>();
for (int j = 0; j <= 10; j++)
row.add(i * j);
table.add(row);
}
for (List<Integer> row : table)
System.out.println(row);
}
```

Which statements could be inserted at // INSERT DECLARATION HERE to allow this code to compile and run? (Choose all that apply.)

Select one or more:

- ☐ **a. List<List<Integer>> table = new ArrayList<List<Integer>>();**
- ☐ **b. List<List, Integer> table = new List<List, Integer>();**
- ☐ **c. List<List<Integer>> table = new ArrayList<ArrayList<Integer>>();**
- ☐ **d. None of these**
- ☐ **e. List<List, Integer> table = new ArrayList<ArrayList, Integer>();**
- ☐ **f. List<List, Integer> table = new ArrayList<List, Integer>();**
- ☐ **g. List<List<Integer>> table = new List<List<Integer>>();**

Question **18**

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

class Test {
int rno;
public:
static void setDetails(int rno)
{
this->rno=rno;
}
void dispDetails()
{
cout<<rno;
}
};
int main()
{
Test t;
Test::setDetails(10);
t.dispDetails();
return 1;
}
```

Select one:

- **a. None of these**
- **b. Compilation Error**
- **c. Displays Garbage Value**
- **d. Displays 10**

Question **19**

Not yet answered

Marked out of 1.00

Given:

```
3. import java.io.*;
4. class Vehicle { }
5. class Wheels { }
6. class Car extends Vehicle implements Serializable { }
7. class Ford extends Car { }
8. class Dodge extends Car {
9. Wheels w = new Wheels();
10. }
```

Instances of which class(es) can be serialized? (Choose all that apply.)

Select one or more:

- **a. Vehicle**
- **b. Car**
- **c. Dodge**
- **d. Ford**
- **e. Wheels**

Question **20**

Not yet answered

Marked out of 1.00

Output of the following C Code

```
#include <stdio.h>

int main()
{
printf(6+"Hello World");

return 0;
}
```

Select one:

- **a. 6 Hello World**
- **b. Compilation fails**
- **c. Hello World**
- **d. World**
- **e. Hello**
- **f. Hello World 6**

# Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=11468)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved.

Version 4.2

/