Question 1

Not yet answered

Marked out of 1.00

```
import static java.lang.System.*;

class StaticImportDemo
{
public static void main(String args[])
{
out.println("welcome to programming");
}
}
```

Select one:

- **a. welcome to programming**
- **b. Runtime Error**
- **c. Compiler Error**
- **d. None of the above**

Question 2

Not yet answered

Marked out of 1.00

Following is C like pseudo code of a function that takes a number as an argument, and uses a stack S to do processing.

```
void fun(int n)
{
Stack S; // Say it creates an empty stack S
while (n > 0)
{
// This line pushes the value of n%2 to stack S
push(&S, n%2);

n = n/2;
}

// Run while Stack S is not empty
while (!isEmpty(&S))
printf("%d ", pop(&S)); // pop an element from S and print it
}
```

What does the above function do in general?

Select one:

- **a. Prints the value of Logn in reverse order**
- **b. Prints the value of Logn**
- **c. Prints binary representation of n in reverse order**
- **d. Prints binary representation of n**

Question 3

Not yet answered

Marked out of 1.00

```
#include <stdio.h>
int main()
{
static int i=5;
if(--i){
main();
printf("%d ",i);
}
}
```

Select one:

- **a. Compiler Error**
- **b. 1 2 3 4**
- **c. 0 0 0 0**
- **d. 4 3 2 1**

Question 4

Not yet answered

Marked out of 1.00

_____ is graphically rendered as a dashed line.

Select one:

- **a. Realization**
- **b. Generalization**
- **c. Dependency**
- **d. Association**

Question 5

Not yet answered

Marked out of 1.00

The most appropriate matching for the following pairs (GATE CS 2000)

X: m=malloc(5); m= NULL;	1: using dangling pointers
Y: free(n); n->value=5;	2: using uninitialized pointers
Z: char *p; *p = 'a';	3. lost memory is:

Select one:

- **a. X—3 Y—1 Z-2**
- **b. X—1 Y—3 Z-2**
- **c. X—2 Y—1 Z-3**
- **d. X—3 Y—2 Z-1**

Question 6

Not yet answered

Marked out of 1.00

Which of the following operators are overloaded by default by the compiler in every user defined classes even if user has not written?

1) Comparison Operator (==)
2) Assignment Operator (=)

Select one:

- **a. None of these**
- **b. Only 1**
- **c. Both 1 and 2**
- **d. Only 2**

Question 7

Not yet answered

Marked out of 1.00

```
#include <stdio.h>
int var = 20;
int main()
{
int var = var;
printf("%d ", var);
return 0;
}
```

Select one:

- **a. Compiler Error**
- **b. Garbage Value**
- **c. None of these**
- **d. 20**

Question **8**

Not yet answered

Marked out of 1.00

```
#include <stdio.h>
int fun(char *str1)
{
char *str2 = str1;
while(*++str1);
return (str1-str2);
}

int main()
{
char *str = "abcdefghi";
printf("%d", fun(str));
return 0;
}
```

Select one:

- **a. 9**
- **b. 8**
- **c. Random Number**
- **d. 10**

Question **9**

Not yet answered

Marked out of 1.00

Forward engineering in UML is the process of transforming _____

Select one:

- **a. a code into a model**
- **b. a model into test**
- **c. a code into design n**
- **d. a model into a code**

Question **10**

Not yet answered

Marked out of 1.00

Consider the following two sequences :

X = < B, C, D, C, A, B, C >, and
Y = < C, A, D, B, C, B >

The length of longest common subsequence of X and Y is :

Select one:

- **a. 5**
- **b. 4**
- **c. 3**
- **d. 2**

Question 11

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

class Test
{
private:
int x;
public:
Test(int x = 0) { this->x = x; }
void change(Test *t) { this = t; }
void print() { cout << "x = " << x << endl; }
};

int main()
{
Test obj(5);
Test *ptr = new Test (10);
obj.change(ptr);
obj.print();
return 0;
}
```

Select one:

- **a. x = 10**
- **b. Runtime Error**
- **c. Compiler Error**
- **d. x = 5**

Question 12

Not yet answered

Marked out of 1.00

You are given a list of 5 integers and these integers are in the range from 1 to 6.
There are no duplicates in list.
One of the integers is missing in the list.
Which of the following expression would give the missing number.
^ is bitwise XOR operator.
~ is bitwise NOT operator.

Let elements of list can be accessed as list[0], list[1], list[2], list[3], list[4]

Select one:

- **a. list[0] ^ list[1] ^ list[2] ^ list[3] ^ list[4] ^ 1 ^ 2 ^ 3 ^ 4 ^ 5**
- **b. ~(list[0] ^ list[1] ^ list[2] ^ list[3] ^ list[4])**
- **c. list[0] ^ list[1] ^ list[2] ^ list[3] ^ list[4] ^ 1 ^ 2 ^ 3 ^ 4 ^ 5 ^ 6**
- **d. list[0] ^ list[1] ^ list[2] ^ list[3] ^ list[4]**

Question **13**

Not yet answered

Marked out of 1.00

```
abstract class demo
{
public int a;
demo()
{
a = 10;
}

abstract public void set();

abstract final public void get();

}

class Test extends demo
{

public void set(int a)
{
this.a = a;
}

final public void get()
{
System.out.println("a = " + a);
}

public static void main(String[] args)
{
Test obj = new Test();
obj.set(20);
obj.get();
}
}
```

Select one:

- **a. a = 10**
- **b. Compilation error**
- **c. a = 20**
- **d. None of these**

Question **14**

Not yet answered

Marked out of 1.00

```
#include <stdio.h>
struct sample {
int a = 0;
char b = 'A';
float c = 10.5;
};
int main()
{
struct sample s;
printf("%d, %c, %f", s.a, s.b, s.c);
return 0;
}
```

Select one:

- **a. No Error, No Output**
- **b. 0, A, 10.500000**
- **c. Error**
- **d. 0, A, 10.5**

Question **15**

Not yet answered

Marked out of 1.00

```
#include <iostream>
using namespace std;

int i;

class A
{
public:
~A()
{
i=10;
}
};

int foo()
{
i=3;
A ob;
return i;
}

int main()
{
cout << foo() << endl;
return 0;
}
```

Select one:

- **a. None of the above**
- **b. 0**
- **c. 10**
- **d. 3**

Question 16

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;
class Point {
public:
Point() { cout << "Constructor called"; }
};

int main()
{
Point t1, *t2;
return 0;
}
```

Select one:

- **a. Constructor called**
- **b. None of these**
- **c. Segmentation fault**
- **d. Compiler Error**
- **e. Constructor called Constructor called**

Question 17

Not yet answered

Marked out of 1.00

Consider the polynomial p(x) = a0 + a1x + a2x^2 +a3x^3, where ai != 0, for all i. The minimum number of multiplications needed to evaluate p on an input x is:

Select one:

- **a. 3**
- **b. 6**
- **c. 9**
- **d. 4**

Question 18

Not yet answered

Marked out of 1.00

What is the return value of f(p, p) if the value of p is initialized to 5 before the call? Note that the first parameter is passed by reference, whereas the second parameter is passed by value.

```
int f(int &x, int c) {
c = c - 1;
if (c == 0) return 1;
x = x + 1;
return f(x, c) * x;
}
```

Select one:

- **a. 161051**
- **b. 3024**
- **c. 6561**
- **d. 55440**

Question 19

Not yet answered

Marked out of 1.00

```
class Test {
public static void main(String[] args) {
for(int i = 0; 0; i++)
{
System.out.println("Hello");
break;
}
}
}
```

Select one:

- **a. Empty Output**
- **b. Runtime error**
- **c. Hello**
- **d. Compiler error**

Question **20**

Not yet answered

Marked out of 1.00

```
class Test
{
public static void main (String[] args)
{
char arr1[] = {'1'};
char arr2[] = {'1'};
if (arr1 == arr2)
System.out.println("Same");
else
System.out.println("Not same");
}
}
```

Select one:

- **a. Same**
- **b. Not same**
- **c. None of these**
- **d. Compilation fails**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=9521)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved.