Question 1

Not yet answered

Marked out of 1.00

Given:

```
1. public class TestOne {
2. public static void main (String[] args) throws Exception {
3. Thread.sleep(3000);
4. System.out.println("sleep");
5. }
6. }
```

What is the result?

Select one:

- **a. The code executes normally and prints "sleep".**
- **b. The code executes normally, but nothing is printed.**
- **c. An exception is thrown at runtime.**
- **d. Compilation fails.**

Question 2

Not yet answered

Marked out of 1.00

Table A
Id Name Age
---
12 Arun 60
15 Shreya 24
99 Rohit 11

Table B
Id Name Age
---
15 Shreya 24
25 Hari 40
98 Rohit 20
99 Rohit 11

Table C
Id Phone Area
---
10 2200 02
99 2100 01

Consider the above tables A, B and C. How many tuples does the result of the following SQL query contains?

```
SELECT A.id
FROM A
WHERE A.age > ALL (SELECT B.age
FROM B
WHERE B. name = "arun");
```

Select one:

- **a. 0**
- **b. 1**
- **c. 4**
- **d. 3**

Question 3

Not yet answered

Marked out of 1.00

Given:

```
1. import java.util.*;
2. public class WrappedString {
3. private String s;
4. public WrappedString(String s) { this.s = s; }
5. public static void main(String[] args) {
6. HashSet<Object> hs = new HashSet<Object>();
7. WrappedString ws1 = new WrappedString("aardvark");
8. WrappedString ws2 = new WrappedString("aardvark");
9. String s1 = new String("aardvark");
10. String s2 = new String("aardvark");
11. hs.add(ws1); hs.add(ws2); hs.add(s1); hs.add(s2);
12. System.out.println(hs.size()); } }
```

What is the result?

Select one:

- **a. 2**
- **b. 1**
- **c. 0**
- **d. An exception is thrown at runtime.**
- **e. 4**
- **f. 3**
- **g. Compilation fails.**

Question 4

Not yet answered

Marked out of 1.00

```
#include "stdio.h"
int main()
{
char arr[100];
printf("%d", scanf("%s", arr));
/* Suppose that input value given
for above scanf is "welcome" */
return 1;
}
```

Select one:

- **a. 9**
- **b. 100**
- **c. 10**
- **d. 1**

Question 5

Not yet answered

Marked out of 1.00

Which of the following is true about new when compared with malloc.

1) new is an operator, malloc is a function
2) new calls constructor, malloc doesn't
3) new returns appropriate pointer, malloc returns void * and pointer needs to typecast to appropriate type.

Select one:

- **a. 1 and 2**
- **b. 1 and 3**
- **c. 2 and 3**
- **d. All 1, 2 and 3**

Question 6

Not yet answered

Marked out of 1.00

```
#include <stdio.h>
#define PRINT(i, limit) do \
{ \
if (i++ < limit) \
{ \
printf("hello\n"); \
continue; \
} \
}while(0)

int main()
{
int i = 0;
PRINT(i, 3);
return 0;
}
```

How many times "hello" is printed in the above program ?

Select one:

- **a. 2**
- **b. 1**
- **c. Compile-time error**
- **d. 3**

Question 7

Not yet answered

Marked out of 1.00

```
#include <iostream>
using namespace std;

class B;
class A {
int a;
public:
A():a(0) { }
void show(A& x, B& y);
};

class B {
private:
int b;
public:
B():b(0) { }
friend void A::show(A& x, B& y);
};

void A::show(A& x, B& y) {
x.a = 10;
cout << "A::a=" << x.a << " B::b=" << y.b;
}

int main() {
A a;
B b;
a.show(a,b);
return 0;
}
```

Select one:

- **a. Compiler Error**
- **b. A::a=10 B::b=0**
- **c. None of these**
- **d. A::a=0 B::b=0**

Question 8

Not yet answered

Marked out of 1.00

Given:

```
11. String test = "a1b2c3";
12. String[] tokens = test.split("\\d");
13. for(String s: tokens) System.out.print(s + " ");
```

What is the result?

Select one:

- **a. a b c**
- **b. An exception is thrown at runtime.**
- **c. The code runs with no output.**
- **d. a1b2c3**
- **e. Compilation fails.**
- **f. 1 2 3**
- **g. a1 b2 c3**

Question 9

Not yet answered

Marked out of 1.00

In below program, what would you put in place of “?” to print "welcome"?

```
#include <stdio.h>
int main()
{
char arr[] = "hellowelcome";
printf("%s", ?);
return 0;
}
```

Select one:

- **a. Not possible**
- **b. arr**
- **c. (arr+4)**
- **d. (arr+5)**

Question 10

Not yet answered

Marked out of 1.00

A good structured design has low cohesion and high coupling arrangements.

Select one:

- **a. Depends on the Application you are working**
- **b. None of these**
- **c. False**
- **d. True**

Question 11

Not yet answered

Marked out of 1.00

```
#include<iostream>

using namespace std;
class P {
public:
void print() { cout <<" Inside P"; }
};

class Q : public P {
public:
void print() { cout <<" Inside Q"; }
};

class R: public Q { };

int main(void)
{
R r;
r.print();
return 0;
}
```

Select one:

- **a. Compiler Error: Ambiguous call to print()**
- **b. Inside P**
- **c. Inside Q**
- **d. None of these**

Question 12

Not yet answered

Marked out of 1.00

The feature of the object oriented paradigm which helps code reuse is _____ .

Select one:

- **a. Inheritance**
- **b. Aggregation**
- **c. Object**
- **d. Class**

Question 13

Not yet answered

Marked out of 1.00

Given the basic ER and relational models, which of the following is INCORRECT?

Select one:

- **a. In a row of a relational table, an attribute can have exactly one value or a NULL value**
- **b. An attribute of an entity can have more than one value**
- **c. An attribute of an entity can be composite**
- **d. In a row of a relational table, an attribute can have more than one value**

Question **14**

Not yet answered

Marked out of 1.00

The average number of key comparisons done in a successful sequential search in a list of length it is

Select one:

- **a. n/2**
- **b. log n**
- **c. (n-1)/2**
- **d. (n+1)/2**

Question **15**

Not yet answered

Marked out of 1.00

Which of the following statements are TRUE about an SQL query?
P : An SQL query can contain a HAVING clause even if it does not have a GROUP BY clause
Q : An SQL query can contain a HAVING clause only if it has a GROUP BY clause
R : All attributes used in the GROUP BY clause must appear in the SELECT clause
S : Not all attributes used in the GROUP BY clause need to appear in the SELECT clause

Select one:

- **a. P and R**
- **b. P and S**
- **c. Q and S**
- **d. Q and R**

Question **16**

Not yet answered

Marked out of 1.00

The elements 32, 15, 20, 30, 12, 25, 16 are inserted one by one in the given order into a Max Heap.

The resultant Max Heap if printed in Level Order is

Select one:

- **a. 32 25 30 12 15 16 20**
- **b. 32 30 25 15 12 16 20**
- **c. 32 30 25 15 12 20 16**
- **d. 32 25 30 12 15 20 16**

Question **17**

Not yet answered

Marked out of 1.00

The most appropriate matching for the following pairs

X: depth first search 1: heap
Y: breadth-first search 2: queue
Z: sorting 3: stack

is

Select one:

- **a. X—1 Y—2 Z-3**
- **b. X—2 Y—3 Z-1**
- **c. X—3 Y—2 Z-1**
- **d. X—3 Y—1 Z-2**

Question **18**

Not yet answered

Marked out of 1.00

Interaction Diagram is a combined term for

Select one:

- **a. Sequence Diagram + Collaboration Diagram**
- **b. Deployment Diagram + Collaboration Diagram**
- **c. Activity Diagram + State Chart Diagram**
- **d. None of the mentioned**

Question **19**

Not yet answered

Marked out of 1.00

output of the following code in C Programming Language

```
#include<stdio.h>
struct Graph
{
int x, y, z;
};

int main()
{
struct Graph p1 = {.y = 0, .z = 1, .x = 2};
printf("%d %d %d", p1.x, p1.y, p1.z);
return 0;
}
```

Select one:

- **a. 0 1 2**
- **b. 2 0 1**
- **c. Compiler Error**
- **d. 2 1 0**

Question **20**

Not yet answered

Marked out of 1.00

```
#include <stdio.h>
int foo(int* a, int* b)
{
int sum = *a + *b;
*b = *a;
return *a = sum - *b;
}
int main()
{
int i = 0, j = 1, k = 2, l;
l = i++ || foo(&j, &k);
printf("%d %d %d %d", i, j, k, l);
return 0;
}
```

Select one:

- **a. 1 2 2 1**
- **b. 1 2 1 1**
- **c. 1 2 2 2**
- **d. 1 1 2 1**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=9775)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved.

Version 4.2

/