Question 1

Not yet answered

Marked out of 1.00

Output of the following in C Language

```
#include <stdio.h>
int main()
{
int i = 5, j = 10, k = 15;
printf("%d ", sizeof(k /= i + j));
printf("%d", k);
return 0;
}
```

Assume size of an integer as 4 bytes. What is the output of above program?

Select one:

- **a. 2 1**
- **b. 4 15**
- **c. 4 1**
- **d. Compile-time error**

Question 2

Not yet answered

Marked out of 1.00

Consider the following two C lines

```
int var1;
extern int var2;
```

Which of the following statements is correct

Select one:

- **a. None of these**
- **b. Both statements declare define variables var1 and var2**
- **c. First statement declares and defines var1, but second statement only declares var2**
- **d. Both statements only declare variables, don’t define them.**

Question 3

Not yet answered

Marked out of 1.00

In C Language , When fopen() is not able to open a file, it returns

Select one:

- **a. NULL**
- **b. EOF**
- **c. Runtime Error**
- **d. Compiler Dependent**

Question **4**

Not yet answered

Marked out of 1.00

Output of the following in C

```
#include<stdio.h>

int main()
{
struct {int a[2];} arr[] = {{1},{2}};

printf("%d %d %d %d",arr[0].a[0],arr[0].a[1],arr[1].a[0],arr[1].a[1]);

return 0;
}
```

Select one:

- **a. No compile error and it'll print 1 2 0 0**
- **b. Compile error because apart from definition of arr, another issue is in the initialization of array of struct i.e. arr[].**
- **c. No compile error and it'll print 1 0 2 0**
- **d. Compile error because of initialization of array of struct i.e. arr[].**
- **e. Compile error because arr has been defined using struct type incorrectly. First struct type should be defined using tag and then arr should be defined using that tag.**

Question **5**

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;
class A
{
int i;
public:
A(int ii = 0) : i(ii) {}
void show() { cout << i << endl; }
};

class B
{
int x;
public:
B(int xx) : x(xx) {}
operator A() const { return A(x); }
};

void g(A a)
{
a.show();
}

int main()
{
B b(10);
g(b);
g(20);
return 0;
}
```

Select one:

- **a. 20**
  20
- **b. 10**
  20
- **c. Compiler Error**
- **d. 10**
  10

Question 6

Not yet answered

Marked out of 1.00

```
#include<iostream>
using namespace std;

class Test
{
private:
int x;
int y;
public:
Test(int x = 0, int y = 0) { this->x = x; this->y = y; }
static void fun1() { cout << "Inside fun1()"; }
static void fun2() { cout << "Inside fun2()"; this->fun1(); }
};

int main()
{
Test obj;
obj.fun2();
return 0;
}
```

Select one:

- **a. Inside fun2() Inside fun1()**
- **b. Inside fun2()**
- **c. Inside fun1() Inside fun2()**
- **d. Compiler Error**

Question 7

Not yet answered

Marked out of 1.00

Which of the following is FALSE about references in C++

Select one:

- **a. References cannot be NULL**
- **b. References cannot refer to constant value**
- **c. A reference must be initialized when declared**
- **d. Once a reference is created, it cannot be later made to reference another object; it cannot be reset.**

Question 8

Not yet answered

Marked out of 1.00

Assume the size of int is 4 bytes and
int * is also 4 bytes

```
#include<iostream>
using namespace std;

class Test
{
static int x;
int *ptr;
int y;
};

int main()
{
Test t;
cout << sizeof(t) << " ";
cout << sizeof(Test *);
}
```

Select one:

- **a. 8 8**
- **b. 12 12**
- **c. 8 4**
- **d. 12 4**

Question 9

Not yet answered

Marked out of 1.00

What is the best time complexity of bubble sort?

Select one:

- **a. N^2**
- **b. NlogN**
- **c. N(logN)^2**
- **d. N**

Question **10**

Not yet answered

Marked out of 1.00

What are the appropriate data structures for following algorithms?

1) Breadth First Search
2) Depth First Search
3) Prim's Minimum Spanning Tree
4) Kruskal' Minimum Spanning Tree

Select one:

- **a. 1) Stack**
  2) Queue
  3) Priority Queue
  4) Union Find
- **b. 1) Queue**
  2) Stack
  3) Priority Queue
  4) Union Find
- **c. 1) Stack**
  2) Queue
  3) Union Find
  4) Priority Queue
- **d. 1) Priority Queue**
  2) Queue
  3) Stack
  4) Union Find

Question **11**

Not yet answered

Marked out of 1.00

What does the following C expression do?

x = x & (x-1)

Select one:

- **a. Turns of the leftmost set bit**
- **b. Makes x equals to 0**
- **c. Sets all bits as 1**
- **d. Turns of the rightmost set bit**

Question 12

Not yet answered

Marked out of 1.00

Given:
11. public class Key {
12. private long id1;
13. private long id2;
14.
15. // class Key methods
16. }

A programmer is developing a class Key, that will be used as a key in a standard java.util.HashMap.
Which two methods should be overridden to assure that Key works correctly as a key? (Choose two.)

Select one or more:

- **a. public int hashCode()**
- **b. public int compareTo(Object o)**
- **c. public boolean equals(Key k)**
- **d. public boolean compareTo(Key k)**
- **e. public boolean equals(Object o)**

Question 13

Not yet answered

Marked out of 1.00

Given:
42. public class ClassA {
43. public int getValue() {
44.int value=0;
45. boolean setting = true;
46. String title="Hello";
47. if (value || (setting && title == "Hello")) { return 1; }
48. if (value == 1 & title.equals("Hello")) { return 2; }
49. }
50. }
And:
70. ClassA a = new ClassA();
71. a.getValue();
What is the result?

Select one:

- **a. 2**
- **b. 1**
- **c. The code runs with no output.**
- **d. An exception is thrown at runtime.**
- **e. Compilation fails.**

Question 14

Not yet answered

Marked out of 1.00

Given:
class CardBoard {
Short story = 5;
CardBoard go(CardBoard cb) {
cb = null;
return cb;
}
public static void main(String[] args) {
CardBoard c1 = new CardBoard();
CardBoard c2 = new CardBoard();
CardBoard c3 = c1.go(c2);
c1 = null;
// do Stuff
} }
When // doStuff is reached, how many objects are eligible for GC?

Select one:

- **a. It is not possible to know.**
- **b. 2**
- **c. Compilation fails.**
- **d. 0**
- **e. 1**
- **f. An exception is thrown at runtime.**

Question 15

Not yet answered

Marked out of 1.00

The "all-or-none" property is commonly referred to as _____

Select one:

- **a. Isolation**
- **b. Durability**
- **c. Atomicity**
- **d. None of the mentioned**

Question 16

Not yet answered

Marked out of 1.00

The deadlock state can be changed back to stable state by using _____ statement.

Select one:

- **a. Deadlock**
- **b. Savepoint**
- **c. Commit**
- **d. Rollback**

Question **17**

Not yet answered

Marked out of 1.00

What operator tests column for the absence of data ?

Select one:

- **a. NOT Operator**
- **b. None of these**
- **c. Exists Operator**
- **d. IS NULL Operator**

Question **18**

Not yet answered

Marked out of 1.00

_____ diagrams are used to illustrate data structures, and the static snapshots instances of the things found in the class diagrams.

Select one:

- **a. Collaboration**
- **b. Sequence**
- **c. use case**
- **d. Object**

Question **19**

Not yet answered

Marked out of 1.00

Forward engineering and reverse engineering can be applicable to _____

Select one:

- **a. stereotypes**
- **b. tagged values**
- **c. adornments**
- **d. class diagram**

Question **20**

Not yet answered

Marked out of 1.00

UML is useful to _____ a system as it is or as we want it to be.

Select one:

- **a. All of these**
- **b. Specify**
- **c. Visualize**
- **d. Document**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=9910)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved.