Question 1

Not yet answered

Marked out of 1.00

```
#include <stdio.h>

void print(int n, int j)
{
if (j >= n)
return;
if (n-j > 0 && n-j >= j)
printf("%d %d\n", j, n-j);
print(n, j+1);
}

int main()
{
int n = 8;
print(n, 1);
}
```

Select one:

- **a. 1 7**
  2 6
  3 5
  4 4
  4 4
- **b. 1 7**
  2 6
  3 5
- **c. 1 7**
  2 6
  3 5
  4 4
- **d. 1 2**
  3 4
  5 6
  7 8

Question 2

Not yet answered

Marked out of 1.00

Which of the following SQL command deletes all records from table but does not delete the table ?

Select one:

- **a. DROP**
- **b. REMOVE**
- **c. DELETE**
- **d. ERASE**

Question **3**

Not yet answered

Marked out of 1.00

Given:

```
3. public class TestDays {
4. public enum Days { MON, TUE, WED };
5. public static void main(String[] args) {
6. for(Days d : Days.values() )
7. ;
8. Days [] d2 = Days.values();
9. System.out.println(d2[2]);
10. }
11. }
```

What is the result? (Choose all that apply.)

Select one or more:

- ☐ **a. Compilation fails due to an error on line 8**
- ☐ **b. The output is unpredictable**
- ☐ **c. Compilation fails due to an error on line 4**
- ☐ **d. TUE**
- ☐ **e. WED**
- ☐ **f. Compilation fails due to an error on line 6**
- ☐ **g. Compilation fails due to an error on line 9**

Question **4**

Not yet answered

Marked out of 1.00

```
#include <stdio.h>
int main (void)
{
int shifty;
shifty = 0570;
shifty = shifty >>4;
shifty = shifty <<6;
printf("the value of shifty is %o",shifty);
}
```

Select one:

- ◯ **a. the value of shifty is 4300**
- ◯ **b. the value of shifty is 2700**
- ◯ **c. the value of shifty is 5700**
- ◯ **d. the value of shifty is 15c0**

Question 5

Not yet answered

Marked out of 1.00

```
#include<stdlib.h>
#include<stdio.h>
#include<iostream>

using namespace std;

class Test {
int x;
public:
void* operator new(size_t size);
void operator delete(void*);
Test(int i) {
x = i;
cout << "Constructor called \n";
}
~Test() { cout << "Destructor called \n"; }
};


void* Test::operator new(size_t size)
{
void *storage = malloc(size);
cout << "new called \n";
return storage;
}

void Test::operator delete(void *p )
{
cout<<"delete called \n";
free(p);
}

int main()
{
Test *m = new Test(5);
delete m;
return 0;
}
```

Select one:

- **a. new called**
  Constructor called
  delete called
  Destructor called
- **b. Constructor called**
  new called
  delete called
  Destructor called
- **c. Constructor called**
  new called
  Destructor called
  delete called

- ◯ **d. new called**
  Constructor called
  Destructor called
  delete called

Question **6**

Not yet answered

Marked out of 1.00

Inheritance relationships are represented in the UML notation by

Select one:

- ◯ **a. Lines with hollow triangular arrow at one end**
- ◯ **b. Lines with solid triangular arrow at both ends**
- ◯ **c. Lines with hollow diamond at one end**
- ◯ **d. Lines with solid diamond at one end**

Question **7**

Not yet answered

Marked out of 1.00

What can UML interfaces be used for?

Select one:

- ◯ **a. To program in Java and C++, but not in C#**
- ◯ **b. To define executable logic that can be reused in several classes**
- ◯ **c. To provide concrete classes with the stereotype "interface"**
- ◯ **d. To specify required services for types of objects**

Question **8**

Not yet answered

Marked out of 1.00

Key elements of use-case diagrams are

Select one:

- ◯ **a. People, computer**
- ◯ **b. Uses, cases**
- ◯ **c. People, classes and objects**
- ◯ **d. Actors, use cases**

Question **9**

Not yet answered

Marked out of 1.00

Given the following class, which of the following is true? (Choose all that apply)

```
1: public class Snake {
2:
3: public void shed(boolean time) {
4:
5: if (time) {
6:
7: }
8: System.out.println(result);
9:
10: }
11: }
```

Select one or more:

- ☐ **a. If String result = "done"; is inserted on line 4, the code will compile.**
- ☐ **b. If String result = "done"; is inserted on line 2, the code will compile.**
- ☐ **c. None of the above changes will make the code compile.**
- ☐ **d. If String result = "done"; is inserted on line 9, the code will compile.**
- ☐ **e. If String result = "done"; is inserted on line 6, the code will compile.**

Question **10**

Not yet answered

Marked out of 1.00

Which of the following is considered as cascading input/output operators in CPP (Choose all that apply)

Select one or more:

- ☐ **a. Cascading operators are not supported in CPP**
- ☐ **b. cin>>a>>b>>c**
- ☐ **c. cout<<"hello"<<a<<endl;**
- ☐ **d. cout<<a<<b<<c**

Question **11**

Not yet answered

Marked out of 1.00

Consider the following recursive function fun(x, y).

What is the value of fun(4, 3)

```
int fun(int x, int y)
{
if (x == 0)
return y;
return fun(x - 1, x + y);
}
```

Select one:

- ○ **a. 10**
- ○ **b. 13**
- ○ **c. 9**
- ○ **d. 12**

Question 12

Not yet answered

Marked out of 1.00

What is the other name of Dijkstra algorithm?

Select one:

- a. **multiple-source shortest path problem**
- b. **single-destination shortest path problem**
- c. **multiple-destination shortest path problem**
- d. **single-source shortest path problem**

Question 13

Not yet answered

Marked out of 1.00

In C++, const qualifier can be applied to

1) Member functions of a class
2) Function arguments
3) To a class data member which is declared as static
4) Reference variables

Select one:

- a. **Only 1, 2 and 3**
- b. **Only 1, 3 and 4**
- c. **All of these**
- d. **Only 1, 2 and 4**

Question 14

Not yet answered

Marked out of 1.00

```
1. public class Electronic implements Device
{ public void doIt() { } }
2.
3. abstract class Phone1 extends Electronic { }
4.
5. abstract class Phone2 extends Electronic
{ public void doIt(int x) { } }
6.
7. class Phone3 extends Electronic implements Device
{ public void doStuff() { } }
8.
9. interface Device { public void doIt(); }
```

What is the result? (Choose all that apply.)

Select one or more:

- a. **Compilation fails with an error on line 7**
- b. **Compilation fails with an error on line 1**
- c. **Compilation succeeds**
- d. **Compilation fails with an error on line 9**
- e. **Compilation fails with an error on line 5**
- f. **Compilation fails with an error on line 3**

Question 15

Not yet answered

Marked out of 1.00

Which of the following is a pure virtual function in CPP

Select one:

- **a. virtual void display() { }**
- **b. void display() = 0;**
- **c. virtual void display() = 0;**
- **d. abstract void display() = 0;**
- **e. void display() { }**

Question 16

Not yet answered

Marked out of 1.00

Identify the correct statement regarding "view" in SQL

Select one:

- **a. All of these**
- **b. View provides automatic security for hidden data**
- **c. Views allow the same data to be seen by different users in different ways at the same time**
- **d. Views can provice logical data independence**

Question 17

Not yet answered

Marked out of 1.00

Consider the following pseudo code. Assume that IntQueue is an integer queue. What does the function fun do?

```
void fun(int n)
{
IntQueue q = new IntQueue();
q.enqueue(0);
q.enqueue(1);
for (int i = 0; i < n; i++)
{
int a = q.dequeue();
int b = q.dequeue();
q.enqueue(b);
q.enqueue(a + b);
print(a);
}
}
```

Select one:

- **a. Prints first n Fibonacci numbers**
- **b. Prints numbers from n-1 to 0**
- **c. Prints first n Fibonacci numbers in reverse order.**
- **d. Prints numbers from 0 to n-1**

Question **18**

Not yet answered

Marked out of 1.00

Choose the correct order of operations in a SELECT statement

Select one:

- ◯ **a. HAVING, WHERE, GROUP BY**
- ◯ **b. WHERE, HAVING, GROUP BY**
- ◯ **c. HAVING,GROUP BY, WHERE**
- ◯ **d. WHERE,GROUP BY, HAVING**

Question **19**

Not yet answered

Marked out of 1.00

Given:

```
4. class Announce {
5. public static void main(String[] args) {
6. for(int __x = 0; __x < 3; __x++) ;
7. int #lb = 7;
8. long [] x [5];
9. Boolean []ba[];
10. enum Traffic { RED, YELLOW, GREEN };
11. }
12. }
```

What is the result? (Choose all that apply.)

Select one or more:

- ☐ **a. Compilation fails with an error on line 8**
- ☐ **b. Compilation fails with an error on line 10**
- ☐ **c. Compilation fails with an error on line 7**
- ☐ **d. Compilation succeeds**
- ☐ **e. Compilation fails with an error on line 6**
- ☐ **f. Compilation fails with an error on line 9**

Question **20**

Not yet answered

Marked out of 1.00

```
#include <stdio.h>

int main()
{
int *ptr;
int x;

ptr = &x;
*ptr = 0;

printf(" x = %d\n", x);
printf(" *ptr = %d\n", *ptr);

*ptr += 5;
printf(" x = %d\n", x);
printf(" *ptr = %d\n", *ptr);

(*ptr)++;
printf(" x = %d\n", x);
printf(" *ptr = %d\n", *ptr);

return 0;
}
```

Select one:

- **a. x = garbage value**
  ***ptr = 0**
  x = garbage value
  ***ptr = 5**
  x = garbage value
  ***ptr = 6**
- **b. x = 0**
  ***ptr = 0**
  x = 0
  ***ptr = 0**
  x = 0
  ***ptr = 0**
- **c. x = 0**
  ***ptr = 0**
  x = 5
  ***ptr = 5**
  x = garbage value
  ***ptr = garbage value**
- **d. x = 0**
  ***ptr = 0**
  x = 5
  ***ptr = 5**
  x = 6
  ***ptr = 6**

Quiz Navigation

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

Finish attempt ... (http://classroom.teleuniv.com/mod/quiz/summary.php?attempt=10104)

Copyright © 2020 Teleparadigm Networks Pvt. Ltd. All Rights Reserved. Version 4.2